

Lightning and surge protection

Let's connect.

Version 2019



Dear Customers,

The PDF versions of our catalogues offer practical additional functions, helping you to find your way around our product range and simplifying the ordering process.

In addition to the catalogue, the PDF also contains:

- Internal page links
- Links to the online catalogue

Try it out for yourself. Click the order number to obtain more detailed information and close-up images via your web browser. The links in the PDF file also enable you to go directly to the next desired catalogue page.

Further Weidmüller product catalogues can be accessed by clicking the following:



Lightning and surge protection

Catalogue 4.4

Lightning and surge protection



Lightning and surge protection for control and instrumentation signals



Lightning and surge protection for low voltage supply



Lightning and surge protection for data interfaces



Mains filter



Surge protection IP67 for intrinsically safe circuits

Contents

A

B

C

D

E

Appendix

Service and support



The basics of lightning and surge protection

Index

Search according to type or order number

V

W

X

Lightning and surge protection for control and instrumentation signals

VARITECTOR SPC

Page A.8



Pluggable surge protection for C&I circuits (IEC 61643-21)

VARITECTOR SSC 6AN

Page A.64



2-stage surge protection with 6 screw connection for C&I circuits (IEC 61643-21)

VARITECTOR SSC 4AN


Page A.94



Pluggable lightning and surge protection with four screw connections for measurement and control technology according to IEC 61643-21

MCZ OVP series

Page A.108



3-stage lightning and surge protection for measurement and control systems, with tension-clamp connection

VARITECTOR SPC EX

Page A.132



Plug-in lightning and surge protection for intrinsically safe circuits in gas and dust atmospheres up to Zone 0

VARITECTOR SSC EX

Page A.152



2-stage lightning and surge protection with screw connections: for intrinsically safe circuits in gas and dust atmospheres up to Zone 0

Lightning and surge protection for low voltage facilities

VPU I 25 kA series

Page B.8



Type I/II lightning and surge protection for LPL I, II, III, IV for installation upstream/downstream of the electrical meter

VPU I 35 kA series

Page B.12



Type I/II lightning and surge protection for the LPL I, II, III, IV for installation before the electrical meter

VPU I N-PE series

Page B.21



Type I/II N-PE lightning and surge protection for LPL I, II, III, IV for installation before the electrical meter

VPU I 12.5 kA series

Page B.24



Type I/II lightning and surge protection for LPL III, IV for installation before/downstream of the electrical meter

VPU ZP series

Page B.36



Type I/II Lightning and surge protection for 40 mm busbars

VPU II series

Page B.40



Type II/III surge protection for installation in main and sub-distributions in various nominal voltages

VPU I and II photovoltaics

Page B.62



Type I and type II/III lightning and surge protection for installation in DC photovoltaic applications

VPU III series

Page B.68



Type III surge protection for installation before the end device to be protected

Lightning and surge protection for data interfaces

VARITECTOR SPC

Page C.4



Plug-in lightning and surge protection certified according to IEC 61643-21: for data ports (e.g. RS485) or high frequency (HF) signals

V DATA CAT.6

Page C.12



Surge protection for 8 wires with RJ45 socket

VARITECTOR SSC 6AN

Page C.14



2-stage lightning and surge protector with six screw connections: for data ports (e.g. RS485 and RS232)

JPOVP CAT.6

Page C.17



Protection for Class-III end devices in IP 20 and IP 67 versions for use in Ethernet Cat. 6 circuits

COAX

Page C.18



Surge protection for COAX interfaces, as BNC, N, F, and UHF adapter plug

Mains filter

Wavefilter

Page D.4




Mains filter, 3 A/6 A/10 A, with screw connection for 230 V devices or voltage supplies

Surge protection IP67 for intrinsically safe circuits

VARIRECTOR Cable Gland (VCG)

Page E.2



VARIRECTOR Cable Gland (VCG) protect intrinsically safe circuits in IP67 applications

Lightning and surge protection for instrumentation and control (I & C)

Lightning and surge protection for control and instrumentation signals	Quick selection guide	A.2
	SIL certification	A.5
	Lightning and surge protection for control and instrumentation signals	A.6
	VARITECTOR SPC	A.8
	V-TEST	A.60
	VARITECTOR SSC 6AN	A.64
	VARITECTOR SSC 4AN	A.94
	MCZ OVP series	A.108
	Earthing for shielded cables	A.120
	Installation advice for instrumentation and control engineering	A.124
Lightning and surge protection for measurement and control systems intrinsically safe circuits (Ex zone)	VARITECTOR SPC EX	A.132
	VARITECTOR SSC EX	A.152
	ATEX and IEC Ex approvals	A.168





Product quick selection for measurement and control signals

Instrumentation and control equipment

Interface/ signal	Mounting	Connection system	Protected wires	Discharge capacity	Operating current	max. voltage	Protection device	Order No. Arrestor	Order No. Direct earthing base	Order No. Indirect earthing base
				8/20 µs	I _{max} .	DC				
0(4) ... 20 mA	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	28 V	VSPC 2CL 24 V DC 0.5 A	8924470000	8924710000	8924270000
0(4) ... 20 mA	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	28 V	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000
0... 10 V	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	28 V	VSPC 2CL 24 V DC 0.5 A	8924470000	8924710000	8924270000
0... 10 V	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	28 V	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000
0-20 mA, 4-20 mA	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.5 A - 1.25 A	28 V	MCZ OVP 1CL 24 V 0.5 A		8448920000	
Hart	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	28 V	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000
Cathodic corrosion protection	on DIN rail, separable	Screw terminals	2	5 kA	2 A	72 V	VSPC GDT 2 CH 90 V 20 kA	8924570000	8924740000	8924300000
PT 100, PT 1000	on DIN rail, compact	Tension clamp terminals	2	5 kA	1.25 A	24 V	MCZ OVP SL 24 V 1.25 A	8448970000		
PT 100	on DIN rail, binary	Screw terminals	4	5 kA	0.45 A	24 V	VSPC 3/4WIRE 24 V DC	8924550000	8924740000	8924300000
RS232	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.5 A	24 V	MCZ OVP SL 24 V 0.5 A	8448940000		
RS422,V11	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.5 A	24 V	MCZ OVP SL 24 V 0.5 A	8448940000		
RS422A, V.11, X.27, RS423A	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
RS449	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
RS485	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.5 A	24 V	MCZ OVP SL 24 V 0.5 A	8448940000		
RS485	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC R485 2 CH	8924670000	8924710000	8924270000
RS232-C / V.24	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
TTL	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.5 A	24 V	MCZ OVP SL 24 V 0.5 A	8448940000		
TTY	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.5 A	24 V	MCZ OVP SL 24 V 0.5 A	8448940000		

Bus systems

Interface/ signal	Mounting	Connection system	Protected wires	Discharge capacity	Operating current	max. voltage	Protection device	Order No. Arrestor	Order No. Direct earthing base	Order No. Indirect earthing base
				8/20 µs	I _{max} .	DC				
ASI	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
BITBUS	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
BLN (Building Level Network)	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	28 V	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000
BLN (Building Level Network)	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	28 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
CAN-Bus	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
CANopen	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	12 V	MCZ OVP HF 12 V 0.3 A	8948610000		
C-BUS	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
C-Bus (Honeywell)	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	5 V	MCZ OVP HF 5 V 0.3 A	8948620000		
CC-LINK	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
Data Highway (Plus), DH+	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
DATEx P	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	24 V	MCZ OVP HF 24 V 0.3 A	8948600000		
Device Net	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	12 V	MCZ OVP HF 12 V 0.3 A	8948610000		
DeviceNet	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
DIN measurement bus	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	15 V	VSPC 1CL 12 V DC 0.5 A	8924450000	8924730000	8924290000
Dupline / Miniplex	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	28 V	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000

Bus systems

Interface/ signal	Mounting	Connection system	Protected wires	Discharge capacity	Operating current	max. voltage	Protection device	Order No. Arrestor	Order No. Direct earthing base	Order No. Indirect earthing base
				8/20 μ s	I _{max}	DC				
E1	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
EIB (European Installation Bus)	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	28 V	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000
ET 200	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	28 V	VSPC 1CL 5 V DC 0.5 A	8924420000	8924730000	8924290000
ET 200	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	5 V	MCZ OVP HF 5 V 0.3 A	8948620000		
Ethernet Cat.6	Plug-in adapter	RJ 45 connection	4	10 kA	1 A	48 V	V DATA Cat.6	1348590000		
Ethernet Cat.6	Adapter plug	RJ 45 connection	4	10 kA		48 V	JACKPAC® Ethernet Cat.6 IP20	8805550000		
FIPIO / FIPWAY	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
Genius I/O Bus	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL 12 V DC 0.5 A	8924440000	8924710000	8924270000
HDSL	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	24 V	MCZ OVP HF 24 V 0.3 A	8948600000		
IEC-BUS	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
Interbus	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	5 V	MCZ OVP HF 5 V 0.3 A	8948620000		
Interbus-Inline I/O	on DIN rail, compact	Tension clamp terminals	2	10 kA	1.25 A	53 V	MCZ OVP CL 48 V 1.25 A	8449040000		
LON™ (Works)	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	85 V	VSPC 1CL 48 V AC 0.5 A	8924520000	8924730000	8924290000
LON™ TP/XF 78	on DIN rail, compact	Tension clamp terminals	2	10 kA	0.5 A	28 V	MCZ OVP CL 24 V 0.5 A	8448920000		
LON™-Bus	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	12 V	MCZ OVP HF 12 V 0.3 A	8948610000		
LRE networks	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
LUXMATE-Bus	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	28 V	VSPC 2CL HF 24 V DC	8924510000	8924710000	8924270000
M-Bus	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	24 V	MCZ OVP HF 24 V 0.3 A	8948600000		
M-Bus (remote reading of meter)	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	28 V	VSPC 1CL 48 V AC 0.5 A	8924520000	8924730000	8924290000
MOD-Bus	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	5 V	MCZ OVP HF 5 V 0.3 A	8948620000		
MODBUS-(PLUS)	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
MPI Bus	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC R485 2 CH	8924670000	8924710000	8924270000
N1 LAN	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
N2 Bus	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	6.4 V	VSPC 2SL 5 V DC 0.5 A	8924210000	8924720000	8924280000
P-NET	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
Procontic CS31	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	15 V	VSPC 1CL 12 V DC 0.5 A	8924450000	8924730000	8924290000
Procontic CS31	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
Procontic T200	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
Profibus	on DIN rail, compact	Screw terminals	2	5 kA	0.3 A	5 V	VSSC 6 RS485 DP	1065010000		
(Profibus DP)	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC RS485 2 CH	8924670000	8924710000	8924270000
Profibus PA	on DIN rail, compact	Tension clamp terminals	2	10 kA	1.25 A	53 V	MCZ OVP CL 48 V 1.25 A	8449040000		
Profinet	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	5 V	MCZ OVP HF 5 V 0.3 A	8948620000		
Process Bus, Panel Bus	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
PSM-EG-RS422...	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
PSM-EG-RS485...	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
RACKBUS	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
SDLC	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
SDSL	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	185 V	VSPC Uko	8924660000	8924710000	8924270000
SecuriLan-LON™-Bus	on DIN rail, separable	Screw terminals	2	5 kA	0.45 A	15 V	VSPC 1CL 12 V DC 0.5 A	8924450000	8924730000	8924290000
SINEC L1	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
Sinec L2	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	5 V	MCZ OVP HF 5 V 0.3 A	8948620000		
SINEC L2 DP	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
TCP / IP	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	5 V	MCZ OVP HF 5 V 0.3 A	8948620000		
Token Ring	on DIN rail, compact	Tension clamp terminals	2	5 kA	0.3 A	5 V	MCZ OVP HF 5 V 0.3 A	8948620000		
TP/FTT 10+TP/LPT10	on DIN rail, compact	Tension clamp terminals	2	10 kA	1.25 A	53 V	MCZ OVP CL 48 V 12.5 A	8449040000		
U-BUS	on DIN rail, separable	Screw terminals	4	5 kA	2 A	72 V	VSPC GDT 2 CH 90 V 20 kA	8924570000	8924740000	8924300000



Product quick selection, data interfaces

Telecommunications

Interface/ signal	Mounting	Connection system	Protected wires	Discharge capacity	Operating current	max. voltage	Protection device	Order No. Arrestor	Order No. Direct earthing base	Order No. Indirect earthing base
				8/20 µs	I _{max}	DC				
ADSL	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	185 V	VSPC Uko	8924660000	8924710000	8924270000
ADVANT	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
HDSL	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	185 V	VSPC Uko	8924660000	8924710000	8924270000
SHDSL	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	185 V	VSPC Uko	8924660000	8924710000	8924270000
T-DSL	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	185 V	VSPC Uko	8924660000	8924710000	8924270000
Telephone analogue	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	185 V	VSPC Uko	8924660000	8924710000	8924270000
TTY, 0(4) - 20 mA	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	28 V	VSPC 2CL 24 V DC 0.5 A	8924470000	8924710000	8924270000
(Uko-Bus)	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	185 V	VSPC Uko	8924660000	8924710000	8924270000
V.35	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	6.4 V	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000
VDSL	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	185 V	VSPC Uko	8924660000	8924710000	8924270000
X.21/X.24	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000
X.25/X.31	on DIN rail, separable	Screw terminals	4	5 kA	0.45 A	15 V	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000

SIL certification for VSSC and VSPC

TUV NORD

Zertifikat

Certificate

Registrier-Nr.
Registration No.
44 799 11 394001-001

Zeichen des Auftraggebers Customer's reference	Auftragsdatum Date of order 16.03.2011	Aktenzeichen File reference 8000394001	Technischer Bericht Nr. Test report no. 11 799 394001-001
Name und Anschrift des Auftraggebers	Weidmüller Interface GmbH & Co. KG Klingenbergstrasse 16 32758 Detmold		Customer's name and address
Geprüft nach	EN 61508-2010 Funktionale Sicherheit sicherheitsbezogener elektrischer/elektronischer/programmierbarer elektronischer Systeme	Tested in accordance with	
Beschreibung des Produktes (Details siehe Anlage 1)	Überspannungsschutz / Overvoltage protection		Description of product (Details see Annex 1)
Typenbezeichnung	VARITECTOR SPC und SSC		Type Description
Bemerkung	Die einzelnen Typen der Überspannungsschutzserie können in SIL2 oder SIL3 Sicherheitskreisen eingesetzt werden! The single types of the overvoltage protection series can be used in SIL2 or SIL3 safety circuits. Die sichere Funktion bezieht sich auf den Einsatz in einem Kommunikationspfad! The safety function is intended for application in a communication path.		

Dieses Zertifikat bescheinigt das Ergebnis der Prüfung an den vorgestellten Prüfgegenstand. Eine allgemein gültige Aussage über die Qualität der Produkte aus der laufenden Fertigung kann hieraus nicht abgeleitet werden.
This certifies the result of the examination of the product sample submitted by the manufacturer. A general statement concerning the quality of the products from the series manufacture cannot be derived there from.

TUV NORD CERT GmbH
Zertifizierungsstelle / Certification body
Maschinen / Machinery

Gültig bis / Valid to: 12.04.2016

Hannover, 13.04.2011

Bitte beachten sie auch die umseitigen Hinweise
Please also pay attention to the information stated overleaf

Langemark: 20 • 45141 Essen • Fon +49 (0)201 825 9120 • Fax +49 (0)201 825 3208 • Email: probent@tuv-nord.de

TUV NORD

Anlage 1 zum Zertifikat Nr.:

Annex 1 to Certificate no.:

44 799 11 394001-001

Rev. 1

Aktenzeichen: 8000394001
File reference

Seite 1 von 2
Page 1 of 2

Allgemeine Angaben
General information

Typenbezeichnung
Type Description

Siehe Seite 1 des Zertifikates
See also page 1 of the Certificate

VARITECTOR SPC und VARITECTOR SSC

Übersicht Parameter VARITECTOR SSC / Overview Parameter VARITECTOR SSC

Type	safe detected As in 1-10 ⁻⁶ t/h	safe undetected As in 1-10 ⁻⁶ t/h	dangerous detected As in 1-10 ⁻⁶ t/h	dangerous undetected As in 1-10 ⁻⁶ t/h	SFF	PFH in 1-10 ⁻⁶ t/h	Max. SIL
VSSC4 CL	6,1	10,95	0	1,95	89,74%	1,95	2
VSSC4 CL FG	7,1	19,95	0	1,95	93,28%	1,95	3
VSSC4 SL	7	35,1	0	0,9	97,91%	0,9	3
VSSC4 SL FG	7	35,1	0	0,9	97,91%	0,9	3
VSSC4 MOV	2,5	22,75	0,75	0	100,00%	0	3
VSSC4 GDT	1	9	0	0	100,00%	0	3
VSSC4 TAZ	2,5	34,25	5,25	0	100,00%	0	3
VSSC4 RC	2,5	24,15	0,75	0,8	97,76%	0,8	3
VSSC8 CL	6,1	10,95	0	1,95	89,74%	1,95	2
VSSC8 CL FG	7,1	19,95	0	1,95	93,28%	1,95	3
VSSC8 TR CL	6,1	10,95	0	1,95	89,74%	1,95	2
VSSC8 TR CL FG	7,1	19,95	0	1,95	93,28%	1,95	3
VSSC8 SL	7	45,2	0	1,8	96,67%	1,8	3
VSSC8 SL FG	7	45,2	0	1,8	96,67%	1,8	3
VSSC8 TR SL	7	45,2	0	1,8	96,67%	1,8	3
VSSC8 TR SL FG	7	45,2	0	1,8	96,67%	1,8	3
VSSC8 MOV	2,5	22,75	0,75	0	100,00%	0	3
VSSC8 GDT	1	9	0	0	100,00%	0	3
VSSC8 TR MOV	2,5	32,85	0,75	0,9	97,57%	0,9	3
VSSC8 TR GDT	1	9	0	0	100,00%	0	3
VSSC8 TR TAZ	2,5	34,35	5,35	0,9	97,91%	0,9	3
VSSC8 RS485 DP	8	43,75	5	3,25	94,58%	3,25	3
VSSC8 RS485 PA	8,5	19,75	2	1,75	93,97%	1,75	3
VSSC8 RTD	8	44,25	7	3,75	94,05%	3,75	3
VSSC8 RTD EX	8	43,75	6	3,25	94,67%	3,25	3

TUV NORD

Anlage 1 zum Zertifikat Nr.:

Annex 1 to Certificate no.:

44 799 11 394001-001

Rev. 1

Aktenzeichen: 8000394001
File reference

Seite 2 von 2
Page 2 of 2

Übersicht Parameter VARITECTOR SPC / Overview Parameter VARITECTOR SPC

Type	safe detected As in 1-10 ⁻⁶ t/h	safe undetected As in 1-10 ⁻⁶ t/h	dangerous detected As in 1-10 ⁻⁶ t/h	dangerous undetected As in 1-10 ⁻⁶ t/h	SFF	PFH in 1-10 ⁻⁶ t/h	Max. SIL
VSPC CL	13,6	29,45	0	1,95	95,67%	1,95	3
VSPC CL R	17,1	57,4	0	3,7	95,27%	3,7	3
VSPC CL HF	15,6	30,45	0	2,95	93,96%	2,95	3
VSPC CL HF R	19,1	58,4	0	4,7	94,28%	4,7	3
VSPC SL	6	27,1	1	8,9	79,35%	8,9	2
VSPC SL R	8,5	55,05	1	10,85	86,02%	10,7	2
VSPC 34 WRB	36	107	0	7	95,33%	7,9	3
VSPC RS485	12	31,75	9	4,25	92,54%	4,25	3
VSPC RS485 R	15,5	59,7	9	6	93,35%	6,9	3
VSPC TELE UAD	15,6	30,45	0	2,95	93,96%	2,95	3
VSPC 1CL FWD	13,6	29,45	0	1,95	95,67%	1,95	3
VSPC GDT 2CH	6	5	0	0	100,00%	0,9	3
VSPC MOV 2CH	2,5	22,75	0,75	0	100,00%	0,9	3
VSPC MOV 2CH R	2,5	73,95	0,75	0	100,00%	0,9	3
VSPC TAZ 2CH	2,5	34,25	5,25	0	100,00%	0,9	3
VSPC TAZ 4CH	2,5	34,25	5,25	0	100,00%	0,9	3

Dieses Zertifikat bescheinigt das Ergebnis der Prüfung an den vorgestellten Prüfgegenstand. Eine allgemein gültige Aussage über die Qualität der Produkte aus der laufenden Fertigung kann hieraus nicht abgeleitet werden.
This certifies the result of the examination of the product sample submitted by the manufacturer. A general statement concerning the quality of the products from the series manufacture cannot be derived there from.

TUV NORD CERT GmbH
Zertifizierungsstelle / Certification body
Maschinen / Machinery


Gültig bis / Valid to: 12.04.2016

Hannover, 13.04.2011

Bitte beachten sie auch die umseitigen Hinweise
Please also pay attention to the information stated overleaf

Langemark: 20 • 45141 Essen • Fon +49 (0)201 825 9120 • Fax +49 (0)201 825 3208 • Email: probent@tuv-nord.de

Lightning and surge protection for control and instrumentation signals




breakdowns or malfunctions can lead to exorbitant costs. As the standards covering low control voltages do not specify many parameters, the use of surge protection, apart from lightning protection zoning concepts, has to be classified according to type of signal, application circuit and the anticipated interference voltage phenomena.

Types of interference voltage


Transient surges coupled into a system via one or more coupling mechanisms occur as normal- or common-mode interference. These are measured as longitudinal or transverse voltages and, depending on the circuit, designated as symmetrical or asymmetrical voltages. (For further information see the "Principles" chapter.)

Basic classification

The current scope of automation technology has resulted in a wide range of applications for surge protection in the field of instrumentation and control engineering. One important prerequisite is the consistent use of coordinated surge protection in all sections of the plant or building. In industry, instrumentation and control systems are important areas and



Common-mode interference (asymmetrical interference): Common-mode voltage between conductor and reference potential. (earth)/mainly caused by capacitive coupling (electrical field)



Normal-mode interference (symmetrical interference): Normal-mode voltage between supply and return conductor load and interference source connected in series, e.g. inductive (magnetic field) or conductive coupling (common impedance)

Types of signal

Binary signals SL $\triangleq$ (symmetrical loop)


These are two-wire signals with a common reference potential which are required by, for example, by switches, PLC switch outputs, photoelectric barriers, position sensors, solenoid valves, warning lamps, PLC inputs, etc. Normally, these signals have a common reference potential that can be either connected or not connected to earth potential, depending on the type of protection. The coupled transient interference is primarily common-mode interference.

Analogue signals CL $\triangleq$ (current loop)

Measuring circuits are normally designed as two-wire current loops or voltage signals without a common reference potential, like the 0(4)...20 mA current loop. The coupled transient interference is primarily normal-mode interference. For temperature measurements with the PT100 measuring shunt in the three-wire version, the voltage drop at the shunt is measured via the third wire. This must be included in the system of protection. The PT100 measuring shunt is also available in a four-wire version in which the voltage drop at the shunt is measured via the two additional lines without additional line losses in the PT100 measuring circuit. The coupled transient normal-mode interference occurs between the various wires.


Essential information for users can be found in the IEC 61643-22 standard (application standard for measurement and control signals) and in the IEC 62305-4 standard (application standard for installing internal lightning protection). It is important to determine which protection category is required. There are divisions for D1 (lightning protection), C2 (surge protection / overvoltage protection) and C1 (end device protection). These categories or classes are specified for the following products. All products were subjected to a test in accordance with product standard IEC 61643-21.

Binary signals




Two-wire, usually with common reference potential, e.g. signals from binary sensors, actuators and indicators such as limit switches, probes, position sensors, photoelectric barriers, contactors, solenoid valves, warning lamps.

Protection for binary signals connected to earth potential.



Protection for binary signals not connected to earth potential.



Protection for two-, three- and four-wire versions.

Type

VSPC 2SL **Page A.30**
VSPC 4SL **Page A.34**
VSPC 3/4 **Page A.38**

VSPC GDT **Page A.40**
VSPC MOV **Page A.42**
VSPC TAZ **Page A.44**
VSPC UKO **Page A.46**

VSSC6 SL LD **Page A.76**
VSSC6 TR SL LD **Page A.78**
VSSC6 SLFG LD **Page A.76**
VSSC6 TR SLFG LD **Page A.78**

VSSC6 MOV **Page A.80**
VSSC6 TR LD MOV **Page A.82**
VSSC6 GDT **Page A.84**
VSSC6 TR GDT **Page A.86**
VSSC6 TAZ **Page A.88**
VSSC6 TR LD TAZ **Page A.88**
VSSC6 RTD **Page A.92**


Type

VSSC4 SL **Page A.98**
VSSC4 SL FG **Page A.98**
VSSC4 MOV **Page A.100**
VSSC4 GDT **Page A.102**
VSSC4 TAZ **Page A.104**
VSSC4 RC **Page A.106**

VSPC 2SL EX **Page A.144**
VSPC 4SL EX **Page A.146**
VSPC 3/4 wire EX **Page A.148**
VSSC4 SL FG EX **Page A.158**
VSSC4 GDT EX **Page A.160**
VSSC6 RTD EX **Page A.166**
VSSC6 TR SL FG EX **Page A.162**

MCZ OVP SL **Page A.115**
MCZ OVP SL FG **Page A.118**
MCZ OVP Filter **Page A.119**

Analogue signals






Two-, three- and four-wire versions without common reference potential.



Signals from current loops (analogue measurements from sensors over long distances), 4...20 mA, 0...20 mA, etc., e.g. level measurements.



Signals from voltage sensors (analogue measurements from sensors over short distances), 0...10 V, PT100, etc., e.g. temperature measurements.



Type

VSPC 1CL **Page A.16**
VSPC 2CL **Page A.20**
VSPC 1CL PW **Page A.28**
VSPC RS485 **Page A.48**

VSSC6 CL **Page A.72**
VSSC6 TR CL **Page A.74**
VSSC6 CLFG **Page A.72**
VSSC6 TR CLFG **Page A.74**
VSSC6 RS485 **Page A.90**
VSSC6 RS485 DP **Page A.90**
VSSC6 RS232 **Page A.90**

VSSC4 CL **Page A.96**
VSSC4 CL FG **Page A.96**

VSPC 1CL EX **Page A.138**
VSPC 2CL EX **Page A.140**
VSPC 1CL PW EX **Page A.142**
VSSC4 CL FG EX **Page A.156**
VSSC6 TR CLFG EX **Page A.162**
VSSC6 RS485 EX **Page A.164**

Type

MCZ OVP HF **Page A.112**
MCZ OVP CL **Page A.114**

VARITECTOR SPC

Pluggable lightning and surge protection for measurement and control circuits


Pluggable lightning and surge protection for 2 analogue signals or 4 binary signals in measurement/control circuits – with integrated error detection and alert functions in only 17.8 mm width.

Our pluggable VARITECTOR SPC surge protection is characterised by highest protective functions with compact dimensions. The arrestor of the modules can be removed, measured or exchanged during running operation impedance-neutral – without interrupting the measuring circuit. These features make this product the ideal secure protection mechanism for interfaces within instrumentation and control circuits.

Maintenance intervals are simplified by the V-TEST test unit, which is used for testing the function of the VARITECTOR SPC. This test method satisfies the requirements of standard IEC 62305.

With the VARITECTOR SPC R modules, error detection and error messages are realised by internal monitoring. The green LED indicates the active protective function. The red LED indicates a fault condition. This information is transmitted to the V-Control evaluation unit. From there, the information can be sent across to e.g. a controller.

Due to the impedance-neutral removing of the arrestor, the VARITECTOR SPC modules can be used instead of terminals. For four binary signals or two analogue signals, just 17.8 mm of space on the mounting rail is used. By simply snapping onto a grounded mounting rail, time savings are also ensured when connecting. A colour code identifies the various voltage levels for all VARITECTOR SPC modules. This simplifies maintenance work during operation. The EMC set offers additional convenience for connecting shielded cables. All VARITECTOR products comply with the latest IEC 61643-21 requirement for a new overstress mode.




Space-saving

Saves space in the switching cabinet: 4 binary signals or 2 analogue signals on 17.8 mm.



Standard-conformant

Usable in accordance with installations standard IEC 62305 safely discharges high impulse currents up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE. Tested for class D1, C1 and C2 to IEC 61643-21.





Monitoring function


Status display and message function: the protective function can be evaluated externally.



Quick identification

Colour-coded marking: simple identification of the different voltage levels in the switching cabinet.

$\leq 12\text{ V}$	= green
24 V	= binary signal, blue
24 V	= analogue signal, yellow
48 V	= red
60 V	= violet
special function	= white



Large variety

A solution for every type of surge protection: current loops and binary signals as well as integrated components and combinations of current loops and voltage supply e.g. 24 V.



Accessories

V-TEST

Instrument for testing the protective function of the product family VSPC to IEC 62305 (periodic testing).



VARITECTOR SPC

Pluggable surge protection for the measurement and control industry VARITECTOR SPC

Weidmüller's VARITECTOR SPC pluggable surge protection is remarkable for its combination of extremely high protective functionality and compact dimensions. It is suited for use in measurement and control circuits. The size is made possible by the selection of INSTA dimensions, with a width of 17.8 mm (1TE).

Two versions are available:

- VSPC: a surge protector **with no** monitoring function
- VSPC R: a surge protector **with** monitoring function

The base components are plugged in to form a direct earthing contact via the mounting rail. This saves you time when making the connection. The VARITECTOR SPC series is optimally designed for compact installations in process automation, industrial automation and building automation. The two-stage surge-protection base components are equipped with gas discharge tubes, suppressor diodes (TVS) and decoupling components. Individual protective components (such as gas-filled spark gaps, varistors and suppressor diodes) supplement this product line. IEC 62305 requires that a periodic inspection of surge protection products be conducted. The functionality of all VARITECTOR SPC modules can be tested using testing equipment (such as the V-TEST Basic) that is available separately. The VARITECTOR SPC R modules also feature an internal monitoring function. The green LED signals when the protection function is ready. The red LED signals an error.

Up to ten modules can be wired together in succession. The modules alert an evaluative module (the VSPC CONTROL UNIT) in the event of an error. VARITECTOR SPC series surge protection is available with rated voltages of 5 V, 12 V, 24 V, 48 V and 60 V. The product's voltage level is colour-coded on the pluggable arrester. An earthing contact is established by snapping onto an earthed TS 35 rail. The TS 35 must be earthed in order to ensure safe power discharging via the terminals of up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s). The rail must be screwed onto the earthed mounting plate for reasons of EMC. In order to optimise the protective function, a PE-contact connection should be made over the VSPC module every 60 cm for equipotential bonding. The pluggable protective element can be pulled out during operations without interrupting the measurement circuit. A testing instrument, available as a Weidmüller accessory, allows you to test the protective element in compliance with the IEC 62305-3 directive. The accessory also includes a simple mechanism for applying the wire shield.





Overview of model types

A VARITECTOR SPC (VSPC) consists of a **pluggable component** and a separate **base component (VSPC BASE)**.

Explanation of terms:

CL = current loop / analogue signals

SL = symmetric loop - for binary signals



VSPC 2CL (CL = current loop) is a two-stage protective combination with a gas discharge tube and a suppressor diode located between the current paths. This VSPC 2CL limits the surge voltage within **two analogue signal circuits** (such as for current loops). This pluggable component can be inserted into the base (VSPC BASE 2CL). The base (VSPC BASE FG 2CL) is used when working with signal circuits which are not earthed. The VSPC 2CL HF is used in order to avoid influencing high-frequency signal circuits (this also includes the VSPC RS485 and the VSPC UKO). This protective combination is also inserted into the base mentioned above.


Monitoring function

The **VSPC 2CL R** products feature monitor and alert functions. As well as the alert function, there are two channels available for current loops in a single housing. The special VSPC BASE 2CL R and SPC BASE 2CL FG R bases





transfer the alert function to a 2-pole screw/plug-in connection in the bases and to the VSPC CONTROL UNIT.




VSPC 1CL

The **VSPC 1CL** is a two-stage protective combination with a gas discharge tube and a suppressor diode located between the current paths. This VSPC 1CL limits the surge voltage within **one analogue signal circuit** (such as for current loops). This pluggable component can be inserted into the base (VSPC BASE 1CL). The base (VSPC BASE FG 1CL) is used when working with signal circuits which are not earthed.

Monitoring function

The **VSPC 1CL R** products feature monitor and alert functions. All channels remain despite the alert function. The special VSPC BASE 1CL R and VSPC BASE 1CL FG R bases transfer the alert function to a 2-pole screw/plug-in connection in the bases and to the VSPC CONTROL UNIT.




VSPC 4SL

The **VSPC 4SL** is a two-stage protective combination with a gas discharge tube and a suppressor diode from the current path to the PE. This VSPC 4SL limits the surge voltage within **four binary signal circuits** (such as for alert contacts). This pluggable component can be inserted into the base (VSPC BASE 4SL). The base (VSPC BASE FG 4CL) is used

when working with signal circuits which are not earthed.

Monitoring function

The **VSPC 4SL R** products feature monitor and alert functions. Even with the alert function, there are still channels available for the four binary signal circuits in a single housing. The special VSPC BASE 4SL R base transfers the alert function to a 2-pole screw/plug-in connection in the base and to the VSPC CONTROL UNIT.




VSPC 2SL

The **VSPC 2SL** is a two-stage protective combination with a gas discharge tube and a suppressor diode from the current path to the PE. This VSPC 2SL limits the surge voltage within **two binary signal circuits** (such as for alert contacts). This pluggable component can be inserted into the base (VSPC BASE 2SL). The base (VSPC BASE 2CL FG) is used when working with signal circuits which are not earthed.


Monitoring function

The VSPC 2SL R products feature monitor and alert functions. Even with the alert function, there are still channels available for the two binary signal circuits in a single housing. The special VSPC BASE 2SL R base transfers the alert function to a 2-pole screw/plug-in connection in the base and to the VSPC CONTROL UNIT.



VSPC 3/4WIRE


The **VSPC 3/4WIRE** is a two-stage protective combination with a gas discharge tube and a suppressor diode from the current path to the GND. This VSPC 3/4WIRE limits the surge voltage within four temperature-measurement circuits (such as for DMS or PT100/100 sensors). For non-earthed measurement circuits, we recommend using the base (VSPC BASE FG 4CL).




VSPC GDT

VSPC MOV 2CH, VSPC TAZ 2CH and VSPC GDT 2CH


Four cables can be protected with the 2CH modules. By wiring the connections differently, either two no-voltage signal lines or four binary signal lines can be protected. Two three-pole gas discharge tubes (GDTs) are used for the VSPC GDT 2CH. This universal protective circuitry limits the voltage between the signal lines and also between each signal line and the PE.



VSPC TAZ




VSPC RS422/485



VSPC MOV

The **VSPC MOV 2CH** and **TAZ 2CH** offer one-stage protection with a varistor (MOV) or suppressor diode (TAZ or TVS) between the current paths. This makes it possible to protect a no-voltage (floating) signal circuit. Two binary signal circuits can also be protected if terminals 1 and 7 are assigned to GND / PE. These VSPC pluggable components are inserted into the base (VSPC BASE 2/4CH). The base (VSPC BASE 2/4CH FG) is used when working with signal circuits which are not earthed.



VSPC 1CL PW

VSPC 1CL PW (power and signal 1CL) offers combined protection that is suitable for the 24 V DC power supply and the current loops within a device. This VSPC protects sensors with an additional 24 V DC.

The **VSPC RS485** is a two-stage protective combination with a gas discharge tube and a suppressor diode located between the current paths. This VSPC RS485 limits the surge voltage within **two high-frequency signal circuits**. This pluggable component can be inserted into the base (VSPC BASE 2CL). The base (VSPC BASE FG 2CL) is used when working with signal circuits which are not earthed.

Monitoring function

The **VSPC RS485 R** product features monitoring and alert functions. Even with the alert function, there are still two channels available for current loops in a single housing. The special VSPC BASE 2CL R and VSPC BASE 2CL FG R bases transfer the alert function to a 2-pole screw/plug-in connection in the bases and to the VSPC CONTROL UNIT.

Earthing unit and test plug

The earthing unit can be used during installation to short out the connected wires to earth. The earthing unit is swapped out for a VSPC pluggable component before the initial commissioning. The test plug has 2.3-mm sockets. These sockets can be used by a meter to check the connected measurement circuit.

Applications

The pluggable INSTA housing was created in compliance with DIN 43880. It consists of a lower section (the VSPC BASE) and a pluggable component (the VSPC). The VSPC BASE is made from black PA6.6 V0. The pluggable component is made from red PA6.6 V0. The temperature range is from -40 °C to + 70 °C. The VSPC series has been tested to comply with IEC 61643-21 04/2008 and EN 61643-21. Modules were tested with categories C1, C2 and C3: with quick-rising edges with up to 300 pulses. Category D1 describes high power testing (10/350 µs lightning protection), so that the VSPC can be used according to IEC 62305-4. The base and pluggable components are colour coded according to the voltage level. This makes installation easier.

Colour coding


The pluggable components transfer their coding to the base element when they are plugged in for the first time. The voltage levels are also labelled with coloured Dekafix markers applied to the VSPC pluggable component. This gives you a better overview within the electrical cabinet.

Voltage level	Colour
≤ 12 V	green
24 V Binary	blue
24 V Analogue	yellow
48 V	red
≥ 60 V	violet
Special function	white

Test possibility / V-TEST

Because the modules are pluggable, it is possible to test the VSPC visually or by using a V-TEST testing device. The VSPC can be easily tested; the user needs only to insert the VSPC pluggable component into the V-TEST. The result is then shown on the display. The VSPC R modules also feature an internal monitoring function for the arrester. An error is displayed at the defective module. The VSPC CONTROL UNIT can then transfer an alert to the control room.

Reoccurring tests / V-TEST




The IEC 62305-3 requires testing and maintenance for lightning protection systems. This includes the testing of the arresters used in the system.

Class of protection	Interval for complete testing	Interval for visual inspection
I/II	2 years	1 year
III/IV	4 years	2 years


Caution! These periodic inspections may be extended with stricter requirements pertaining to special applications or regions.

Remote error diagnostics



When the VSPC module labelled "R" is inserted into the corresponding "R" base component, it is then possible to use the outage alert function via a two-pole plug. This screw/plug-in connection has a clamping range from 0.5 to 1.5 mm².


The wire stripping length is 6 to 6.5 mm. A screwdriver with a 2-mm blade width is used to turn the screw. The VSPC Rs are connected in succession to the VSPC CONTROL UNIT evaluative module. Up to ten VSPC Rs can be connected in succession to the VSPC CONTROL UNIT. The evaluative module is supplied with 24 V DC. It is then responsible for the switching and for the voltage supply to the VSPC modules. A no-voltage (floating) CO contact can then be used to alert in the event of an outage. The error on the module, with the LED changing colour from green to red. An automatic reset is carried out by the VSPC CONTROL UNIT within one minute after the failed VSPC pluggable component is replaced.



Installation

The VSPC series is appropriate for protecting signal circuits. In order to achieve a complete protective strategy for the facility, the power feed must be protected against Type II surge voltages (for example, by using our VPU II series). For existing lightning protection facilities, Type I protection must be used (for example, by using our VPU I series). Type II protection (for example, our VPU II) is sufficient when there is no lightning protection in place.

Fusing



The VSPC surge protection modules are designed so that they are decoupled between the individual protective stages.

The following must be observed when providing fuse protection externally:

- Max. rated current
- Deratings curve
- Type of installation
- Application



VARITECTOR SPC

Discharge capacity

Testing is conducted using voltage and current pulses according to the IEC 61643-21 standard concerning surge protection in networks which process signals.

Category	Testing pulse	Surge voltage	Surge current	Pulse	Type
C1	Quick rising edge	0.5-2 kV with 1.2/50 µs	0.25-1 kA with 8/20 µs	300	Surge voltage arrester
C2	Quick rising edge	2-10 kV with 1.2/50 µs	1-5 kA with 8/20 µs	10	Surge voltage arrester
C3	Quick rising edge	≥ 1 kV with 1 kV/µs	10-100 A with 10/10.000 µs	300	Surge voltage arrester
D1	High power	≥ 1 kV	0.5-2.5 kA with 10/350 µs	2	Arrester for lightning current and surge voltages

Category C reflects the interference pulses with quick-rising edges and minimised power. Category D uses quick-rising edges and high power to detail the interference pulses. This energy simulates the high-power load that stems from coupled partial lightning currents.

Error mode

The VSSC and VSPC series are tested pursuant to IEC/EN 61643-21 and meet Mode 1 and 2 requirements.

More information can be found in Chapter W.

General technical data

Storage temperature -40 °C...+80 °C
Operating temperature: -40 °C...+70 °C
Air humidity 5%...96% RH with no condensation
Material: V0, IP 20

Connection: screw connection
screwdriver blade: 0.6 x 3.5 DIN 5264
(for example, 0.6x3.5x200,
order no. 9010110000)
rated torque: 0.5 Nm
max. torque: 0.8 Nm
stripping length: 7 mm
solid: 0.5...4 mm²
flexible: 0.5...2.5 mm²
wire-end ferrule with plastic collar:
0.5...2.5 mm²

Remote signalling connection:
screw connection
screwdriver blade: 0.4 x 2.0 DIN 5264
(for example, SD 0.4x2.0x60,
order no. 9037160000)
max. torque: 0.2 Nm
stripping length: 6...6.5 mm
solid: 0.5...1.5 mm²

Dimensions

Height: 90 mm
Height: with remote signalling contact:
98 mm
Depth: 69 mm
Width: 17.8 mm

Accessories

Markers

The VSPC BASE lower section can be labelled with Dekafix-5 markers. The VSPC pluggable modules are colour coded with Dekafix-5 markers according to their rated voltage.

V-TEST

Testing device for functional tests of the pluggable VSPC surge protection.



VSPC Ground

This plug is attached to unused wires in the base element, so that all wires have the same potential.

VARITECTOR SPC – Choice of device depending on the interface

Interface	Pluggable arrestor	Order No. Arrestor	Order No. Base	Order No. Base floating ground (FG)	Pluggable arrestor with operation message (R)	Order No. Arrestor	Order No. Base	Order No. Base floating ground (FG)
0(4) ... 20 mA	VSPC 2CL 24 V DC 0.5 A	8924470000	8924710000	8924270000	VSPC 2CL 24 V DC 0.5 A R	8951480000	8951710000	8951720000
0(4) ... 20 mA	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000	VSPC 1CL 12 V DC 0.5 A R	8951540000	8951730000	8951740000
0 ... 10 V	VSPC 2CL 24 V DC 0.5 A	8924470000	8924710000	8924270000	VSPC 2CL 24 V DC 0.5 A R	8951480000	8951710000	8951720000
0 ... 10 V	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000	VSPC 1CL 12 V DC 0.5 A R	8951540000	8951730000	8951740000
ADSL	VSPC Uko	8924660000	8924710000	8924270000				
ADVANT	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
ARCNET (Plus)	VSPC RS485 2ch	8924670000	8924710000	8924270000	VSPC RS485 2ch R	8951670000	8951710000	8951720000
ASI	VPU III R 48 V DC	1351600000			VPU III R 48 V DC	1351600000		
	VPU III R 24 V DC	1351580000			VPU III R 24 V DC	8860360000		
BIBBUS	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL 12 V DC 0.5 A R	8951470000	8951710000	8951720000
BLN (Building Level Network)	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL 12 V DC 0.5 A R	8951470000	8951710000	8951720000
	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000	VSPC 1CL 12 V DC 0.5 A R	8951540000	8951730000	8951740000
CAN-Bus	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
C-BUS	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
CC-LINK	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
Data Highway (Plus), DH+	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
Datex-P	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
DeviceNet	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
DIN measurement bus	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
Dupline/Miniplux	VSPC 1CL 12 V DC 0.5 A	8924450000	8924730000	8924290000	VSPC 1CL 12 V DC 0.5 A R	8951540000	8951730000	8951740000
EIB (European Installation Bus)	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000	VSPC 1CL 24 V DC 0.5 A R	8951550000	8951730000	8951740000
ET 200	VSPC 1CL 5 V DC 0.5 A	8924420000	8924730000	8924290000	VSPC 1CL 5 V DC 0.5 A R	8951530000	8951730000	8951740000
E1	VSPC Uko	8924660000	8924710000	8924270000				
	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
FIPIO/FIPWAY	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
Genius I/O Bus	VSPC 2CL 12 V DC 0.5 A	8924440000	8924710000	8924270000	VSPC 2CL 12 V DC 0.5 A R	8951470000	8951710000	8951720000
Hart	VSPC 1CL 24 V DC 0.5 A	8924480000	8924730000	8924290000	VSPC 1CL 24 V AC 0.5 A R	8951560000	8951730000	8951740000
HDSL	VSPC Uko	8924660000	8924710000	8924270000				
IEC-BUS	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
ISDN Basic connection (Uko-Bus)	VSPC Uko	8924660000	8924710000	8924270000				
Cathodic corrosion prevention	VSPC GDT 2ch 90 V 20 kA	8924570000	8924740000	8924300000				
LON™ (Works)	VSPC 1CL 48 V AC 0.5 A	8924520000	8924730000	8924290000				
LRE networks	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
LUXMATE-Bus	VSPC 2CL HF 24 V DC	8924510000	8924710000	8924270000	VSPC 2CL HF 24 V DC R	8951700000	8951710000	8951720000
M-Bus (Remote readout of counter)	VSPC 1CL 48 V AC 0.5 A	8924520000	8924730000	8924290000	VSPC 1CL 24 V DC 0.5 A R	8951550000	8951730000	8951740000
MODBUS-(PLUS)	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
MPI-Bus	VSPC RS485 2ch	8924670000	8924710000	8924270000				
N1 LAN	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
N2 Bus	VSPC 2SL 5 V DC 0.5 A	8924210000	8924720000	8924280000	VSPC 2SL 5 V DC 0.5 A R	8951610000	8951770000	8951780000
P-NET	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
Proconic CS31	VSPC 1CL 12 V DC 0.5 A	8924450000	8924730000	8924290000	VSPC 1CL 12 V DC 0.5 A R	8951540000	8951730000	8951740000
	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
Proconic T200	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
Profibus DP (FMS)	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
Process-Bus	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
Panel-Bus								
PT100	VSPC 3/4WIRE 24 V DC	8924550000	8924740000	8924300000				
P-Bus	VPU III R 24 V DC	1351580000			VPU III R 24 V DC	1351580000		
PSM-EG-RS422...	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
PSM-EG-RS485...	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
RACKBUS	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
RS422A, V.11, X.27, RS423A	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
RS449	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
RS485	VSPC RS485 2ch	8924670000	8924710000	8924270000	VSPC RS485 2ch R	8951670000	8951710000	8951720000
RS232-C/V.24	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
SDLC	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
SDSL	VSPC Uko	8924660000	8924710000	8924270000				
SecuriLan-LON™-Bus	VSPC 1CL 12 V DC 0.5 A	8924450000	8924730000	8924290000	VSPC 1CL 12 V DC 0.5 A R	8951540000	8951730000	8951740000
SHDSL	VSPC Uko	8924660000	8924710000	8924270000				
SINEC L1	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
SINEC L2 DP	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
Profibus DP	VSPC RS485 2ch	8924670000	8924710000	8924270000	VSPC RS485 2ch R	8951670000	8951710000	8951720000
T-DSL	VSPC Uko	8924660000	8924710000	8924270000				
Telephone analog	VSPC Uko	8924660000	8924710000	8924270000				
TTY, 0(4) - 20 mA	VSPC 2CL 24 V DC 0.5 A	8924470000	8924710000	8924270000	VSPC 2CL 24 V DC 0.5 A R	8951480000	8951710000	8951720000
U-BUS	VSPC GDT 2ch 90 V 20 kA	8924570000	8924740000	8924300000				
VDL	VSPC Uko	8924660000	8924710000	8924270000				
V.35	VSPC 2CL HF 5 V DC	8924430000	8924710000	8924270000	VSPC 2CL HF 5 V DC R	8951680000	8951710000	8951720000
X.21/X.24	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000
X.25/X.31	VSPC 2CL HF 12 V DC	8924460000	8924710000	8924270000	VSPC 2CL HF 12 V DC R	8951690000	8951710000	8951720000


This table contains recommendations for the choice of device. Our technical consultants will be glad to assist you with your individual requirements.



VARITECTOR SPC


VSPC 1CL - protection for one analogue signal

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I ₁ (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Dimensions of complete module (arrester + base element)		no remote sig. contact
Height x width x depth	mm	90 / 17.8 / 69
Note		
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.		

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 1CL FG	1	8924290000
Base element, direct earthing	VSPC BASE 1CL	1	8924730000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section.
-------------	---



VSPC 1CL - arrester / plug-in elements



Ordering data

	VSPC 1CL 5 V DC	VSPC 1CL 12 V DC	VSPC 1CL 24 V DC	VSPC 1CL 24 V AC
Rated voltage (AC)				24 V
Rated voltage (DC)	5 V	12 V	24 V	34 V
Max. continuous voltage, U_c (AC)				28 V
Max. continuous voltage, U_c (DC)	6.4 V	15 V	28 V	40 V
Rated current I_n	450 mA	450 mA	450 mA	450 mA
Input attenuation	730 KHz	1.7 MHz	2.4 MHz	2.7 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 450 ms
Residual voltage, U_r typical	< 800 V	< 800 V	< 800 V	< 800 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	12 V	25 V	45 V	60 V
Protection level wire-wire 8/20 μ s, type	12 V	25 V	45 V	60 V
Protection level wire-PE 1kV/ μ s, type	450 V	450 V	450 V	450 V
Protection level wire-PE 8/20 μ s, type	< 800 V	< 800 V	< 800 V	< 800 V

Ordering data

without function indicator	Type	VSPC 1CL 5VDC	VSPC 1CL 12VDC	VSPC 1CL 24VDC
Order No.		8924420000	8924450000	8924480000
Qty.		1	1	1
Note				

Ordering data

	VSPC 1CL 48 V AC	VSPC 1CL 60 V AC
Rated voltage (AC)	48 V	60 V
Rated voltage (DC)	68 V	85 V
Max. continuous voltage, U_c (AC)	60 V	72 V
Max. continuous voltage, U_c (DC)	85 V	102 V
Rated current I_n	350 mA	250 mA
Input attenuation	4.8 MHz	7.3 MHz
Pulse-reset capacity	≤ 500 ms	≤ 500 ms
Residual voltage, U_r typical	< 800 V	< 800 V
Protection level		
Protection level wire-wire 1kV/ μ s, type	85 V	100 V
Protection level wire-wire 8/20 μ s, type	85 V	100 V
Protection level wire-PE 1kV/ μ s, type	450 V	450 V
Protection level wire-PE 8/20 μ s, type	< 800 V	< 800 V

Ordering data


without function indicator	Type	VSPC 1CL 48VAC
Order No.		8924520000
Qty.		1
Note		



VARITECTOR SPC


VSPC 1CL - protection for one analogue
signal with remote alert

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Dimensions of complete module (arrester + base element)	with remote signalling (R)
Height x width x depth	mm 98 / 17.8 / 69

Note The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing with remote contact	VSPC BASE 1CL R	1	8951730000
Base element, indirect earthing with remote contact	VSPC BASE 1CL FG R	1	8951740000

Note Technical data can be found at the beginning of the VARITECTOR SPC section.
Order with VSPC CONTROL UNIT.

VSPC 1CL - arrester / plug-in components
with remote alert



Ordering data

	VSPC 1CL 5 V DC R	VSPC 1CL 12 V DC R	VSPC 1CL 24 V DC R	VSPC 1CL 24 V AC R
Rated voltage (AC)				24 V
Rated voltage (DC)	5 V	12 V	24 V	34 V
Max. continuous voltage, U_c (AC)				28 V
Max. continuous voltage, U_c (DC)	6.4 V	15 V	28 V	40 V
Rated current I_n	450 mA	450 mA	450 mA	450 mA
Signalling contact	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace
Input attenuation	730 KHz	1.7 MHz	2.4 MHz	2.6 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 450 ms
Residual voltage, U_p typical	< 800 V	< 800 V	< 800 V	< 800 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	12 V	25 V	45 V	60 V
Protection level wire-wire 8/20 μ s, type	12 V	25 V	45 V	60 V
Protection level wire-PE 1kV/ μ s, type	450 V	450 V	450 V	450 V
Protection level wire-PE 8/20 μ s, type	< 800 V	< 800 V	< 800 V	< 800 V

Ordering data					
with function indicator	Type	VSPC 1CL 5VDC R	VSPC 1CL 12VDC R	VSPC 1CL 24VDC R	VSPC 1CL 24VAC R
	Order No.	8951530000	8951540000	8951550000	8951560000
	Qty.	1	1	1	1
Note					






VARITECTOR SPC


VSPC 2CL - protection for two analogue signals

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data


Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Complete module, direct earthing



Complete module, indirect earthing



Dimensions of complete module (arrester + base element)	no remote sig. contact
Height x width x depth	mm 90 / 17.8 / 69

Note	The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.
-------------	---

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 2CL FG	1	8924270000
Base element, direct earthing	VSPC BASE 2CL	1	8924710000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section.
-------------	---



VSPC 2CL - arrester / plug-in elements



Ordering data

	VSPC 2CL 5 V DC	VSPC 2CL 12 V DC	VSPC 2CL 24 V DC	VSPC 2CL 24 V AC
Rated voltage (AC)				24 V
Rated voltage (DC)	5 V	12 V	24 V	24 V
Max. continuous voltage, U_c (AC)				28 V
Max. continuous voltage, U_c (DC)	6.4 V	15 V	28 V	40 V
Rated current I_n	450 mA	450 mA	450 mA	450 mA
Input attenuation	730 KHz	1.7 MHz	2.3 MHz	2.7 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 450 ms
Residual voltage, U_r typical	< 800 V	< 800 V	< 800 V	< 800 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	12 V	25 V	45 V	60 V
Protection level wire-wire 8/20 μ s, type	12 V	25 V	45 V	60 V
Protection level wire-PE 1kV/ μ s, type	450 V	450 V	450 V	450 V
Protection level wire-PE 8/20 μ s, type	< 800 V	< 800 V	< 800 V	< 800 V

Ordering data

		VSPC 2CL 5VDC	VSPC 2CL 12VDC	VSPC 2CL 24VDC	VSPC 2CL 24VAC
without function indicator	Type				
	Order No.	8924400000	8924440000	8924470000	8924490000
	Qty.	1	1	1	1
Note					

Ordering data

	VSPC 2CL 48 V AC
Rated voltage (AC)	48 V
Rated voltage (DC)	68 V
Max. continuous voltage, U_c (AC)	60 V
Max. continuous voltage, U_c (DC)	85 V
Rated current I_n	350 mA
Input attenuation	4.8 MHz
Pulse-reset capacity	≤ 500 ms
Residual voltage, U_r typical	< 800 V
Protection level	
Protection level wire-wire 1kV/ μ s, type	85 V
Protection level wire-wire 8/20 μ s, type	85 V
Protection level wire-PE 1kV/ μ s, type	450 V
Protection level wire-PE 8/20 μ s, type	< 800 V


Ordering data

		VSPC 2CL 48VAC
without function indicator	Type	
	Order No.	8951490000
	Qty.	1
Note		

VARITECTOR SPC


VSPC 2CL - protection for two analogue signals with remote alert

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data


Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Complete module, direct earthing, with remote alert



Complete module, indirect earthing, with remote alert



Dimensions of complete module (arrester + base element) with remote signalling (R)

Height x width x depth mm 98 / 17.8 / 69

Note The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing with remote contact	VSPC BASE 2CL R	1	8951710000
Base element, indirect earthing with remote contact	VSPC BASE 2CL FG R	1	8951720000

Note Technical data can be found at the beginning of the VARITECTOR SPC section.
Order with VSPC CONTROL UNIT.

VSPC 2CL - arrester / plug-in components
with remote alert



Ordering data

	VSPC 2CL 5 V DC R	VSPC 2CL 12 V DC R	VSPC 2CL 24 V DC R	VSPC 2CL 24 V AC R
Rated voltage (AC)				24 V
Rated voltage (DC)	5 V	12 V	24 V	24 V
Max. continuous voltage, U_c (AC)				28 V
Max. continuous voltage, U_c (DC)	6.4 V	15 V	28 V	40 V
Rated current I_n	450 mA	450 mA	450 mA	450 mA
Signalling contact	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace
Input attenuation	730 KHz	1.7 MHz	2.3 MHz	2.7 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 450 ms
Residual voltage, U_p typical	< 800 V	< 800 V	< 800 V	< 800 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	12 V	25 V	45 V	60 V
Protection level wire-wire 8/20 μ s, type	12 V	25 V	45 V	60 V
Protection level wire-PE 1kV/ μ s, type	450 V	450 V	450 V	450 V
Protection level wire-PE 8/20 μ s, type	< 800 V	< 800 V	< 800 V	< 800 V

Ordering data					
with function indicator	Type	VSPC 2CL 5VDC R	VSPC 2CL 12VDC R	VSPC 2CL 24VDC R	VSPC 2CL 24VAC R
	Order No.	8951460000	8951470000	8951480000	1093400000
	Qty.	1	1	1	1
Note					






VARITECTOR SPC


VSPC 2CL HF - protection for two analogue signals

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_{imp} (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Dimensions of complete module (arrester + base element) no remote sig. contact

Height x width x depth mm 90 / 17.8 / 69

Note

The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 2CL FG	1	8924270000
Base element, direct earthing	VSPC BASE 2CL	1	8924710000

Note

Technical data can be found at the beginning of the VARITECTOR SPC section.

VSPC 2CL HF - arrester / plug-in components




Ordering data		VSPC 2CL HF 5 V DC	VSPC 2CL HF 12 V DC	VSPC 2CL HF 24 V DC
Rated voltage (AC)				
Rated voltage (DC)		5 V	12 V	24 V
Max. continuous voltage, U _c (AC)				
Max. continuous voltage, U _c (DC)		6.4 V	15 V	28 V
Rated current I _n		450 mA	450 mA	450 mA
Input attenuation		103 MHz	104 MHz	109 MHz
Pulse-reset capacity		≤ 20 ms	≤ 80 ms	≤ 40 ms
Residual voltage, U _p typical		< 800 V	< 800 V	< 800 V
Protection level				
Protection level wire-wire 1kV/μs, type		12 V	25 V	45 V
Protection level wire-wire 8/20 μs, type		12 V	25 V	45 V
Protection level wire-PE 1kV/μs, type		450 V	450 V	450 V
Protection level wire-PE 8/20 μs, type		< 800 V	< 800 V	< 800 V

Ordering data		VSPC 2CL HF 5VDC	VSPC 2CL HF 12VDC	VSPC 2CL HF 24VDC
without function indicator	Type			
	Order No.	8924430000	8924460000	8924510000
	Qty.	1	1	1
Note				

VARITECTOR SPC



VSPC 2CL HF - protection for two analogue signals with remote alert

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Dimensions of complete module (arrester + base element)	with remote signalling (R)
Height x width x depth	mm 98 / 17.8 / 69
Note	
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.	

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing with remote contact	VSPC BASE 2CL R	1	8951710000
Base element, indirect earthing with remote contact	VSPC BASE 2CL FG R	1	8951720000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section. Order with VSPC CONTROL UNIT.
------	--

VSPC 2CL HF - arrester / plug-in components
with remote alert



Ordering data		VSPC 2CL HF 5 V DC R	VSPC 2CL HF 12 V DC R	VSPC 2CL HF 24 V DC R
Rated voltage (AC)				
Rated voltage (DC)		5 V	12 V	24 V
Max. continuous voltage, U _c (AC)				
Max. continuous voltage, U _c (DC)		6.4 V	15 V	28 V
Rated current I _N		450 mA	450 mA	450 mA
Signalling contact		U _N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U _N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U _N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display		green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace
Input attenuation		103 MHz	104 MHz	109 MHz
Pulse-reset capacity		≤ 20 ms	≤ 80 ms	≤ 40 ms
Residual voltage, U _p typical		< 800 V	< 800 V	< 800 V
Protection level				
Protection level wire-wire 1kV/μs, type		12 V	25 V	45 V
Protection level wire-wire 8/20 μs, type		12 V	25 V	45 V
Protection level wire-PE 1kV/μs, type		450 V	450 V	450 V
Protection level wire-PE 8/20 μs, type		< 800 V	< 800 V	< 800 V


Ordering data		VSPC 2CL HF 5VDC R	VSPC 2CL HF 12VDC R	VSPC 2CL HF 24VDC R
with function indicator	Type			
	Order No.	8951680000	8951690000	8951700000
	Qty.	1	1	1
Note				



VARITECTOR SPC


VSPC 1CL PW - combination of current loop
protection and end device protection

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with V-TEST testing device
- Version with floating-earth PE connection for avoiding voltage potential differences
- Usable in accordance with installation standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1, C1, C2, C3
- Tested in accordance with IEC/EN 61643-11 Class III
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Measurement and control protection data	
Volume resistance	2.20 Ω
Rated current	450 mA
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Standards	IEC 61643-21, HART-compatible
Discharge current I_L (8/20 μ s) wire-wire	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test current, I_{imp} (10/350 μ s) wire-wire	2.5 kA / 2.5 kA / 2.5 kA
End device protection data	
Combined pulse U_{OC}	6 kV
Max. continuous voltage, U_c (DC)	38 V
Residual voltage, U_p typical	$\leq$ 0.9 kV
Rated current I_N	10 A
General data	
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 $^{\circ}$ C...80 $^{\circ}$ C
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Ambient temperature (operational)	-40 $^{\circ}$ C...70 $^{\circ}$ C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 1CL PW FG	1	1105700000
Base element, direct earthing	VSPC BASE 1CL PW	1	1070230000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section.
------	---

VSPC 1CL PW - arrester / plug-in components



Ordering data		VSPC 1CL PW 24 V DC
Rated voltage (AC)		24 V
Rated voltage (DC)		24 V
Max. continuous voltage, U _c (AC)		27 V
Max. continuous voltage, U _c (DC)		38 V
Signalling contact		No
Optical function display		For Class III protection, green = OK; red = arrester is defective - replace
Input attenuation		3 MHz
Pulse-reset capacity		≤ 10 ms
Residual voltage, U _p typical		≤ 0.9 kV
Protection level		
Protection level wire-wire 1kV/μs, type		60 V
Protection level wire-wire 8/20 μs, type		60 V
Protection level wire-PE 1kV/μs, type		450 V
Protection level wire-PE 8/20 μs, type		≤ 0.9 kV


Ordering data		
without function indicator	Type	VSPC 1CL PW 24V
	Order No.	8951510000
	Qty.	1
Note		



VARITECTOR SPC


VSPC 2SL - protection for two binary signals

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Volume resistance	4.7 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I ₁ (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	43
MTTF	2665
SIL in compliance with IEC 61508	2
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions of complete module (arrester + base element)	no remote sig. contact
Height x width x depth	mm 90 / 17.8 / 69
Note	
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.	

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 2SL FG	1	8924280000
Base element, direct earthing	VSPC BASE 2SL	1	8924720000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section.
-------------	---



VSPC 2SL - arrester / plug-in components



Ordering data

	VSPC 2SL 5 V DC	VSPC 2SL 12 V DC	VSPC 2SL 24 V DC	VSPC 2SL 48 V AC
Rated voltage (AC)				48 V
Rated voltage (DC)	5 V	12 V	24 V	68 V
Max. continuous voltage, U_c (AC)				60 V
Max. continuous voltage, U_c (DC)	6.4 V	15 V	28 V	85 V
Rated current I_n	300 mA	300 mA	300 mA	250 mA
Input attenuation	1.2 MHz	2.5 MHz	2.7 MHz	8.7 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 60 ms
Residual voltage, U_r typical	< 200 V	< 200 V	250 V	≤ 300 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	25 V	45 V	80 V	210 V
Protection level wire-wire 8/20 μ s, type	25 V	45 V	80 V	80 V
Protection level wire-PE 1kV/ μ s, type	12 V	25 V	40 V	85 V
Protection level wire-PE 8/20 μ s, type	< 200 V	< 200 V	250 V	≤ 300 V

Ordering data

		VSPC 2SL 5VDC	VSPC 2SL 12VDC	VSPC 2SL 24VDC	VSPC 2SL 48VAC
without function indicator	Type				
	Order No.	8924210000	8924230000	8924330000	8924370000
	Qty.	1	1	1	1
Note					

Ordering data

	VSPC 2SL 24 V AC
Rated voltage (AC)	24 V
Rated voltage (DC)	34 V
Max. continuous voltage, U_c (AC)	28 V
Max. continuous voltage, U_c (DC)	39 V
Rated current I_n	300 mA
Input attenuation	5.5 MHz
Pulse-reset capacity	≤ 60 ms
Residual voltage, U_r typical	250 V
Protection level	
Protection level wire-wire 1kV/ μ s, type	110 V
Protection level wire-wire 8/20 μ s, type	80 V
Protection level wire-PE 1kV/ μ s, type	60 V
Protection level wire-PE 8/20 μ s, type	250 V

Ordering data


		VSPC 2SL 24VAC
without function indicator	Type	
	Order No.	8924350000
	Qty.	1
Note		



VARITECTOR SPC


VSPC 2SL - protection for two binary signals
with remote alert

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE




Technical data


Volume resistance	4.7 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_{imp} (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	43
MTTF	2665
SIL in compliance with IEC 61508	2
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Complete module, direct earthing, with remote alert



Complete module, indirect earthing, with remote alert



Dimensions of complete module (arrester + base element) with remote signalling (R)

Height x width x depth mm 98 / 17.8 / 69

Note

The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing with remote contact	VSPC BASE 2SL R	1	8951770000
Base element, indirect earthing with remote contact	VSPC BASE 2SL FG R	1	8951780000

Note

Technical data can be found at the beginning of the VARITECTOR SPC section.
Order with VSPC CONTROL UNIT.

**VSPC 2SL - arrester / plug-in elements with
remote alert**

Ordering data

	VSPC 2SL 5 V DC R	VSPC 2SL 12 V DC R	VSPC 2SL 24 V DC R	VSPC 2SL 24 V AC R
Rated voltage (AC)				24 V
Rated voltage (DC)	5 V	12 V	24 V	34 V
Max. continuous voltage, U_c (AC)				28 V
Max. continuous voltage, U_c (DC)	6.4 V	15 V	28 V	40 V
Rated current I_N	300 mA	300 mA	300 mA	300 mA
Signalling contact	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace
Input attenuation	1.2 MHz	2.5 MHz	2.7 MHz	5.5 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 60 ms
Residual voltage, U_p typical	< 200 V	< 200 V	< 200 V	250 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	25 V	45 V	80 V	110 V
Protection level wire-wire 8/20 μ s, type	25 V	45 V	80 V	80 V
Protection level wire-PE 1kV/ μ s, type	12 V	25 V	40 V	60 V
Protection level wire-PE 8/20 μ s, type	< 200 V	< 200 V	< 200 V	250 V

Ordering data					
with function indicator	Type	VSPC 2SL 5VDC R	VSPC 2SL 12VDC R	VSPC 2SL 24VDC R	VSPC 2SL 24VAC R
	Order No.	8951610000	8951620000	8951630000	8951640000
	Qty.	1	1	1	1
Note					






VARITECTOR SPC


VSPC 4SL - protection for four binary signals

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE




Technical data


Volume resistance	4.7 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_{imp} (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	43
MTTF	2665
SIL in compliance with IEC 61508	2
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Complete module, direct earthing



Complete module, indirect earthing



Dimensions of complete module (arrester + base element) no remote sig. contact

Height x width x depth mm 90 / 17.8 / 69

Note

The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 4SL FG	1	8924260000
Base element, direct earthing	VSPC BASE 4SL	1	8924700000

Note

Technical data can be found at the beginning of the VARITECTOR SPC section.



VSPC 4SL - arrester / plug-in elements



Ordering data

	VSPC 4SL 5 V DC	VSPC 4SL 12 V DC	VSPC 4SL 24 V DC	VSPC 4SL 48 V AC
Rated voltage (AC)				48 V
Rated voltage (DC)	5 V	12 V	24 V	68 V
Max. continuous voltage, U_c (AC)				60 V
Max. continuous voltage, U_c (DC)	6.4 V	15 V	28 V	85 V
Rated current I_n	300 mA	300 mA	300 mA	250 mA
Input attenuation	1.2 MHz	2.5 MHz	4 MHz	8.7 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 60 ms
Residual voltage, U_p typical	< 200 V	< 200 V	250 V	≤ 300 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	25 V	45 V	80 V	210 V
Protection level wire-wire 8/20 μ s, type	25 V	45 V	80 V	80 V
Protection level wire-PE 1kV/ μ s, type	12 V	25 V	40 V	85 V
Protection level wire-PE 8/20 μ s, type	< 200 V	< 200 V	250 V	≤ 300 V

Ordering data

without function indicator		Type	VSPC 4SL 5VDC	VSPC 4SL 12VDC	VSPC 4SL 24VDC	VSPC 4SL 48VAC
		Order No.	8924200000	8924220000	8924320000	8924360000
		Qty.	1	1	1	1
Note						

Ordering data

	VSPC 4SL 24 V AC	VSPC 4SL 60 V AC
Rated voltage (AC)	24 V	60 V
Rated voltage (DC)	34 V	85 V
Max. continuous voltage, U_c (AC)	28 V	72 V
Max. continuous voltage, U_c (DC)	40 V	101 V
Rated current I_n	300 mA	200 mA
Input attenuation	2.7 MHz	13.6 MHz
Pulse-reset capacity	≤ 40 ms	≤ 60 ms
Residual voltage, U_p typical	250 V	350 V
Protection level		
Protection level wire-wire 1kV/ μ s, type	110 V	280 V
Protection level wire-wire 8/20 μ s, type	80 V	80 V
Protection level wire-PE 1kV/ μ s, type	60 V	110 V
Protection level wire-PE 8/20 μ s, type	250 V	350 V

Ordering data


without function indicator		Type	VSPC 4SL 24VAC	VSPC 4SL 60VAC
		Order No.	8924340000	8924380000
		Qty.	1	1
Note				



VARITECTOR SPC


VSPC 4SL - protection for four binary signals with remote alert

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE




Technical data


Volume resistance	4.7 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	43
MTTF	2665
SIL in compliance with IEC 61508	2
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Complete module, direct earthing, with remote alert



Complete module, indirect earthing, with remote alert



Dimensions of complete module (arrester + base element) with remote signalling (R)

Height x width x depth mm 98 / 17.8 / 69

Note

The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing with remote contact	VSPC BASE 4SL R	1	8951750000
Base element, indirect earthing with remote contact	VSPC BASE 4SL FG R	1	8951760000

Note

Technical data can be found at the beginning of the VARITECTOR SPC section.
Order with VSPC CONTROL UNIT.

**VSPC 4SL - arrester / plug-in elements with
remote alert**

Ordering data

	VSPC 4SL 5 V DC R	VSPC 4SL 12 V DC R	VSPC 4SL 24 V DC R	VSPC 4SL 24 V AC R
Rated voltage (AC)				24 V
Rated voltage (DC)	5 V	12 V	24 V	34 V
Max. continuous voltage, U_c (AC)				28 V
Max. continuous voltage, U_c (DC)	6.4 V	15 V	28 V	40 V
Rated current I_N	300 mA	300 mA	300 mA	300 mA
Signalling contact	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace
Input attenuation	1.2 MHz	2.5 MHz	4 MHz	2.7 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 40 ms
Residual voltage, U_p typical	< 200 V	< 200 V	< 200 V	250 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	25 V	45 V	80 V	110 V
Protection level wire-wire 8/20 μ s, type	25 V	45 V	80 V	80 V
Protection level wire-PE 1kV/ μ s, type	12 V	25 V	40 V	60 V
Protection level wire-PE 8/20 μ s, type	< 200 V	< 200 V	< 200 V	250 V

Ordering data					
with function indicator	Type	VSPC 4SL 5VDC R	VSPC 4SL 12VDC R	VSPC 4SL 24VDC R	VSPC 4SL 24VAC R
	Order No.	8951570000	8951580000	8951590000	8951600000
	Qty.	1	1	1	1
Note					






VARITECTOR SPC


VSPC 4 SL WIRE - protection for 3/4-wire signals

- Protection of measuring bridge signals
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Version with floating-earth PE connection for avoiding voltage potential differences
- Space-saving design for 4 binary signals
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Volume resistance	0.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	43
MTTF	2655
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions of complete module (arrester + base element)		no remote sig. contact
Height x width x depth	mm	90 / 17.8 / 69
Note		
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.		

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing	VSPC BASE 2/4CH	1	8924740000
Base element, indirect earthing / floating earth FG	VSPC BASE 2/4CH FG	1	8924300000

Note	
Technical data can be found at the beginning of the VARITECTOR SPC section. Order with VSPC CONTROL UNIT.	

VSPC 4SL WIRE - arrester / plug-in components



Ordering data		VSPC 3/4 WIRE 5 V DC	VSPC 3/4 WIRE 24 V DC
Rated voltage (AC)			
Rated voltage (DC)		3 V	24 V
Max. continuous voltage, U _c (AC)			
Max. continuous voltage, U _c (DC)		6.4 V	28 V
Rated current I _n		450 mA	450 mA
Signalling contact		No	No
Optical function display		No	No
Capacitance		2.3 nF	935 pF
Pulse-reset capacity		≤ 20 ms	≤ 30 ms
Residual voltage, U _p typical		< 800 V	< 800 V
Protection level			
Protection level wire-wire 1kV/μs, type		35 V	50 V
Protection level wire-wire 8/20 μs, type		35 V	50 V
Protection level wire-PE 1kV/μs, type		250 V	270 V
Protection level wire-PE 8/20 μs, type		< 800 V	< 800 V



Ordering data		VSPC 3/4WIRE 5VDC	VSPC 3/4WIRE 24VDC
without function indicator	Type		
	Order No.	8924540000	8924550000
	Qty.	1	1
Note			




VARITECTOR SPC

VSPC GDT - with sparkover gap (GDT)

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Version with floating-earth PE connection for avoiding voltage potential differences
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Complete module, direct earthing



Complete module, indirect earthing

Technical data

Volume resistance	0.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _a (8/20 µs) wire-wire/wire-PE/GND-PE	2 x 2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	2 x 10 kA / / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2 x 0.2 kA / / 0.2 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	11
MTTF	10378
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; UL
Standards	According to IEC61643-21

Dimensions of complete module (arrester + base element)	no remote sig. contact
Height x width x depth	mm 90 / 17.8 / 69
Note	The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing	VSPC BASE 2/4CH	1	8924740000
Base element, indirect earthing / floating earth FG	VSPC BASE 2/4CH FG	1	8924300000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section. Order with VSPC CONTROL UNIT.
-------------	--

VSPC GDT - arrester / plug-in components



Ordering data	VSPC GDT 2CH 90 V	VSPC GDT 2CH 150 V AC/230 V DC
Rated voltage (AC)	48 V	110 V
Rated voltage (DC)	68 V	150 V
Max. continuous voltage, U _c (AC)	50 V	125 V
Max. continuous voltage, U _c (DC)	72 V	180 V
Rated current I _n	2 A	2 A
Signalling contact	No	No
Optical function display	No	No
Capacitance	9.37 pF	7.45 pF
Pulse-reset capacity		
Residual voltage, U _p typical	< 1000 V	< 1000 V
Protection level		
Protection level wire-wire 1kV/μs, type	650 V	450 V
Protection level wire-wire 8/20 μs, type	1000 V	800 V
Protection level wire-PE 1kV/μs, type	650 V	800 V
Protection level wire-PE 8/20 μs, type	< 1000 V	< 1000 V


Ordering data		
without function indicator	Type	
	Order No.	
	Qty.	
Note		
	VSPC GDT 2CH 90V	VSPC GDT 2CH 150Vac/230Vdc
	8924570000	8924590000
	1	1
	The 90 V gas discharge tube has a tolerance of +/- 20 %.	The 230 V gas discharge tube has a tolerance of +/- 20 %.



VARITECTOR SPC


VSPC MOV - protection with varistor

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional monitoring function with status display and alert functions for MOV components
- Version with floating-earth PE connection for avoiding voltage potential differences
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Volume resistance	0.20 Ω
Overload - failure mode	Mode 1
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	1.5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	0.5 kA 10/350 µs
Discharge current I ₁ (8/20 µs) wire-wire/wire-PE/GND-PE	0.2 kA / 2.5 kA / 0.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	1.5 kA / / 1.5 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	0.2 kA / / 0.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	26
MTTF	4391
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing	VSPC BASE 2/4CH	1	8924740000
Base element, direct earthing with remote contact	VSPC BASE 2/4CH R	1	8951790000
Base element, indirect earthing with remote contact	VSPC BASE 2/4CH FG R	1	8951800000
Base element, indirect earthing / floating earth FG	VSPC BASE 2/4CH FG	1	8924300000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section. Order with VSPC CONTROL UNIT.
-------------	--

VSPC MOV - arrester / plug-in components



Ordering data

	VSPC MOV 2CH 24 V	VSPC MOV 2CH 230 V	VSPC MOV 2CH 24 V R	VSPC MOV 2CH 230 V R
Rated voltage (AC)	24 V	230 V	24 V	230 V
Rated voltage (DC)	30 V	230 V	30 V	230 V
Max. continuous voltage, U_c (AC)	30 V	275 V	30 V	275 V
Max. continuous voltage, U_c (DC)	38 V	350 V	38 V	350 V
Rated current I_n	10 A	10 A	10 A	10 A
Signalling contact	No	No	U_n 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U_n 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display	No	No	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace
Capacitance	14.5 nF	720 pF	14.5 nF	720 pF
Residual voltage, U_r typical	200 V	850 V	200 V	850 V
Protection level				
Protection level wire-wire 1kV/ μ s, type	80 V	600 V	80 V	600 V
Protection level wire-wire 8/20 μ s, type	95 V	700 V	95 V	700 V
Protection level wire-PE 1kV/ μ s, type				
Protection level wire-PE 8/20 μ s, type				

Ordering data	Without functional display	Without functional display	With functional display	With functional display
Type	VSPC MOV 2CH 24V	VSPC MOV 2CH 230V	VSPC MOV 2CH 24V R	VSPC MOV 2CH 230V R
Order No.	8924600000	8924610000	8951650000	8951660000
Qty.	1	1	1	1
Note				






VARITECTOR SPC


VSPC TAZ protection with suppressor diode

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional monitoring function with status display and alert functions for MOV components
- Lower residual voltage
- Version with floating-earth PE connection for avoiding voltage potential differences
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Volume resistance	0.20 Ω
Overload - failure mode	Mode 1
Requirements category acc. to IEC 61643-21	C3
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	
Surge current-carrying capacity C3	20 A 10/1000 µs
Surge current-carrying capacity D1	
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	0.05 kA /
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	0,1 kA /
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	32
MTTF	3567
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	According to IEC61643-21



Dimensions of complete module (arrester + base element)	no remote sig. contact
Height x width x depth	mm 90 / 17.8 / 69
Note	The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing	VSPC BASE 2/4CH	1	8924740000
Base element, indirect earthing / floating earth FG	VSPC BASE 2/4CH FG	1	8924300000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section. Order with VSPC CONTROL UNIT.
-------------	--

VSPC TAZ - arrester / plug-in components



Ordering data		VSPC TAZ 4CH 24 V
Rated voltage (AC)		24 V
Rated voltage (DC)		28 V
Max. continuous voltage, Uc (AC)		28 V
Max. continuous voltage, Uc (DC)		39 V
Rated current I _n		10 A
Signalling contact		No
Optical function display		No
Capacitance		680 pF
Pulse-reset capacity		
Residual voltage, U _p typical		65 V
Protection level		
Protection level wire-wire 1kV/μs, type		50 V
Protection level wire-wire 8/20 μs, type		55 V
Protection level wire-PE 1kV/μs, type		55 V
Protection level wire-PE 8/20 μs, type		65 V


Ordering data		
without function indicator	Type	VSPC TAZ 4CH 24V
	Order No.	8924650000
	Qty.	1
Note		



VARITECTOR SPC



VSPC TELE UK0 - protection for telephones

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Two-wire input interface - U_{ko}
- Version with floating-earth PE connection for avoiding voltage potential differences
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_{imp} (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	0.2 kA / 2 x 0.2 kA / 0.2 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	49
MTTF	2330
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; UL
Standards	According to IEC61643-21



Dimensions of complete module (arrester + base element)		no remote sig. contact
Height x width x depth	mm	90 / 17.8 / 69
Note		
Order the associated VSPC base element with this. The dimension information provided refers to the complete module.		

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 2CL FG	1	8924270000
Base element, direct earthing	VSPC BASE 2CL	1	8924710000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section.
-------------	---

VSPC TELE UK0 - arrester/plug-in components



Ordering data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U _c (AC)
Max. continuous voltage, U _c (DC)
Rated current I _n
Input attenuation
Pulse-reset capacity
Residual voltage, U _p typical

Protection level

Protection level wire-wire 1kV/μs, type
Protection level wire-wire 8/20 μs, type
Protection level wire-PE 1kV/μs, type
Protection level wire-PE 8/20 μs, type

VSPC TELE UK0 2 WIRE

127 V
120 V
130 V
180 V
450 mA
101.7 MHz
≤ 60 ms
< 800 V
250 V
300 V
450 V
< 800 V

Ordering data

without function indicator	Type
	Order No.
	Qty.

Note


VSPC TELE UK0 2WIRE
8924660000
1



VARITECTOR SPC



VSPC RS485 - protection for data signals

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with V-TEST testing device
- Optional monitoring function with status indicator and alert functions
- Low residual voltage
- Version with floating-earth PE connection for avoiding voltage potential differences
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _s (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	0.2 kA / 2 x 0.2 kA / 0.2 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	57
MTTF	2003
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions of complete module (arrester + base element)	no remote sig. contact
Height x width x depth	mm 90 / 17.8 / 69
Note	
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.	

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 2CL FG	1	8924270000
Base element, direct earthing	VSPC BASE 2CL	1	8924710000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section.
------	---

VSPC RS485 - arrester / plug-in elements



Ordering data		VSPC RS485 2CH
Rated voltage (AC)		5 V
Rated voltage (DC)		5 V
Max. continuous voltage, U _c (AC)		5 V
Max. continuous voltage, U _c (DC)		6.4 V
Rated current I _n		450 mA
Input attenuation		113.6 MHz
Pulse-reset capacity		≤ 20 ms
Residual voltage, U _p typical		250 V
Protection level		
Protection level wire-wire 1kV/μs, type		10 V
Protection level wire-wire 8/20 μs, type		15 V
Protection level wire-PE 1kV/μs, type		10 V
Protection level wire-PE 8/20 μs, type		250 V


Ordering data		
without function indicator	Type	VSPC RS485 2CH
	Order No.	8924670000
	Qty.	1
Note		



VARITECTOR SPC




VSPC RS485 - protection for data signals with remote alert

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional monitoring function with status indicator and alert functions
- Lower residual voltage
- Version with floating-earth PE connection for avoiding voltage potential differences
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_{imp} (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	0.2 kA / 2 x 0.2 kA / 0.2 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	90
MTTF	1266
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions of complete module (arrester + base element) with remote signalling (R)	
Height x width x depth	mm 98 / 17.8 / 69
Note	
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.	

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
Base element, direct earthing with remote contact	VSPC BASE 2CL R	1	8951710000
Base element, indirect earthing with remote contact	VSPC BASE 2CL FG R	1	8951720000

Note	
Technical data can be found at the beginning of the VARITECTOR SPC section. Order with VSPC CONTROL UNIT.	

VSPC RS485 - arrester / plug-in elements
with remote alert



Ordering data		VSPC RS485 2CH R
Rated voltage (AC)		5 V
Rated voltage (DC)		5 V
Max. continuous voltage, U _c (AC)		5 V
Max. continuous voltage, U _c (DC)		6.4 V
Rated current I _N		450 mA
Signalling contact		U _N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display		green = OK; red = arrester is defective - replace
Input attenuation		113.6 MHz
Pulse-reset capacity		≤ 20 ms
Residual voltage, U _p typical		250 V
Protection level		
Protection level wire-wire 1kV/μs, type		10 V
Protection level wire-wire 8/20 μs, type		15 V
Protection level wire-PE 1kV/μs, type		10 V
Protection level wire-PE 8/20 μs, type		250 V


Ordering data		
with function indicator	Type	VSPC RS485 2CH R
	Order No.	8951670000
	Qty.	1
Note		



VARITECTOR SPC

Direct earthing

VSPC BASE



Technical data

- Stripping length, rated connection
- Wire cross-section, stranded, min.
- Wire cross-section, stranded, max.
- Wire cross-section, solid, min.
- Wire cross-section, solid, max.
- Clamping range, min.
- Clamping range, max.
- Tightening torque, min.
- Tightening torque, max.
- Type of connection
- Certificate No. (UL)
- Approvals
- Ambient temperature (operational)
- Storage temperature
- UL 94 flammability rating
- Pollution degree
- Overvoltage category
- Protection degree
- Rail
- Humidity

CSA protection data

- Input current, max. I_i
- Gas groups A, B
- Gas group C
- Gas group D
- Internal inductance, max. L_i

7 mm
0.5 mm ²
2.5 mm ²
0.5 mm ²
4 mm ²
0.5 mm ²
4 mm ²
0.5 Nm
0.8 Nm
Screw connection
E311081VOL1SEC2
CE, CSAEX, EAC, UL
-40 °C...70 °C
-40 °C...80 °C
V-0
2
III
IP20
TS 35, TS 35 x 7.5
5...96 %
450 mA
IIC
IIB
IIA

Dimensions

Height x width

90 / 17.8

Note

Ordering data

No remote sig. contact

Type	Qty.	Order No.
VSPC BASE 1CL	1	8924730000
VSPC BASE 2SL	1	8924720000
VSPC BASE 2CL	1	8924710000
VSPC BASE 2/4CH	1	8924740000
VSPC BASE 1CL PW	1	1070230000
VSPC BASE 4SL	1	8924700000

Note

Technical data can be found at the beginning of the VARITECTOR SPC section.


Accessories

Note

Marker: DEK 5

Indirect earthing

VSPC BASE FG



Technical data

- Stripping length, rated connection
- Wire cross-section, stranded, min.
- Wire cross-section, stranded, max.
- Wire cross-section, solid, min.
- Wire cross-section, solid, max.
- Clamping range, min.
- Clamping range, max.
- Tightening torque, min.
- Tightening torque, max.
- Type of connection
- Certificate No. (UL)
- Approvals
- Ambient temperature (operational)
- Storage temperature
- UL 94 flammability rating
- Pollution degree
- Overvoltage category
- Protection degree
- Rail
- Humidity

CSA protection data

- Input current, max. I_i
- Gas groups A, B
- Gas group C
- Gas group D
- Internal inductance, max. L_i

7 mm
0.5 mm ²
2.5 mm ²
0.5 mm ²
4 mm ²
0.5 mm ²
4 mm ²
0.5 Nm
0.8 Nm
Screw connection
E311081VOL1SEC2
CE, CSAEX, EAC, UL
-40 °C...70 °C
-40 °C...80 °C
V-0
2
III
IP20
TS 35, TS 35 x 7.5
5...96 %
450 mA
IIC
IIB
IIA

Dimensions

Height x width

90 / 17.8

Note

Ordering data

No remote sig. contact

Type	Qty.	Order No.
VSPC BASE 1CL FG	1	8924290000
VSPC BASE 2SL FG	1	8924280000
VSPC BASE 2CL FG	1	8924270000
VSPC BASE 1CL PW FG	1	1105700000
VSPC BASE 2/4CH FG	1	8924300000
VSPC BASE 4SL FG	1	8924260000

Note

Technical data can be found at the beginning of the VARITECTOR SPC section.

Accessories

Note


Marker: DEK 5



VARITECTOR SPC

Direct earthing, with remote alert

VSPC BASE R



Technical data

- Stripping length, rated connection
- Wire cross-section, stranded, min.
- Wire cross-section, stranded, max.
- Wire cross-section, solid, min.
- Wire cross-section, solid, max.
- Clamping range, min.
- Clamping range, max.
- Tightening torque, min.
- Tightening torque, max.
- Type of connection
- Certificate No. (UL)
- Approvals
- Ambient temperature (operational)
- Storage temperature
- UL 94 flammability rating
- Pollution degree
- Overvoltage category
- Protection degree
- Rail
- Humidity

CSA protection data

- Input current, max. I_i
- Gas groups A, B
- Gas group C
- Gas group D
- Internal inductance, max. L_i

7 mm
0.5 mm ²
2.5 mm ²
0.5 mm ²
4 mm ²
0.5 mm ²
4 mm ²
0.5 Nm
0.8 Nm
Screw connection
E311081VOL1SEC2
CE, CSAEX, EAC, UL
-40 °C...70 °C
-40 °C...80 °C
V-0
2
III
IP20
TS 35, TS 35 x 7.5
5...96 %
450 mA
IIC
IIB
IIA

Dimensions

Height x width

98 / 17.8

Note

Ordering data

With remote sig. contact (R)

Type	Qty.	Order No.
VSPC BASE 2SL R	1	8951770000
VSPC BASE 1CL R	1	8951730000
VSPC BASE 2CL R	1	8951710000
VSPC BASE 2/4CH R	1	8951790000
VSPC BASE 4SL R	1	8951750000

Note

Technical data can be found at the beginning of the VARITECTOR SPC section.
Order with VSPC CONTROL UNIT.


Accessories

Note

Marker: DEK 5

Indirect earthing, with remote alert

VSPC BASE FG R



Technical data

- Stripping length, rated connection
- Wire cross-section, stranded, min.
- Wire cross-section, stranded, max.
- Wire cross-section, solid, min.
- Wire cross-section, solid, max.
- Clamping range, min.
- Clamping range, max.
- Tightening torque, min.
- Tightening torque, max.
- Type of connection
- Certificate No. (UL)
- Approvals
- Ambient temperature (operational)
- Storage temperature
- UL 94 flammability rating
- Pollution degree
- Overvoltage category
- Protection degree
- Rail
- Humidity

CSA protection data

- Input current, max. I_i
- Gas groups A, B
- Gas group C
- Gas group D
- Internal inductance, max. L_i

7 mm
0.5 mm ²
2.5 mm ²
0.5 mm ²
4 mm ²
0.5 mm ²
4 mm ²
0.5 Nm
0.8 Nm
Screw connection
E311081VOL1SEC2
CE, CSAEX, EAC, UL
-40 °C...70 °C
-40 °C...80 °C
V-0
2
III
IP20
TS 35, TS 35 x 7.5
5...96 %
300 mA
IIC
IIB
IIA

Dimensions

Height x width

98 / 17.8

Note

Ordering data

With remote sig. contact (R)

Type	Qty.	Order No.
VSPC BASE 2SL FG R	1	8951780000
VSPC BASE 1CL FG R	1	8951740000
VSPC BASE 2CL FG R	1	8951720000
VSPC BASE 2/4CH FG R	1	8951800000
VSPC BASE 4SL FG R	1	8951760000

Note

Technical data can be found at the beginning of the VARITECTOR SPC section.
Order with VSPC CONTROL UNIT.

Accessories

Note

Marker: DEK 5




VARITECTOR SPC

VSPC accessories

VSPC Ground

- Can be applied to unassigned wires
- Usable during start-up and maintenance
- Earthing of all sensor cables
- Can be plugged into standard base sockets



Technical data

Rated voltage (DC)	230 V AC
Max. continuous voltage, U_c (DC)	255 V AC
Rated current	< 0.5 A
Volume resistivity per path	< 0.2 Ω
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...+80 °C
Ambient temperature (operational)	-40 °C...+70 °C
Rel. humidity	5 %...96 % RH
Degree of protection	IP 20

Note


Ordering data

Arrester / plug-in elements	Type
	Order No.
	Qty.
Note	

VSPC GROUND
VSPC GROUND
8924680000
1

The interlock mechanism on the VSPC Series pluggable arresters delivers extra reliability and an improved permanent contact under strong vibrating conditions.

VSPC Locking Clip



Technical data

Colour
Marking
Function
Weight
Note

yellow
Individually with a label
Removal with screwdriver
Snap-on by hand (press on)
10 g


Ordering data

Note

Type	Qty.	Order No.
VSPC LOCKING CLIP	100	1317340000

Cross-connection (QB) between the VSPC signal contacts can be installed quickly. Cross-connections can be individually separated for the alert function, with maximum of 10 VSPC R.

QB 17,8/2



Technical data

Version
Dimensions (L x W x H)
Pitch
Rated current
Cross-section
Weight
Colour
Note

2-pole with 9 QBs together = 1 strip
9 mm (15.5 mm with contact) x 6 mm x 21 mm (9 QBs = 160.7 mm)
17.8 mm
17.5 A
1.5 mm ²
12.4 g/QB
yellow

Ordering data


Note

Type	Qty.	Order No.
QB 17.8/2	10 strips, with 9 QBs each	1309470000

VARITECTOR SPC

VSPC CONTROL UNIT 24 V DC

- For monitoring up to 10 protective modules
- Signalling module for all VSPCs with status indicator
- Signalling of cable breaks / signal interruptions
- Voltage supply from 18...31 V DC
- Potential-free changeover contact
- Function indicator (red/green LED)
- Other NC-contact monitoring functions can be integrated into the signal circuit (e.g. VPU I, VPU II and VPU III)




Technical data

Input	
Rated voltage (DC)	18 V...24 V DC...31 V DC
Rated current	max. 50 mA
Power rating	1.5 W
Output	
Current loop	8 mA at < 51 V
Monitoring option	1...10 VSPC modules
Signal output	
Type	1 CO contact
Max. switching voltage / continuous current	250 V / 1 A
Diagnostics	
Operating status	Green LED
Defect at current loop	Red LED (control unit and defective module)
Wire breakage	Red/green LED, flashing
General data	
Terminal rail	TS 35
Design, Protection class	Insta-enclosure, IP 20
Type of connection	BL / SL
Storage temperature	-40 °C...+80 °C
Ambient temperature (operational)	-40 °C...+70 °C
Rel. humidity	5 %...96 % RH
Start-up time after fault correction	60 s

Dimensions	
Dimensions incl. enclosure H x W x D	mm 102 x 18 x 71.5
Note	

Application



Status indication		Function	
LED green	LED red		
		OK	✓
		Error (one or more VSPC ... R are defective)	
		Line break in the monitoring circuit; arrester pulled out or plug not in base	

Ordering data

Type	
Order No.	
Qty.	
Note	

VSPC CONTROL UNIT 24 V DC

Type	VSPC CONTROL UNIT 24Vdc
Order No.	8972270000
Qty.	1 piece



A

V-TEST

Testing device from the VARITECTOR SPC Series

A testing device for pluggable surge protection: for testing in compliance with the IEC 62305-3 standard

The V-TEST is a compact, easily carried, testing device for pluggable protection modules from the VARITECTOR SPC family. The testing device can be used to test the protective function of the overvoltage protection components in accordance with the test intervals required in IEC 62305-3. It provides information regarding the functional status of the protective components.

The backlit display shows the measured reading per component (GDT, MOV, TAZ) as "OK" or "not OK". This function allows you to detect ageing components as it highlights possible damage right away. Thus total protection is guaranteed.

The V-TEST is equipped with a charger and a battery set which allows autonomous use in the field. A comfortable and protective carry bag is delivered free with the tester.



Always delivers precise readings

The V-TEST self-calibrates when it is turned on, ensuring that it can always deliver precise measurement and test values.



Portable

The compact device comes with an integrated rechargeable battery and protective case – making it perfect for use in the field.





Quick and easy to operate

It only takes a few simple menu steps (in German or English) to navigate directly to the measurement function.



Ensures timely testing intervals

The portable V-TEST can be used to carry out repeated testing in compliance with IEC 62305-3.

Lightning protection level	Visual inspection	Extensive check	Extensive check in critical situations ^{a), b)}
	Year	Year	Year
I und II	1	2	1
III und IV	2	4	1

a) Lightning protection systems for explosive structural facilities should be visually inspected every six months. The installation should be metrologically tested once per year. To obtain findings about the seasonal fluctuations, it is permissible to take measurements at 14 to 15-month intervals so as to determine the earth wire circuit resistance at different times of the year.

b) "Critical situations" could refer to structural facilities containing systems that are sensitive to interference or to office buildings, commercial properties or places where a large number of people may reside.



V-TEST

VSPC accessories

V-TEST

- Testing device for testing the protective functions of the VARITECTOR SPC series
- Device for implementing the IEC 62305 standard (regarding periodic testing)
- Easy-to-use device with integrated battery set for on-site measurements
- Result display via LCD display
- Including protective bag and power supply
- Intuitive user navigation in German and English

The V-TEST is a compact, portable test device for pluggable surge protection Varitector SPC (VSPC). Using this testing instrument, Weidmüller surge protection can be tested for their protective function in line with the testing schedules laid down in IEC 62305-3 (DIN VDE 185 part 3).
In a display with background illumination, the test result is indicated for each component with „OK“ or „Not OK“.



Technical data

Rated voltage		100...240 V AC
Accumulator set		8 NiMH with 2600 mA
Storage temperature		0 °C ... 40 °C
Ambient temperature (operational)		0 °C ... 40 °C
Degree of protection		IP 20
Measuring range		U < 1000 V / I = 1 mA
UL94 flammability class		V0
General tolerances of measurement range		
Gas discharge tube		+/- 10%
Varistor		+/- 5%
TVS-diode		+/- 5%
Note		

Ordering data

Dimensions	
Height x Width x Depth	mm
Ordering data	
Type	
Order No.	
Qty.	
Note	

V-TEST	
230 x 122 x 65	
V-TEST	
8951860000	
1	



A

VARITECTOR SSC 6AN

Lightning and surge protection in terminal block design

Lightning and surge protection in 6 mm overall width for measurement and control circuits including isolation/measuring function

The VARITECTOR SSC combined surge protection, a direct PE contact function, separation of signal paths and operational status indication in one module. It is suitable for C&I applications.

The disconnect lever in the terminal guarantees that the measurement/control circuit can be quickly and precisely switched off to test the signal path. Using a test plug (PS 2.3 mm), the measuring instrument can be easily inserted into the integrated test socket on Torx®/Slot headed screws. The shield can be attached onto the additional lower level of the VSSC 6AN which then leads directly to the PE potential on the mounting rail. Weidmüller's SNAPMARK device marker can be snapped onto a terminal so that the equipment identification can be easily read regardless of the installation position. The VSSC 6AN features all the advantages found in the VARITECTOR SSC product line: a thin 6.2 mm width, quick PE contact to rail (with up to 20 kA discharge capacity), simple colour coding for quick identification, large-surface versatile markers, and the new Torx®/slot headed screw.

All VARITECTOR products comply with the latest IEC 61643-21 requirement for a new overstress mode and with categories D1, C3, C2 and C1 according to IEC 61643-22.



Convenient

Connection convenience is assured by a clamping range of 0.5 mm² to 6 mm² with a Torx®/slot headed screw and a 0.8 Nm tightening torque.



Space-saving


A terminal of just 6.2 mm for four binary signals or two analogue signals. Terminals can be fitted side by side.





Simple and precise isolation

The disconnect lever guarantees a simple signal path disconnection and a safe disconnect point that is easy to see.




Fast identification

Versatile marking options: markers for equipment and terminals and SNAPMARK markers that are easy to read in any installation position.




Testing and measuring

To enable simple testing it is possible to insert the test plug (PS 2.3 mm) of the measuring instrument into the integrated test socket of the Torx®/slot headed screw.



Easy and safe

A shield can be mounted on both sides of the unit which will provide direct connection to PE. It features a very high discharge current of up to 20 kA for increased plant safety.



VARITECTOR SSC

Surge protection in a terminal block: for measurement and control systems


VARITECTOR SSC

Weidmüller's VARITECTOR SSC series for surge protection (VSSC4 and VSSC6) is well suited for protecting measurement and control circuits. It features good protective functionality in a compact terminal-block design. This is due to its 6.2 mm width. The combined Torx®/ slotted screw ensures that the proper nominal or max. torque is applied to the connection. The required screwdrivers are available from Weidmüller under the following order numbers:
4-mm slotted SD 0.8 x 4.0 x 100 (order no. 9008340000) or T15 Torx® (order no. 9009170000). The VSSC can be snapped on, to directly earth it to the DIN rail. The VSSC series is available with four clamping yokes (VSSC4) and six clamping yokes (VSSC6). The screw terminal has a nominal torque of 0.5 Nm, but it can be tightened to 0.8 Nm. The VARITECTOR SSC series is optimally designed for compact installation locations in process automation, industrial automation or building automation.

The two-stage surge protection terminals are equipped with gas discharge tubes (GDT), suppressor diodes (TVS) and decoupling components. Individual protective components (such as gas-filled spark gaps, varistors and suppressor diodes) supplement this product line. Our VARITECTOR SSC surge protectors are available for components with nominal voltages of 12 V, 24 V, 48 V to 230 V. Please contact us for other voltages or special applications.

The two-stage surge protection terminals are equipped with gas discharge tubes (GDT), suppressor diodes (TVS) and decoupling components. Individual protective

components (such as gas-filled spark gaps, varistors and suppressor diodes) supplement this product line. Our VARITECTOR SSC surge protectors are available for components with nominal voltages of 12 V, 24 V, 48 V to 230 V. Please contact us for other voltages or special applications. The PE contact is established by snapping onto an earthed DIN rail. The TS 35 must be earthed in order to ensure safe power discharging via the terminals of up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs). The DIN rail must be screwed onto the earthed mounting plate to ensure EMC. The best protection is achieved when a PE contact is established every 60 cm / 24 inch using the terminal at the VARITECTOR SSC terminals with direct equipotential bonding. The cable should correspond to the max. cross-section of the VSSC connection. The four-port VARITECTOR SSC terminal can be used for binary and / or analogue signal circuits. The six-port VARITECTOR SSC can also be used to open signal circuits via an isolated level and monitor them using the optional built-in LED.




VARITECTOR SSC6




VARITECTOR SSC4

Overview of model types



The **VSSC4 CL** is a two-stage protective combination that has a suppressor diode between the current paths. This VSSC4 CL limits the surge voltage in **an analogue signal circuit** (e.g. a current loop).

The **VSSC4 CL FG** is a two-stage protective combination that has a suppressor diode between the current paths. The gas discharge tube to the PE provides a high-resistance earthing for the protective circuitry. Thus the current loop can be operated with a floating ground. This VSSC4 CL FG limits the surge voltage in **an analogue unearthed signal circuit** (e.g. a current loop).




The basic principle of a binary current circuit

The **VSSC4 SL** is a two-stage protective combination with a suppressor diode for each stage from the current path to PE. This **VSSC4 SL** limits the surge voltage in an **earthed binary signal** (e.g. for alert contacts). The VSSC4 SL FG is used for **non-earthed signal circuits**.




VARITECTOR SSC


The **VSSC4 SL FG** is a two-stage protective combination with a suppressor between the current paths and common return wire. The gas discharge tube to the PE provides a high-resistance earthing for the protective circuitry. Thus the protective circuitry can be operated with a floating earth. This VSSC4 SL FG limits the surge voltage in **a binary floating signal circuit**.




The **VSSC4 MOV** provides one-stage protection with a varistor (MOV) for the current path to PE. This **VSSC4 MOV** limits the surge voltage in **a circuit** (e.g. for solenoid valves). The thermally monitored MOV is available in voltages of 12 V, 24 V, 48 V, 60 V, 120 V, 150 V and 240 V.




The **VSSC4 GDT** provides one-stage protection with a gas discharge tube (GDT) for the current path to PE. This **VSSC4 GDT** limits the surge voltage in **a circuit**. This terminal is used where no leakage current is permitted to flow to the earth, or where a high-impedance cable shield is connected to the earth. The GDT is available in voltages of 90 V, 110 V and 240 V.



The **VSSC4 TAZ** provides one-stage protection with a quick-response (<10 ps) suppressor diode (TAZ) for the current path to PE. This **VSSC4 TAZ** limits the surge voltage in **a circuit** (e.g. for digital inputs). The TAZ is available in voltages of 12 V, 24 V, 48 V and 60 V.



VSSC4 RC is the final protective variant in the VSSC series. This variant combines a thermally monitored varistor and an RC combination. It can be used for spark suppression on inductive loads. The VSSC4 RC is available in 24 V and 240 V.



The **VSSC6 CL** is a two-stage protective combination that has a suppressor diode between the current paths. This VSSC6 CL limits the surge voltage in **an analogue signal circuit** (e.g. a current loop). The PE potential can be provided on terminal point 3/6 by snapping the terminal on an earthed DIN rail. This allows a shield connection to be connected. This version is also available as the **VSSC6 CL FG** floating-ground protective circuit.

The **VSSC6 TR CL** is built like the VSSC6 CL and also has two isolators. The 2.3-mm PS 2.3 (order number 018040000) can be plugged into the Torx® screw head. The isolation makes it possible to take measurements in the field, in the electrical cabinet or via the surge protection. This version is also available as the **VSSC6 TR CL FG** floating-ground protective circuit.

The **VSSC6 SL LD** is a two-stage protective combination with a suppressor between the current paths and common return wire. This VSSC6 SL limits the surge voltage in **two binary signal circuits**. The signal status for each signal circuit is indicated by an LED.

The **VSSC6 TR SL LD** is built like the VSSC6 L LD but also has two isolators. The 2.3-mm plug uses the screws to provide easy signal measurements. This version is also available as the **VSSC6 TR SL FG** floating-ground protective circuit.

The **VSSC6 MOV** provides one-stage protection with two thermally monitored varistors (MOV) between the current paths and common return wire. This VSSC6 MOV limits the surge voltage in **two binary signal circuits**.

The **VSSC6 TR LD MOV** provides one-stage protection with two thermally monitored varistors (MOV) between the current paths and common return wire. The VSSC6 MOV limits the surge voltage in **two binary signal circuits** and also has an isolator and an LED for each signal circuit.




VARITECTOR SSC 6AN

The **VSSC6 GDT** provides one-stage protection with two gas discharge tubes (GDT) between the current paths and common return wire. This VSSC6 GDT limits the surge voltage in **two binary signal circuits**.


The **VSSC6 TR LD GDT** provides two-stage protection with two gas discharge tubes (GDT) between the current paths and common return wire. The VSSC6 GDT limits the surge voltage in **two binary signal circuits** and also has an isolator for each signal circuit.

The **VSSC6 TAZ** provides one-stage protection with two suppressor diodes (TAZ) between the current paths and common return wire. The VSSC6 TAZ limits the surge voltage in **two binary signal circuits** and also has an isolator and an LED for each signal circuit.

The **VSSC6 TR LD TAZ** provides one-stage protection with two suppressor diodes (TAZ) between the current paths and common return wire. The VSSC6 TAZ limits the surge voltage in **two binary signal circuits** and also has an isolator and an LED for each signal circuit.



The **VSSC6 RS485** is a two-stage protective combination that has suppressor diodes between the current paths. This VSSC6 RS485 limits the surge voltage in **two high-frequency signal circuits** with common return wires. The VSSC RS485 is available in the PROFIBUS PA and DP variants.



The **VSSC6 RS232** is a two-stage protective combination that has suppressor diodes between the current paths. This VSSC6 RS232 limits the surge voltage in **a signal circuit**.

Black Material PA6.6 with UL94 V0 is used for the VSSC4 and VSSC6 series so that they are suitable for use in many applications. They are suitable for use in temperatures ranging from -40 to +70 °C.

Discharge capacity


Tested in compliance with standard IEC 61643-21 for providing surge protection in signalling networks with voltage and current pulses. The VSSC series has been tested to comply with IEC 61643-21 and EN 61643-21. Modules were tested with categories C1, C2 and C3: with quick-rising edges with up to 300 pulses. Category D1 describes high-power testing (10/350 µs), so that the VSSC series can be used in compliance with IEC 62305-4. The VSSC is colour-coded so that it is easy to detect the voltage level (or the signal location SL or CL).

Colour coding

Voltage level	Colour
≤ 12 V	green
24 V Binary	blue
24 V Analogue	yellow
48 V	red
≥ 60 V	violet
Special function	white

Installation

The VSSC series is used to protect signal circuits. In order to achieve a complete protective strategy for the facility, the power feed must be protected with Type II surge protection (for example, by using the VPU II series). For existing lightning protection facilities, Type I protection must be used (for example, by using the VPU I series). Type II protection (for example, the VPU II) is sufficient when there is no lightning protection facility.



Fusing

The VSPC surge protection modules are designed so that they are decoupled between the individual protective stages. When relying on an external fuse, make sure to maintain the following:

- Maximum nominal current
- Derating curve
- Type of installation
- Application

Category

IEC 61643-21

C1, C2, C3, D1

VARITECTOR SSC

Category	Testing pulse	Surge voltage	Surge current	Pulse Type	Type
C1	Quick rising edge	0,5 < 2 kV 1.2/50 µs	0.25 < 1 kA 8/20 µs	300	Surge voltage arrester
C2	Quick rising edge	2 < 10 kV 1.2/50 µs	1 < 5 kA 8/20 µs	10	Surge voltage arrester
C3	Quick rising edge	≥ 1 kV 1 kV/µs	10 < 100 A 10/10.000 µs	300	Surge voltage arrester
D1	High power	≥ 1 kV	0.5 < 2.5 kA 10/350 µs	2	Arrester for lightning current and surge voltages

Category C reflects the interference pulses with quick-rising edges and minimised power. Category D uses quick-rising edges and high power to detail the interference pulses. This energy simulates the high-power load that stems from coupled partial lightning currents.

General technical data

Storage temperature: -40 °C ... +80 °C
Operating temperature: -40 °C ... +70 °C
Humidity: 5 % ... 96 % 5 %...96 %
RH without condensation
Material: VO, IP 20

Connection: VSSC4 and VSSC6
Torx®: T15 900917
Slotted: 0.8 x 4
(order number 9008340000)
Nominal torque: 0.5 Nm
Max. Drehmoment: 1 Nm
Max. torque: 10 mm
Solid core: 0.5...6 mm²
Stranded: 0.5 ... 4 mm²
Finely stranded: 0.5 4 mm²
Finely stranded with ferrule: 0.5 4 mm²

Dimensions

VSSC4:

Width: 6.1 mm
Width with frame: 12.2 mm
Height: 76 mm
Depth: 58.5 mm with TS 35 x 7.5

Top connections:
Unprotected: 1
Protected: 4
Bottom connections:
Unprotected: 2
Protected: 3

VSSC6:

Width: 6.1 mm
Width with frame: 12.2 mm
Height: 88.5 mm
Depth: 81 mm with TS 35 x 7.5


Top connections:
Unprotected: 1
Protected: 4
Mid-level connections:
Unprotected: 2
Protected: 5
Bottom connections:
Unprotected: 3
Protected: 6

Markers for VSSC4 and VSSC6:


Dekafix: DEK 5 for the connections
WS 10/6 middle as device marker
SNAPMARK only for the VSSC6 and DEK5/5 for the terminal points.

Derating curves


VSSC4 GDT MOV TAZ




VSSC4 RC



VSSC6 GDT MOV



Other VSSC4 und VSS





Quick product selection for the VARITECTOR SSC

Technical data

Interface	Product designation	Order No.
Q(4) ... 20 mA / 0 ...10 V	VSSC4 CL 24 V UC 0.5 A	1063730000
	VSSC6 CL 24 V UC 0.5 A	1064170000
	VSSC6TR CL FG 24 V UC 0.5 A	1064310000
	VSSC4 CL FG 24 V UC 0.5 A	1063770000
	VSSC6 CL FG 24 V UC 0.5 A	1064270000
	VSSC6TR CL FG 24 V UC 0.5 A	1064310000
ARCNET (Plus)	VSSC6 RS485	1064980000
BLN (Building Level Network)	see Q(4) ... 20 mA / 0 ...10 V	
DeviceNet	VSSC6 RS485	1064980000
DIN measurement bus	see Q(4) ... 20 mA / 0 ...10 V	
Dupline / Miniplex	VSSC6 CL 12 V DC 0.5 A	1064150000
EIB (European Instalation Bus)	VSSC6 GDT 110 V UC 10 kA	1064690000
EIB (European Instalation Bus)	VSSC6 GDT 110 V UC 20 kA	1064700000
ET200	VSSC6 CL 12 V DC 0.5 A	1064150000
Genius I/O Bus	see Q(4) ... 20 mA / 0 ...10 V	
Hart	see Q(4) ... 20 mA / 0 ...10 V	
Cathodic corrosion protection	VSSC6 GDT 230 V UC 20 kA	1064720000
LON™ (Works)	VSSC6 CL 48 V UC 0.5 A	1064190000
M-Bus (Remote meter reading)	see Q(4) ... 20 mA / 0 ...10 V	
MPI Bus	VSSC6 RS485	1064980000
N2 Bus	VSSC6 SL LD 12 V DC 0.5 A	1064340000
Procontic CS31	VSSC6TR CL FG 12 V DC 0.5 A	1064300000
Profibus DP (FMS)	VSSC6 RS485 DP	1065010000
PT100	VSSC6 RTD	1139710000
PSM-EG-RS422...	VSSC6 RS485 DP	1065010000
PSM-EG-RS485...	VSSC6 RS485 DP	1065010000
RS422A, V.11, X.27, RS423A	VSSC6 RS485 DP	1065010000
RS485	VSSC6 RS485 DP	1065010000
RS232-C / V.24	VSSC6 RS232	1064990000
SecuriLan-LON™-Bus	see Q(4) ... 20 mA / 0 ...10 V	
(Profibus DP)	VSSC6 RS485 DP	1065010000
TTY, Q(4) - 20 mA	see Q(4) ... 20 mA / 0 ...10 V	
U-BUS	VSSC6 GDT 110 V UC 20 kA	1064700000
Note: This tables contains selection recommendations. Our technical consultants will be glad to assist you with your individual application requirements.		




A



VARITECTOR SSC 6AN

VSSC 6 CL and CL FG - protection for analogue signals

- Two-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design: 1 analogue signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Rated current I_N	500 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21, HART-compatible
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA
Surge current-carrying capacity C3	50 A
Surge current-carrying capacity D1	0.5 kA
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I_{tmax} (8/20 μ s) wire-wire/wire-PE/GND-PE	5 kA / 5 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0

Connection data




Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35

Failure probability

λ_{ges}	19
MTTF	6008
SIL in compliance with IEC 61508	2

Approvals

Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Dimensions


Height x width x depth

Dimensions

mm 88.5 / 6.2 / 81

Note

VSSC 6 CL and CL FG



Ordering data

	CL 12 V DC	CL 24 V UC	CL 48 V UC	CL 60 V UC
Rated voltage (AC)		24 V	48 V	60 V
Rated voltage (DC)	12 V	34 V	68 V	85 V
Max. continuous voltage, U_c (AC)		30 V	60 V	75 V
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	106 V
Rated current I_n	500 mA	500 mA	500 mA	500 mA
Optical function display	No	No	No	No
Isolating function	No	No	No	No
Input attenuation	≤ 700 kHz	3.4 MHz	5 Mhz	6.8 MHz
Pulse-reset capacity	≤ 20 ms	≤ 170 ms	≤ 150 ms	≤ 20 ms
Residual voltage, U_r typical	900 V	900 V	770 V	780 V

Ordering data

Type	VSSC6 CL 12VDC 0.5A	VSSC6 CL 24VAC/DC 0.5A	VSSC6 CL 48VAC/DC 0.5A	VSSC6 CL 60VAC/DC 0.5A
Order No.	1064150000	1064170000	1064190000	1064210000
Qty.	10	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000

Ordering data

	CLFG 12 V DC	CLFG 24 V UC	CLFG 48 V UC	CLFG 60 V UC
Rated voltage (AC)		24 V	48 V	60 V
Rated voltage (DC)	12 V	34 V	68 V	85 V
Max. continuous voltage, U_c (AC)		30 V	60 V	75 V
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	106 V
Rated current I_n	500 mA	500 mA	500 mA	500 mA
Optical function display	No	No	No	No
Isolating function	No	No	No	No
Input attenuation	≤ 700 kHz	3.4 MHz	5 Mhz	6.8 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 20 ms	≤ 20 ms
Residual voltage, U_r typical	1600 V	1632 V	≤ 1510 V	≤ 1510 V

Ordering data

Type	VSSC6 CL FG 12VDC 0.5A	VSSC6 CLFG24VAC/DC0.5A	VSSC6 CLFG48VAC/DC0.5A	VSSC6 CLFG60VAC/DC0.5A
Order No.	1064260000	1064270000	1064280000	1064290000
Qty.	10	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000







VARITECTOR SSC 6AN


VSSC 6 TR CL and TR CL FG - protection for
floating current loops

- Two-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design: 1 analogue signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	500 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21, HART-compatible
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	50 A 10/1000 μ s
Surge current-carrying capacity D1	0.5 kA 10/350 μ s
Discharge current I_{Δ} (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge $I_{\Delta max}$ (8/20 μ s) wire-wire/wire-PE/GND-PE	5 kA / 5 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	19
MTTF	6008
SIL in compliance with IEC 61508	2
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Dimensions		Dimensions
Height x width x depth	mm	88.5 / 6.2 / 81
Note		

VSSC 6TR CL and TR CL FG



Ordering data

	TR CL 12 V DC	TR CL 24 V UC	TR CL 48 V UC	TR CL 60 V UC
Rated voltage (AC)		24 V	48 V	60 V
Rated voltage (DC)	12 V	34 V	68 V	85 V
Max. continuous voltage, U_c (AC)		30 V	60 V	75 V
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	106 V
Rated current I_n	500 mA	500 mA	500 mA	500 mA
Optical function display	No	No	No	No
Isolating function	Yes	Yes	Yes	Yes
Input attenuation	270 Mhz	270 Mhz	270 Mhz	270 Mhz
Pulse-reset capacity	≤ 20 ms	≤ 170 ms	≤ 150 ms	≤ 20 ms
Residual voltage, U_r typical	900 V	900 V	770 V	780 V

Ordering data

Type	VSSC6 TR CL 12VDC 0.5A	VSSC6 TRCL24VAC/DC0.5A	VSSC6 TRCL48VAC/DC0.5A	VSSC6 TRCL60VAC/DC0.5A
Order No.	1064220000	1064230000	1064240000	1064250000
Qty.	10	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000

Ordering data

	TR CLFG 12 V DC	TR CLFG 24 V UC	TR CLFG 48 V UC	TR CLFG 60 V UC
Rated voltage (AC)		24 V	48 V	60 V
Rated voltage (DC)	12 V	34 V	68 V	85 V
Max. continuous voltage, U_c (AC)		30 V	60 V	75 V
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	106 V
Rated current I_n	500 mA	500 mA	500 mA	500 mA
Optical function display	No	No	No	No
Isolating function	Yes	Yes	Yes	Yes
Input attenuation	270 Mhz	270 Mhz	270 Mhz	270 Mhz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 20 ms	≤ 20 ms
Residual voltage, U_r typical	≤ 1.7 kV	≤ 1650 V	≤ 1550 V	≤ 1550 V

Ordering data


Type	VSSC6TRCLFG12VDC0.5A	VSSC6TRCLFG24VAC/DC0.5A	VSSC6TRCLFG48VAC/DC0.5A	VSSC6TRCLFG60VAC/DC0.5A
Order No.	1064300000	1064310000	1064320000	1064330000
Qty.	10	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000



VARITECTOR SSC 6AN

VSSC 6 SL and SL FG - protection for binary signals with
signal display

- One-stage surge protection with screw connection for measurement
and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design for two signals
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: C1, C2
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and
2.5 kA (10/350 µs) to PE




Technical data

Rated current I_N	500 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 µs
Surge current-carrying capacity C3	10 A 10/1000 µs
Surge current-carrying capacity D1	1 kA 10/350 µs
Discharge current I_{Δ} (8/20 µs) wire-wire/wire-PE/GND-PE	/ 2.5 kA
Discharge $I_{\Delta max}$ (8/20 µs) wire-wire/wire-PE/GND-PE	/ 10 kA
Lightning test I_{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/ 1 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0

Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35


Failure probability	
λ_{ges}	54
MTTF	2114
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions	
Height x width x depth	mm 88.5 / 6.2 / 81

Note	
-------------	--

VSSC 6 SL and SL FG



Ordering data

	SL LD 12 V DC	SL LD 24 V UC	SLFG LD 12 V DC	SLFG LD 24 V UC
Rated voltage (AC)		24 V		24 V
Rated voltage (DC)	12 V	34 V	12 V	34 V
Max. continuous voltage, U_c (AC)		30 V		30 V
Max. continuous voltage, U_c (DC)	15 V	42 V	15 V	42 V
Rated current I_n	500 mA	500 mA	500 mA	500 mA
Optical function display	Yes	Yes	Yes	Yes
Isolating function	No	No	No	No
Input attenuation	750 KHz	3.2 MHz	750 KHz	3.2 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 20 ms	≤ 20 ms
Residual voltage, U_r typical	≤ 100 V	150 V	≤ 100 V	150 V

Ordering data

Type	VSSC6SL LD 12VDC 0.5A	VSSC6SL LD24VAC/DC0.5A	VSSC6SL FG LD12VDC0.5A	VSSC6SLFGLD24VAC/DC0.5A
Order No.	1064340000	1064350000	1064420000	1064430000
Qty.	10	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000

Ordering data

	SLFG LD 48 V UC
Rated voltage (AC)	48 V
Rated voltage (DC)	68 V
Max. continuous voltage, U_c (AC)	60 V
Max. continuous voltage, U_c (DC)	85 V
Rated current I_n	500 mA
Optical function display	Yes
Isolating function	No
Input attenuation	4.6 MHz
Pulse-reset capacity	≤ 20 ms
Residual voltage, U_r typical	< 200 V

Ordering data


Type	VSSC6SLFGLD48VAC/DC0.5A
Order No.	1064440000
Qty.	10
Note	End plate AP VSSC6 1063110000



VARITECTOR SSC 6AN

VSSC 6 TR SL and TR SL FG - protection for
floating signals with signal display

- Two-stage surge protection with screw connection for measurement and control signals with signal display
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design for two signals
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Rated current I_N	500 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	10 A 10/1000 μ s
Surge current-carrying capacity D1	1 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 1 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0

Connection data




Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35

Failure probability

λ_{ges}	54
MTTF	2114
SIL in compliance with IEC 61508	3

Approvals

Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions

Height x width x depth	mm	88.5 / 6.2 / 81
------------------------	----	-----------------

Note

VSSC 6 TR SL and TR CL FG



Ordering data

	TR SL LD 12 V DC	TR SL LD 24 V UC	TR SL 24 V AC	TR SL LD 48 V UC
Rated voltage (AC)		24 V	24 V	48 V
Rated voltage (DC)	12 V	34 V	34 V	68 V
Max. continuous voltage, U_c (AC)		30 V	30 V	60 V
Max. continuous voltage, U_c (DC)	15 V	42 V	42 V	85 V
Rated current I_n	500 mA	500 mA	500 mA	500 mA
Optical function display	Yes	Yes	No	Yes
Isolating function	Yes	Yes	Yes	Yes
Input attenuation	750 KHz	3.2 MHz	3.2 MHz	4.6 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 20 ms	≤ 20 ms
Residual voltage, U_r typical	≤ 100 V	150 V	150 V	< 200 V

Ordering data

Type	VSSC6TRSLD12VDC0.5A	VSSC6TRSLD24VAC/DC0.5A	VSSC6TRSL24VAC/DC0.5A	VSSC6TRSLD48VAC/DC0.5A
Order No.	1064380000	1064390000	1354790000	1064400000
Qty.	10	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000

Ordering data

	TR SLFG LD 12 V DC	TR SLFG LD 24 V UC	TR SL FG 24 V AC
Rated voltage (AC)		24 V	24 V
Rated voltage (DC)	12 V	34 V	34 V
Max. continuous voltage, U_c (AC)		30 V	30 V
Max. continuous voltage, U_c (DC)	15 V	42 V	42 V
Rated current I_n	500 mA	500 mA	500 mA
Optical function display	Yes	Yes	No
Isolating function	Yes	Yes	Yes
Input attenuation	750 KHz	3.2 MHz	3.2 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 20 ms
Residual voltage, U_r typical	≤ 100 V	150 V	150 V

Ordering data



Type	VSSC6TRSLFGLD12VDC0.5A	VSSC6TRSLFGLD24VUC 0.5A	VSSC6TRSLFG24VAC/DC0.5A
Order No.	1064490000	1064500000	1354800000
Qty.	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000



VARITECTOR SSC 6AN


VSSC 6 MOV - protection with Varistor (MOV)

- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design for two signals
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: C1, C2
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	12 A
Volume resistance	< 0.1 Ω
Overload - failure mode	Mode 1
Requirements category acc. to IEC 61643-21	C1
Standards	According to IEC61643-21
Surge current-carrying capacity C1	0.25 kA 8/20 μ s 0.5 kV 1.2/50 μ s
Surge current-carrying capacity C2	
Surge current-carrying capacity C3	
Surge current-carrying capacity D1	
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 1 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	26
MTTF	4391
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	According to IEC61643-21



Dimensions		Dimensions
Height x depth	mm	88.5 / 81
Note		

VSSC 6 MOV



Ordering data

	MOV 12 V DC	MOV 24 V UC	MOV 48 V UC	MOV 60 V UC
Rated voltage (AC)		24 V	48 V	60 V
Rated voltage (DC)	12 V	34 V	68 V	85 V
Max. continuous voltage, U_c (AC)		30 V	60 V	75 V
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	106 V
Rated current I_n	12 A	12 A	12 A	12 A
Optical function display	No	No	No	No
Isolating function	No	No	No	No
Input attenuation				
Pulse-reset capacity				
Residual voltage, U_r typical				
Capacitance	10.8 nF	4.6 nF	2.0 nF	1.78 nF
Width	6.2 mm	6.2 mm	6.2 mm	6.2 mm

Ordering data

Type	VSSC6 MOV 12VDC	VSSC6 MOV 24VAC/DC	VSSC6 MOV 48VAC/DC	VSSC6 MOV 60VAC/DC
Order No.	1064530000	1064540000	1064570000	1064600000
Qty.	8	8	8	8
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000

Ordering data

	MOV 120 V UC	MOV 240 V UC
Rated voltage (AC)	120 V	240 V
Rated voltage (DC)	170 V	339 V
Max. continuous voltage, U_c (AC)	150 V	288 V
Max. continuous voltage, U_c (DC)	212 V	407 V
Rated current I_n	12 A	12 A
Optical function display	No	No
Isolating function	No	No
Input attenuation		
Pulse-reset capacity		
Residual voltage, U_r typical		
Capacitance	283 pF	0.5 nF
Width	12.4 mm	12.4 mm

Ordering data



Type	VSSC6 MOV 120VAC/DC	VSSC6 MOV 240VAC/DC
Order No.	1064610000	1064630000
Qty.	5	5
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000



VARITECTOR SSC 6AN

VSSC 6 TR LD MOV - protection with varistor (MOV)

- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design for two signals
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: C1, C2
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	12 A
Volume resistance	< 0.1 Ω
Overload - failure mode	Mode 1
Requirements category acc. to IEC 61643-21	C1
Standards	IEC 61643-21
Surge current-carrying capacity C1	0.25 kA 8/20 μ s 0.5 kV 1.2/50 μ s
Surge current-carrying capacity C2	
Surge current-carrying capacity C3	
Surge current-carrying capacity D1	
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 1 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0

Connection data


Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35

Failure probability

λ_{ges}	37
MTTF	3085
SIL in compliance with IEC 61508	3

Approvals

Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions

Height x depth	mm	88.5 / 81
----------------	----	-----------

Note

VSSC 6 TR LD MOV



Ordering data

	TR LD MOV 12 V DC	TR LD MOV 24 V UC	TR LD MOV 48 V UC	TR LD MOV 120 V UC
Rated voltage (AC)		24 V	48 V	120 V
Rated voltage (DC)	12 V	34 V	68 V	170 V
Max. continuous voltage, U_c (AC)		30 V	60 V	150 V
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	212 V
Rated current I_n	12 A	12 A	12 A	12 A
Optical function display	Yes	Yes	Yes	Yes
Isolating function	Yes	Yes	Yes	Yes
Input attenuation				
Pulse-reset capacity				
Residual voltage, U_r typical				
Capacitance	10.8 nF	4.6 nF	2.0 nF	283 pF
Width	6.2 mm	6.2 mm	6.2 mm	12.4 mm

Ordering data

Type	VSSC6 TRLDMOV 12VDC	VSSC6 TRLDMOV 24VAC/DC	VSSC6 TRLDMOV 48VAC/DC	VSSC6 TRLDMOV120VAC/DC
Order No.	1064800000	1064810000	1064820000	1064840000
Qty.	8	8	8	5
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000

Ordering data

	TR LD MOV 240 V UC
Rated voltage (AC)	240 V
Rated voltage (DC)	339 V
Max. continuous voltage, U_c (AC)	288 V
Max. continuous voltage, U_c (DC)	407 V
Rated current I_n	12 A
Optical function display	Yes
Isolating function	Yes
Input attenuation	
Pulse-reset capacity	
Residual voltage, U_r typical	
Capacitance	0.5 nF
Width	12.4 mm

Ordering data



Type	VSSC6 TRLDMOV240VAC/DC
Order No.	1064860000
Qty.	5
Note	End plate AP VSSC6 1063110000



VARITECTOR SSC 6AN

VSSC 6 GDT - protection with sparkover gap (GDT)

- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 12.4 mm
- Space-saving design for two signals
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data

Rated current I_N	12 A
Volume resistance	< 0.1 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	50 A 10/1000 μ s
Surge current-carrying capacity D1	1 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 2.5 kA
Discharge I_{tmax} (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 1 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0

Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35

Failure probability	
λ_{ges}	10
MTTF	11416
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY
Standards	IEC 61643-21



Dimensions		Dimensions
Height x depth	mm	88.5 / 81

Note



VSSC 6 GDT

Ordering data

	GDT 24 V UC 10 kA	GDT 110 V UC 10 kA	GDT 240 V UC 10 kA	GDT 110 V UC 20 kA
Rated voltage (AC)	24 V	110 V	240 V	110 V
Rated voltage (DC)	34 V	156 V	339 V	156 V
Max. continuous voltage, U_c (AC)	30 V	138 V	288 V	138 V
Max. continuous voltage, U_c (DC)	42 V	195 V	407 V	195 V
Rated current I_n	12 A	12 A	12 A	12 A
Optical function display	No	No	No	No
Isolating function	No	No	No	No
Input attenuation				
Pulse-reset capacity				
Residual voltage, U_r typical				
Capacitance	1.5 nF	4.2 nF	3.0 nF	2.5 nF
Width	6.2 mm	6.2 mm	12.4 mm	12.4 mm

Ordering data				
Type	VSSC6 GDT 24VAC/DC 10kA	VSSC6 GDT 110VAC/DC10kA	VSSC6 GDT 240VAC/DC10kA	VSSC6 GDT 110VAC/DC20kA
Order No.	1064640000	1064690000	1064710000	1064700000
Qty.	10	10	5	5
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000

Ordering data

	GDT 240 V UC 20 kA
Rated voltage (AC)	240 V
Rated voltage (DC)	339 V
Max. continuous voltage, U_c (AC)	288 V
Max. continuous voltage, U_c (DC)	407 V
Rated current I_n	12 A
Optical function display	No
Isolating function	No
Input attenuation	
Pulse-reset capacity	
Residual voltage, U_r typical	
Capacitance	2.4 nF
Width	12.4 mm



Ordering data	
Type	VSSC6 GDT 240VAC/DC20kA
Order No.	1064720000
Qty.	5
Note	End plate AP VSSC6 1063110000



VARITECTOR SSC 6AN

VSSC 6 TR GDT - protection with sparkover gap (GDT)

- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm or 12.4 mm
- Space-saving design for two signals
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data

Rated current I_N	12 A
Volume resistance	< 0.1 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	50 A 10/1000 μ s
Surge current-carrying capacity D1	1 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 1 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...80 °C
Protection degree	IP20
UL 94 flammability rating	V-0

Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35

Failure probability	
λ_{ges}	10
MTTF	11416
SIL in compliance with IEC 61508	3

Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY
Standards	IEC 61643-21



Dimensions	
Height x depth	mm 88.5 / 81

Note	
------	--

VSSC 6 TR GDT

Ordering data

	TR GDT 24 V UC 10 kA	TR GDT 110 V UC 10 kA	TR GDT 240 V UC 10 kA
Rated voltage (AC)	24 V	110 V	240 V
Rated voltage (DC)	34 V	156 V	339 V
Max. continuous voltage, U_c (AC)	30 V	138 V	288 V
Max. continuous voltage, U_c (DC)	42 V	195 V	407 V
Rated current I_n	12 A	12 A	12 A
Optical function display	No	No	No
Isolating function	Yes	Yes	Yes
Input attenuation			
Pulse-reset capacity			
Residual voltage, U_r typical			
Capacitance	1.5 nF	4.2 nF	3.0 nF
Width	6.2 mm	6.2 mm	12.4 mm

Ordering data			
Type	VSSC6TRGDT24VAC/DC10kA	VSSC6TRGDT110VAC/DC10kA	VSSC6TRGDT240VAC/DC10kA
Order No.	1064870000	1064890000	1064920000
Qty.	10	10	5
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000







VARITECTOR SSC 6AN


VSSC 6 TAZ and TR TAZ - suppressor diode,
with and without isolation option (TR)

- Two-stage surge protection with screw connection for PROFIBUS RS422/485 data interfaces
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design: 1 signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	12 A
Volume resistance	$< 0.1 \Omega$
Overload - failure mode	Mode 1
Requirements category acc. to IEC 61643-21	C3
Standards	According to IEC61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	
Surge current-carrying capacity C3	50 A 10/1000 µs
Surge current-carrying capacity D1	
Discharge current I , (8/20 µs) wire-wire/wire-PE/GND-PE	/ 0.2 kA
Discharge I_{max} (8/20 µs) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Lightning test I_{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	32
MTTF	3567
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	According to IEC61643-21



Dimensions		Dimensions
Height x width x depth	mm	88.5 / 6.2 / 81
Note		

VSSC 6 TAZ and TR LD TAZ

Ordering data

	TAZ 12 V DC	TAZ 24 V UC	TR LD TAZ 24 V UC
Rated voltage (AC)		24 V	24 V
Rated voltage (DC)	12 V	34 V	34 V
Max. continuous voltage, U_c (AC)		30 V	30 V
Max. continuous voltage, U_c (DC)	15 V	42 V	42 V
Rated current I_n	12 A	12 A	12 A
Optical function display	No	No	Yes
Isolating function	No	No	Yes
Residual voltage, U_r typical	< 50 V	70 V	≤ 100 V
Capacitance	4.9 pF	0.8 nF	0.8 nF

Ordering data			
Type	VSSC6 TAZ 12VDC	VSSC6 TAZ 24VAC/DC	VSSC6 TRLDTAZ 24VAC/DC
Order No.	1064730000	1064740000	1064950000
Qty.	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000







VARITECTOR SSC 6AN


VSSC 6 RS485 - protection for RS232/RS485
signal interfaces

- Two-stage surge protection with screw connection for RS422/RS485 data interfaces
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design: 1 signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	500 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	10 A 10/1000 μ s
Surge current-carrying capacity D1	0.5 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	60
MTTF	1903
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions		Dimensions
Height x width x depth	mm	88.5 / 6.2 / 81
Note		

VSSC 6 RS485, RS485 DP and RS232

Ordering data

	RS485	RS485 DP	RS232
Rated voltage (AC)			
Rated voltage (DC)	12 V	12 V	12 V
Max. continuous voltage, U_c (AC)			
Max. continuous voltage, U_c (DC)	15 V	15 V	15 V
Rated current I_N	500 mA	500 mA	500 mA
Optical function display	No	No	No
Isolating function	No	No	No
Input attenuation	113.6 MHz	113.6 MHz	1.4 MHz
Pulse-reset capacity	≤ 15 ms	≤ 15 ms	≤ 15 ms
Residual voltage, U_p typical	≤ 100 V	≤ 100 V	≤ 100 V

Ordering data			
Type	VSSC6 RS485	VSSC6 RS485 DP	VSSC6 RS232
Order No.	1064980000	1065010000	1064990000
Qty.	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000







VARITECTOR SSC 6AN

VSSC 6 RTD - protection for PT100 signal interfaces

- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design for two signals
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	300 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	10 A 10/1000 μ s
Surge current-carrying capacity D1	0.5 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I_{tmax} (8/20 μ s) wire-wire/wire-PE/GND-PE	5 kA / 5 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	63
MTTF	1812
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21

Dimensions		Dimensions
Height x width x depth	mm	88.5 / 6.2 / 81
Note		

VSSC 6 RTD

Ordering data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (DC)
Rated current I_N
Optical function display
Isolating function
Input attenuation
Residual voltage, U_r typical

RTD

1 V
5 V
300 mA
No
113.6 MHz
150 V

Ordering data

Type
Order No.
Qty.

VSSC6 RTD
1139710000
10
End plate AP VSSC6 1063110000

Note

VARITECTOR SSC 4AN

Lightning and surge protection in terminal block design

**The new and comprehensive surge protection family
for measurement and control technology in 6 mm
overall width**

The interfaces in C&I applications must be protected against surges, since coupling of surges on lines can interfere with or destroy signal inputs. It is therefore necessary that C&I devices be protected in their immediate vicinity. For this purpose, VARITECTOR SSC, with its compact terminal-block format, is ideal for this application. The protective circuits are matched to the current loops and to binary signals.

The VARITECTOR SSC products are tested according to the latest standards (IEC61643-21): They satisfy the safe short-circuit mode in the event of overload by AC currents in classes D1, C2 and C1. The products are ATEX-tested for use in intrinsically safe circuits.


Easy to use

The clamping area of 0.5 mm² – 6 mm² is covered with combined Torx®/Slot headed screw and a tightening torque of 0.8 Nm.




Space-saving

Modular width of terminals just 6.2 mm for two binary signals or per analogue signal.



Large variety

A solution for every type of surge protection:
More than 100 variations: current loops and
binary signals for 5 V, 12 V, 24 V, 48 V and
60 V, with integrated components, e.g. varistors.

**Quick identification**

Large-area marking options: marking of devices
and single connections as well as colour-
coded marking of the voltage levels for fast
identification in the switching cabinet.

**Simple and safe**

Simple installation and high safety through
direct PE contact when mounting on the
terminal rail, with a very high discharge current
of up to 20 kA.






VARITECTOR SSC 4AN



VSSC 4 CL and CL FG - protection for current loops

- Two-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design: 1 analogue signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Rated current I_N	500 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21, HART-compatible
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	50 A 10/1000 μ s
Surge current-carrying capacity D1	0.5 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I_{tmax} (8/20 μ s) wire-wire/wire-PE/GND-PE	5 kA / 5 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	19
MTTF	6008
SIL in compliance with IEC 61508	2
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Dimensions		Dimensions	
Height x width x depth	mm	76 / 6.2 / 58.5	
Note			

VSSC 4 CL and CL FG



Ordering data

	VSSC4 CL 12 V DC 0.5 A	VSSC4 CL 24 V UC 0.5 A	VSSC4 CL 48 V UC 0.5 A	VSSC4 CL FG 12 V DC 0.5 A
Rated voltage (AC)		24 V	48 V	
Rated voltage (DC)	12 V	34 V	68 V	12 V
Max. continuous voltage, U_c (AC)		30 V	60 V	
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	15 V
Rated current I_n	500 mA	500 mA	500 mA	500 mA
Optical function display	No	No	No	No
Isolating function	No	No	No	No
Input attenuation	750 KHz	3.4 MHz	5 Mhz	750 KHz
Pulse-reset capacity	≤ 20 ms	≤ 150 ms	≤ 110 ms	≤ 20 ms
Residual voltage, U_r typical	< 1000 V	< 1000 V	< 800 V	≤ 1500 V

Ordering data

Type	VSSC4 CL 12VDC 0.5A	VSSC4 CL 24VAC/DC 0.5A	VSSC4 CL 48VAC/DC 0.5A	VSSC4 CL FG 12VDC 0.5A
Order No.	1063720000	1063730000	1063740000	1063760000
Qty.	10	10	10	10
Note	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000

Ordering data

	VSSC4 CL FG 24 V UC 0.5 A	VSSC4 CL FG 48 V UC 0.5 A
Rated voltage (AC)	24 V	48 V
Rated voltage (DC)	34 V	68 V
Max. continuous voltage, U_c (AC)	30 V	60 V
Max. continuous voltage, U_c (DC)	42 V	85 V
Rated current I_n	500 mA	500 mA
Optical function display	No	No
Isolating function	No	No
Input attenuation	3.4 MHz	5 Mhz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms
Residual voltage, U_r typical	≤ 1500 V	≤ 1500 V


Ordering data

Type	VSSC4 CL FG24VAC/DC0.5A	VSSC4 CL FG48VAC/DC0.5A
Order No.	1063770000	1063780000
Qty.	10	10
Note	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000

VARITECTOR SSC 4AN




VSSC 4 SL and SL FG - protection for binary signal

- Two-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design: 1 binary signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Rated current I_N	500 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	10 A 10/1000 μ s
Surge current-carrying capacity D1	1 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	43
MTTF	2655
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions	Dimensions
Height x width x depth	mm 76 / 6.2 / 58.5

Note

VSSC 4 SL and SL FG



Ordering data

	VSSC4 SL 12 V DC 0.5 A	VSSC4 SL 24 V UC 0.5 A	VSSC4 SL 48 V UC 0.5 A	VSSC4 SL 60 V UC 0.5 A
Rated voltage (AC)		24 V	48 V	60 V
Rated voltage (DC)	12 V	34 V	68 V	85 V
Max. continuous voltage, U_c (AC)		30 V	60 V	75 V
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	106 V
Rated current I_n	500 mA	500 mA	500 mA	500 mA
Optical function display	No	No	No	No
Isolating function	No	No	No	No
Input attenuation	860 KHz	3.4 MHz	5.2 MHz	6.6 MHz
Pulse-reset capacity	≤ 20 ms	≤ 35 ms	≤ 20 ms	≤ 20 ms
Residual voltage, U_r typical	≤ 100 V	150 V	< 200 V	250 V

Ordering data

	VSSC4 SL 12VDC 0.5A	VSSC4 SL 24VAC/DC 0.5A	VSSC4 SL 48VAC/DC 0.5A	VSSC4 SL 60VAC/DC 0.5A
Type				
Order No.	1063830000	1063840000	1063860000	1063870000
Qty.	10	10	10	10
Note	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000

Ordering data

	VSSC4 SL FG 12 V DC 0.5 A	VSSC4 SL FG 24 V UC 0.5 A
Rated voltage (AC)		24 V
Rated voltage (DC)	12 V	34 V
Max. continuous voltage, U_c (AC)		30 V
Max. continuous voltage, U_c (DC)	15 V	42 V
Rated current I_n	500 mA	500 mA
Optical function display	No	No
Isolating function	No	No
Input attenuation	860 KHz	3.4 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms
Residual voltage, U_r typical	≤ 100 V	150 V



Ordering data

	VSSC4 SL FG 12VDC 0.5A	VSSC4 SL FG24VAC/DC0.5A
Type		
Order No.	1063880000	1063890000
Qty.	10	10
Note	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000

VARITECTOR SSC 4AN


VSSC 4 MOV - protection with Varistor
(MOV)

- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design for one signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: C1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	20 A
Volume resistance	< 0.1 Ω
Overload - failure mode	Mode 1
Requirements category acc. to IEC 61643-21	C1
Standards	IEC 61643-21
Surge current-carrying capacity C1	0.25 kA 8/20 μ s 0.5 kV 1.2/50 μ s
Surge current-carrying capacity C2	1 kA 8/20 μ s
Surge current-carrying capacity C3	
Surge current-carrying capacity D1	
Discharge current I , (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Discharge I_{max} , (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 1 kA
Lightning test I_{imp} , (10/350 μ s) wire-wire/wire-PE/GND-PE	/
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	26
MTTF	4391
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions		Dimensions
Height x width x depth	mm	76 / 6.2 / 58.5
Note		



VSSC MOV 4 - components

Ordering data

	VSSC4 MOV 12 V DC	VSSC4 MOV 24 V UC	VSSC4 MOV 48 V UC	VSSC4 MOV 60 V UC
Rated voltage (AC)		24 V	48 V	60 V
Rated voltage (DC)	12 V	34 V	68 V	85 V
Max. continuous voltage, U_c (AC)		30 V	60 V	75 V
Max. continuous voltage, U_c (DC)	15 V	42 V	85 V	106 V
Rated current I_n	20 A	20 A	20 A	20 A
Optical function display	No	No	No	No
Isolating function	No	No	No	No
Requirements category acc. to IEC 61643-21	C1	C1	C1, C2	C1, C2
Pulse-reset capacity				
Residual voltage, U_r typical	≤ 100 V	150 V	250 V	< 300 V
Capacitance	11.2 nF	4.8 nF	1.9 nF	1.7 nF

Ordering data

Type	VSSC4 MOV 12VDC	VSSC4 MOV 24VAC/DC	VSSC4 MOV 48VAC/DC	VSSC4 MOV 60VAC/DC
Order No.	1063950000	1063960000	1063970000	1063980000
Qty.	10	10	10	10
Note	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000

Ordering data

	VSSC4 MOV 120 V UC	VSSC4 MOV 150 V UC	VSSC4 MOV 240 V UC
Rated voltage (AC)	120 V	150 V	240 V
Rated voltage (DC)	170 V	212 V	339 V
Max. continuous voltage, U_c (AC)	150 V	188 V	288 V
Max. continuous voltage, U_c (DC)	212 V	266 V	407 V
Rated current I_n	20 A	20 A	20 A
Optical function display	No	No	No
Isolating function	No	No	No
Requirements category acc. to IEC 61643-21	C1, C2	C1, C2	C1, C2
Pulse-reset capacity			
Residual voltage, U_r typical	< 600 V	< 700 V	< 1200 V
Capacitance	1.48 nF	0.97 nF	0.7 nF

Ordering data



Type	VSSC4 MOV 120VAC/DC	VSSC4 MOV 150VAC/DC	VSSC4 MOV 240VAC/DC
Order No.	1063990000	1064010000	1064020000
Qty.	5	5	5
Note	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000



VARITECTOR SSC 4AN

VSSC 4 GDT - protection with sparkover gap (GDT)


- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 12.4 mm
- Space-saving design for one signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: C1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



VSSC4 GDT

Technical data

Rated current I_N	20 A
Volume resistance	< 0.1 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 20 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 2.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	10
MTTF	11416
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY
Standards	IEC 61643-21



Dimensions	Dimensions
Height x width x depth	mm 76 / 12.4 / 58.5
Note	

VSSC 4 GDT - components

Ordering data

	VSSC4 GDT 110 V UC 20 kA	VSSC4 GDT 240 V UC 20 kA
Rated voltage (AC)	110 V	240 V
Rated voltage (DC)	156 V	339 V
Max. continuous voltage, U_c (AC)	138 V	288 V
Max. continuous voltage, U_c (DC)	195 V	407 V
Rated current I_n	20 A	20 A
Optical function display	No	No
Isolating function	No	No
Residual voltage, U_r typical	< 1000 V	$\leq$ 1200 V
Capacitance	4.65 pF	4.65 pF

Ordering data		
Type	VSSC4 GDT 110VAC/DC20kA	VSSC4 GDT 240VAC/DC20kA
Order No.	1064050000	1064060000
Qty.	5	5
Note	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000







VARITECTOR SSC 4AN

VSSC 4 TAZ - protection with suppressor diode (TAZ)


- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design for one signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: C1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	20 A
Volume resistance	< 0.1 Ω
Overload - failure mode	Mode 1
Requirements category acc. to IEC 61643-21	C3
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	
Surge current-carrying capacity C3	50 A
Surge current-carrying capacity D1	
Discharge current I_t (8/20 µs) wire-wire/wire-PE/GND-PE	/ 0.2 kA
Discharge I_{max} (8/20 µs) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Lightning test I_{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0

Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	32
MTTF	3567
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions	Dimensions
Height x width x depth	mm 76 / 6.2 / 58.5

Note

VSSC 4 TAZ - components

Ordering data

Rated voltage (AC)
 Rated voltage (DC)
 Max. continuous voltage, U_c (AC)
 Max. continuous voltage, U_c (DC)
 Rated current I_n
 Optical function display
 Isolating function
 Residual voltage, U_r typical
 Capacitance
 Surge current-carrying capacity C3

VSSC4 TAZ 12 V DC

12 V
 15 V
 20 A
 No
 No
 30 V
 5.06 nF
 50 A

VSSC4 TAZ 24 V UC

24 V
 34 V
 30 V
 42 V
 20 A
 No
 No
 70 V
 0.82 nF
 15 A

VSSC4 TAZ 48 V UC

48 V
 75 V
 60 V
 85 V
 20 A
 No
 No
 < 165 V
 0.45 nF
 15 A

Ordering data

Type
 Order No.
 Qty.

VSSC4 TAZ 12VDC

1064070000

10

End plate AP VSSC4 1063120000

VSSC4 TAZ 24VAC/DC

1064080000

10

End plate AP VSSC4 1063120000

VSSC4 TAZ 48VAC/DC

1064090000

10

End plate AP VSSC4 1063120000



Note



VARITECTOR SSC 4AN


VSSC 4 RC - protection with a combination of resistors
and capacitors

- Two-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 12.4 mm
- Space-saving design for one signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	20 A
Volume resistance	< 0.1 Ω
Overload - failure mode	Mode 1
Requirements category acc. to IEC 61643-21	C1
Standards	IEC 61643-21
Surge current-carrying capacity C1	0.25 kA 8/20 μ s 0.5 kV 1.2/50 μ s
Surge current-carrying capacity C2	
Surge current-carrying capacity C3	
Surge current-carrying capacity D1	
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	/
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	
Failure probability	
λ_{ges}	28
MTTF	4048
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions		Dimensions
Height x width x depth	mm	76 / 12.4 / 58.5
Note		

VSSC 4 RC - components

Ordering data

	VSSC4 RC 24 V UC	VSSC4 RC 240 V UC
Rated voltage (AC)	24 V	240 V
Rated voltage (DC)	34 V	339 V
Max. continuous voltage, U_c (AC)	30 V	275 V
Max. continuous voltage, U_c (DC)	42 V	388 V
Rated current I_n	20 A	20 A
Optical function display	No	No
Isolating function	No	No
Input attenuation		
Pulse-reset capacity		
Residual voltage, U_r typical	150 V	< 500 V
Capacitance	8.5 nF	220 nF

Ordering data		
Type	VSSC4 RC 24VAC/DC	VSSC4 RC 240VAC/DC
Order No.	1064120000	1064130000
Qty.	5	5
Note	End plate AP VSSC4 1063120000	End plate AP VSSC4 1063120000



MCZ OVP

Lightning and surge protection for data interfaces



Weidmüller's "MCZ OVP" surge protection for industrial bus systems and data interfaces: Narrow surge-protection terminals with tension-clamp connections for PROFIBUS, Interbus, CAN, DeviceNet – with no signal delay. The Omega stainless steel spring used for DIN rail contact ensures outstanding discharging characteristics that are consistent and reliable.


Space-saving

The narrow 6-mm MCZ OVP surge protector is installed simply and quickly due to its terminal block design.

Quick to connect


Maintenance-free tension-clamp wire connection: providing strong contact force and quick wiring times. This ensures a more securely clamped wire across the entire clamping area.






Vibration-resistant PE contact

Up to 10 kA (8/20 μ s) of surge voltage can be reliably discharged via the stainless steel Omega spring. This contact snaps onto the rail and requires no tools to install.



High transfer rates with protection

Variants are available for protecting data lines (including the following industrial bus systems: PROFIBUS, PROFINET, Interbus, C-Bus, MODBUS, CAN, DeviceNet, etc.)



Narrow surge protection terminals with tension-clamp wire connections for measurement and control systems

Weidmüller MCZ surge protection terminals are characterised by their maximum protective function, and a compact design of only 6 mm. The tension spring connection and direct earthing via the terminal rail contact results in time-savings during installation. The MCZ OVP terminals are suitable for installing in the tightest of places in automated process, industrial and building services systems.



The three-stage surge protection terminals are fitted with gas discharge tubes, varistors, suppression diodes (TAZ) and decoupling inductors. Individual protective components such as varistors and suppression diodes complement the range. The MCZ OVP surge protection terminals are available with rated voltages of 24 V and 48 V. The response time for the 3-stage MCZ OVP is typically 100 ps. The earth contact is produced by clipping the terminal to an earthed terminal rail. To guarantee a safe energy discharge of up to 10 kA (8/20 μ s) via these terminals, the TS 35 rail must be earthed.

EMC regulations require the terminal rail to be securely screwed to an earthed mounting plate. Optimum protection is achieved when the PE contact is made via a tension spring terminal every 600 mm.

The different models

MCZ OVP HF is a two-stage protective combination with a bridge circuit consisting of suppressor diodes. With this circuitry, high transmission rates of up to 100 Mhz can be reached in 100 Ohm systems.

The protective circuitry is particularly suitable for protecting high-speed data transmission systems and high-speed analogue systems.


MCZ OVP CL is a three-stage protective combination with a suppression diode between the current paths. It limits the surge in analogue signal circuits, e.g. current loops.

MCZ OVP SL is a three-stage protective combination with two suppression diodes, each from the signal line to earth. It limits the surge in binary circuits, e.g. for actuators.

MCZ OVP CL FG is a three-stage protective combination with a suppression diode between the current paths. It limits the surge in analogue signal circuits. A high-resistance earth connection is achieved with a gas discharge tube.


MCZ-OVP Filter-Terminals contain selected varistors, capacitors and series inductances. They form reliable noise filters. Coupled interference in the kHz range is safely discharged to earth. For example, the signal inputs of a PLC, which can be protected against interference voltages and RF interference.

Attenuation chart MCZ OVP Filter




MCZ OVP SL FG is a three-stage protective combination with two suppression diodes, each from the signal line to earth. It limits the surge in binary circuits, e.g. for actuators. A high-resistance earth connection is achieved with three gas discharge tubes.

Derating curve MCZ OVP $I_{\max} = 0,5\text{ A}$



Derating curve MCZ OVP $I_{\max} = 1,25\text{ A}$





MCZ OVP series





2-stage protection with tension clamp

connection

- Slim overvoltage protection terminal with tension clamp connection
- 6 mm slim fine overvoltage protection
- Fast wiring thanks to TS contact and tension clamp connections

MCZ OVP HF 5 V 0.3 A

MCZ OVP HF 12 V 0.3 A



Technical data

Rated voltage (AC) / Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Rated voltage (DC), max.
Operating current, I_{max}
Volume resistance
Gas discharge tube
Limiting frequency (-3 dB) at load resistance
Discharge current, max. (8/20 μ s)
Lightning test current I_{imp} (10/350 μ s)
Requirements category acc. to IEC 61643-21
Storage temperature
Ambient temperature (operational)

Protection level

Protection level wire-PE 1kV/ μ s, type
Protection level wire-PE 8/20 μ s, type
Protection level wire-wire 1kV/ μ s, type
Protection level wire-wire 8/20 μ s, type

Approvals

Approvals

5 V / 5 V
7 V
10 V
0.3 A
2.50 Ω
Yes
100 MHz (measured in 100- Ω system)
5 kA

D1, C3, C2, C1
-40 °C...85 °C
-40 °C...60 °C

15 V
30 V
15 V
15 V

CE; EAC

13 V / 12 V
13 V
18.5 V
0.3 A
2.50 Ω
Yes
100 MHz (measured in 100- Ω system)
5 kA

D1, C3, C2, C1
-40 °C...85 °C
-40 °C...60 °C

25 V
40 V
25 V
25 V

CE; EAC

Dimensions

Height x width x depth mm

91 / 6 / 63.5

91 / 6 / 63.5

Note

Ordering data

Type	Qty.	Order No.
MCZ OVP HF 5V 0,3A	10	8948620000

Type	Qty.	Order No.
MCZ OVP HF 12V 0,3A	10	8948610000

Note

Accessories

Note


End plate
AP MCZ 1,5 SW: 1046410000

End plate
AP MCZ 1,5 SW: 1046410000



2-stage protection with tension clamp

connection

- Slim overvoltage protection terminal with tension clamp connection
- 6 mm slim fine overvoltage protection
- Fast wiring thanks to TS contact and tension clamp connections



MCZ OVP HF 24 V 0.3 A



Technical data

Rated voltage (AC) / Rated voltage (DC)	24 V / 24 V
Max. continuous voltage, U _c (AC)	28 V
Rated voltage (DC), max.	40 V
Operating current, I _{max}	0.3 A
Volume resistance	2.50 Ω
Gas discharge tube	Yes
Limiting frequency (-3 dB) at load resistance	100 MHz (measured in 100-Ω system)
Discharge current, max. (8/20 μs)	5 kA
Lightning test current I _{imp} (10/350 μs)	
Requirements category acc. to IEC 61643-21	D1, C3, C2, C1
Storage temperature	-40 °C...85 °C
Ambient temperature (operational)	-40 °C...60 °C
Protection level	
Protection level wire-PE 1kV/μs, type	80 V
Protection level wire-PE 8/20 μs, type	150 V
Protection level wire-wire 1kV/μs, type	80 V
Protection level wire-wire 8/20 μs, type	80 V
Approvals	
Approvals	CE; EAC

Dimensions	
Height x width x depth	mm 91 / 6 / 63.5

Note	
------	--

Ordering data

Type	Qty.	Order No.
MCZ OVP HF 24V 0,3A	10	8948600000

Note	
------	--

Accessories


Note	End plate AP MCZ 1,5 SW: 1046410000
------	--



MCZ OVP series


3- or 1-stage protection with
tension clamp connection

- Slim overvoltage protection terminal with tension clamp connection
- 6 mm slim fine overvoltage protection
- Fast wiring thanks to TS contact and tension clamp connections




MCZ OVP CL 24 V DC 0.5 A

Protection for current loops



MCZ OVP CL 24 V AC 0.5 A

Protection for current loops



Technical data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Operating current, I_{max}
Volume resistance
Gas discharge tube
Varistor
Suppression diodes
Limiting frequency (-3 dB) at load resistance
Discharge current, max. (8/20 μ s)
Lightning test current I_{imp} (10/350 μ s)
Requirements category acc. to IEC 61643-21
Design
Storage temperature
Ambient temperature (operational)

Protection level

Protection level wire-PE 1kV/ μ s, type
Protection level wire-PE 8/20 μ s, type
Protection level wire-wire 1kV/ μ s, type
Protection level wire-wire 8/20 μ s, type

Approvals

Approvals

24 V
28 V
0.5 A
2.50 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
1 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

40 V
65 V
40 V
65 V

CE; EAC; UL

24 V
28 V
38 V
0.5 A
1.00 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
1 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

45 V
70 V
45 V
70 V

CE; EAC; UL

Dimensions

Height x width x depth

mm

91 / 6 / 63.5

Note

See derating curve in the introductory text chapter in Catalogue 4.4

91 / 6 / 63.5

See derating curve in the introductory text chapter in Catalogue 4.4

Ordering data

Type	Qty.	Order No.
MCZ OVP CL 24VDC 0,5A	10	8448920000

Type	Qty.	Order No.
MCZ OVP CL 24VAC 0,5A	10	8472880000

Note

Accessories

Note


End plate
AP MCZ 1,5 SW: 1046410000

End plate
AP MCZ 1,5 SW: 1046410000




3- or 1-stage protection with
tension clamp connection

- Slim overvoltage protection terminal with tension clamp connection
- 6 mm slim fine overvoltage protection
- Fast wiring thanks to TS contact and tension clamp connections




MCZ OVP CL 24 V UC 1.25 A

Protection for current loops



MCZ OVP SL 24 V DC 0.5 A

Protection for binary signals



Technical data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Operating current, I_{max}
Volume resistance
Gas discharge tube
Varistor
Suppression diodes
Limiting frequency (-3 dB) at load resistance
Discharge current, max. (8/20 μ s)
Lightning test current I_{imp} (10/350 μ s)
Requirements category acc. to IEC 61643-21
Design
Storage temperature
Ambient temperature (operational)

Protection level

Protection level wire-PE 1 kV/ μ s, type
Protection level wire-PE 8/20 μ s, type
Protection level wire-wire 1 kV/ μ s, type
Protection level wire-wire 8/20 μ s, type

Approvals

Approvals

24 V
24 V
27 V
1.25 A
1.00 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
1 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

40 V
65 V
80 V
130 V

CE; EAC; UL

24 V
28 V
0.5 A
2.50 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
1 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

40 V
65 V
80 V
130 V

CE; EAC; UL

Dimensions

Height x width x depth mm

91 / 6 / 63.5

Note

See derating curve in the introductory text chapter in Catalogue 4.4

91 / 6 / 63.5

See derating curve in the introductory text chapter in Catalogue 4.4

Ordering data

Type	Qty.	Order No.
MCZ OVP CL 24VUC 1,25A	10	8448960000

Type	Qty.	Order No.
MCZ OVP SL 24VDC 0,5A	10	8448940000

Note

Accessories

Note

End plate
AP MCZ 1,5 SW: 1046410000


End plate
AP MCZ 1,5 SW: 1046410000



MCZ OVP series


3- or 1-stage protection with
tension clamp connection

- Slim overvoltage protection terminal with tension clamp connection
- 6 mm slim fine overvoltage protection
- Fast wiring thanks to TS contact and tension clamp connections




MCZ OVP SL 24 V UC 1.25 A

Protection for binary signals



MCZ OVP CL 48 V UC 0.5 A

Protection for current loops



Technical data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Operating current, I_{max}
Volume resistance
Gas discharge tube
Varistor
Suppression diodes
Limiting frequency (-3 dB) at load resistance
Discharge current, max. (8/20 μs)
Lightning test current I_{imp} (10/350 μs)
Requirements category acc. to IEC 61643-21
Design
Storage temperature
Ambient temperature (operational)

Protection level

Protection level wire-PE 1kV/ μs , type
Protection level wire-PE 8/20 μs , type
Protection level wire-wire 1kV/ μs , type
Protection level wire-wire 8/20 μs , type

Approvals

Approvals

24 V
24 V
28 V
1.25 A
1.00 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
1 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

40 V
65 V
80 V
130 V

CE; EAC; UL

48 V
48 V
53 V
0.5 A
2.50 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
2.5 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

80 V
150 V
82 V
150 V

CE; EAC; UL

Dimensions

Height x width x depth

mm

91 / 6 / 63.5

Note

See derating curve in the introductory text chapter in Catalogue 4.4

91 / 6 / 63.5

See derating curve in the introductory text chapter in Catalogue 4.4

Ordering data

Type	Qty.	Order No.
MCZ OVP SL 24VUC 1,25A	10	8448970000

Type	Qty.	Order No.
MCZ OVP CL 48VUC 0,5A	10	8449000000

Note

Accessories

Note


End plate
AP MCZ 1,5 SW: 1046410000

End plate
AP MCZ 1,5 SW: 1046410000




3- or 1-stage protection with
tension clamp connection

- Slim overvoltage protection terminal with tension clamp connection
- 6 mm slim fine overvoltage protection
- Fast wiring thanks to TS contact and tension clamp connections




MCZ OVP SL 48 V UC 0.5 A

Protection for binary signals



MCZ OVP CL 48 V UC 1.25 A

Protection for current loops



Technical data

Rated voltage (AC)	48 V
Rated voltage (DC)	48 V
Max. continuous voltage, U _c (AC)	53 V
Operating current, I _{max}	0.5 A
Volume resistance	2.50 Ω
Gas discharge tube	Yes
Varistor	Yes
Suppression diodes	Yes
Limiting frequency (-3 dB) at load resistance	500 kHz 240 Ω
Discharge current, max. (8/20 μs)	5 kA
Lightning test current I _{imp} (10/350 μs)	1 kA
Requirements category acc. to IEC 61643-21	D1
Design	Terminal
Storage temperature	-40 °C...85 °C
Ambient temperature (operational)	-40 °C...60 °C
Protection level	82 V
Protection level wire-PE 1 kV/μs, type	150 V
Protection level wire-PE 8/20 μs, type	160 V
Protection level wire-wire 1 kV/μs, type	300 V
Protection level wire-wire 8/20 μs, type	
Approvals	CE; EAC; UL

Rated voltage (AC)	48 V
Rated voltage (DC)	48 V
Max. continuous voltage, U _c (AC)	53 V
Operating current, I _{max}	1.25 A
Volume resistance	1.00 Ω
Gas discharge tube	Yes
Varistor	Yes
Suppression diodes	Yes
Limiting frequency (-3 dB) at load resistance	500 kHz 240 Ω
Discharge current, max. (8/20 μs)	5 kA
Lightning test current I _{imp} (10/350 μs)	1 kA
Requirements category acc. to IEC 61643-21	D1
Design	Terminal
Storage temperature	-40 °C...85 °C
Ambient temperature (operational)	-40 °C...60 °C
Protection level	82 V
Protection level wire-PE 1 kV/μs, type	150 V
Protection level wire-PE 8/20 μs, type	82 V
Protection level wire-wire 1 kV/μs, type	150 V
Protection level wire-wire 8/20 μs, type	
Approvals	CE; EAC; UL

Rated voltage (AC)	48 V
Rated voltage (DC)	48 V
Max. continuous voltage, U _c (AC)	53 V
Operating current, I _{max}	1.25 A
Volume resistance	1.00 Ω
Gas discharge tube	Yes
Varistor	Yes
Suppression diodes	Yes
Limiting frequency (-3 dB) at load resistance	500 kHz 240 Ω
Discharge current, max. (8/20 μs)	5 kA
Lightning test current I _{imp} (10/350 μs)	1 kA
Requirements category acc. to IEC 61643-21	D1
Design	Terminal
Storage temperature	-40 °C...85 °C
Ambient temperature (operational)	-40 °C...60 °C
Protection level	82 V
Protection level wire-PE 1 kV/μs, type	150 V
Protection level wire-PE 8/20 μs, type	82 V
Protection level wire-wire 1 kV/μs, type	150 V
Protection level wire-wire 8/20 μs, type	
Approvals	CE; EAC; UL

Dimensions	
Height x width x depth	mm

91 / 6 / 63.5

91 / 6 / 63.5

Note

See derating curve in the introductory text chapter in Catalogue 4.4
--

See derating curve in the introductory text chapter in Catalogue 4.4
--

Ordering data

--

Type	Qty.	Order No.
MCZ OVP SL 48VUC 0,5A	10	8449030000

Type	Qty.	Order No.
MCZ OVP CL 48VUC 1,25A	10	8449040000

Note

--

--

Accessories

Note

End plate AP MCZ 1,5 SW: 1046410000
--


End plate AP MCZ 1,5 SW: 1046410000
--



MCZ OVP series


3- or 1-stage protection with
tension clamp connection

- Slim overvoltage protection terminal with tension clamp connection
- 6 mm slim fine overvoltage protection
- Fast wiring thanks to TS contact and tension clamp connections




MCZ OVP SL 48 V UC 1.25 A

Protection for binary signals



MCZ OVP SL FG 24 V AC 0.5 A

Floating earth



Technical data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Operating current, I_{max}
Volume resistance
Gas discharge tube
Varistor
Suppression diodes
Limiting frequency (-3 dB) at load resistance
Discharge current, max. (8/20 μs)
Lightning test current I_{imp} (10/350 μs)
Requirements category acc. to IEC 61643-21
Design
Storage temperature
Ambient temperature (operational)

Protection level

Protection level wire-PE 1 kV/ μs , type
Protection level wire-PE 8/20 μs , type
Protection level wire-wire 1 kV/ μs , type
Protection level wire-wire 8/20 μs , type

Approvals

Approvals

48 V
48 V
53 V
1.25 A
1.00 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
2.5 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

80 V
150 V
160 V
300 V

CE; EAC; UL

24 V
24 V
28 V
0.5 A
1.00 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
1 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

40 V
65 V
40 V
65 V

CE; EAC

Dimensions

Height x width x depth

mm

91 / 6 / 63.5

Note

See derating curve in the introductory text chapter in Catalogue 4.4

91 / 6 / 63.5

See derating curve in the introductory text chapter in Catalogue 4.4

Ordering data

Type	Qty.	Order No.
MCZ OVP SL 48VUC 1,25A	10	8449050000

Type	Qty.	Order No.
MCZ OVP SL FG 24VUC 0,5A	10	8823280000

Note

Accessories


Note

End plate
AP MCZ 1,5 SW: 1046410000

End plate
AP MCZ 1,5 SW: 1046410000


3- or 1-stage protection with
tension clamp connection

- Slim overvoltage protection terminal with tension clamp connection
- 6 mm slim fine overvoltage protection
- Fast wiring thanks to TS contact and tension clamp connections



MCZ OVP CL FG 24 V AC 0.5 A

Floating earth



Technical data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Operating current, I_{max}
Volume resistance
Gas discharge tube
Varistor
Suppression diodes
Limiting frequency (-3 dB) at load resistance
Discharge current, max. (8/20 μ s)
Lightning test current I_{imp} (10/350 μ s)
Requirements category acc. to IEC 61643-21
Design
Storage temperature
Ambient temperature (operational)

Protection level

Protection level wire-PE 1kV/ μ s, type
Protection level wire-PE 8/20 μ s, type
Protection level wire-wire 1kV/ μ s, type
Protection level wire-wire 8/20 μ s, type

Approvals

Approvals

24 V
24 V
28 V
0.5 A
2.50 Ω
Yes
Yes
Yes
500 kHz 240 Ω
5 kA
1 kA
D1
Terminal
-40 °C...85 °C
-40 °C...60 °C

40 V
65 V
40 V
65 V

CE; EAC

Dimensions

Height x width x depth mm

91 / 6 / 63.5

Note

See derating curve in the introductory text chapter in Catalogue 4.4

Ordering data

Type	Qty.	Order No.
MCZ OVP CL FG 24VUC 0,5A	10	8704240000

Note

Accessories

Note

End plate
AP MCZ 1,5 SW: 1046410000




Differences between earthing and shielding

The terms “earthing” and “shielding” are classified according to their relation to human safety or facility safety. The earth is installed primarily to protect human life and for this reason is referred to as the protective earth conductor. On the other hand, shielding is used to ensure that the electrical system functions properly. It also ensures electromagnetic compatibility.

These main differences between the two terms influence the electrical design and installation. Shielding is not designed to transfer power, although leakage currents may flow on them. A protective earth conductor, however, must be able to briefly discharge a high fault current (IEC 60947-7-2). The short-term current resistance of the PE connection must be 120 A/mm² for the connected cross-section.

The illustration below shows how these two topics relate to each other in application.

As shown in the picture below, the cable’s shielding is connected to the earth potential so that the shield’s current can be discharged. Depending on the sensitivity of the facility, isolated areas of potential can be created. However it is still typical to mix the areas, so that the shielding is on a common equipotential earth. This illustration shows how the number of shields and PE conductors that need to be connected can increase quite rapidly (in this case only one component is used). The shielding and earthing systems must be planned carefully to provide adequate safeguards for personnel and equipment. The following sections describe the complexity and uniqueness in more detail.



Connection diagram for a frequency converter



Earthing for shielded cables

Electrical and electronic systems should be designed and installed so that they are essentially protected against electrical interference, so that they also function reliably in the event of transient interference voltages.

Electrical interference is introduced into circuits in many different ways. The most frequent cause is inductive interference effects. However, conductive or capacitive coupling plus electrical fields and other phenomena can also cause interference voltages. In these cases high-frequency voltage oscillations – the so-called transients – are very likely the cause of the interference.

Shielded lines enhance interference immunity

The sources of interference voltages can never be eliminated completely. Therefore, we have to take measures to deal with their effects. Generally, it is true to say that the more effectively we can keep interference voltages away or discharge them from circuit elements, the smaller are their disturbing effects. This can be done in many ways – with differing degrees of effectiveness. One really effective measure for protecting against inductive influences, i.e. guaranteeing the electromagnetic compatibility, is to shield the electric functional components at earth potential. One way of doing this is to install components in metal, earthed housings and to shield the connecting lines.

Generally, it is true to say that counteracting the interference effects of lines is feasible by laying the lines as far apart as possible, keeping the common return as short as practical, or using twisted lines. A far better method of protection, however, is to provide a continuous shield for all lines. This is the most effective measure that can be taken against the coupling together of interferences.

The best form of shielding consists of a braided hose of individual wires made from a non-magnetic material (copper, aluminium). The braiding should be sufficiently robust and as solid as possible. Care must be taken with lines protected by a foil shield because of the foil's low mechanical strength and low current-carrying capacity.

Correct use of shielded lines

Adding shielding to lines achieves the desired effect only when they are properly designed and installed. Incorrect earthing or the use of components that do not function satisfactorily reduce the effect or even nullify it altogether. It is not sufficient to connect the shielding to earth potential at just any point because it could be the case that this earth connection is inadequate for high frequencies. In addition, we must also watch out for earth loops, the shielding must be earthed over a large area, and the quality of the shield bonding lines and earthing accessories is also important.



Shielding



In practice, the shield is often twisted and connected to a terminal point. There is very high attenuation (voltage drop) on these connections, especially for high-frequency interference. Therefore this type of shielding should not be used, even for short cable lengths. The cable shield is practically negated and can, at best, be helpful for low-frequency interference. We recommend a large, extensive contact with the braided shield of the cable.

There are four main types of coupling:


- Galvanic coupling
- Capacitive coupling
- Inductive coupling
- Radiation coupling

Such interferences usually occur mixed together, but they can be categorised as follows:


- Electromagnetic fields
- Ripple voltage (50 Hz)
- Lightning
- Interference pulses (current, voltage)
- Transient surge voltages
- Radio interference
- ESD (electrostatic)
- Burst
- Mains feedback

The conductor "flow" is another detail for concern with the shield contact. The temperature changes caused by the current flow lead to changes in the wire's diameter. A rigid contact can therefore only be partially effective. A self-adjusting contact is what is really required. Weidmüller's clamping yoke products (KLBÜ) provide the perfect solution for this challenge.

The following pictures show examples of use:



Shield connection via functional earth




Shield connection on common earth

Effective shielding


It is important to remember that the shielding should not be connected to the earth of the module connected, but rather to the protective earth (PE). In the case of modules mounted in an earthed, metal housing, the shielding must be connected to this housing. If an earthed housing is not available, the shielding must be connected to a separate earth.

When laying earth connections to shields it must also always be ensured that no earth loops are formed. The smaller the earth loop, the lower is the risk of inducing interference voltages. Therefore, a true star arrangement is the best answer.




The sketches below show general, feasible connections between shield and protective earth.


Connecting the shield at one end protects against capacitive-coupled interference voltages.



Connecting the shield at both ends is suitable for protecting against inductive-coupled interference fields.




A high-resistance connection at one end of the shield is recommended when trying to avoid the disadvantages of forming an earth loop in the case of shields connected at both ends.



On longer shielded lines, e.g. when a sensor has to be routed to the control room, the potential difference between the two ends should not be ignored. If a current-carrying shield bonding line is used, it is possible to compensate for the potential difference between the measuring point and the control room by means of this shield. However, such shield lines are relatively expensive and also complicated to fabricate and install. Another possibility is to lay an additional equipotential bonding line between the measuring point and the control room. The shield can then be connected at both ends.

Yet another possibility is a high-resistance earth. The shield is then connected to earth potential in the control room, and at the measuring point connected to earth via a gas discharge tube in a high-resistance arrangement. This solves the problems of potential transfer and a 50 Hz hum. Two gas discharge tubes must be installed for non-floating measuring points. One connects the shield to earth and the other to the non-floating measuring point. This prevents conductive coupling between the measuring circuit and the earthed measuring point.




Summary

The earthing is an important factor affecting the reliable operation of electrical installations in the event of interference effects. RF aspects must be taken into account. Only the correct use of materials and well-thought-out circuit design can bring success.

Installation advice for instrumentation and control engineering

The supply and earth lines to protective modules should be kept short in order to achieve optimum protection for equipment.

The fuses for the protective modules should be chosen depending on the rated current as well as on the type of line and its route.



Installation position


The protective modules are frequently installed at both ends of the line.

It is important to ensure that protected and unprotected lines are routed separately. In addition, there must be some distance between power lines and data lines. A common cable duct should be connected with metal partitions.

The protective modules should be mounted in a panel near the entry point of the lines. Unprotected lines should not be fed into parts of the system. Therefore, the lower level in the panel should be used for the protective modules.

Mounting rail contact as earth in connection for MCZ OVP

Contact to the rail is automatically established using the snap-on attachment. The TS35 rail must be earthed in order to ensure safe power discharging via the surge protection elements of up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s). The DIN rail should be screwed onto the earthed mounting plate to ensure EMC. It is also possible to contact the PE every 60 cm / 24 inch using the tension-clamp terminal on the MCZ OVP.



The shielded signal lines should be connected to PE via terminal clamps (Weidmüller KLBÜ). Unshielded lines should be twisted. Neutral earthing is preferred. All the protective modules belonging to one part of the system should have neutral earthing. A through-connection of the earth line should be avoided.

Protected and unprotected lines must be laid separately. A common cable duct should be connected with metal partitions.

Likewise, signal and power lines should be laid separately. Electrical isolation, e.g. with relay couplers or analogue converters, should be employed for installations involving several buildings. This avoids interference currents via minus, PE or N.

The supply and earth lines to protective modules should be kept short in order to achieve optimum protection for equipment. Transmission paths should also be kept as short as possible because the longer the line, the greater is the chance that interference can affect the line. The inclusion of surge protection also increases the attenuation of the line and therefore changes the signal-to-noise ratio.


Surge protection for binary signals

The VSPC 4 SL plug-in surge protector can be used to protect the 24-V supply and also the 24-V switching signals.

The unprotected side points in the direction where the pulse or interference is expected. The connecting cable's shield is connected to terminal 3 e. g. the Weidmüller clamping bracket (KLBÜ) can be used.

The earthed DIN rail can then pick up the pulse and discharge it to the earth.

For long cables, and especially for current loops, additional protection is set-up at the sensors. The VSPC BASE FG floating-earth base can be used there. A built-in gas discharge tube makes this a "high impedance" earth, which prevents an interference current on the shield.




Surge protection for sensors with current loop output 0 (4)...20 mA

VSPC 2CL plug-in surge protector for protecting two current loops with 0 (4)...20 mA.

The unprotected side points in the direction where the pulse or interference is expected. The connecting cable's shield is connected to terminal 3 e. g. the Weidmüller clamping bracket (KLBÜ) can be used.

The earthed DIN rail can then pick up the pulse and discharge it to the earth.

For long cables, and especially for current loops, additional protection is set-up at the sensors. The VSPC BASE FG floating-earth base can be used there. A built-in gas discharge tube makes this a "high impedance" earth, which prevents an interference current on the shield.




Surge protection for sensors with supply voltage and a current loop 0 (4)...20 mA

The VSPC 1CL PW plug-in surge protector uses a Type III arrester to protect the 24-V supply voltage and also a D1/C2/C1-arrester for the current loop 0 (4)...20 mA. This 17.5-mm configuration protects both power and measurement/control (e.g. for a pumping facility).

The unprotected side points in the direction where the pulse or interference is expected. The connecting cable's shield is connected to terminal 3 e.g. the Weidmüller clamping bracket (KLBÜ) can be used.

The earthed DIN rail can then pick up the pulse and discharge it to the earth.

For long cables, and especially for current loops, additional protection is set-up at the sensors. The VSPC BASE FG floating-earth base can be used there. A built-in gas discharge tube makes this a "high impedance" earth, which prevents an interference current on the shield.




Surge protection for sensors with 4-wire connection or temperature measurement

The plug-in VSPC 3/4 surge protector is used to protect 3- or 4-wire measurement signals (e.g. from temperature sensors or load cells).

The unprotected side points in the direction where the pulse or interference is expected. The connecting cable's shield is connected to terminal 3 e. g. the Weidmüller clamping bracket (KLBÜ) can be used.

The earthed DIN rail can then pick up the pulse and discharge it to the earth.

For long cables, and especially for current loops, additional protection is set-up at the sensors. The VSPC BASE FG floating-earth base can be used there. A built-in gas discharge tube makes this a "high impedance" earth, which prevents an interference current on the shield.




Surge protection for telephone signals U_{ko}

The VSPC U_{ko} plug-in surge protector is used to protect up to two phone lines with up to 4 wires.

The unprotected side points in the direction where the pulse or interference is expected. The connecting cable's shield is connected to terminal 3 e. g. the Weidmüller clamping bracket (KLBÜ) can be used.

The earthed DIN rail can then pick up the pulse and discharge it to the earth.

For long cables, and especially for current loops, additional protection is set-up at the sensors. The VSPC BASE FG floating-earth base can be used there. A built-in gas discharge tube makes this a "high impedance" earth, which prevents an interference current on the shield.




Surge protection for data lines, RS485 or RS422

The VSPC RS485 plug-in surge protector is used to protect an RS485 data line or two RS422 data lines.

The unprotected side points in the direction where the pulse or interference is expected. The connecting cable's shield is connected to terminal 3 e. g. the Weidmüller clamping bracket (KLBÜ) can be used.

The earthed DIN rail can then pick up the pulse and discharge it to the earth.





A

VARITECTOR SPC EX and ACT20X




Pluggable surge protection and a universal signal converter for C&I signals in hazardous area applications

Intrinsically safe circuits to limit energy are used in hazardous areas. In these circuits, the intrinsically safe signal converters with their galvanic isolation and Ex approved surge arresters provide excellent protection for sensitive control electronics.

Surge voltages on the field side of the measurement and control lines can damage the facility. The VARITECTOR SPC EX can discharge surge voltages in hazardous area applications (zone 0, 1 and 2). The pluggable arresters conform to the requirements of the current standards with regards to Ex intrinsic safety. They also comply with the IEC 61643-21 surge protection product standard and are certified for protection classes D1, C2 and C3.

The ACT20X-HUI-SAO-LP offers an intrinsically safe input for standard DC signals, temperature signals and resistance signals. It also isolates the Ex zone from the safe area. The 12.5 mm wide module is powered via the 4 ... 20 mA output. The global ATEX, IECEx and cULus Ex approvals allow it to be used throughout the world.




Space saving

The VSPC EX uses less space in the electrical cabinet, with four binary or two analogue signals in only 17.8 mm width.



Unlimited protection

The VSPC EX products are special, intrinsically safe surge arresters. Low Li and Ci values mean they are not relevant for the entire application's proof of intrinsic safety.





Hazardous area applications

The ACT20X signal converter is approved for installation in zone 2 and converts signals from zones 0, 1 or 2 for the controller. The product is approved by ATEX, IECEx, and cULus Ex Div 1.



Universal intrinsically safe input


The ACT20X-HUI-SAO-LP isolates and converts intrinsically safe signals such as ± 25 mA, ± 28 V, potentiometer up to 500 k Ω , resistance up to 12 k Ω , RTD signals and thermocouple signals.

For hazardous areas up to zone 0

Due to the Ex II 1 G Ex ia IIC T4...T6 Ga and Ex II 1D Ex ia III T135 °C...T85 °C approvals, the VARITECTOR SPC EX surge protection component can be installed directly in zones 0, 1 or 2 in order to protect signals.

Configuration via FDT/DTM

The new ACT20X module can be quickly and comfortably configured with vendor neutral FDT/DTM software such as the WI-Manager software. The software also offers monitoring and diagnostic options.



VARITECTOR SPC EX



Pluggable surge protection for measurement and control systems

VARITECTOR SPC EX

Weidmüller's VARITECTOR SPC EX pluggable surge protector is remarkable for its combination of extremely high protective functionality and compact dimensions. It protects intrinsically safe measurement and control circuits. The size is made possible by the selection of INSTA dimensions, with a width of 17.8 mm (1 TE). You save time on connections because of the screw connection and the indirect earthing contact via the DIN rail. The VARITECTOR SPC series is optimally designed for compact installations in process automation, industrial automation and building automation. The two-stage surge protection terminals are equipped with gas discharge tubes, suppressor diodes (TVS) and decoupling components. IEC 62305 requires that a periodic inspection of surge protection products be conducted. The functionality of all VARITECTOR SPC modules can be tested using testing equipment (such as the V-TEST) that is available separately.

You can get our VARITECTOR SPC surge protection series in the nominal voltages of 5 V, 12 V and 24 V. The product's voltage level is colour-coded on the pluggable arrester.

It can be snapped on an earthed DIN for indirect earthing. The TS 35 must be earthed in order to ensure safe power discharging via the terminals of up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s). The DIN rail must be screwed onto the earthed mounting plate to ensure EMC.

In order to optimise the protective function, the PE contact should be made every 60 cm / 24 inch using the terminal on the VARITECTOR SPC module.

A testing device, available as a Weidmüller accessory, allows you to test the protective element in compliance with the IEC 62305-3 directive. Accessories also include the EMC SET which provides a simple method for creating the cable shield.



VARITECTOR SPC EX

Overview of model types

Surge protection consists of a separate plug-in VARITECTOR SPC EX and a separate base unit VARITECTOR SPC BASE.

ATEX



The VSPC EX series comes in a light blue housing and is used to protect electronics connected to intrinsically safe circuits. The unearthed (floating ground - FG) VARITECTOR SPCs have negligible internal inductance and capacitance.

Labelling of the VSPC EX equipment

ATEX:

For gas
T II 1 G Ex ia IIC T4 ... T6 Ga or
For dust
T II 1 D Ex ia IIIC T135°C ... T85°C Da
KEMA 10 ATEX 0148 X

IEC EX:

For gas
Ex ia IIC T4 ... T6 Ga
For dust
Ex ia IIIC T135 °C ... T85 °C Da

The basic health and safety functions are fulfilled by compliance with:
EN 60079-0, EN 60079-11,
EN 60079-26 and EN 61241-11,
IEC 61643-21






Products for intrinsically safe circuits

VSPC 1CL 12 V ATEX
and VSPC 1CL 24 V ATEX

This VSPC surge protector is used to protect an intrinsically safe current loop.



VSPC EX 1 CL 24 V/Power ATEX

This VARITECTOR SPC surge protector protects an analogue signal and has an intrinsically safe power supply which is protected by a Type III end-device protection mechanism.


All in one product it is suitable for an intrinsically safe sensor, which also requires an intrinsically safe power supply.

VSPC EX 2SL 12 V DC ATEX

VSPC EX 2SL 12 V AC ATEX

VSPC EX 2SL 24 V DC ATEX

These VSPC EX surge protection modules are used for protecting two intrinsically safe binary signals.



VSPC EX 3/4 wire 5 V ATEX

This VSPC EX surge protector is suitable for 3- or 4-wire measurement systems with signals going in and out of the intrinsically safe zone.

VSPC EX 1CL 5 V ATEX

This VSPC EX surge protector is suitable for temperature signals which goes in and out of the intrinsically safe zone.

VSPC EX 1CL 12 V ATEX (Namur)

This VSPC EX surge protector is used to protect a Namur sensor signal in an intrinsically safe zone.

Colour coding

The pluggable components transfer their coding to the BASE when they are plugged in for the first time.


The voltage level is also marked with coloured Dekafix on the VSPC EX plug section. This gives you a better overview within the electrical cabinet.

Voltage level	Colour
≤ 12 V	green
24 V Binary	blue
24 V Analogue	yellow
Special function	white

Testing option

Because the modules are pluggable, it is possible to test the VSPC EX using the V-TEST testing device. The user inserts the VSPC EX into the testing device for testing. The result is then shown on the display.

Periodic inspections



IEC 62305-3 requires testing and maintenance for lightning protection systems.

This includes the testing of the arresters used in the system.

Lightning protection level	Visual inspection	Extensive check	Extensive check in critical situations ^{a), b)}
	Year	Year	Year
I und II	1	2	1
III und IV	2	4	1

Caution! These periodic inspections may be extended with stricter requirements pertaining to special applications or regions.

Markers

The VSPC BASE lower section can be labelled with Dekafix 5 markers. The VSPC pluggable modules are colour coded with Dekafix 5 according to their nominal voltage.

Installation

The VSPC EX series is used to protect signal circuits. In order to achieve a complete protective strategy for the facility, the power feed must be protected with Type II surge protection (for example, by using the VPU II series). For existing lightning protection facilities, Type I protection must be used (for example, by using the VPU I series).

When there is no lightning protection system, the Type II protection is sufficient (such as the VPU II).



VARITECTOR SPC EX

Discharge capacity

Testing is conducted using voltage and current pulses according to the IEC 61643-21 standard concerning surge protection in networks which process signals.

Cate- gory	Testing pulse	Surge voltage	Surge current	Pulse	Type
C1	Quick rising edge	$0.5 < 2 \text{ kV}$ with $1.2/50 \mu\text{s}$	$0.25 < 1 \text{ kA}$ with $8/20 \mu\text{s}$	300	Surge voltage arrester
C2	Quick rising edge	$2 < 10 \text{ kV}$ with $1.2/50 \mu\text{s}$	$1 < 5 \text{ kA}$ with $8/20 \mu\text{s}$	10	Surge voltage arrester
C3	Quick rising edge	$\geq 1 \text{ kV}$ with $1 \text{ kV}/\mu\text{s}$	$10 < 100 \text{ A}$ with $10/10.000 \mu\text{s}$	300	Surge voltage arrester
D1	High power	$\geq 1 \text{ kV}$	$0.5 < 2.5 \text{ kA}$ with $10/350 \mu\text{s}$	2	Arrester for lightning current and surge voltages

Category C reflects the interference pulses with quick-rising edges and minimised power. Category D uses quick-rising edges and high power to detail the interference pulses. This energy simulates the high-power load that stems from coupled partial lightning currents.

General technical data

Storage temperature: $-40^\circ\text{C} \dots +80^\circ\text{C}$
Operating temperature: $-40^\circ\text{C} \dots 70^\circ\text{C}$
Humidity: 5 %...96 % RH without
condensation
Material: VO, IP 20

Wire connection: screw
SD blade: $0.6 \times 3.5 \text{ DIN } 5264$
Nominal torque: 0.5 Nm
Max. torque: 0.8 Nm
Stripping length: 7 mm
Solid core: $0.5 \dots 4 \text{ mm}^2$
Finely stranded: $0.5 \dots 2.5 \text{ mm}^2$
Ferrule with plastic collar:
 $0.5 \dots 2.5 \text{ mm}^2$

Dimensions

Height: 90 mm
Depth: 69 mm
Width: 17,8 mm



A



VARITECTOR SPC EX

VSPC 1CL EX - protection for one analogue signal in
intrinsically safe circuits

- For use in zones 2, 1, and 0
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Version with floating-earth PE connection for avoiding voltage potential differences
- Can be used in accordance with installation standard IEC 62305 as well as in ATEX applications
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data

Dielectric strength at FG against PE	≥ 500 V
Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	1 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Temperature class T6/85 °C (-40 °C ... +60 °C) li	250 mA
Temperature class T5/100 °C (-40 °C ... +75 °C) li	250 mA
Temperature class T4/135 °C (-40 °C ... +85 °C) li	350 mA
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; IECXDEK; KEMAATEX
Standards	IEC 61643-21, IEC 62305, DIN EN 60079-0:2009, DIN EN 60079-11:2007, DIN EN 60079-26:2007, DIN EN 61241-11:2006, HART-compatible
ATEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
ATEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga
IECEx - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
IECEx - gas labelling	II 1 G Ex ia IIC T4... T6 Ga

Dimensions	Dimensions
Height x width x depth	mm 90 / 17.8 / 69
Note	The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base


Description	Type	Qty.	Order No.
EX base element, indirect earthing / floating earth FG	VSPC BASE 1CL FG EX	1	8951810000

Note	Technical data can be found at the beginning of VARITECTOR SPC EX.
-------------	--

VSPC 1CL EX - plug-in components / arrester



Pluggable component / Arrester



Base element / Base

Ordering data

Rated voltage (AC)
 Rated voltage (DC)
 Rated current I_n
 Optical function display
 Input attenuation
 Pulse-reset capacity
 Residual voltage, U_p typical

EX protection data

Input voltage, max. U_i
 Internal capacity, max. C_i
 Internal inductance, max. L_i
 Input power, max. P_i

Protection level

Protection level wire-wire 1kV/ μ s, type
 Protection level wire-wire 8/20 μ s, type
 Protection level wire-PE 1kV/ μ s, type
 Protection level wire-PE 8/20 μ s, type

VSPC 1CL 5 V DC EX

5 V
 350 mA
 No
 730 KHz
 ≤ 20 ms
 < 800 V

6 V
 < 4 nF
 0μ H
 3 W

12 V
 12 V
 450 V
 < 800 V

VSPC 1CL 12 V DC EX

12 V
 350 mA
 No
 1.7 MHz
 ≤ 20 ms
 < 800 V

14 V
 < 4 nF
 0μ H
 3 W

25 V
 25 V
 450 V
 < 800 V

VSPC 1CL 24 V DC EX

24 V
 350 mA
 No
 2.4 MHz
 ≤ 30 ms
 < 800 V

26 V
 < 4 nF
 0μ H
 3 W

45 V
 45 V
 450 V
 < 800 V

Ordering data

Type
 Order No.
 Qty.

VSPC 1CL 5VDC EX

8953660000

1

VSPC 1CL 12VDC EX

8953590000

1

VSPC 1CL 24VDC EX

8953600000

1


Note



VARITECTOR SPC EX

VSPC 2CL EX – protection for two analogue
signals in intrinsically safe circuits

- For use in zones 2, 1, and 0
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Space-saving design for 3 analogue signals
- Version with floating-earth PE connection for avoiding voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Complete module, indirect earthing

Technical data

Dielectric strength at FG against PE	≥ 500 V
Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	1 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Temperature class T6/85 °C (-40 °C ... +60 °C) li	250 mA
Temperature class T5/100 °C (-40 °C ... +75 °C) li	250 mA
Temperature class T4/135 °C (-40 °C ... +85 °C) li	350 mA
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; IECXDEK; KEMAATEX
Standards	IEC 61643-21, IEC 62305, DIN EN 60079-0:2009, DIN EN 60079-11:2007, DIN EN 60079-26:2007, DIN EN 61241-11:2006, HART-compatible
ATEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
ATEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga
IECEx - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
IECEx - gas labelling	II 1 G Ex ia IIC T4... T6 Ga

Dimensions	Dimensions
Height x width x depth	mm 90 / 17.8 / 69
Note	
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.	

Base elements / base to arresters



Ordering data for base


Description	Type	Qty.	Order No.
EX base element, indirect earthing / floating earth FG	VSPC BASE 2CL FG EX	1	8951820000

Note	Technical data can be found at the beginning of VARITECTOR SPC EX.
-------------	--

VSPC 2CL EX - plug-in components / arrester



Pluggable component / Arrester



Base element / Base

Ordering data

Rated voltage (AC)
Rated voltage (DC)
Rated current I_n
Optical function display
Input attenuation
Pulse-reset capacity
Residual voltage, U_r typical
EX protection data
Input voltage, max. U_i
Internal capacity, max. C_i
Internal inductance, max. L_i
Input power, max. P_i
Protection level
Protection level wire-wire 1kV/ μ s, type
Protection level wire-wire 8/20 μ s, type
Protection level wire-PE 1kV/ μ s, type
Protection level wire-PE 8/20 μ s, type

VSPC 2CL 24 V DC EX	
	24 V
	250 mA
	No
	2.3 MHz
	≤ 30 ms
	< 800 V
EX protection data	
Input voltage, max. U_i	26 V
Internal capacity, max. C_i	< 4 nF
Internal inductance, max. L_i	0 μ H
Input power, max. P_i	3 W
Protection level	
Protection level wire-wire 1kV/ μ s, type	45 V
Protection level wire-wire 8/20 μ s, type	45 V
Protection level wire-PE 1kV/ μ s, type	450 V
Protection level wire-PE 8/20 μ s, type	< 800 V

Ordering data

Type
Order No.
Qty.
Note

VSPC 2CL 24VDC EX
8953720000
1



VARITECTOR SPC EX

VSPC 1CL PW EX - combinations in current loop signal and device protection in intrinsically safe circuits

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Version with floating-earth PE connection for avoiding voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- For use in zones 2, 1, and 0
- Tested in accordance with IEC/EN 61643-11 Class III
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE



Technical data

Rated voltage (DC)	24 V
Max. continuous voltage, U_c (DC)	38 V
Dielectric strength at FG against PE	≥ 500 V
Volume resistance	2.20Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1

Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Input attenuation	3 MHz
Pulse-reset capacity	≤ 10 ms
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Residual voltage, U_r typical	
Protection level wire-PE 1kV/ μ s, type	450 V
Protection level wire-PE 8/20 μ s, type	
Protection level wire-wire 1kV/ μ s, type	60 V
Protection level wire-wire 8/20 μ s, type	60 V
Standards	IEC 61643-21, IEC 62305, DIN EN 60079-0:2009, DIN EN 60079-11:2007, DIN EN 60079-26:2007, DIN EN 61241-11:2006, HART-compatible

Power protection class III	
Rated voltage (DC)	24 V
Max. continuous voltage, U_c (DC)	38 V
Combined pulse U_{oc}	6 kV
Residual voltage, U_r typical	
Rated current	
Input voltage, max. U_i	20 V

Dimensions	Dimensions
Height x width x depth	mm 90 / 17.8 / 69

Note	The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.
-------------	---

Base elements / base to arresters



Ordering data for base

Description	Type	Qty.	Order No.
EX base element, indirect earthing / floating earth FG	VSPC BASE 1CL PW FG EX	1	1070470000

Note	Technical data can be found at the beginning of VARITECTOR SPC EX.
-------------	--

VSPC 1CL PW EX - plug-in components / arrester



Pluggable component / Arrester



Base element / Base

Ordering data	
VSPC 1CL PW 24 V EX	
Rated voltage (AC)	24 V
Rated voltage (DC)	24 V
Rated current I _N	350 mA
Optical function display	For Class III protection, green = OK; red = arrester is defective - replace
Input attenuation	3 MHz
Pulse-reset capacity	≤ 10 ms
Residual voltage, U _p typical	≤ 0.9 kV
EX protection data	
Input voltage, max. U _i	20 V
Internal capacity, max. C _i	< 4 nF
Internal inductance, max. L _i	0 µH
Input power, max. P _i	3 W
Protection level	
Protection level wire-wire 1kV/µs, type	60 V
Protection level wire-wire 8/20 µs, type	60 V
Protection level wire-PE 1kV/µs, type	450 V
Protection level wire-PE 8/20 µs, type	≤ 0.9 kV

Ordering data	
Type	VSPC 1CL PW 24V EX
Order No.	8953610000
Qty.	1
Note	



VARITECTOR SPC EX

VSPC 2SL EX – protection for two binary
signals in intrinsically safe circuits

- For use in zones 2, 1, and 0
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Version with floating-earth PE connection for avoiding voltage potential differences
- Can be used in accordance with installation standard IEC 62305 as well as in ATEX applications
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data

Dielectric strength at FG against PE	≥ 500 V
Volume resistance	4.7 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Temperature class T6/85 °C (-40 °C ... +60°C) li	250 mA
Temperature class T5/100°C (-40 °C ... +75°C) li	250 mA
Temperature class T4/135°C (-40°C ... +85°C) li	350 mA
Failure probability	
Ages	43
MTTF	2665
SIL in compliance with IEC 61508	2
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; IECXDEK; KEMAATEX
Standards	IEC 61643-21, IEC 62305, DIN EN 60079-0:2009, DIN EN 60079-11:2007, DIN EN 60079-26:2007, DIN EN 61241-11:2006
ATEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
ATEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga
IECEx - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
IECEx - gas labelling	II 1 G Ex ia IIC T4... T6 Ga

Dimensions	Dimensions
Height x width x depth	mm 90 / 17.8 / 69
Note	Order the associated VSPC base element with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base


Description	Type	Qty.	Order No.
EX base element, indirect earthing / floating earth FG	VSPC BASE 2SL FG EX	1	8951830000

Note	Technical data can be found at the beginning of VARITECTOR SPC EX.
------	--

VSPC 2SL EX - plug-in components / arrester



Pluggable component / Arrester



Base element / Base

Ordering data

	VSPC 2SL 12 V DC EX	VSPC 2SL 12 V AC EX	VSPC 2SL 24 V DC EX	VSPC 2SL 48 V AC EX
Rated voltage (AC)		12 V		48 V
Rated voltage (DC)	12 V	16 V	24 V	68 V
Rated current I_n	250 mA	250 mA	250 mA	250 mA
Optical function display	No	No	No	No
Input attenuation	1.2 MHz	2.5 MHz	2.7 MHz	2.7 MHz
Pulse-reset capacity	≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 60 ms
Residual voltage, U_p typical	< 200 V	250 V	250 V	≤ 300 V
EX protection data				
Input voltage, max. U_i	14 V	19 V	26 V	75 V
Internal capacity, max. C_i	< 4 nF	< 4 nF	< 4 nF	< 4 nF
Internal inductance, max. L_i	0 μ H	0 μ H	0 μ H	0 μ H
Input power, max. P_i	3 W	3 W	3 W	3 W
Protection level				
Protection level wire-wire 1kV/ μ s, type	20 V	20 V	40 V	80 V
Protection level wire-wire 8/20 μ s, type	45 V	55 V	75 V	80 V
Protection level wire-PE 1kV/ μ s, type	25 V	30 V	40 V	85 V
Protection level wire-PE 8/20 μ s, type	< 200 V	250 V	250 V	≤ 300 V

Ordering data

	VSPC 2SL 12VDC EX	VSPC 2SL 12VAC EX	VSPC 2SL 24VDC EX	VSPC 2SL 48VAC EX
Type	VSPC 2SL 12VDC EX	VSPC 2SL 12VAC EX	VSPC 2SL 24VDC EX	VSPC 2SL 48VAC EX
Order No.	8953620000	8953630000	8953670000	8953640000
Qty.	1	1	1	1
Note				






VARITECTOR SPC EX

VSPC 4SL EX - protection for four binary signals
in intrinsically safe circuits

- For use in zones 2, 1, and 0
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Version with floating-earth PE connection for avoiding voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Complete module, indirect earthing

Technical data

Dielectric strength at FG against PE	≥ 500 V
Volume resistance	4.7 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Temperature class T6/85 °C (-40 °C ... +60 °C) li	250 mA
Temperature class T5/100 °C (-40 °C ... +75 °C) li	250 mA
Temperature class T4/135 °C (-40 °C ... +85 °C) li	350 mA
Failure probability	
Ages	43
MTTF	2665
SIL in compliance with IEC 61508	2
Approvals	
Approvals	CE; CSAEX; EAC; IECEXDEK; KEMAATEX
Standards	IEC 61643-21, IEC 62305, DIN EN 60079-0:2009, DIN EN 60079-11:2007, DIN EN 60079-26:2007, DIN EN 61241-11:2006
ATEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
ATEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga
IECEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
IECEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga

Dimensions	Dimensions
Height x width x depth	mm 90 / 17.8 / 69
Note	
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.	

Base elements / base to arresters



Ordering data for base


Description	Type	Qty.	Order No.
EX base element, indirect earthing / floating earth FG	VSPC BASE 4SL FG EX	1	8951840000

Note	Technical data can be found at the beginning of VARITECTOR SPC EX.
------	--

VSPC 4SL EX - plug-in components / arrester



Pluggable component / Arrester



Base element / Base

Ordering data

Rated voltage (AC)
Rated voltage (DC)
Rated current I_n
Optical function display
Input attenuation
Pulse-reset capacity
Residual voltage, U_R typical
EX protection data
Input voltage, max. U_i
Internal capacity, max. C_i
Internal inductance, max. L_i
Input power, max. P_i
Protection level
Protection level wire-wire 1kV/ μ s, type
Protection level wire-wire 8/20 μ s, type
Protection level wire-PE 1kV/ μ s, type
Protection level wire-PE 8/20 μ s, type

VSPC 4SL 12 V DC EX	VSPC 4SL 12 V AC EX	VSPC 4SL 24 V DC EX	VSPC 4SL 24 V AC EX
	12 V		24 V
12 V	16 V	24 V	34 V
300 mA	300 mA	300 mA	300 mA
No	No	No	No
1.2 MHz	2.5 MHz	4 MHz	2.7 MHz
≤ 20 ms	≤ 20 ms	≤ 30 ms	≤ 30 ms
< 200 V	250 V	250 V	250 V
14 V	19 V	26 V	38 V
< 4 nF	< 4 nF	< 4 nF	< 4 nF
0 μ H	0 μ H	0 μ H	0 μ H
3 W	3 W	3 W	3 W
45 V	55 V	80 V	110 V
45 V	55 V	80 V	80 V
25 V	30 V	40 V	60 V
< 200 V	250 V	250 V	250 V

Ordering data

Type	VSPC 4SL 12VDC EX	VSPC 4SL 12VAC EX	VSPC 4SL 24VDC EX	VSPC 4SL 24VAC EX
Order No.	1161170000	1161150000	1161190000	1161180000
Qty.	1	1	1	1
Note				



VARITECTOR SPC EX


VSPC 3/4 SL WIRE EX - protection for 3/4-wire signals in intrinsically safe areas

- Protection of measuring bridge signals in zones 0, 1 and 2
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Version with floating-earth PE connection for avoiding voltage potential differences
- Can be used in accordance with installation standard IEC 62305 and in ATEX applications
- Tested in accordance with IEC/EN 61643-21: D1, C1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data


Dielectric strength at FG against PE	≥ 500 V
Volume resistance	0.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _Δ (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Temperature class T6/85 °C (-40 °C ... +60 °C) II	250 mA
Temperature class T5/100 °C (-40 °C ... +75 °C) II	250 mA
Temperature class T4/135 °C (-40 °C ... +85 °C) II	350 mA
Failure probability	
Ages	43
MTTF	2655
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; IECXDEK; KEMAATEX
Standards	IEC 61643-21, IEC 62305, DIN EN 60079-0:2009, DIN EN 60079-11:2007, DIN EN 60079-26:2007, DIN EN 61241-11:2006
ATEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
ATEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga
IECEx - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
IECEx - gas labelling	II 1 G Ex ia IIC T4... T6 Ga



Complete module, indirect earthing

Dimensions	Dimensions
Height x width x depth	mm 90 / 17.8 / 69
Note	The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Ordering data for base


Description	Type	Qty.	Order No.
EX base element, indirect earthing / floating earth FG	VSPC BASE 4SL FG EX	1	8951840000

Note	Technical data can be found at the beginning of VARITECTOR SPC EX.
------	--

VSPC 3/4SL WIRE EX- plug-in components / arrester



Pluggable component / Arrester



Base element / Base

Ordering data	
VSPC 3/4 WIRE 5 V DC EX	
Rated voltage (AC)	
Rated voltage (DC)	3 V
Rated current I _N	300 mA
Optical function display	No
Input attenuation	750 KHz
Pulse-reset capacity	≤ 20 ms
Residual voltage, U _r typical	< 800 V
EX protection data	
Input voltage, max. U _i	6 V
Internal capacity, max. C _i	< 4 nF
Internal inductance, max. L _i	0 μH
Input power, max. P _i	3 W
Protection level	
Protection level wire-wire 1kV/μs, type	35 V
Protection level wire-wire 8/20 μs, type	35 V
Protection level wire-PE 1kV/μs, type	250 V
Protection level wire-PE 8/20 μs, type	< 800 V

Ordering data	
Type	VSPC 3/4WIRE 5VDC EX
Order No.	8953650000
Qty.	1
Note	




VARITECTOR SPC EX

Indirect earthing

Base element, indirect earthing via spark gap FG, floating earth for ATEX applications.

VSPC BASE FG EX



Technical data

- Stripping length, rated connection
- Wire cross-section, stranded, min.
- Wire cross-section, stranded, max.
- Wire cross-section, solid, min.
- Wire cross-section, solid, max.
- Clamping range, min.
- Clamping range, max.
- Tightening torque, min.
- Tightening torque, max.
- Type of connection
- Approvals
- Ambient temperature (operational)
- Storage temperature
- UL 94 flammability rating
- Pollution degree
- Overvoltage category

7 mm
0.5 mm ²
2.5 mm ²
0.5 mm ²
4 mm ²
0.5 mm ²
4 mm ²
0.5 Nm
0.8 Nm
Screw connection
CE; CSAEX; EAC; IECExDEK; KEMAATEX
-40 °C...70 °C
-40 °C...80 °C
V-0
2
III

Dimensions

Height x width

90 / 17.8

Note

Ordering data

No remote sig. contact

Type	Qty.	Order No.
VSPC BASE 1CL FG EX	1	8951810000
VSPC BASE 2CL FG EX	1	8951820000
VSPC BASE 1CL PW FG EX	1	1070470000
VSPC BASE 2SL FG EX	1	8951830000
VSPC BASE 4SL FG EX	1	8951840000

Note

Technical data can be found at the beginning of VARITECTOR SPC EX.

Accessories

Note

Marker: DEK 5



A


VARITECTOR SSC EX



Lightning and surge protection for intrinsically safe circuits in the explosion hazard area

When used in intrinsically safe circuits within EX zones 2 to 0, the VARITECTOR SSC can reliably protect measurement and control signals from lightning and surge voltages.

Lightning and surge voltages – whether direct at the facilities, near field or far field – can cause signal interference or even destroy connected devices. They could even lead to an explosion within hazardous areas applications. The VARITECTOR SSC EX product line, with a width of 12.4 mm, offers protection against these risks. These products comply with the new IEC 61643-21 standard. They fulfil the “over-stress mode” described. They are also in compliance with the most current ATEX Standard, in EN 60079. Lightning and surge protection components are versatile and simple to use since they feature direct contact to the PE, many marking and diagnostic options, and an easily disconnected signal path. The VARITECTOR SSC EX takes advantages of these features so that it can easily be used in place of a transfer terminal.



Space-saving

A compact installation is possible because of the VSSC EX module's terminal design and 12.4 mm alignment width.




No limitations when used in the EX zone

The EX zone approval provides the proof that the VSSC EX can be used in all EX zones (from zone 2 to zone 0) for dust or gas.




**Fast identification**

Versatile labelling: labels for equipment and individual connections, also easy to read
SnapMark markers for any installation position.

**Complete, standard compliant protection**

The VSSC EX prevents compensation currents in the PE. It also complies with the over stress mode of the IEC 61643-21 standard.

**No proof of intrinsic safety**

Because of the negligible Li and Ci values, no special proof is required for EX zone use.



VARITECTOR SSC EX



VARITECTOR SSC EX

12.4-mm-wide lightning and surge protection for measurement and control signals in the Ex zone

When used in intrinsically safe circuits within Ex zones 2 to 0, the VARITECTOR SSC can reliably protect measurement and control signals from lightning and surge voltages. Lightning and surge voltages – coupled from the field side to machines and facilities – can cause signal interference or even destroy connected devices. They could even lead to an explosion within high-risk Ex-zone applications. The new VARITECTOR SSC EX product line, with a width of 12.4 mm, offers protection against these risks. These products comply with the new IEC 61643-21:2008 standard. They fulfil the “over-stress mode” described. They also meet the latest ATEX standards, EN 60079. These lightning and surge components are a versatile and efficient solution because they feature a direct PE contact, extensive labelling and diagnostic options, and easy separation of the signal paths. The VARITECTOR SSC EX takes advantage of these features so that it can easily be used in place of a transfer terminal.

Labelling of the VSSC EX equipment

ATEX:

For gas
II 1 G Ex ia IIC T4...T6
For dust
II 1 D Ex ia IIIC T135 °C...T85 °C
DEKRA 11ATEX0023X

IEX EX:

For gas
Ex ia IIC T4...T6 Ga
For dust
Ex ia IIIC T135 °C...T85 °C Da

Basic health and safety functions are fulfilled through compliance with:
IEC 61643-21, EN 60079-0,
EN 60079-1, EN 60079-26,
EN 61241-11;

The VSSC series comes in a light blue housing and is used to protect electronics connected to intrinsically safe circuits. The VSSC has a negligible internal inductance and capacitance.

Products for intrinsically safe circuits

VSSC4 CL FG EX are used to protect an intrinsically safe current loop.

VSSC4 SL FG EX are used to protect intrinsically safe **binary signal circuits** (such as alarm contacts).

VSSC4 GDT 24Vuc 20kA EX can be used to provide high-resistance earthing for shields

VSSC6 TR CL 24Vuc EX are used to protect an intrinsically safe current loop. Measurements can be taken in the current loop by simply opening the isolator. A test plug can be inserted in the 2.3-mm test socket (built into the head of the Torx® screws).

VSSC6 RS485 PA EX is used to protect the intrinsically safe PROFIBUS-DP.

General technical data

Storage temperature: -40 °C...+80 °C
Operating temperature: -40 °C...70 °C
Humidity: 5 %...96 % RH without condensation

Material: V0, IP 20
Connection: VSSC4 and VSSC6
Torx® T15 900917
Slotted: 0.8 x 4 900834
Nominal torque: 0.5 Nm
Max. torque: 1 Nm
Stripping length: 10 mm
Solid core: 0.5...6 mm²
Finely stranded: 0.5...4 mm²
Finely stranded with ferrule: 0.5...4 mm²

Dimensions

VSSC4:

Width with frame: 12.4 mm
Height: 76 mm
Depth: 58.5 mm with TS 35 x 7.5
Top connections:
Unprotected: 1
Protected: 4
Bottom connections:
Unprotected: 2
Protected: 3

VSSC6:

Width with frame: 12,4 mm
Height: 88,5 mm
Depth: 81 mm mit TS 35 x 7,5
Top connections:
Unprotected: 1
Protected: 4
Mid-level connections:
Unprotected: 2
Protected: 5
Bottom connections:
Unprotected: 3
Protected: 6

Markers for VSSC4 and VSSC6:

Dekafix: DEK6 for the connections
WS10/6 middle for the device markers
SNAPMARK only for the VSSC6







A



VARITECTOR SSC EX

VSSC 4 CL FG EX - protection for floating earth,
intrinsically safe current loops

- 2-level surge protection with screw connection for intrinsically safe instrumentation and control signals
- Surge protection in terminal block design
- Width of only 12.4 mm
- Torx® for the connection
- Version with floating-earth PE connection used to avoid differences in voltage potential
- Can be used in accordance with installation standard IEC 62305 as well as in ATEX user standards
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	300 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006, HART-compatible
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 µs 5 kV 1.2/50 µs
Surge current-carrying capacity C3	50 A 10/1000 µs
Surge current-carrying capacity D1	0.5 kA 10/350 µs
Discharge current I_t (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I_{max} (8/20 µs) wire-wire/wire-PE/GND-PE	5 kA / 5 kA
Lightning test I_{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	29
MTTF	3936
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; DEKRAATEX; EAC; FUSAFETY; IECExDEK
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006, HART-compatible

Dimensions	Dimensions
Height x width x depth	mm 76 / 12.4 / 58.5
Note	
ATEX approval: II 1 G EX ia IIC T4...T6 Ga II 1 D EX ia IIIC T135°C...T85°C DEKRA N.º: 11ATEX0023 X	

VSSC 4 CL FG EX

Ordering data	VSSC4 CL FG 24 V UC EX	VSSC4 CL FG 48 V UC EX
	24 V	48 V
Rated voltage (AC)	34 V	68 V
Rated voltage (DC)	300 mA	300 mA
Rated current I _N	No	No
Optical function display	3.4 MHz	5 Mhz
Input attenuation	≤ 15 ms	≤ 15 ms
Pulse-reset capacity	≤ 2000 V	≤ 2000 V
Residual voltage, U _r typical		
EX protection data		
Input voltage, max. U _i	42 V	55 V
Internal capacity, max. C _i	1 nF	1 nF
Internal inductance, max. L _i	0 μH	0 μH
Input power, max. P _i	0.75 W	0.75 W



Ordering data		
Type	VSSC4 CL FG 24VAC/DC Ex	VSSC4 CL FG 48VAC/DC Ex
Order No.	1063810000	1063820000
Qty.	1	1
Note	End plate AP VSSC4 LB 1067240000	End plate AP VSSC4 LB 1067240000



VARITECTOR SSC EX

**VSSC 4 SL FG EX - protection for floating earth,
binary, intrinsically safe signals**

- 2-stage surge protection. Screw connection for intrinsically safe measurement, control & feedback control signals
- Terminal block design
- Modular width of only 12.4 mm
- Space-saving design: 1 binary floating ground signal
- Torx® for the connection
- Complies with installation standard IEC 62305 and ATEX applications
- Complies with IEC 61643-21: D1, C1, C2, C3
- Integrated PE foot, discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE

**Technical data**

Rated current I_N	300 mA
Volume resistance	1.8 n 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 µs 5 kV 1.2/50 µs
Surge current-carrying capacity C3	10 A 10/1000 µs
Surge current-carrying capacity D1	1 kA 10/350 µs
Discharge current I_t (8/20 µs) wire-wire/wire-PE/GND-PE	/ 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 µs) wire-wire/wire-PE/GND-PE	/ 10 kA / 10 kA
Lightning test I_{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	43
MTTF	2655
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; DEKRAATEX; EAC; FUSAFETY; IECExDEK; OEVE
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006

Dimensions		Dimensions
Height x width x depth	mm	76 / 12.4 / 58.5
Note		ATEX approval: II 1 G EX ia IIC T4...T6 Ga II 1 D EX ia IIIC T135°C...T85°C DEKRA N.º: 11ATEX0023 X

VSSC 4 SL FG EX

Ordering data

Rated voltage (AC)
Rated voltage (DC)
Rated current I_N
Optical function display
Input attenuation
Pulse-reset capacity
Residual voltage, U_R typical
EX protection data
Input voltage, max. U_i
Internal capacity, max. C_i
Internal inductance, max. L_i
Input power, max. P_i

VSSC4 SL FG 24 V UC EX	VSSC4 SL FG 48 V UC EX
24 V	48 V
34 V	68 V
300 mA	300 mA
No	No
3.4 MHz	5.2 MHz
≤ 35 ms	≤ 20 ms
150 V	< 200 V
42 V	55 V
1 nF	1 nF
0 μ H	0 μ H
0.75 W	0.75 W

Ordering data
Type
Order No.
Qty.
Note


VSSC4 SL FG 24VAC/DC Ex	VSSC4 SL FG 48VAC/DC Ex
1063930000	1063940000
1	1
End plate AP VSSC4 LB 1067240000	End plate AP VSSC4 LB 1067240000



VARITECTOR SSC EX

VSSC 4 GDT EX - protection with sparkover gap (GDT)

- One-stage surge protection with screw connection for measurement and control signals
- Surge protection in terminal block design
- Modular width of only 12.4 mm
- Space-saving design for one signal
- Torx® slotted screw connection®
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: C1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	300 mA
Volume resistance	< 0.1 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_n (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	/ 20 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	10
MTTF	11416
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; DEKRAATEX; EAC; FUSAFETY; IECExDEK
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006

Dimensions	Dimensions
Height x width x depth	mm 76 / 12.4 / 58.5
Note	
ATEX approval: II 1 G EX ia IIC T4...T6 Ga II 1 D EX ia IIIC T135°C...T85°C DEKRA N.º: 11ATEX0023 X	

VSSC 4 GDT EX

Ordering data

Rated voltage (AC)
Rated voltage (DC)
Rated current I_n
Optical function display
Capacitance
Residual voltage, U_p typical

EX protection data

Input voltage, max. U_i
Internal capacity, max. C_i
Internal inductance, max. L_i
Input power, max. P_i

VSSC4 GDT 55 V UC 20 kA EX

55 V
80 V
300 mA
No
4.65 pF
≤ 1900 V

55 V
0 nF
0 μ H
0.75 W

Ordering data

Type
Order No.
Qty.

Note


VSSC4 GDT55VUC 20kA EX
1064040000
1
End plate AP VSSC4 LB 1067240000



VARITECTOR SSC EX

**VSSC 6 TR FG EX - protection for floating,
intrinsically safe current loops with isolator function**

- 2-level surge protection with screw connection for intrinsically safe instrumentation and control signals
- Surge protection in terminal block design
- Alignment width of only 12.4 mm
- Signals can be separated for measurement
- For use in zones 2, 1, and 0
- Torx screw® for the connection
- Can be used in compliance with installation standard IEC 62305
- Tested according to IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE

**Technical data**

Rated current I_N	300 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006, HART-compatible
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 µs 5 kV 1.2/50 µs
Surge current-carrying capacity C3	50 A 10/1000 µs
Surge current-carrying capacity D1	0.5 kA 10/350 µs
Discharge current I_t (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I_{max} (8/20 µs) wire-wire/wire-PE/GND-PE	5 kA / 5 kA
Lightning test I_{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	29
MTTF	3936
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; DEKRAATEX; EAC; FUSAFETY; IECExDEK
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006, HART-compatible

Dimensions		Dimensions
Height x width x depth	mm	88.5 / 12.4 / 81
Note		ATEX approval: II 1 G EX ia IIC T4...T6 Ga II 1 D EX ia IIIC T135°C...T85°C DEKRA N.º: 11ATEX0023 X

VSSC 6 TR FG EX

Ordering data

Rated voltage (AC)
Rated voltage (DC)
Rated current I_N
Optical function display
Input attenuation
Pulse-reset capacity
Residual voltage, U_R typical
EX protection data
Input voltage, max. U_i
Internal capacity, max. C_i
Internal inductance, max. L_i
Input power, max. P_i

VSSC6 TR CLFG 24 V UC EX	VSSC6 TR SLFG 24 V DC EX
24 V	24 V
34 V	34 V
300 mA	300 mA
No	No
270 Mhz	270 Mhz
≤ 20 ms	≤ 20 ms
≤ 1870 V	≤ 1870 V
42 V	42 V
2 nF	2 nF
0 μH	0 μH
0.75 W	0.75 W



Ordering data		
Type	VSSC6TRCLFG24VAC/DC EX	VSSC6SLTRFG24VAC/DC EX
Order No.	1066490000	1421440000
Qty.	1	1
Note	End plate AP VSSC LB 1067230000	End plate AP VSSC LB 1067230000



VARITECTOR SSC EX

VSSC 6 RS485 PROFIBUS PA - protection for RS422/485
intrinsically safe signal interfaces

- Two-stage surge protection with screw connection for PROFIBUS PA RS422/485 data interfaces
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- For use in zones 2, 1, and 0
- Space-saving design: 1 signal
- Torx® slotted screw connection®
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Dielectric strength at FG against PE	≥ 500 V
Volume resistance	1.8 n 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 µs 5 kV 1.2/50 µs
Surge current-carrying capacity C3	10 A 10/1000 µs
Surge current-carrying capacity D1	0.5 kA 10/350 µs
Discharge current I _Δ (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	5 kA / 5 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Type of connection	Screw connection
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ _{ges}	29
MTTF	3936
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; DEKRAATEX; EAC; FUSAFETY; IECExDEK
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006
ATEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
ATEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga
IECEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
IECEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga

Dimensions		Dimensions
Height x width x depth	mm	88.5 / 12.4 / 81
Note		ATEX approval: II 1 G EX ia IIC T4...T6 Ga II 1 D EX ia IIC T135°C...T85°C DEKRA N.º: 11ATEX0023 X

VSSC 6 RS485 PROFIBUS PA

Ordering data	VSSC6 RS485 PA EX
Rated voltage (AC)	
Rated voltage (DC)	12 V
Rated current I_N	300 mA
Optical function display	No
Input attenuation	113.6 MHz
Pulse-reset capacity	≤ 15 ms
Residual voltage, U_r typical	≤ 2 kV
EX protection data	
Input voltage, max. U_i	35 V
Internal capacity, max. C_i	1 nF
Internal inductance, max. L_i	0 μ H
Input power, max. P_i	0.75 W



Ordering data	
Type	VSSC6 RS485 PA EX
Order No.	1065020000
Qty.	1
Note	End plate AP VSSC LB 1067230000



VARITECTOR SSC EX

VSSC 6 RTD EX - protection for intrinsically safe
PT100 signal interfaces

- Two-stage surge protection with screw connection for intrinsically safe PT100/PT1000 signals
- Surge protection in terminal block design
- Modular width of only 12.4 mm
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Dielectric strength at FG against PE	≥ 500 V
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, D1
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 µs 5 kV 1.2/50 µs
Surge current-carrying capacity C3	10 A 10/1000 µs
Surge current-carrying capacity D1	0.5 kA 10/350 µs
Discharge current I _Δ (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	5 kA / 5 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Type of connection	Screw connection
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	
Rail	TS 35
Failure probability	
λ _{ges}	61
MTTF	1871
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; DEKRAATEX; EAC; FUSAFETY; IECExDEK
Standards	IEC61643-21:2009, DIN EN 60079-0:2009, DIN EN 60079-26:2007, DIN EN 61241-11:2006
ATEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
ATEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga
IECEX - dust labelling	II 1 D Ex ia IIC T135 °C ...T85 °C Da
IECEX - gas labelling	II 1 G Ex ia IIC T4... T6 Ga

Dimensions		Dimensions
Height x width x depth	mm	88.5 / 12.4 / 81
Note		ATEX approval: II 1 G EX ia IIC T4...T6 Ga II 1 D EX ia IIC T135°C...T85°C DEKRA No: 11ATEX0023 X

VSSC 6 RTD EX

Ordering data	VSSC6 RTD EX
Rated voltage (AC)	
Rated voltage (DC)	1 V
Rated current I_N	300 mA
Optical function display	No
Input attenuation	120 Mhz
Pulse-reset capacity	≤ 10 ms
Residual voltage, U_r typical	≤ 1.8 kV
EX protection data	
Input voltage, max. U_i	5 V
Internal capacity, max. C_i	7 nF
Internal inductance, max. L_i	0 μH
Input power, max. P_i	0.75 W

Ordering data	
Type	VSSC6 RTD EX
Order No.	1130670000
Qty.	1
Note	End plate AP VSSC LB 1067230000

Approval – VSPC-ATEX

CERTIFICATE
EC-Type Examination

(1) Equipment and protective systems intended for use in potentially explosive atmospheres - Directive 94/9/EC
(2) EC-Type Examination Certificate Number: KEMA 10ATEX0148 X Issue Number: 3
(3) Equipment: Surge Voltage Protection Unit, Type VSPC ... Ex
(4) Manufacturer: Weidmüller Interface GmbH & Co. KG
(5) Address: Klingenbergstraße 16, 32758 Detmold, Germany
(6) This equipment and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.
(7) DEKRA Certification B.V., notified body number 0344 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the directive.
(8) The examination and test results are recorded in confidential test report no. NL/DEK/EXTR11.0099/03.
(9) Compliance with the Essential Health and Safety Requirements has been established by conformity with:
EN 60079-0 : 2012 EN 60079-11 : 2012 EN 60730-3 : 2007
(10) If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.
(11) This EC-Type Examination Certificate relates only to the design, examination and tests of the specific equipment according to the Directive 94/9/EC. Further requirements of the directive apply to the manufacturing process and supply of this equipment. These are not covered by this certificate.
(12) The marking of the equipment shall include the following:

 II G Ex Ia IIC T4 ... T6 Ga or
II D Ex Ia IIC T135 °C ... T85 °C Da

This certificate is issued on 13 December 2013 and, as far as applicable, shall be revised before the date of cessation of presumption of conformity of (one of) the standards mentioned above as communicated in the Official Journal of the European Union.

DEKRA Certification B.V.

R. Scheller
Certification Manager

Page 1/3

 "Integral publication of this certificate and a signing report is allowed. This Certificate may only be reproduced in its entirety and without any change."
DEKRA Certification B.V. Meander 1051, 6825 MJ Arnhem P.O. Box 5185, 6802 ED Arnhem The Netherlands
T +31 88 96 83000 F +31 88 96 83100 www.dekra-certification.com Registered Arnhem 09065396



(13) **SCHEDULE**
(14) to EC-Type Examination Certificate KEMA 10ATEX0148 X Issue No. 3
(15) **Description**
The Surge Voltage Protection Unit of Series VSPC ... Ex serves to limit eventual surge voltages in intrinsically safe circuits.
The Units consist out of a Base Module for rail mounting and a pluggable protection Module provided with a (for each Base Module type) unique mechanical key.
The Plug-in unit Type VSPC 1CL PW 24Vac EX also contains a LED error-Indication.
Several units for different intrinsically safe circuits may be mounted next to each other.

Electrical data
Input circuit (Terminals 1, 5, 7 and 11):
in type of protection intrinsic safety Ex ia IIC or Ex ia IIIC, only for connection to a certified intrinsically safe circuit, with the following maximum values:
L_i = 0 µH; C_i = 25 nF (for Type VSPC 1CL PW 24VAC EX); C_i = 4 nF (for the other Types).
The values of U_i for the different types of pluggable modules are listed in the following table:

Pluggable protection Module Types	U _i
VSPC ... 5VDC EX	6 V
VSPC ... 12VDC EX	14 V
VSPC ... 12VAC EX	19 V
VSPC ... 24VDC EX	26 V
VSPC 1CL PW 24VAC EX	27 V
VSPC ... 24VAC EX	38 V
VSPC ... 48VAC EX	75 V

Page 2/3
Form 101
Version 5 (2013-07)



(13) **SCHEDULE**
(14) to EC-Type Examination Certificate KEMA 10ATEX0148 X Issue No. 3
The temperature class / maximum surface temperature of the Base modules, depending on I_i and the ambient temperature range is listed in the following table:

Base Module Type	I _i	Ambient temperature range	Temperature class / Maximum surface temperature
VSPC BASE 4SL FG EX VSPC BASE 2CL FG EX VSPC BASE 1CL PW FG EX	250 mA	-40 to +60 °C	T6 / T85 °C
	250 mA	-40 to +75 °C	T5 / T100 °C
	350 mA	-40 to +85 °C	T4 / T135 °C
VSPC BASE 2CH FG EX	3,3 A	-40 to +60 °C	T6 / T85 °C
		-40 to +75 °C	T5 / T100 °C
		-40 to +85 °C	T4 / T135 °C

Output circuits (Terminals 2, 6, 8 and 12):
in type of protection intrinsic safety Ex ia IIC or Ex ia IIIC. The output parameters are equal to the output parameters of the external intrinsically safe circuits connected to the input circuit. For the determination of the maximum allowed external capacitance (C_e) and inductance (L_e), the values of the internal capacitance (C_i) and inductance (L_i) shall be taken into account.

Installation instructions
The instructions provided with the equipment shall be followed in detail to assure safe operation.

(16) **Test Report**
No. NL/DEK/EXTR11.0099/03.

(17) **Special conditions for safe use**
For application in explosive dust atmospheres:
The Surge Voltage Protection Units shall be installed in an enclosure, which provides a degree of protection of at least IP6X in accordance with EN 60529, and is suitable for the application and correctly installed. The maximum surface temperature of the enclosure is specified in the description (15).
Measures shall be taken to avoid the danger of ignition due to electrostatic charges.

(18) **Essential Health and Safety Requirements**
Covered by the standards listed at (9).

(19) **Test documentation**
As listed in Test Report No. NL/DEK/EXTR11.0099/03.

Page 3/3
Form 101
Version 5 (2013-07)

Approval – VSSC-ATEX

CERTIFICATE
EC-Type Examination

(1) **Equipment and protective systems intended for use in potentially explosive atmospheres - Directive 94/9/EC**

(2) EC-Type Examination Certificate Number: DEKRA 11ATEX0023 X Issue Number: 2

(3) **Equipment:** Surge Voltage Protection Unit, Series VSSC ... Ex

(4) **Manufacturer:** Weidmüller Interface GmbH & Co. KG

(5) **Address:** Klingenbergstraße 16, 32758 Detmold, Germany

(6) This equipment and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

(7) DEKRA Certification B.V., notified body number 0344 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the directive.

The examination and test results are recorded in confidential test report no. NL/DEK/EXTR11.0016/1**.

(8) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 60079-0 : 2012 EN 60079-11 : 2012 EN 60079-26 : 2007

(9) If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.

(10) This EC-Type Examination Certificate relates only to the design, construction and tests of the specified equipment and supply of this equipment. These are not covered by this certificate.

(11) The marking of the equipment shall include the following:

Ex II 1 G Ex ia IIC T4 ... T6 Ga
or
II 1 D Ex ia IIC T135 °C ... T85 °C Da

This certificate is issued on 20 August 2013 and, as far as applicable, shall be revised before the date of cessation of presumption of conformity of (one of) the standards mentioned above as communicated in the Official Journal of the European Union.

DEKRA Certification B.V.
[Signature]
Certification Manager

Page 1/3

® Reproduction of this certificate for marketing purposes is allowed. This Certificate may only be reproduced in its entirety and without any change.

DEKRA Certification B.V., Meander 1051, 6825 MJ Arnhem P.O. Box 5185, 6802 ED Arnhem The Netherlands
T +31 88 96 83000 F +31 88 96 83100 www.dekra-certification.com Registered Arnhem 09083396

DEKRA

(13) **SCHEDULE**

(14) to EC-Type Examination Certificate DEKRA 11ATEX0023 X Issue No. 2

(15) **Description**

The Surge Voltage Protection Unit of Series VSSC ... Ex serves to limit any surge voltages in intrinsically safe circuits.

The earth connection can be made via the mounting foot to a normalized metal mounting rail and via a terminal.

Several units for different intrinsically safe circuits may be mounted next to each other.

Ambient temperature range: -40 °C to +70 °C (T6 / T85 °C),
-40 °C to +85 °C (T5 / T100 °C),
-40 °C to +120 °C (T4 / T135 °C).

Electrical data

Input circuit (Terminals 1, 2):
in type of protection intrinsic safety Ex ia IIC or Ex ia IIC, only for connection to a certified intrinsically safe circuit, with the following maximum values:
I_a = 300 mA; P_a = 0,75 W; L_a = 0 µH.
The values of U_i and C_i for the different types are listed in the following table:

Type	U _i	C _i
VSSC4 CL FG 24VAC/DC EX	42 V	1 nF
VSSC4 CL FG 48VAC/DC EX	55 V	1 nF
VSSC4 SL FG 24VAC/DC EX	42 V	1 nF
VSSC4 SL FG 48VAC/DC EX	55 V	1 nF
VSSC4 GDT 55Vuc 20kA EX	55 V	0 nF
VSSC6 TR CL FG 24VAC/DC EX	42 V	1 nF
VSSC6 RS485 PA EX	35 V	1 nF
VSSC6 RTD EX	5 V	7 nF
VSSC6 TR SL FG 24VAC/DC EX	42 V	2 nF

Output circuit (Terminals 3, 4):
in type of protection intrinsic safety Ex ia IIC or Ex ia IIC. The output parameters are equal to the output parameters of the external intrinsically safe circuit connected to the input circuit.
For the determination of the maximum allowed external capacitance (C_e) and inductance (L_e), the values of the internal capacitance (C_i) and inductance (L_i) shall be taken into account.

Installation instructions

The instructions provided with the equipment shall be followed in detail to assure safe operation.

(16) **Test Report**

No. NL/DEK/EXTR11.0016/1**.

Page 2/3
Form 101
Version 5 (2013-07)

DEKRA

(13) **SCHEDULE**

(14) to EC-Type Examination Certificate DEKRA 11ATEX0023 X Issue No. 2

(17) **Special conditions for safe use**

The intrinsic safe signal of Surge Voltage Protection Unit, Type VSSC4 GDT 55Vuc 20kA EX, is directly connected to earth.

For ambient temperature range, see (15).

(18) **Essential Health and Safety Requirements**

Covered by the standards listed at (9).

(19) **Test documentation**

As listed in Test Report No. NL/DEK/EXTR11.0016/1**.

Page 3/3
Form 101
Version 5 (2013-07)



Approval – VSSC-IEC Ex

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION
IEC Certification Scheme for Explosive Atmospheres
for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx DEK 11.0020X Issue No.: 1
Status: Current
Date of Issue: 2013-08-20 Page 1 of 4

Applicant: Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16, 32758 Detmold
Germany

Electrical Apparatus: Surge Voltage Protection Unit, Series VSSC ... Ex
Optional accessory:

Type of Protection: Ex ia

Marking: Ex ia IIC T4 ... T0 Ga or
Ex ia IIIC T135 °C ... T35 °C Da

Approved for issue on behalf of the IECEx: R. Schuller
Certification Body: Certification Manager
Position: 
Signature: (for printed version)
Date: 2013-08-20

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:
DEKRA Certification B.V.
Meander 1051,
6825 NJ Arnhem
The Netherlands

DEKRA

IECEx Certificate of Conformity

Certificate No.: IECEx DEK 11.0020X
Date of Issue: 2013-08-20 Issue No.: 1
Page 2 of 4

Manufacturer: Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16, 32758 Detmold
Germany

Additional Manufacturing location (s):
Weidmüller Interface (Suzhou) Co., Ltd
New Technology Park
81 Xiangyang Road
Suzhou New District
Jiangsu Province
China

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx ID and Operational Documents as amended.

STANDARDS:
The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Explosive atmospheres - Part 0: General requirements
Edition: 3.0
IEC 60079-11 : 2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "I"
Edition: 6.0
IEC 60079-26 : 2006 Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga
Edition: 2

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:
A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in Test Report:
NL/DEK/EX1R11.00160

Quality Assessment Report:
NL/DEK/QAR12.005200 NL/DEK/QAR12.007200

IECEx Certificate of Conformity

Certificate No.: IECEx DEK 11.0020X
Date of Issue: 2013-08-20 Issue No.: 1
Page 3 of 4

Schedule

EQUIPMENT:
Equipment and systems covered by this certificate are as follows:
The Surge Voltage Protection Unit of Series VSSC ... Ex serves to limit any surge voltages in intrinsically safe circuits.
For thermal and electrical data, refer to Annexee.

CONDITIONS OF CERTIFICATION: YES as shown below:
The intrinsic safe signal of Surge Voltage Protection Unit Type VSSC4 GDT 55Vuc 20 kA EX, is directly connected to earth (PE).
For ambient temperature ranges, refer to Annex.

DEKRA

Annex 1 to Certificate of Conformity IECEx DEK 11.0020X, Issue 1

General product information:
The Surge Voltage Protection Unit of Series VSSC ... Ex serves to limit any surge voltages in intrinsically safe circuits.
The earth connection can be made via the mounting foot to a normalized metal mounting rail and via a terminal.
Several units for different intrinsically safe circuits may be mounted next to each other.

Thermal data
Ambient temperature range: -40 °C to +70 °C (T6 / T85 °C),
-40 °C to +85 °C (T5 / T100 °C),
-40 °C to +120 °C (T4 / T135 °C).

Electrical data
Input circuit (Terminals 1, 2):
in type of protection intrinsic safety Ex ia IIC or Ex ia IIIC, only for connection to a certified intrinsically safe circuit, with the following maximum values:
 $I_n = 320 \text{ mA}$, $U_n = 0 \text{ V}$, $P_n = 0.75 \text{ W}$.
The values of U_n and C_n for the different types are listed in the following table:


Type	U_n	C_n
VSSC4 CL FG 24VAC/DC EX	42 V	1 nF
VSSC4 CL FG 48VAC/DC EX	55 V	1 nF
VSSC4 SL FG 24VAC/DC EX	42 V	1 nF
VSSC4 SL FG 48VAC/DC EX	55 V	1 nF
VSSC4 GDT 55Vuc 20kA EX	55 V	0 nF
VSSC6 TR CL FG 24VAC/DC EX	42 V	1 nF
VSSC6 RS485 PA EX	35 V	1 nF
VSSC6 RTD EX	5 V	7 nF
VSSC6 TR SL FG 24VAC/DC EX	42 V	2 nF

Output circuit (Terminals 3, 4):
in type of protection intrinsic safety Ex ia IIC or Ex ia IIIC. The output parameters are equal to the output parameters of the external intrinsically safe circuit connected to the input circuit.
For the determination of the maximum allowed external capacitance (C_n) and inductance (L_n), the values of the internal capacitance (C_i) and inductance (L_i) shall be taken into account.

Page 1 of 1
From 134
Version 1 (2011-02)

DEKRA Certification B.V. Meander 1051, 6825 MJ Arnhem P.O. Box 5185, 6802 ED Arnhem The Netherlands
T +31 88 96 83000 F +31 88 96 83100 www.dekra-certification.com Registered Arnhem 0908396

Approval – VSPC-IEC Ex

IEC		IECEx		IECEx Certificate of Conformity	
INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres for rules and details of the IECEx Scheme visit www.iecex.com					
Certificate No.:	IECEx DEK 11.0088X	Issue No. 2	Certificate history: Issue No. 2 (2013-12-23) Issue No. 1 (2013-05-09) Issue No. 0 (2011-10-12)		
Status:	Current	Page 1 of 4			
Date of issue:	2013-12-23				
Applicant:	Weidmüller Interface GmbH & Co. KG Klingenbergstraße 16 32758 Detmold Germany				
Electrical Apparatus:	Surge Voltage Protection Unit Series VSPC...Ex				
Optional accessory:					
Type of Protection:	Ex ia				
Marking:	Ex ia IIC T4 ... T6 Ga or Ex ia IIC T135 °C ... T85 °C Da				
Approved for issue on behalf of the IECEx Certification Body:	R. Schüller Certification Manager				
Signature:					
Date:	2013-12-23				
1. This certificate and schedule may only be reproduced in full. 2. This certificate is not transferable and remains the property of the issuing body. 3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.					
Certificate issued by: DEKRA Certification B.V. Utrechtseweg 310 6612 AR Arnhem The Netherlands 					

IEC		IECEx		IECEx Certificate of Conformity							
Certificate No.:	IECEx DEK 11.0088X	Issue No. 2	Page 2 of 4								
Date of issue:	2013-12-23										
Manufacturer:	Weidmüller Interface GmbH & Co. KG Klingenbergstraße 16 32758 Detmold Germany										
Additional Manufacturing location(s):											
This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx Q2 and Operational Documents as amended.											
STANDARDS: The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards: <table border="0"> <tr> <td>IEC 60079-0: 2011 Edition 5.0</td> <td>Explosive atmospheres - Part 0: General requirements</td> </tr> <tr> <td>IEC 60079-11: 2011 Edition 5.0</td> <td>Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"</td> </tr> <tr> <td>IEC 60079-26: 2009 Edition 2</td> <td>Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga</td> </tr> </table> This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.						IEC 60079-0: 2011 Edition 5.0	Explosive atmospheres - Part 0: General requirements	IEC 60079-11: 2011 Edition 5.0	Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"	IEC 60079-26: 2009 Edition 2	Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga
IEC 60079-0: 2011 Edition 5.0	Explosive atmospheres - Part 0: General requirements										
IEC 60079-11: 2011 Edition 5.0	Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"										
IEC 60079-26: 2009 Edition 2	Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga										
TEST & ASSESSMENT REPORTS: A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in Test Report: NU/DEKEXTR11.0098/00 NU/DEKEXTR11.0099/01 NU/DEKEXTR11.0099/02 Quality Assessment Report: NU/DEKQAR12.0052/00											

IEC		IECEx		IECEx Certificate of Conformity	
Certificate No.:	IECEx DEK 11.0088X	Issue No. 2	Page 3 of 4		
Date of issue:	2013-12-23				
Schedule					
EQUIPMENT: Equipment and systems covered by this certificate are as follows: The Surge Voltage Protection Unit of Series VSPC...Ex serves to limit eventual surge voltages in intrinsically safe circuits. The Units consist out of a Base unit for rail mounting and a pluggable protection Module provided with a (for each Unit Model) unique mechanical key. The Plug-in unit Type VSPC 1CL PIV 24Vac EX also contains a LED error-indication. Several units for different intrinsically safe circuits may be mounted next to each other. See annex "attachment to IECEx DEK 11.0088 X Issue 2" for more detailed information.					
CONDITIONS OF CERTIFICATION: YES as shown below: For application in explosive dust atmospheres: The Surge Voltage Protection Units shall be installed in an enclosure, which provides a degree of protection of at least IP6X in accordance with IEC 60529, and is suitable for the application and correctly installed. The maximum surface temperature of the enclosure is specified in the annex "attachment to IECEx DEK 11.0088 X Issue 2". Measures shall be taken to avoid the danger of ignition due to electrostatic charges.					

IEC		IECEx		IECEx Certificate of Conformity	
Certificate No.:	IECEx DEK 11.0088X	Issue No. 2	Page 4 of 4		
Date of issue:	2013-12-23				
DETAILS OF CERTIFICATE CHANGES (for issues 1 and above): Assessment in accordance with the latest edition of the standards. Annex: Attachment to IECEx DEK 11.0088X, Issue 2.pdf					





Approval – VSPC-IEC Ex

Attachment 1 to IECEx DEK 11.0086 X, Issue 2

General product information:

The Surge Voltage Protection Unit of Series VSPC...Ex serves to limit eventual surge voltages in intrinsically safe circuits.

The Units consist out of a Base unit for rail mounting and a pluggable protection Module provided with a (for each Unit Model) unique mechanical key.

The Plug-in unit Type VSPC 1CL PW 24Vac EX also contains a LED error-indication.

Several units for different intrinsically safe circuits may be mounted next to each other.

Electrical data

Input circuit (Terminals 1, 5, 7 and 11):
in type of protection intrinsic safety Ex ia IIC or Ex ia IIIC, only for connection to a certified intrinsically safe circuit, with the following maximum values:
L = 0 µH; C = 25 nF (for Type VSPC 1CL PW 24VAC EX);
C = 4 nF (for the other Types).

The values of U_i for the different types of pluggable modules are listed in the following table:

Pluggable protection Module Types	U _i
VSPC ... 6VDC EX	6 V
VSPC ... 12VDC EX	14 V
VSPC ... 12VAC EX	19 V
VSPC ... 24VDC EX	26 V
VSPC 1CL PW 24VAC EX	27 V
VSPC ... 24VAC EX	38 V
VSPC ... 48VAC EX	75 V

The temperature class / maximum surface temperature of the Base modules, depending on I and the ambient temperature range is listed in the following table:

Base Module Type	I	Ambient temperature range	Temperature class / Maximum surface temperature
VSPC BASE 4SL FG EX	250 mA	-40 to +60 °C	T6 / T85 °C
VSPC BASE 2CL FG EX	250 mA	-40 to +75 °C	T5 / T100 °C
VSPC BASE 1CL PW FG EX	350 mA	-40 to +85 °C	T4 / T135 °C
VSPC BASE 1CL FG EX		-40 to +60 °C	T6 / T85 °C
		-40 to +75 °C	T5 / T100 °C
		-40 to +85 °C	T4 / T135 °C
VSPC BASE 24CH FG EX	3.3 A	-40 to +60 °C	T6 / T85 °C
		-40 to +75 °C	T5 / T100 °C
		-40 to +85 °C	T4 / T135 °C

Page: 1/2

Attachment 1 to IECEx DEK 11.0086 X, Issue 2

Output circuits (Terminals 2, 6, 8 and 12):
in type of protection intrinsic safety Ex ia IIC or Ex ia IIIC. The output parameters are equal to the output parameters of the external intrinsically safe circuits connected to the input circuit. For the determination of the maximum allowed external capacitance (C_e) and inductance (L_e), the values of the internal capacitance (C_i) and inductance (L_i) shall be taken into account.

Page 2/2

Lightning and surge protection for low voltage supply

Lightning and surge protection for low voltage supply	Quick selection guide	B.2
	Type I and II lightning arrester	B.8
	Type II surge protection	B.38
	Lightning and surge protection for photovoltaic systems on the DC side	B.62
	Type III surge protection for terminal devices	B.68
	VARITECTOR TEST II-test device	B.76



Product quick selection, power supply

Type I

Product	Version	Rated voltage	Lightning test current I_{imp} (10/350 μs)	Discharge current I_n (8/20 μs)	Discharge current I_{max} (8/20 μs)	Protection level U_p	Max. backup fuse	Signalling contact	Overall width	Order No.
		Uc (AC)								
Type I - leakage current free 35 kA										
VPU I 1 LCF 280V/35kA	1-pole	280 V	35 kA	25 kA	100 kA	1.8 kV	315 A		4 TE	1351350000
VPU I 1 R LCF 280V/35kA	1-pole	280 V	35 kA	25 kA	100 kA	1.8 kV	315 A	1 CO	4 TE	1351330000
VPU I 1 LCF 400V/35kA	1-pole	280 V	35 kA	25 kA	100 kA	2.5 kV	315 A		4 TE	1351400000
VPU I 1 R LCF 400V/35kA	1-pole	400 V	35 kA	25 kA	100 kA	2.5 kV	315 A	1 CO	4 TE	1351380000
Type I - leakage current free 25 kA / 280 V										
VPU I 1 LCF 280V/25kA	1-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A		2 TE	1351590000
VPU I 1 R LCF 280V/25kA	1-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A	1 CO	2 TE	1351570000
VPU I 1+1 LCF 280V/25kA	2-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A		4 TE	1351750000
VPU I 1+1 R LCF 280V/25kA	2-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A	1 CO	4 TE	1351740000
VPU I 2 LCF 280V/25kA	2-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A		4 TE	1351640000
VPU I 2 R LCF 280V/25kA	2-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A	1 CO	4 TE	1351620000
VPU I 3 LCF 280V/25kA	3-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A		6 TE	1351690000
VPU I 3 R LCF 280V/25kA	3-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A	1 CO	6 TE	1351670000
VPU I 3+1 LCF 280V/25kA	4-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A		8 TE	1351780000
VPU I 3+1 R LCF 280V/25kA	4-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A	1 CO	8 TE	1351770000
VPU I 4 LCF 280V/25kA	4-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A		8 TE	1351730000
VPU I 4 R LCF 280V/25kA	4-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.6 kV	250 A	1 CO	8 TE	1351720000
Type I - 25 kA / 280 V										
VPU I 1+1 280V/25kA	2-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.4 kV	250 A		4 TE	2063060000
VPU I 1+1 R 280V/25kA	2-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.4 kV	250 A	1 CO	4 TE	2063040000
VPU I 3 280V/25kA	3-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.4 kV	250 A		6 TE	2062940000
VPU I 3 R 280V/25kA	3-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.4 kV	250 A	1 CO	6 TE	2062910000
VPU I 3+1 280V/25kA	4-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.4 kV	250 A		8 TE	2063080000
VPU I 3+1 R 280V/25kA	4-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.4 kV	250 A	1 CO	8 TE	2063070000
VPU I 4 280V/25kA	4-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.4 kV	250 A		8 TE	2062960000
VPU I 4 R 280V/25kA	4-pole, pluggable	280 V	25 kA	25 kA	100 kA	1.4 kV	250 A	1 CO	8 TE	2062950000
Type I - 25 kA / 400 V										
VPU I 1 400V/25kA	1-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A		2 TE	1351820000
VPU I 1 R 400V/25kA	1-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A	1 CO	2 TE	1351800000
VPU I 1+1 400V/25kA	2-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A		4 TE	1351840000
VPU I 1+1 R 400V/25kA	2-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A	1 CO	4 TE	1351830000
VPU I 3 400V/25kA	3-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A		6 TE	1351870000
VPU I 3 R 400V/25kA	3-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A	1 CO	6 TE	1351850000
VPU I 3+1 400V/25kA	4-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A		8 TE	1351890000
VPU I 3+1 R 400V/25kA	4-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A	1 CO	8 TE	1351880000
VPU I 4 400V/25kA	4-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A		8 TE	1438010000
VPU I 4 R 400V/25kA	4-pole, pluggable	400 V	25 kA	25 kA	100 kA	1.9 kV	250 A	1 CO	8 TE	1438020000
Type I - leakage current free 25 kA / 440 V										
VPU AC I 1 440/25 LCF	1-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A		2 TE	2619100000
VPU AC I 1 R 440/25 LCF	1-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A	1 CO	2 TE	2619120000
VPU AC I 1+1 440/25 LCF	2-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A		4 TE	2619210000
VPU AC I 1+1 R 440/25 LCF	2-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A	1 CO	4 TE	2619220000
VPU AC I 2 440/25 LCF	2-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A		4 TE	2619130000
VPU AC I 2 R 440/25 LCF	2-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A	1 CO	4 TE	2619140000
VPU AC I 3 440/25 LCF	3-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A		6 TE	2619160000
VPU AC I 3 R 440/25 LCF	3-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A	1 CO	6 TE	2619170000
VPU AC I 3+1 440/25 LCF	4-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A		8 TE	2619240000
VPU AC I 3+1 R 440/25 LCF	4-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A	1 CO	8 TE	2619260000
VPU AC I 4 440/25 LCF	4-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A		8 TE	2619190000
VPU AC I 4 R 440/25 LCF	4-pole	440 V	25 kA	20 kA	100 kA	1.9 kV	315 A	1 CO	8 TE	2619200000
Type I - leakage current free 12.5 kA / 300 V										
VPU AC I 1 300/12.5 LCF	1-pole, pluggable	300 V	12.5 kA	20 kA	65 kA	1.5 kV	315 A		1 TE	2636950000
VPU AC I 1 R 300/12.5 LCF	1-pole, pluggable	300 V	12.5 kA	20 kA	65 kA	1.5 kV	315 A	1 CO	1 TE	2636960000
VPU AC I 1+1 300/12.5 LCF	2-pole, pluggable	300 V	12.5 kA	20 kA	65 kA	1.5 kV	315 A		2 TE	2636930000
VPU AC I 1+1 R 300/12.5 LCF	2-pole, pluggable	300 V	12.5 kA	20 kA	65 kA	1.5 kV	315 A	1 CO	2 TE	2636940000
VPU AC I 3 300/12.5 LCF	3-pole, pluggable	300 V	12.5 kA	20 kA	65 kA	1.5 kV	315 A		3 TE	2636970000
VPU AC I 3 R 300/12.5 LCF	3-pole, pluggable	300 V	12.5 kA	20 kA	65 kA	1.5 kV	315 A	1 CO	3 TE	2636980000
VPU AC I 3+1 300/12.5 LCF	4-pole, pluggable	300 V	12.5 kA	20 kA	65 kA	1.5 kV	315 A		4 TE	2636910000
VPU AC I 3+1 R 300/12.5 LCF	4-pole, pluggable	300 V	12.5 kA	20 kA	65 kA	1.5 kV	315 A	1 CO	4 TE	2636920000



Type I

Product	Version	Rated voltage	Lightning test current I_{imp} (10/350 µs)	Discharge current I_n (8/20 µs)	Discharge current I_{max} (8/20 µs)	Protection level U_p	Max. backup fuse	Signalling contact	Overall width	Order No.
Type I - 12.5 kA / 300 V										
VPU AC I 1 300/12.5	1-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A		1 TE	2591380000
VPU AC I 1 R 300/12.5	1-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	1 TE	2591390000
VPU AC I 1+1 300/12.5	2-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A		2 TE	2591480000
VPU AC I 1+1 R 300/12.5	2-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	2 TE	2591490000
VPU AC I 2 300/12.5	2-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A		2 TE	2591400000
VPU AC I 2 R 300/12.5	2-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	2 TE	2591410000
VPU AC I 3 300/12.5	3-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A		3 TE	2591440000
VPU AC I 3 R 300/12.5	3-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	3 TE	2591450000
VPU AC I 3+1 300/12.5	4-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A		4 TE	2591460000
VPU AC I 3+1 R 300/12.5	4-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	4 TE	2591470000
VPU AC I 4 300/12.5	4-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A		4 TE	2591420000
VPU AC I 4 R 300/12.5	4-pole, pluggable	300 V	12.5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	4 TE	2591430000
Type I - 10 kA / 480 V										
VPU AC I 1 480/10	1-pole, pluggable	480 V	10 kA	20 kA	50 kA	2.1 kV	315 A		1 TE	2591510000
VPU AC I 1 R 480/10	1-pole, pluggable	480 V	10 kA	20 kA	50 kA	2.1 kV	315 A	1 CO	1 TE	2591520000
VPU AC I 3 480/10	3-pole, pluggable	480 V	10 kA	20 kA	50 kA	2.1 kV	315 A		3 TE	2591530000
VPU AC I 3 R 480/10	3-pole, pluggable	480 V	10 kA	20 kA	50 kA	2.1 kV	315 A	1 CO	3 TE	2591540000
VPU AC I 4 480/10	4-pole, pluggable	480 V	10 kA	20 kA	50 kA	2.1 kV	315 A		4 TE	2591550000
VPU AC I 4 R 480/10	4-pole, pluggable	480 V	10 kA	20 kA	50 kA	2.1 kV	315 A	1 CO	4 TE	2591560000
Type I - N-PE										
VPU I 1 N-PE 260V/50KA	1-pole, pluggable	260 V	50 kA	50 kA	100 kA	1.5 kV	-		1 TE	1351900000
VPU I 1 N-PE 260V/100KA	1-pole, pluggable	260 V	100 kA	100 kA	100 kA	1.6 kV	-		2 TE	1351920000
VPU AC I 1 N-PE 305/50	1-pole, pluggable	305 V	50 kA	50 kA	100 kA	1.5 kV	-		1 TE	2591570000
VPU I 1 N-PE 440V/50KA	1-pole, pluggable	440 V	50 kA	50 kA	100 kA	2.7 kV	-		1 TE	1351950000
VPU I 1 N-PE 440V/100KA	1-pole, pluggable	440 V	100 kA	100 kA	100 kA	3.0 kV	-		2 TE	1351970000
Type I - for busbars										
VPU ZP I 3 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	160 A		58 mm	2638450000
VPU ZP I 3 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	160 A		58 mm	2659900000
VPU ZP I 3+1 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	160 A		58 mm	2638440000
VPU ZP I 3+1 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	160 A		58 mm	2659910000
VPU ZPA I 3 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	315 A		47 mm	2674350000
VPU ZPA I 3 R 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	47 mm	2674310000
VPU ZPA I 3 A 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	315 A	Voltage tap	47 mm	2674360000
VPU ZPA I 3 RA 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO + Voltage tap	47 mm	2674370000
VPU ZPA I 3+1 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	315 A		47 mm	2674380000
VPU ZPA I 3+1 R 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	47 mm	2674390000
VPU ZPA I 3+1 A 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	315 A	Voltage tap	47 mm	2674400000
VPU ZPA I 3+1 RA 300/12,5	40 mm busbars	300 V	12,5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO + Voltage tap	47 mm	2674410000
VPU ZPA I 3 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	315 A		47 mm	2674420000
VPU ZPA I 3 R 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	47 mm	2674430000
VPU ZPA I 3 A 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	315 A	Voltage tap	47 mm	2674440000
VPU ZPA I 3 RA 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO + Voltage tap	47 mm	2674450000
VPU ZPA I 3+1 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	315 A		47 mm	2674460000
VPU ZPA I 3+1 R 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO	47 mm	2674470000
VPU ZPA I 3+1 A 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	315 A	Voltage tap	47 mm	2674500000
VPU ZPA I 3+1 RA 300/7,5	40 mm busbars	300 V	7,5 kA	20 kA	50 kA	1.5 kV	315 A	1 CO + Voltage tap	47 mm	2674510000



Product quick selection, power supply

Type II

Product	Version	Rated voltage	Discharge current I_n (8/20 μ s)	Discharge current I_{max} (8/20 μ s)	Protection level U_p	Max. backup fuse	Signalling contact	Overall width	Order No.
		U_c (AC)							
Type II - 75 V / 50 kA									
VPU AC II 1 75/50	1-pole, pluggable	75 V	20 kA	50 kA	0.8 kV	315 A		1 TE	2636990000
VPU AC II 1 R 75/50	1-pole, pluggable	75 V	20 kA	50 kA	0.8 kV	315 A	1 CO	1 TE	2591620000
VPU AC II 2 75/50	2-pole, pluggable	75 V	20 kA	50 kA	0.8 kV	315 A		2 TE	2637000000
VPU AC II 2 R 75/50	2-pole, pluggable	75 V	20 kA	50 kA	0.8 kV	315 A	1 CO	2 TE	2591630000
Type II - 150 V / 50 kA									
VPU AC II 1 150/50	1-pole, pluggable	150 V	20 kA	50 kA	1.25 kV	315 A		1 TE	2591650000
VPU AC II 1 R 150/50	1-pole, pluggable	150 V	20 kA	50 kA	1.25 kV	315 A	1 CO	1 TE	2591660000
VPU AC II 2 150/50	2-pole, pluggable	150 V	20 kA	50 kA	1.25 kV	315 A		2 TE	2591670000
VPU AC II 2 R 150/50	2-pole, pluggable	150 V	20 kA	50 kA	1.25 kV	315 A	1 CO	2 TE	2591680000
VPU AC II 3 150/50	3-pole, pluggable	150 V	20 kA	50 kA	1.25 kV	315 A		3 TE	2591690000
VPU AC II 3 R 150/50	3-pole, pluggable	150 V	20 kA	50 kA	1.25 kV	315 A	1 CO	3 TE	2591700000
VPU AC II 4 150/50	4-pole, pluggable	150 V	20 kA	50 kA	1.25 kV	315 A		4 TE	2591710000
VPU AC II 4 R 150/50	4-pole, pluggable	150 V	20 kA	50 kA	1.25 kV	315 A	1 CO	4 TE	2591000000
Type II - 300 V / 50 kA									
VPU AC II 1 300/50	1-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A		1 TE	2591020000
VPU AC II 1 R 300/50	1-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A	1 CO	1 TE	2591030000
VPU AC II 1+1 300/50	2-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A		2 TE	2591060000
VPU AC II 1+1 R 300/50	2-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A	1 CO	2 TE	2591070000
VPU AC II 2 300/50	2-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A		2 TE	2591040000
VPU AC II 2 R 300/50	2-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A	1 CO	2 TE	2591050000
VPU AC II 3 300/50	3-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A		3 TE	2591160000
VPU AC II 3 R 300/50	3-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A	1 CO	3 TE	2591170000
VPU AC II 3+1 300/50	4-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A		4 TE	2591080000
VPU AC II 3+1 R 300/50	4-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A	1 CO	4 TE	2591090000
VPU AC II 4 300/50	4-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A		4 TE	2591140000
VPU AC II 4 R 300/50	4-pole, pluggable	300 V	20 kA	50 kA	1.5 kV	315 A	1 CO	4 TE	2591150000
Type II - 300 V / 50 kA (Status indicator red, yellow, green)									
VPU AC II 1 R 300/50 Y	1-pole, pluggable	300 V	20 kA	50 kA	1.3 kV	160 A	1 CO	1 TE	2639350000
VPU AC II 1+1 R 300/50 Y	2-pole, pluggable	300 V	20 kA	50 kA	1.3 kV	160 A	1 CO	2 TE	2639340000
VPU AC II 2 R 300/50 Y	2-pole, pluggable	300 V	20 kA	50 kA	1.3 kV	160 A	1 CO	2 TE	2639360000
VPU AC II 3 R 300/50 Y	3-pole, pluggable	300 V	20 kA	50 kA	1.3 kV	160 A	1 CO	3 TE	2639330000
VPU AC II 3+1 R 300/50 Y	4-pole, pluggable	300 V	20 kA	50 kA	1.3 kV	160 A	1 CO	4 TE	2639320000
VPU AC II 4 R 300/50 Y	4-pole, pluggable	300 V	20 kA	50 kA	1.3 kV	160 A	1 CO	4 TE	2639370000
Type II - 350 V / 50 kA									
VPU AC II 1 350/50	1-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A		1 TE	2591350000
VPU AC II 1 R 350/50	1-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A	1 CO	1 TE	2591360000
VPU AC II 1+1 350/50	2-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A		2 TE	2637030000
VPU AC II 1+1 R 350/50	2-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A	1 CO	2 TE	2637040000
VPU AC II 2 350/50	2-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A		2 TE	2637010000
VPU AC II 2 R 350/50	2-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A	1 CO	2 TE	2637020000
VPU AC II 3 350/50	3-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A		3 TE	2591100000
VPU AC II 3 R 350/50	3-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A	1 CO	3 TE	2591110000
VPU AC II 3+1 350/50	4-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A		4 TE	2637050000
VPU AC II 3+1 R 350/50	4-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A	1 CO	4 TE	2637060000
VPU AC II 4 350/50	4-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A		4 TE	2591120000
VPU AC II 4 R 350/50	4-pole, pluggable	350 V	20 kA	50 kA	1.75 kV	315 A	1 CO	4 TE	2591130000
Type II - 480 V / 50 kA									
VPU AC II 1 480/50	1-pole, pluggable	480 V	20 kA	50 kA	2.3 kV	315 A		1 TE	2591210000
VPU AC II 1 R 480/50	1-pole, pluggable	480 V	20 kA	50 kA	2.3 kV	315 A	1 CO	1 TE	2591220000
VPU AC II 2 480/50	2-pole, pluggable	480 V	20 kA	50 kA	2.3 kV	315 A		2 TE	2591230000
VPU AC II 2 R 480/50	2-pole, pluggable	480 V	20 kA	50 kA	2.3 kV	315 A	1 CO	2 TE	2591240000
VPU AC II 3 480/50	3-pole, pluggable	480 V	20 kA	50 kA	2.3 kV	315 A		3 TE	2591250000
VPU AC II 3 R 480/50	3-pole, pluggable	480 V	20 kA	50 kA	2.3 kV	315 A	1 CO	3 TE	2591260000
VPU AC II 4 480/50	4-pole, pluggable	480 V	20 kA	50 kA	2.3 kV	315 A		4 TE	2591270000
VPU AC II 4 R 480/50	4-pole, pluggable	480 V	20 kA	50 kA	2.3 kV	315 A	1 CO	4 TE	2591280000



Type II

Product	Version	Rated voltage	Discharge current I_n (8/20μs)	Discharge current I_{max} (8/20μs)	Protection level U_p	Max. backup fuse	Signalling contact	Overall width	Order No.
		U_c (AC)							
Typ II - 750 V / 35 kA									
VPU AC II 1 R 750/35	1-pole, pluggable	750 V	20 kA	35 kA	3.4 kV	315 A	1 CO	1 TE	2591300000
VPU AC II 2 R 750/35	2-pole, pluggable	750 V	20 kA	35 kA	3.4 kV	315 A	1 CO	2 TE	2591310000
VPU AC II 3 R 750/35	3-pole, pluggable	750 V	20 kA	35 kA	3.4 kV	315 A	1 CO	3 TE	2591320000
Typ II - 1000 V / 40 kA									
VPU II 1 1000V/40kA AC	1-pole, pluggable	1000 V	20 kA	40 kA	3.8 kV	125 A		1 TE	1473440000
Typ II - N-PE									
VPU AC II 1 N-PE 305/65	1-pole, pluggable	305 V	40 kA	65 kA	1.5 kV	-		1 TE	2591180000

Product quick selection, power supply

Type III

Product	Version	Rated voltage	Discharge capacity	Protection level	Follow current suppression capability	blow-out/ encapsulated	Max. backup fuse	Signalling contact	Overall width	Order No.
		U _c	I _{max} (8/20)	typ.	I _{fi}		A gl/gG			
Type III - TS 35										
VPU III R 12V/4kV AC/DC	1-pole, separable	20 V	2 kA	980 V	no follow current	encapsulated	16 A	1 CO	1 TE	1351550000
VPU III R 24V/4kV AC/DC	1-pole, separable	32 V	2 kA	890 V	no follow current	encapsulated	16 A	1 CO	1 TE	1351580000
VPU III R 48V/4kV AC/DC	1-pole, separable	50 V	2 kA	950 V	no follow current	encapsulated	16 A	1 CO	1 TE	1351600000
VPU III R 120V/6kV AC/DC	1-pole, separable	150 V	3 kA	1750 V	no follow current	encapsulated	16 A	1 CO	1 TE	1351630000
VPU III R 230V/6kV AC	1-pole, separable	300 V	3 kA	1800 V	no follow current	encapsulated	16 A	1 CO	1 TE	1351650000
VPU III 3/280V AC	3-pole	275 V	3 kA	1800 V	no follow current	encapsulated	16 A	1 NC	3 TE	1393050000
Type III - SO LD										
VPU III SO LD	1-pole	275 V	1,5 kA	1500 V	no follow current	encapsulated	16 A			1351680000
VPU III SO LD+A	1-pole	275 V	1,5 kA	1500 V	no follow current	encapsulated	16 A			1351700000



Product quick selection, power supply



Lightning and surge protection for photovoltaic systems

Product	Version	Rated voltage	Lightning test current	Discharge current	Protection level	Short-circuit resistance	Operating altitude up to	Signalling contact	Overall width	Order No.
		U_c (DC)	I_{imp} (10/350µs)	I_{max} (8/20µs)	U_p	I_{SCPV}				
Type I + II										
VPU PV I+II 3 1000	3-pole, pluggable	1000 V	6.25 kA	40 kA	3.8 kV	11 kA	4000 m		3 TE	2530610000
VPU PV I+II 3 R 1000	3-pole, pluggable	1000 V	6.25 kA	40 kA	3.8 kV	11 kA	4000 m	1 CO	3 TE	2530620000
VPU PV I+II 3 1500	3-pole, pluggable	1500 V	5 kA	30 kA	5.0 kV	11 kA	4000 m		3 TE	2530580000
VPU PV I+II 3 R 1500	3-pole, pluggable	1500 V	5 kA	30 kA	5.0 kV	11 kA	4000 m	1 CO	3 TE	2530590000
Type II										
VPU II 2 PV 600V DC	2-pole, pluggable	600 V	-	40 kA	2.2 kV	200 A	2000 m		2 TE	1351340000
VPU II 2 R PV 600V DC	2-pole, pluggable	600 V	-	40 kA	2.2 kV	200 A	2000 m	1 CO	2 TE	1351370000
VPU II PV 3 1000	3-pole, pluggable	1100 V	-	40 kA	3.8 kV	11 kA	4000 m		3 TE	2530550000
VPU II PV 3 R 1000	3-pole, pluggable	1100 V	-	40 kA	3.8 kV	11 kA	4000 m	1 CO	3 TE	2530180000
VPU II PV 3 1500	3-pole, pluggable	1500 V	-	30 kA	5.0 kV	11 kA	4000 m		3 TE	2530640000
VPU II PV 3 R 1500	3-pole, pluggable	1500 V	-	30 kA	5.0 kV	11 kA	4000 m	1 CO	3 TE	2530650000

VPU I lightning and surge protection

Maximum type I protection from lightning and surges

The current product and application standards underline the importance of reliable overvoltage protection. The combined lightning and overvoltage devices VARITECTOR PU I protect your systems from lightning and overvoltage in accordance with Type I and Type II specifications. A combination of varistor and spark gap technology (GDT) ensures the highest level of protection and, if necessary, ensures zero-leakage current for pre-meter applications.

The VPU I series offers products for mains voltages 230 / 400 V and 400 / 690 V with lightning currents of 12.5 kA or 25 kA.

For main fuses up to 250 A (for 25 kA variants) and up to 315 A (for 12.5 kA variants), no additional back-up fuse is required in front of the VPU I.



Global applicable

Certification in accordance with international IEC/EN standards and the latest UL 1449 Ed. 4 standard guarantees universal use in any application.

Faster to assemble

The optimised mounting rail clip enables easy and quick assembly and removal, without the need for tools.





Rapid status messaging

The remote signaling contact with PUSH IN connection can be quickly connected and provides reliable information on the status of the protective function.



Best overview

The large, central, status window provides highly visible information on the status of the protective function.



Securely locked

The arresters in narrow 1TE design are secured in the socket with the aid of a locking clip. This ensures maximum vibration resistance, ensuring that for example the high requirements of the wind turbine manufacturers are met.



Lightning and surge protection

Type I / type II lightning and surge protection

Weidmüller's VPU I series offers combined lightning and surge protection (type I / type II) featuring varistor technology with a leakage current capacity of 12.5 kA to 35 kA (10/350 µs). The pluggable, self-monitoring surgevoltage arresters of up to 35 kA are optionally available as 1-, 2-, 3- or 4-pole versions – with or without a remote signalling contact.

The advantages for you:

- Remote signalling function
- Suitable for various types of mains voltages (TN/TT)
- Tested in compliance with IEC 61643-11 and EN 61643-11
- Convenient installation in sub-distribution boards and electrical cabinets
- Designed for use in buildings according to lightning protective level III/IV for 12.5 kA and I/II for 25 kA
- Very low residual voltage, thus also suitable as Typ II / Typ III surge protection

Lightning conductors with spark gap for lightning protection or equipotential bonding providing Surge protection type I


According to the requirements of type I (DIN VDE 0675 part 6) and type I according to IEC 61643-11, the lightning arrester serves as lightning equipotential bonding at the transition from protection zone LPZ 0 to LPZ 1 (according to IEC 1312-1). In combination with several lightning arresters, surge protection is used in the mains forms TN, TT and IT. During lightning strikes, the triggered sparkover gaps are used to establish the required equipotential bonding between the building's surge protection and the power supplier's earthing system.

VPU I LCF

Lightning and surge protection for installation before the electric meter in the highest lightning protection level (LPL)

The VPU I LCF family of leakage current free lightning and surge protectors for power are installed before the meter. The arrester protects low-voltage consumers and electronic devices from the direct influences of lightning and surge couplings.

VPU I LCF is approved as type I / type II according to the valid IEC/EN 61643-11.





Electrical connection for building installation

The type 1 VPU I series lightning arrester is connected between the external conductors (L1, L2, L3) and N/PE. The N/PE spark gap is produced with the VPU I LCF N-PE 50 kA or 100 kA. Cables as short as possible should be used. The maximum permissible operating voltage U_c is 480 V AC. Decoupling to downstream type II arresters is not necessary. Please note the installation instructions.

Energy co-ordination


All lightning and surge protection products of the VARITECTOR series are energetically coordinated with each other. No additional downstream components are required for decoupling.

Checking operation, maintenance and approvals



All arresters based on varistor technology have large status windows. If the status window is red, the corresponding arrester must be changed.

Dimensional drawing VPU I

Width: 17.5 mm (1 x TE)



Dimensional drawing VPU AC I




Type I and II lightning arrester

Type I and II lightning arrester

- No-leakage-current version suitable for use upstream of the electrical meter
- Suitable with 35 kA (10/350 µs) for protective level I, II, III and IV (LPL I/II/III/IV)
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used as Type II surge protection


VPU I 1/R LCF 280 V / 35 kA

1-phase



VPU I 1/R LCF 400 V / 35 kA

1-phase



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current I_{imp} (10/350 µs) (L-PE)
Discharge current I_a (8/20µs) wire-PE
Discharge current I_{max} (8/20µs) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_{imp} (L/N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature
Connection according to IEC 947-7-1
Solid
Stranded
Stripping length
Tightening torque
Approvals
Approvals
Standards

230 V
280 V
35 kA
25 kA
100 kA
T1, T2
25 kA
1 µA
100 A
315 A gl
440 V
≤ 1.8 kV
≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
black
-40 °C...70 °C
-40 °C...80 °C
4...16 mm²
2.5...50 mm²
15 mm
2...3 Nm
CE; EAC
IEC61643-11, EN61643-11

400 V
400 V
35 kA
25 kA
100 kA
T1, T2
25 kA
1 µA
100 A
315 A gl
440 V
≤ 2.5 kV
≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
black
-40 °C...70 °C
-40 °C...80 °C
4...16 mm²
2.5...50 mm²
15 mm
2...3 Nm
CE; EAC
IEC61643-11, EN61643-11

Dimensions / Signalling contact info	
Clamping range (nominal / min. / max.)	mm²
Height x width x depth	mm
Signalling contact	
Note	

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
94 / 71.2 / 69	106 / 71.2 / 69
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
94 / 71.2 / 69	106 / 71.2 / 69
No	250 V 1A 1CO

Ordering data

	without remote signalling contact
	with remote signalling contact (R)

Type	Qty.	Order No.
VPU I 1 LCF 280V/35KA	1	1351350000
VPU I 1 R LCF 280V/35KA	1	1351330000

Type	Qty.	Order No.
VPU I 1 LCF 400V/35KA	1	1351400000
VPU I 1 R LCF 400V/35KA	1	1351380000

Note

Accessories


Note

Type I and II lightning arrester

- No-leakage-current version suitable for use upstream of the electrical meter
- Pluggable arrester
- Suitable with 25 kA (10/350 μ s) for protection levels I, II, III and IV (LPL I/II/III/IV)
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used for Type II surge protection


VPU I 3/R LCF 280 V / 25 kA

TN-C



VPU I 4/R LCF 280 V / 25 kA

TN-S



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_a (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature
Connection according to IEC 947-7-1
Solid
Stranded
Stripping length
Tightening torque
Approvals
Approvals
Standards

230 V
280 V
25 kA
25 kA
100 kA
T1, T2
25 kA
1 μ A
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.6 kV
≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 6 TE, Insta IP 20
black, orange
-40 °C...70 °C
-40 °C...80 °C
4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm
CE; EAC; OEVE
IEC61643-11, EN61643-11

230 V
280 V
25 kA
25 kA
100 kA
T1, T2
25 kA
1 μ A
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.6 kV
≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 8 TE, Insta IP 20
black, orange
-40 °C...70 °C
-40 °C...80 °C
4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm
CE; EAC; OEVE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info	
Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	
Note	

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
94 / 106.8 / 69	106 / 106.8 / 69
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 142.4 / 69	106 / 142.4 / 69
No	250 V 1A 1CO

Ordering data

without remote signalling contact
with remote signalling contact (R)

Type	Qty.	Order No.
VPU I 3 LCF 280V/25KA	1	1351690000
VPU I 3 R LCF 280V/25KA	1	1351670000

Type	Qty.	Order No.
VPU I 4 LCF 280V/25KA	1	1351730000
VPU I 4 R LCF 280V/25KA	1	1351720000

Note

Accessories

Note

Pluggable spare arrester VPU I 0 LCF 280 V/25 kA-1351540000

Pluggable spare arrester VPU I 0 LCF 280 V/25 kA-1351540000




Type I and II lightning arrester

Type I and II lightning arrester

- No-leakage-current version suitable for use upstream of the electrical meter
- Pluggable arrester
- Suitable with 25 kA (10/350 μ s) for protection levels I, II, III and IV (LPL I/II/III/IV)
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used for Type II surge protection


VPU I 3+1/R LCF 280 V / 25 kA

TN-S, TT



VPU I 1+1/R LCF 280 V / 25 kA

Single-phase



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_n (8/20 μ s) N-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Protection level U_p at I_n (N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

230 V
280 V
260 V
25 kA
100 kA
25 kA
100 kA
100 kA
100 kA
100 kA
T1, T2
25 kA
1 μ A
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.6 kV
≤ 1.6 kV
≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing: 8 TE, Insta IP 20
black, orange, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC; OEVE
IEC61643-11, EN61643-11

230 V
280 V
260 V
25 kA
100 kA
25 kA
100 kA
100 kA
100 kA
100 kA
T1, T2
25 kA
1 μ A
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.6 kV
≤ 1.6 kV
≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing: 4TE, Insta IP 20
black, orange, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC; OEVE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

	without remote signalling contact
	with remote signalling contact (R)

Note

Accessories

Note

no remote sig. contact with remote signalling (R)

16 / 4 / 35	16 / 4 / 35
94 / 142.4 / 69	106 / 142.4 / 69
No	250 V 1A 1C0

no remote sig. contact with remote signalling (R)

16 / 4 / 35	16 / 4 / 35
94 / 71.2 / 69	106 / 71.2 / 69
No	250 V 1A 1C0

Type	Qty.	Order No.
VPU I 3+1 LCF 280V/25KA	1	1351780000
VPU I 3+1 R LCF 280V/25KA	1	1351770000

Type	Qty.	Order No.
VPU I 1+1 LCF 280V/25KA	1	1351750000
VPU I 1+1 R LCF 280V/25KA	1	1351740000

Pluggable spare arrester L-N VPU I 0 LCF 280V/25kA-1351540000;
N-PE VPU I 0 N-PE 260V/100KA-1351940000


Pluggable spare arrester L-N VPU I 0 LCF 280 V/25 kA-1351540000;
N-PE VPU I 0 N-PE 260 V/100 kA-1351940000

Type I and II lightning arrester

- No-leakage-current version suitable for use upstream of the electrical meter
- Pluggable arrester
- Suitable with 25 kA (10/350 µs) for protection levels I, II, III and IV (LPL I/II/III/IV)
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used for Type II surge protection


VPU I 2/R LCF 280 V / 25 kA

1-phase



VPU I 1/R LCF 280 V / 25 kA

1-phase



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current I_{imp} (10/350 µs) (L-PE)
Discharge current I_a (8/20µs) wire-PE
Discharge current I_{max} (8/20µs) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_{in} (L/N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature
Connection according to IEC 947-7-1
Solid
Stranded
Stripping length
Tightening torque
Approvals
Approvals
Standards

230 V
280 V
25 kA
25 kA
100 kA
T1, T2
25 kA
1 µA
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.6 kV
≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
black, orange
-40 °C...70 °C
-40 °C...80 °C
4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm
CE; EAC; OEVE
IEC61643-11, EN61643-11

230 V
280 V
25 kA
25 kA
100 kA
T1, T2
25 kA
1 µA
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.6 kV
≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
black, orange
-40 °C...70 °C
-40 °C...80 °C
4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm
CE; EAC; OEVE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	
Note	

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
94 / 71.2 / 69	106 / 71.2 / 69
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
94 / 35.6 / 69	106 / 35.6 / 69
No	250 V 1A 1CO

Ordering data

without remote signalling contact
with remote signalling contact (R)

Type	Qty.	Order No.
VPU I 2 LCF 280V/25KA	1	1351640000
VPU I 2 R LCF 280V/25KA	1	1351620000

Type	Qty.	Order No.
VPU I 1 LCF 280V/25KA	1	1351590000
VPU I 1 R LCF 280V/25KA	1	1351570000

Note

Accessories

Note

Pluggable spare arrester VPU I 0 LCF 280 V/25 kA-1351540000

Pluggable spare arrester VPU I 0 LCF 280 V/25 kA-1351540000




Type I and II lightning arrester


Type I and II lightning arresters

- Pluggable arrester
- Suitable with 25 kA (10/350 μ s) for protective level I, II, III and IV (LPL I/II/III/IV)
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used as Type II surge protection
- Field of application downstream of the main electrical meter

VPU I 3/R 280 V / 25 kA



VPU I 4/R 280 V / 25 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature
Connection according to IEC 947-7-1
Solid
Stranded
Stripping length
Tightening torque
Approvals
Approvals
Standards

230 V
280 V
25 kA
25 kA
100 kA
T1, T2
25 kA
100 μ A
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.4 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 6 TE, Insta IP 20
black, orange
-40 °C...70 °C
-40 °C...80 °C
4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm
CE
IEC61643-11, EN61643-11

230 V
280 V
25 kA
25 kA
100 kA
T1, T2
25 kA
100 μ A
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.4 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 8 TE, Insta IP 20
black, orange
-40 °C...70 °C
-40 °C...80 °C
4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm
CE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info	
Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	
Note	

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
94 / 106.8 / 69	106 / 106.8 / 69
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
94 / 142.4 / 69	106 / 142.4 / 69
No	250 V 1A 1CO

Ordering data

	without remote signalling contact
	with remote signalling contact (R)

Type	Qty.	Order No.
VPU I 3 280V/25KA	1	2062940000
VPU I 3 R 280V/25KA	1	2062910000

Type	Qty.	Order No.
VPU I 4 280V/25KA	1	2062960000
VPU I 4 R 280V/25KA	1	2062950000

Note

Accessories

Note


Pluggable spare arrester VPU I 0 280 V/25 kA-2067650000

Pluggable spare arrester VPU I 0 280 V/25 kA-2067650000


Type I and II lightning arresters

- Pluggable arrester
- Suitable with 25 kA (10/350 μ s) for protective level I, II, III and IV (LPL I/II/III/IV)
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used as Type II surge protection
- Field of application downstream of the main electrical meter

VPU I 3+1/R 280 V / 25 kA



VPU I 1+1/R 280 V / 25 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_n (8/20 μ s) N-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Protection level U_p at I_n (N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

230 V
280 V
260 V
25 kA
100 kA
25 kA
100 kA
100 kA
100 kA
100 kA
T1, T2
25 kA
100 μ A
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.4 kV
≤ 1.6 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing: 8 TE, Insta IP 20
black, orange, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE
IEC61643-11, EN61643-11

230 V
280 V
260 V
25 kA
100 kA
25 kA
100 kA
100 kA
100 kA
100 kA
T1, T2
25 kA
100 μ A
100 A
250 A gL (if back up fuse > 250 A)
438 V
≤ 1.4 kV
≤ 1.6 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing: 4TE, Insta IP 20
black, orange, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

Accessories

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 25	16 / 4 / 25
94 / 142.4 / 69	106 / 142.4 / 69
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU I 3+1 280V/25KA	1	2063080000
VPU I 3+1 R 280V/25KA	1	2063070000

Pluggable spare arrester VPU I 0 280 V/25 kA-2067650000; VPU I 0 N-PE 260 V/100 kA-1351940000
--

no remote sig. contact	with remote signalling (R)
16 / 4 / 25	16 / 4 / 25
94 / 71.2 / 69	106 / 71.2 / 69
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU I 1+1 280V/25KA	1	2063060000
VPU I 1+1 R 280V/25KA	1	2063040000

Pluggable spare arrester VPU I 0 280 V/25 kA-2067650000; VPU I 0 N-PE 260 V/100 kA-1351940000
--




Type I and II lightning arrester

Type I and II lightning arrester

- Suitable with 25 kA (10/350 μ s) for protection levels I, II, III and IV (LPL I/II/III/IV)
- Pluggable arrester
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used for Type II surge protection
- Field of application: downstream of the main electrical meter


VPU I 3/R 400 V / 25 kA

TN-C



VPU I 1/R 400 V / 25 kA

1-phase



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

400 V
400 V
25 kA
25 kA
100 kA
T1, T2
25 kA
100 μ A
100 A
250 A gL (if back up fuse > 250 A)
620 V
 ≤ 1.9 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 6 TE, Insta IP 20
black, orange
-40 $^{\circ}$ C...70 $^{\circ}$ C
-40 $^{\circ}$ C...80 $^{\circ}$ C

4...16 mm²
2.5...50 mm²
15 mm
2...3 Nm

CE; EAC; OEVE
IEC61643-11, EN61643-11

400 V
400 V
25 kA
25 kA
100 kA
T1, T2
25 kA
100 μ A
100 A
250 A gL (if back up fuse > 250 A)
620 V
 ≤ 1.9 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
black, orange
-40 $^{\circ}$ C...70 $^{\circ}$ C
-40 $^{\circ}$ C...80 $^{\circ}$ C

4...16 mm²
2.5...50 mm²
15 mm
2...3 Nm

CE; EAC; OEVE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

no remote sig. contact with remote signalling (R)

16 / 4 / 35 16 / 4 / 35
94 / 106.8 / 69 106 / 106.8 / 69
No 250 V 1A 1CO

no remote sig. contact with remote signalling (R)

16 / 4 / 35 16 / 4 / 35
94 / 35.6 / 69 106 / 35.6 / 69
No 250 V 1A 1CO

Ordering data

without remote signalling contact
with remote signalling contact (R)

Type	Qty.	Order No.
VPU I 3 400V/25KA	1	1351870000
VPU I 3 R 400V/25KA	1	1351850000

Type	Qty.	Order No.
VPU I 1 400V/25KA	1	1351820000
VPU I 1 R 400V/25KA	1	1351800000

Note

Accessories

Note

Pluggable spare arrester VPU I 0 400 V/25 kA-1351790000

Pluggable spare arrester VPU I 0 400 V/25 kA-1351790000




Type I and II lightning arresters

- Suitable with 25 kA (10/350 µs) for protection levels I, II, III and IV (LPL I/II/III/IV)
- Pluggable arrester
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used for Type II surge protection
- Field of application: downstream of the main electrical meter

VPU I 4/R 400V / 25kA

TN-S, TN C-S



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current I_{imp} (10/350 µs) (L-PE)
Discharge current I_a (8/20µs) wire-PE
Discharge current I_{max} (8/20µs) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

400 V
400 V
25 kA
25 kA
100 kA
T1, T2
25 kA
100 µA
100 A
250 A gL (if back up fuse > 250 A)
620 V
≤ 1.9 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 8 TE, Insta IP 20
black, orange
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
106 / 142.4 / 69	106 / 142.4 / 69
No	250 V 1A 1C0

Type	Qty.	Order No.
VPU I 4 400V/25KA	1	1438010000
VPU I 4 R 400V/25KA	1	1438020000

Accessories

Note

Replacement arrester VPU I 0 400 V/25 kA-1351790000 for plug-in




Type I and II lightning arrester

Type I and II lightning arresters

- Suitable with 25 kA (10/350 μ s) for protection levels I, II, III and IV (LPL I/II/III/IV)
- Pluggable arrester
- Tested according to IEC 61643-11 for Type I and II surge protection
- Can also be used for Type II surge protection
- Field of application: downstream of the main electrical meter


VPU I 3+1/R 400 V / 25 kA

TN-S, TT, IT



VPU I 1+1/R 400 V / 25 kA

1-phase



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_n (8/20 μ s) N-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Protection level U_p at I_n (N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

400 V
400 V
440 V
25 kA
100 kA
25 kA
100 kA
100 kA
100 kA
T1, T2
25 kA
100 μ A
100 A
250 A gL (if back up fuse > 250 A)
620 V
≤ 1.9 kV
≤ 3 kV
≤ 25 ns, ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing: 8 TE, Insta IP 20
black, orange, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC; OEVE
IEC61643-11, EN61643-11

400 V
400 V
440 V
25 kA
100 kA
25 kA
100 kA
100 kA
100 kA
T1, T2
25 kA
100 μ A
100 A
250 A gL (if back up fuse > 250 A)
620 V
≤ 1.9 kV
≤ 3 kV
≤ 25 ns, ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing: 4TE, Insta IP 20
black, orange, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC; OEVE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

no remote sig. contact with remote signalling (R)

16 / 4 / 25	16 / 4 / 25
94 / 142.4 / 69	106 / 142.4 / 69
No	250 V 1A 1CO

no remote sig. contact with remote signalling (R)

16 / 4 / 25	16 / 4 / 25
94 / 71.2 / 69	106 / 71.2 / 69
No	250 V 1A 1CO

Accessories

Note

Pluggable spare arrester L-N VPU I 0 280 V/25 kA-1351790000,
N-PE VPU I 0 440 V/100 kA-1351990000

Pluggable spare arrester L-N VPU I 0 280 V/25 kA-1351790000,
N-PE VPU I 0 N-PE 440 V/100 kA-1351990000

Type I and II lightning arrester


N-PE path

Suitable for 230/400 V mains systems

- Pluggable arrester
- High energy absorption with short time to sparkover
- Installation in distribution board


VPU I 1 N-PE 260 V / 50 kA

N-PE arrester 260 V



VPU I 1 N-PE 260 V / 100 kA

N-PE arrester 260 V



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (N-PE)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Discharge current I_n (8/20 μ s) N-PE
Discharge current I_{max} (8/20 μ s) N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Protection level U_p at I_n (N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

230 V
260 V
50 kA
50 kA
100 kA
T1, T2

0 μ A
Not required
1200 V

≤ 1.5 kV
≤ 100 ns
No

Installation housing: 1TE, Insta IP 20
black, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC; OEVE
IEC61643-11, EN61643-11

230 V
260 V
100 kA
100 kA
100 kA
T1, T2

0 μ A
Not required
1200 V

≤ 1.6 kV
≤ 100 ns
No

Installation housing: 2TE, Insta IP 20
black, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC; OEVE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

no remote sig. contact

16 / 4 / 35
94 / 17.8 / 69
No

no remote sig. contact

16 / 4 / 35
94 / 35.6 / 69
No

Ordering data

without remote signalling contact

Type	Qty.	Order No.
VPU I 1 N-PE 260V/50KA	1	1351900000

Type	Qty.	Order No.
VPU I 1 N-PE 260V/100KA	1	1351920000

Note

Accessories

Note

Pluggable spare arrester VPU I 0 N-PE 260 V/50 kA-1351930000

Pluggable spare arrester N-PE VPU AC II 0 N-PE 260/100kA 1351940000






Type I and II lightning arrester

- Pluggable arrester
- Suitable with 50 kA for LPL III/IV
- Suitable with 100 kA for LPL III/IV LPL I/II/III/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I N-PE 305 V / 50 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (N-PE)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Discharge current I_n (8/20 μ s) N-PE
Discharge current I_{max} (8/20 μ s) N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
 I_n
Category

230 V
305 V
50 kA
50 kA
100 kA
T1, T2
0.1 kA
1 μ A
Not required
1200 V
 ≤ 1.5 kV
 ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing: 1TE, Insta IP 20
blue, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²
15 mm
2...4.5 Nm

CE: cURus; VDE
IEC61643-11, EN61643-11

0 V
1200 V
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

no remote sig. contact

16 / 4 / 35
90 / 18 / 93
No

Ordering data

without remote signalling contact

Type	Qty.	Order No.
VPU AC I 1 N-PE 305/50	1	2591570000

Note

Accessories

Note

Pluggable spare arrester N-PE VPU AC II 0 N-PE 305/50 2591590000

Type I and II lightning arrester


N-PE path

Suitable for 400/690 V mains systems

- Tested according to IEC 61643-11 as Type I and Type II
- Pluggable arrester
- High energy absorption with short response time
- Installation in distribution board


VPU I 1 N-PE 440 V / 50 kA

N-PE arrester 440 V



VPU I 1 N-PE 440 V / 100 kA

N-PE arrester 440 V



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (N-PE)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Discharge current I_n (8/20 μ s) N-PE
Discharge current I_{max} (8/20 μ s) N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Protection level U_p at I_n (N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

400 V
440 V
50 kA
50 kA
100 kA
T1, T2

0 μ A
Not required
1200 V

≤ 2.7 kV
≤ 100 ns
No

Installation housing; 1TE, Insta IP 20
black, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC
IEC61643-11, EN61643-11

400 V
440 V
100 kA
100 kA
100 kA
T1, T2

0 μ A
Not required
1200 V

≤ 3 kV
≤ 100 ns
No

Installation housing; 2TE, Insta IP 20
black, blue
-40 °C...70 °C
-40 °C...80 °C

4...16 mm ²
2.5...50 mm ²
15 mm
2...3 Nm

CE; EAC
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

no remote sig. contact

16 / 4 / 35
94 / 17.8 / 69
No

no remote sig. contact

16 / 4 / 35
94 / 35.6 / 69
No

Ordering data

without remote signalling contact

Type	Qty.	Order No.
VPU I 1 N-PE 440V/50kA	1	1351950000

Type	Qty.	Order No.
VPU I 1 N-PE 440V/100kA	1	1351970000

Note

Accessories

Note

Pluggable spare arrester N-PE VPU I 0 N-PE 440/50kA 1351980000

Pluggable spare arrester N-PE VPU I 0 N-PE 440/100kA 1351990000




Type I and II lightning arresters


Type I and II lightning arresters for 230/400 V system with LPL III / IV

- Back-up fuse not necessary up to 315 A
- Pluggable arrester
- Suitable with 12.5 kA for LPL III/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU I AC 1+1/R 300/12.5 LCF



VPU I AC 1+1/R 300/12.5 LCF



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scor}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
MCOV (L/N-PE)
 I_n
Category

230 V
300 V

12.5 kA
20 kA
65 kA
T1, T2
50 kA
1 μ A
250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
442 V
 ≤ 1.5 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 1TE, Insta IP 20
orange, black
-40 °C...70 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V
300 Vac
20 kA
SPD TYPE 4CA

230 V
300 V
50 kA
12.5 kA
20 kA
65 kA
T1, T2
50 kA
1 μ A
250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
442 V
 ≤ 1.5 kV
 ≤ 25 ns, ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
orange, black, blue
-40 °C...70 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V
300 Vac
20 kA
SPD TYPE 4CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

Accessories

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 18 / 93	106 / 18 / 93
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 36 / 93	106 / 36 / 93
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 1 300/12.5 LCF	1	2636950000
VPU AC I 1 R 300/12.5 LCF	1	2636960000

Type	Qty.	Order No.
VPU AC I 1+1 300/12.5 LCF	1	2636930000
VPU AC I 1+1 R 300/12.5 LCF	1	2636940000


Pluggable spare arrester L-N VPU AC I 0 300/12.5 LCF 263900000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 LCF 263900000,
N-PE VPU I 0 N-PE 260V/50KA LCF 2668450000


Type I and II lightning arresters for 230/400 V system with LPL III / IV

- Back-up fuse not necessary up to 315 A
- Pluggable arrester
- Suitable with 12.5 kA for LPL III/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU I AC 1+3/R 300/12.5 LCF



VPU I AC 3+1/R 300/12.5 LCF



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scorr}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
MCOV (L/N-PE)
 I_n
Category

230 V
300 V

12.5 kA
20 kA
65 kA
T1, T2
50 kA
1 μ A
250 gG @50 kA I_{scorr} , 315 gG @25 kA I_{scorr}
442 V
 ≤ 1.5 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 3TE, Insta IP 20
orange, black
-40 °C...70 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²

15 mm

2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V
300 Vac
20 kA
SPD TYPE 4CA

230 V
300 V
50 kA
12.5 kA
20 kA
65 kA
T1, T2
50 kA
1 μ A
250 gG @50 kA I_{scorr} , 315 gG @25 kA I_{scorr}
442 V
 ≤ 1.5 kV
 ≤ 25 ns, ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
orange, black, blue
-40 °C...70 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²

15 mm

2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V
300 Vac
20 kA
SPD TYPE 4CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

Accessories

Note

no remote sig. contact with remote signalling (R)

16 / 4 / 35 16 / 4 / 35
90 / 52 / 93 106 / 52 / 93
No 250 V 1A 1CO

no remote sig. contact with remote signalling (R)

16 / 4 / 35 16 / 4 / 35
90 / 76 / 93 106 / 76 / 93
No 250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 3 300/12.5 LCF	1	2636970000
VPU AC I 3 R 300/12.5 LCF	1	2636980000

Type	Qty.	Order No.
VPU AC I 3+1 300/12.5 LCF	1	2636910000
VPU AC I 3+1 R 300/12.5 LCF	1	2636920000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 LCF 263900000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 LCF 263900000




Type I and II lightning arrester


Type I and II lightning arresters for 230 /400 V system with LPL III / IV

- Back-up fuse not necessary up to 315 A
- Pluggable arrester
- Suitable with 12.5 kA for LPL III/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I/R 3 300 V / 12.5 kA



VPU AC I/R 3+1 300 V / 12.5 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scor}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
 I_n
Category

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

Accessories

Note

230 V
300 V

12.5 kA
20 kA
50 kA
T1, T2
50 kA
0.6 mA
250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
337 V
 ≤ 1.5 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 3TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²

15 mm

2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V

900 V

150 kA

20 kA

SPD TYPE 1CA

no remote sig. contact

16 / 4 / 35

90 / 54 / 93

No

with remote signalling (R)

16 / 4 / 35

106 / 54 / 93

250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 3 300/12.5	1	2591440000
VPU AC I 3 R 300/12.5	1	2591450000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 2591370000

230 V
300 V
50 kA
12.5 kA
20 kA
50 kA
T1, T2
50 kA
1 μ A
250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
337 V
 ≤ 1.5 kV
 ≤ 25 ns, ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
black, orange, blue
-40 °C...85 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²

15 mm

2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V

900 V

1200 V

150 kA

20 kA

SPD TYPE 1CA

no remote sig. contact

16 / 4 / 35

90 / 76 / 93

No

with remote signalling (R)

16 / 4 / 35

106 / 76 / 93

250 V 1A 1CO


Type	Qty.	Order No.
VPU AC I 3+1 300/12.5	1	2591460000
VPU AC I 3+1 R 300/12.5	1	2591470000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 2591370000, N-PE VPU AC I 1 N-PE 305/50 2591570000


Type I and II lightning arresters for 230 /400 V system with LPL III / IV

- Back-up fuse not necessary up to 315 A
- Pluggable arrester
- Suitable with 12.5 kA for LPL III/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I/R 4 300 V / 12.5 kA



VPU AC I/R 2 300 V / 12.5 kA



Technical data

Rated voltage (AC)
 Max. continuous voltage, U_c (AC)
 Lightning test current, I_{imp} (10/350 μ s) (N-PE)
 Lightning test current I_{imp} (10/350 μ s) (L-PE)
 Discharge current I_n (8/20 μ s) wire-PE
 Discharge current I_{max} (8/20 μ s) wire-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{scor}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
 Stripping length
 Tightening torque

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (L/N-PE)
 VPR (N-PE)
 SCCR
 I_n
 Category

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

Ordering data

without remote signalling contact
 with remote signalling contact (R)

Note

Accessories

Note

230 V
 300 V
 12.5 kA
 20 kA
 50 kA
 T1, T2
 50 kA
 0.6 mA
 250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
 337 V
 ≤ 1.5 kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 4TE, Insta IP 20
 orange, black
 -40 °C...85 °C
 -40 °C...85 °C

4...16 mm² / 4...35 mm²

15 mm

2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V

900 V

150 kA

20 kA

SPD TYPE 1CA

no remote sig. contact

16 / 4 / 35

90 / 76 / 93

No

with remote signalling (R)

16 / 4 / 35

106 / 76 / 93

250 V 1A 1CO

230 V
 300 V
 12.5 kA
 20 kA
 50 kA
 T1, T2
 50 kA
 0.6 mA
 250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
 337 V
 ≤ 1.5 kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 2TE, Insta IP 20
 orange, black
 -40 °C...85 °C
 -40 °C...85 °C

4...16 mm² / 4...35 mm²

15 mm

2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V

900 V

150 kA

20 kA

SPD TYPE 1CA

no remote sig. contact

16 / 4 / 35

90 / 36 / 93

No

with remote signalling (R)

16 / 4 / 35

106 / 36 / 93

250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 4 300/12.5	1	2591420000
VPU AC I 4 R 300/12.5	1	2591430000

Type	Qty.	Order No.
VPU AC I 2 300/12.5	1	2591400000
VPU AC I 2 R 300/12.5	1	2591410000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 2591370000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 2591370000




Type I and II lightning arrester


Type I and II lightning arresters for 230 /400 V system with LPL III / IV

- Back-up fuse not necessary up to 315 A
- Pluggable arrester
- Suitable with 12.5 kA for LPL III/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I/R 1 300 V / 12.5 kA



VPU AC I/R 1+1 300 V / 12.5 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scor}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

	without remote signalling contact
	with remote signalling contact (R)

Note

Accessories

Note

230 V
300 V
12.5 kA
20 kA
50 kA
T1, T2
50 kA
0.6 mA
250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
337 V
≤ 1.5 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 1TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C
4...16 mm ² / 4...35 mm ²
15 mm
2...4.5 Nm
CE; cURus; VDE
IEC61643-11, EN61643-11
240 V
900 V
150 kA
20 kA
SPD TYPE 1CA

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 18 / 93	106 / 18 / 93
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 1 300/12.5	1	2591380000
VPU AC I 1 R 300/12.5	1	2591390000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 2591370000

230 V
300 V
50 kA
12.5 kA
20 kA
50 kA
T1, T2
50 kA
1 μ A
250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
337 V
≤ 1.5 kV
≤ 25 ns, ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
black, orange, blue
-40 °C...85 °C
-40 °C...85 °C
4...16 mm ² / 4...35 mm ²
15 mm
2...4.5 Nm
CE; cURus; VDE
IEC61643-11, EN61643-11
240 V
900 V
1200 V
150 kA
20 kA
SPD TYPE 1CA

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 36 / 93	106 / 36 / 93
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 1+1 300/12.5	1	2591480000
VPU AC I 1+1 R 300/12.5	1	2591490000

Pluggable spare arrester L-N VPU AC I 0 300/12.5 2591370000, N-PE VPU AC I 1 N-PE 305/50 2591570000




Type I and II lightning arrester


Type I and II lightning arresters for 400 / 690 V system with LPL III / IV

- Back-up fuse not necessary up to 315 A
- Pluggable arrester
- Suitable with 12.5 kA for LPL III/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I/R 1 480 V / 10 kA



VPU AC I/R 3 480 V / 10 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scor}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

	without remote signalling contact
	with remote signalling contact (R)

Note

Accessories

Note

400 V
480 V
10 kA
20 kA
50 kA
T1, T2
50 kA
0.6 mA
250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
762 V
≤ 2.1 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 1TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²

15 mm

2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

400 V

1500 V

200 kA

20 kA

SPD TYPE 1CA

no remote sig. contact

16 / 4 / 35

90 / 18 / 93

No

with remote signalling (R)

16 / 4 / 35

106 / 18 / 93

250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 1 480/10	1	2591510000
VPU AC I 1 R 480/10	1	2591520000

Pluggable spare arrester L-N VPU AC I 0 480/10 2591500000

400 V
480 V
10 kA
20 kA
50 kA
T1, T2
50 kA
0.6 mA
250 gG @50 kA I_{scor} , 315 gG @25 kA I_{scor}
762 V
≤ 2.1 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 3TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²

15 mm

2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

400 V

1500 V

200 kA

20 kA

SPD TYPE 1CA

no remote sig. contact

16 / 4 / 35

90 / 54 / 93

No

with remote signalling (R)

16 / 4 / 35

106 / 54 / 93

250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 3 480/10	1	2591530000
VPU AC I 3 R 480/10	1	2591540000


Pluggable spare arrester L-N VPU AC I 0 480/10 2591500000



Type I and II lightning arresters for 400 / 690 V system with LPL III / IV

- Back-up fuse not necessary up to 315 A
- Pluggable arrester
- Suitable with 12.5 kA for LPL III/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I/R 4 480 V / 10 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scor}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

Accessories

Note

400 V
480 V
10 kA
20 kA
50 kA
T1, T2
50 kA
0.6 mA
250 gG @50 kA Isccr, 315 gG @25 kA Isccr
762 V
≤ 2.1 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ² / 4...35 mm ²
15 mm
2...4.5 Nm
CE; cURus; VDE
IEC61643-11, EN61643-11
400 V
1500 V
200 kA
20 kA
SPD TYPE 1CA

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 76 / 93	106 / 76 / 93
No	250 V 1A 1C0

Type	Qty.	Order No.
VPU AC I 4 480/10	1	2591550000
VPU AC I 4 R 480/10	1	2591560000


Pluggable spare arrester L-N VPU AC I 0 480/10 2591500000

Type I and II lightning arrester


Type I and II lightning arresters for 400 / 690 V system with LPL III / IV

- Back-up fuse not necessary up to 250 A
- Leakage current free arrester
- Suitable with 25 kA for LPL I/II/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I/R 4 440V / 25 kA LCF



VPU AC I/R 3+1 440 V / 25 kA LCF



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

400 V
440 V

25 kA
25 kA
100 kA
T1, T2
50 kA
5 μ A
100 A
250 A gL (if back up fuse > 250 A)
762 V
 ≤ 2.5 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing: 8 TE, Insta IP 20
black
-40 °C...85 °C
-40 °C...85 °C

6...16 mm² / 6...35 mm²
13 mm
2...3 Nm

CE
IEC61643-11, EN61643-11, EN 60068-2-27:2009, EN 60068-2-64:2008, EN 60068-2-6:2008

400 V
440 V
100 kA
25 kA
25 kA
100 kA
T1, T2
50 kA
5 μ A
100 A
250 A gL (if back up fuse > 250 A)
762 V
 ≤ 2.5 kV
 ≤ 25 ns, ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing: 8 TE, Insta IP 20
black
-40 °C...85 °C
-40 °C...85 °C

6...16 mm² / 6...35 mm²
13 mm
2...3 Nm

CE
IEC61643-11, EN61643-11, EN 60068-2-27:2009, EN 60068-2-64:2008, EN 60068-2-6:2008

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

no remote sig. contact	with remote signalling (R)
16 / 6 / 35	16 / 6 / 35
99 / 144 / 93	106 / 144 / 93
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 6 / 35	16 / 6 / 35
99 / 144 / 93	106 / 144 / 93
No	250 V 1A 1CO

Ordering data

Type	Qty.	Order No.
VPU AC I 4 440/25 LCF	1	2619190000
VPU AC I 4 R 440/25 LCF	1	2619200000

Type	Qty.	Order No.
VPU AC I 3+1 440/25 LCF	1	2619240000
VPU AC I 3+1 R 440/25 LCF	1	2619260000

Note


Accessories

Note


Type I and II lightning arresters for 400 / 690 V system with LPL III / IV

- Back-up fuse not necessary up to 250 A
- Leakage current free arrester
- Suitable with 25 kA for LPL I/II/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I/R 3 440 V / 25 kA LCF



VPU AC I/R 2 440 V / 25 kA LCF



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

400 V
440 V

25 kA
25 kA
100 kA
T1, T2
50 kA
5 μ A
100 A
250 A gL (if back up fuse > 250 A)
762 V
 ≤ 2.5 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing: 6 TE, Insta IP 20
black
-40 °C...85 °C
-40 °C...85 °C

6...16 mm² / 6...35 mm²
13 mm
2...3 Nm

CE

IEC61643-11, EN61643-11, EN 60068-2-27:2009, EN 60068-2-64:2008, EN 60068-2-6:2008

400 V
440 V

25 kA
25 kA
100 kA
T1, T2
50 kA
5 μ A
100 A
250 A gL (if back up fuse > 250 A)
762 V
 ≤ 2.5 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing: 4TE, Insta IP 20
black
-40 °C...85 °C
-40 °C...85 °C

6...16 mm² / 6...35 mm²
13 mm
2...3 Nm

CE

IEC61643-11, EN61643-11, EN 60068-2-27:2009, EN 60068-2-64:2008, EN 60068-2-6:2008

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

Accessories

Note

no remote sig. contact	with remote signalling (R)
16 / 6 / 35	16 / 6 / 35
99 / 108 / 93	106 / 108 / 93
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 6 / 35	16 / 6 / 35
99 / 72 / 93	106 / 72 / 93
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 3 440/25 LCF	1	2619160000
VPU AC I 3 R 440/25 LCF	1	2619170000

Type	Qty.	Order No.
VPU AC I 2 440/25 LCF	1	2619130000
VPU AC I 2 R 440/25 LCF	1	2619140000




Type I and II lightning arrester


Type I and II lightning arresters for 400 / 690 V system with LPL III / IV

- Back-up fuse not necessary up to 250 A
- Leakage current free arrester
- Suitable with 25 kA for LPL I/II/IV
- Tested according to IEC/EN61643-11 as Type I and Type II

VPU AC I/R 1 440 V / 25 kA LCF



VPU AC I/R 1+1 440 V / 25 kA LCF



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Lightning test current, I_{imp} (10/350 μ s) (N-PE)
Lightning test current I_{imp} (10/350 μ s) (L-PE)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Rated load current I_L
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

400 V
440 V
25 kA
25 kA
100 kA
T1, T2
50 kA
5 μ A
100 A
250 A gL (if back up fuse > 250 A)
762 V
≤ 2.5 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
black
-40 °C...85 °C
-40 °C...85 °C

6...16 mm ² / 6...35 mm ²
13 mm
2...3 Nm

CE
IEC61643-11, EN61643-11, EN 60068-2-27:2009, EN 60068-2-64:2008, EN 60068-2-6:2008

400 V
440 V
100 kA
25 kA
25 kA
100 kA
T1, T2
50 kA
5 μ A
100 A
250 A gL (if back up fuse > 250 A)
762 V
≤ 2.5 kV
≤ 25 ns, ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
black
-40 °C...85 °C
-40 °C...85 °C

6...16 mm ² / 6...35 mm ²
13 mm
2...3 Nm

CE
IEC61643-11, EN61643-11, EN 60068-2-27:2009, EN 60068-2-64:2008, EN 60068-2-6:2008

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

	without remote signalling contact
	with remote signalling contact (R)

Note

Accessories

Note

no remote sig. contact	with remote signalling (R)
16 / 6 / 35	16 / 6 / 35
99 / 36 / 93	106 / 36 / 93
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 6 / 35	16 / 6 / 35
99 / 72 / 93	106 / 72 / 93
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU AC I 1 440/25 LCF	1	2619100000
VPU AC I 1 R 440/25 LCF	1	2619120000

Type	Qty.	Order No.
VPU AC I 1+1 440/25 LCF	1	2619210000
VPU AC I 1+1 R 440/25 LCF	1	2619220000



VPU ZP I lightning and surge protection VARITECTOR PU ZP for quick installation on 40 mm busbar systems

According to the specifications of DIN VDE 0100-443 and -534, surge protection is an obligatory component of every energy supply, especially in building infrastructures. Commercial and private buildings must, therefore, provide surge protection.

Our compact lightning current arresters for 3-phase power supply networks are ideally suited for building infrastructures and fit on 40 mm busbars. They enable direct contact to the busbar with separate PE connection and combine type I and type II arresters for lightning and surge protection in a single product.

In addition, the VARITECTOR PU ZP are suitable for use in main power supply systems in accordance with the new connection condition VDE-AR-N 4100:2019-04.

Soon
in narrow
47mm
design



Remote signalling contact and phase tap

The optional signalling output allows remote signalling of the protection status. The optional phase tap can be used to supply the network operator's communication equipment with power in a space-saving manner.



Safe and easy to use

Easy and space-saving installation directly in the main cabinet. Safe mounting directly on the busbars for reliable contact without manual wiring.

**Standard-compliant protection**


The VARITECTOR PU ZP product range meets the current requirements of IEC/EN 61643-11.

**Complete status control**

The VPU ZP series has a distinctly visible status indicator. You can see the protection status at any time without manual operation.

**Protective circuit without leakage current**

The connection of varistor and spark gap (Gas Discharge Tube) in series guarantees leakage current free protection between the lines and towards the protective conductor.






Type II surge protection

Type I and II lightning arresters for 40 mm


Busbar

- Simple and safe to use and install
- Complete and permanent status control
- Leakage current-free surge protection
- Available with discharge capacity I_{imp} of 7.5 kA or 12.5 kA

VPU ZP I 3 300 V / 12.5 kA



VPU ZP I 3 300 V / 7.5 kA



Technical data

Rated voltage (AC)	230 V	230 V
Max. continuous voltage, U_c (AC)	300 V	300 V
Lightning test current, I_{imp} (10/350 μ s) (N-PE)		
Lightning test current I_{imp} (10/350 μ s) (L-PE)	12.5 kA	7.5 kA
Discharge current I_n (8/20 μ s) wire-PE	20 kA	20 kA
Discharge current I_{max} (8/20 μ s) wire-PE	50 kA	50 kA
Requirements class, acc. to EN 61643-11	T1, T2	T1, T2
Short-circuit current rating I_{scor}	25 kA	25 kA
Leakage current at U_n	20 μ A	20 μ A
Low voltage network	TN-C	TN-C
Fuse	160 A gG	160 A gG
Temporary surge voltage (over-voltage) - TOV	442 V	442 V
Protection level U_p (typ.)	≤ 1.5 kV	≤ 1.5 kV
Response time	≤ 100 ns	≤ 100 ns
Optical function display	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace
Design	miscellaneous	miscellaneous
Colour	grey	grey
Ambient temperature (operational)	-40 °C...85 °C	-40 °C...85 °C
Storage temperature	-40 °C...85 °C	-40 °C...85 °C
Connection according to IEC 947-7-1		
Stranded	16...35 mm ²	16...35 mm ²
Approvals		
Approvals	CE	CE
Standards	IEC61643-11, EN61643-11	IEC61643-11, EN61643-11

Dimensions / Signalling contact info	no remote sig. contact	no remote sig. contact
Height x width x depth mm	206 / 58 / 88	206 / 58 / 88
Signalling contact	No	No
Note		

Ordering data

Type	Qty.	Order No.	Type	Qty.	Order No.
VPU ZP I 3 300/12,5	1	2638450000	VPU ZP I 3 300/7,5	1	2659900000

Note		
------	--	--

Accessories


Note		
------	--	--

Type I and II lightning arresters for 40 mm


Busbar

- Simple and safe to use and install
- Complete and permanent status control
- Leakage current-free surge protection
- Available with discharge capacity I_{imp} of 7.5 kA or 12.5 kA

VPU ZP I 3+1 300 V / 12.5 kA



VPU ZP I 3+1 300 V / 7.5 kA



Technical data

Rated voltage (AC)
 Max. continuous voltage, U_c (AC)
 Lightning test current, I_{imp} (10/350 μ s) (N-PE)
 Lightning test current I_{imp} (10/350 μ s) (L-PE)
 Discharge current I_n (8/20 μ s) wire-PE
 Discharge current I_{max} (8/20 μ s) wire-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{scor}
 Leakage current at U_n
 Low voltage network
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Stranded

Approvals

Approvals

Standards

230 V
 300 V
 12.5 kA
 20 kA
 50 kA
 T1, T2
 25 kA
 5 μ A
 TN-C-S, TN-S, TT
 160 A gG
 442 V
 ≤ 1.5 kV
 ≤ 100 ns
 green = OK; red = arrester is defective - replace
 miscellaneous
 grey
 -40 °C... 85 °C
 -40 °C... 85 °C
 16...35 mm²
 CE
 IEC61643-11, EN61643-11

230 V
 300 V
 7.5 kA
 20 kA
 50 kA
 T1, T2
 25 kA
 5 μ A
 TN-C-S, TN-S, TT
 160 A gG
 442 V
 ≤ 1.5 kV
 ≤ 100 ns
 green = OK; red = arrester is defective - replace
 miscellaneous
 grey
 -40 °C... 85 °C
 -40 °C... 85 °C
 16...35 mm²
 CE
 IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Height x width x depth mm
 Signalling contact

Note

no remote sig. contact

206 / 58 / 88
 No

no remote sig. contact

206 / 58 / 88
 No

Ordering data

without remote signalling contact

Type	Qty.	Order No.
VPU ZP I 3+1 300/12,5	1	2638440000

Type	Qty.	Order No.
VPU ZP I 3+1 300/7,5	1	2659910000

Note

Accessories

Note



VPU AC II surge protection

VARITECTOR PU AC provides safety with efficient surge protection

With increasing digitalisation, an increasingly sensitive infrastructure of intelligent devices and systems is emerging. As a result, surge protection is becoming considerably more important in all application areas and industries.

Ever more efficient overvoltage protection solutions are required, especially in energy supply areas like renewable energy generation, process industry, and building infrastructure. VARITECTOR PU AC surge protection devices offer a leading price-performance ratio. They enable fuseless operation up to 315 A, are certified according to UL 1449 Ed. 4 and convince with particularly efficient design.

The VPU AC II series offers products for the following nominal voltages (AC):

- 48 V
- 120 V
- 230 V
- 400 V
- 690 V
- 830 V

Extended N/PE protection

N/PE surge arresters in product variants VPU AC 3+1 and VPU AC 1+1 indicate the status of the protective element and transmit it via the remote signaling output.





Global applicable

Certification in accordance with international IEC/EN standards and the latest UL 1449 Ed. 4 standard guarantees universal use in any application.

**Fuseless
operation**

up to 315 A

Complete status control

All products of the VPU AC series have optical signaling. Variants with a pre-warning display enable uninterrupted protection. The remote signaling output indicates the pre-warning status.



High performance

The specially developed disconnection mechanism enables safe operation with high fuse ratings up to 315 A for type I and II products. UL classification as 1CA/2CA allows use in the most demanding application classes.



Surge protection for low-voltage consumer installations and electronics

Surge protection of type II

Weidmüller VPU AC II surge protection products protect low-voltage consumer installations and electronic devices against surge voltages that can occur as a result of atmospheric discharges (thunderstorms) or switching operations (transients).

The VPU AC II series satisfies the type II requirements of IEC 61643-11 and type 2 requirements of EN 61643-11.

Electrical connection

VPU AC II surge protection is connected with the shortest possible cables between the phase conductors (L1, L2, L3) or the neutral conductor (N) and the earthing of the consumer system.



Routing unprotected lines (e.g. lines to the meter) in parallel with protected lines must be avoided.

The universal „3+1“ circuit for the TN or TT network is available from the Weidmüller delivery programme.

The VPU AC II surge protection is available as a compact module with 1, 2, 3 or 4 poles, with the PE connections already internally connected within the module.

The following rated voltage variants are available:

U_n : 48 V AC = U_c : 75 V
 U_n : 120/230 V AC = U_c : 150 V
 U_n : 230/400 V AC = U_c : 300 V and 350 V
 U_n : 400/690 V AC = U_c : 480 V
 U_n : 750/1200 V AC = U_c : 750 V and 1.000 V

The VPU AC II series is selected according to voltage ($U_n \leq U_c$) and number of arresters due to different mains systems. National regulations and safety guidelines must be observed, see IEC 60364-5-53 and/or DIN VDE 0100 T.534

Function control, maintenance and approvals

The VPU AC II surge protection modules are visually inspected. Visual inspection is simple because the arrester is equipped with a thermal cut-off mechanism. If this has responded, i.e. no protection remains, the colour in the display window changes from green to red.



An arrester that is no longer functional can be replaced by a specialist without disconnecting the wiring. The pluggable varistor upper parts are voltage coded. So only the suitable replacement varistor can be plugged in.

Advantage Status Indication (ASI)

The VPU AC II Y series is equipped with ASI – Advanced Status Indication technology. The yellow status signal indicates that the product is approaching its performance limit due to frequent overvoltages. Your system is still protected because the arrester units are redundant with two varistors. If a varistor fails, full protection is still available. This status is signaled by means of a yellow display in the status window and at the remote signaling contact. Only when showing the red status the arrester is completely disconnected from the power grid.



Connection

The cross-section of the earth conductor is in accordance with the national requirements of the standards. The fuse protection for the VPU AC II modules is selected depending on the conductor cross-section and the type of installation. If the main fuse is smaller than 315 A, no additional back-up fuse is required before the surge protection.

VPU II series arresters from Weidmüller are suitable for the following cross-sections:

solid wire: 2.5...16 mm²

stranded wire: 2.5...50 mm²

flexible: 2.5...25 mm²

The operating temperature range is -40 °C...+85 °C.

V-shaped connection


If the cross-connection bridges from the RCD or fuses to the VPU II are used, V-shaped wiring can be installed.

Remote signalling contact (R)

All modules of the VPU II series are available with the option of a remote signalling contact which is integrated directly in the module.

This potential-free contact should be connected as a changeover contact using a PUSH IN plug connection. The contact's electrical data is: 250 V AC / 1 A or 24 V DC / 0.1 A.

Dimensional drawing VPU AC II series



Overall width

VPU AC II, single-pole, 18 mm


VPU AC II, two-pole, 36 mm

VPU AC II, three-pole, 54 mm


VPU AC II, four-pole, 72 mm

Coordination with other arresters

The VPU AC II series can be installed to the following Weidmüller surge protectors without decoupling.



Dimensional drawing VPU II series



Overall width

VPU II, single-pole, 18 mm

VPU II, two-pole, 36 mm

VPU II, three-pole, 54 mm

VPU II, four-pole, 72 mm

Accessories: Remote signalling contact


Type	Remote signalling contact	PLUG VPU	1402570000
			

VPU AC II series surge protection


VPU AC II series surge protection Uc: 75 V

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 1 75 V / 50 kA



VPU AC II/R 2 75 V / 50 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, Uc (AC)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

48 V
75 V
20 kA
50 kA
T2
50 kA
0.32 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
114 V
< 800 V
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 1TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

60 V
600 V

100 kA
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

no remote sig. contact

16 / 4 / 35
90 / 18 / 68
250 V 1A 1CO

Ordering data

without remote signalling contact

Type	Qty.	Order No.
VPU AC II 1 R 75/50	1	2591620000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 75/50 2591610000


Pluggable spare arrester L-N VPU AC II 0 75/50 2591610000

VPU AC II series surge protection


Suitable for 120 / 208 V mains systems

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 1 150 V / 50 kA



VPU AC II/R 2 150 V / 50 kA



Technical data

Rated voltage (AC)
 Max. continuous voltage, U_c (AC)
 Discharge current I_n (8/20 μ s) wire-PE
 Discharge current I_{max} (8/20 μ s) wire-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{scCR}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (L/N-PE)
 VPR (N-PE)
 SCCR
 I_n
 Category

120 V
 150 V
 20 kA
 50 kA
 T2
 50 kA
 0.3 mA
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 229 V
 ≤ 1.25 kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 1TE, Insta IP 20
 orange, black
 -40 °C... 85 °C
 -40 °C... 85 °C

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

120 V
 1200 V

200 kA
 20 kA
 SPD TYPE 1CA

120 V
 150 V
 20 kA
 50 kA
 T2
 50 kA
 0.4 mA
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 229 V
 ≤ 1.25 kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 2TE, Insta IP 20
 orange, black
 -40 °C... 85 °C
 -40 °C... 85 °C

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

120 V
 1200 V

200 kA
 20 kA
 SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

Ordering data

without remote signalling contact
 with remote signalling contact (R)

Note

Accessories

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 18 / 68	95 / 18 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 36 / 68	95 / 36 / 68
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU AC II 1 150/50	1	2591650000
VPU AC II 1 R 150/50	1	2591660000

Type	Qty.	Order No.
VPU AC II 2 150/50	1	2591670000
VPU AC II 2 R 150/50	1	2591680000

Pluggable spare arrester L-N VPU AC II 0 150/50 2591640000

Pluggable spare arrester L-N VPU AC II 0 150/50 2591640000




VPU AC II series surge protection

VPU AC II series surge protection


Suitable for 120 / 208 V mains systems

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 3 150 V / 50 kA



VPU AC II/R 4 150 V / 50 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

120 V
150 V
20 kA
50 kA
T2
50 kA
0.5 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
229 V
≤ 1.25 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 3TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

120 V
1200 V

200 kA
20 kA
SPD TYPE 1CA

120 V
150 V
20 kA
50 kA
T2
50 kA
0.7 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
229 V
≤ 1.25 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

120 V
1200 V

200 kA
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

without remote signalling contact
with remote signalling contact (R)

Note

Accessories

Note

no remote sig. contact with remote signalling (R)

16 / 4 / 35	16 / 4 / 35
90 / 54 / 68	95 / 54 / 68
No	250 V 1A 1CO

no remote sig. contact with remote signalling (R)

16 / 4 / 35	16 / 4 / 35
90 / 72 / 68	95 / 72 / 68
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU AC II 3 150/50	1	2591690000
VPU AC II 3 R 150/50	1	2591700000



Type	Qty.	Order No.
VPU AC II 4 150/50	1	2591710000
VPU AC II 4 R 150/50	1	2591000000

Pluggable spare arrester L-N VPU AC II 0 150/50 2591640000

Pluggable spare arrester L-N VPU AC II 0 150/50 2591640000

VPU AC II series surge protection**Suitable for 230 / 400 V mains systems**

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 1 300 V / 50 kA**VPU AC II/R 1+1 300 V 50 / 65 kA****Technical data**

Rated voltage (AC)
 Max. continuous voltage, U_c (AC) / N-PE
 Discharge current I_n (8/20 μ s) wire-PE / N-PE
 Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{scCR}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (L/N-PE)
 VPR (N-PE)
 SCCR
 I_n
 Category

230 V
 300 V /
 20 kA /
 50 kA /
 T2
 50 kA
 0.3 mA
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 337 V
 ≤ 1.5 kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 1TE, Insta IP 20
 orange, black
 $-40^\circ\text{C} \dots 85^\circ\text{C}$
 $-40^\circ\text{C} \dots 85^\circ\text{C}$

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V
 900 V

150 kA
 20 kA
 SPD TYPE 1CA

230 V
 300 V / 305 V
 20 kA / 40 kA
 50 kA / 65 kA
 T2
 50 kA
 1 μ A
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 337 V
 ≤ 1.5 kV
 ≤ 25 ns, ≤ 100 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 2TE, Insta IP 20
 black, orange, blue
 $-40^\circ\text{C} \dots 85^\circ\text{C}$
 $-40^\circ\text{C} \dots 85^\circ\text{C}$

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V
 900 V
 1000 V
 150 kA
 20 kA
 SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 18 / 68	95 / 18 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 36 / 68	95 / 36 / 68
No	250 V 1A 1CO

Ordering data

	without remote signalling contact
	with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 1 300/50	1	2591020000
VPU AC II 1 R 300/50	1	2591030000

Type	Qty.	Order No.
VPU AC II 1+1 300/50	1	2591060000
VPU AC II 1+1 R 300/50	1	2591070000

Note**Accessories****Note**

Pluggable spare arrester L-N VPU AC II 0 300/50 2591010000

Pluggable spare arrester L-N VPU AC II 0 300/50 2591010000,
 N-PE VPU AC II 1 N-PE 305/50 2591570000




VPU AC II series surge protection

VPU AC II series surge protection


Suitable for 230 / 400 V mains systems

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 2 300 V / 50 kA



VPU AC II/R 3 300 V / 50 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC) / N-PE
Discharge current I_n (8/20 μ s) wire-PE / N-PE
Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

230 V
300 V /
20 kA /
50 kA /
T2
50 kA
0.4 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
337 V
≤ 1.5 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V
900 V

150 kA
20 kA
SPD TYPE 1CA

230 V
300 V /
20 kA /
50 kA /
T2
50 kA
0.5 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
337 V
≤ 1.5 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 3TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V
900 V

150 kA
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 36 / 68	95 / 36 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 54 / 68	95 / 54 / 68
No	250 V 1A 1CO

Ordering data

without remote signalling contact
with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 2 300/50	1	2591040000
VPU AC II 2 R 300/50	1	2591050000

Type	Qty.	Order No.
VPU AC II 3 300/50	1	2591160000
VPU AC II 3 R 300/50	1	2591170000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 300/50 2591010000


Pluggable spare arrester L-N VPU AC II 0 300/50 2591010000

VPU AC II series surge protection


Suitable for 230 / 400 V mains systems

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 3+1 300 V 50 / 65 kA



VPU AC II/R 4 300 V / 50 kA



Technical data

Rated voltage (AC)
 Max. continuous voltage, U_c (AC) / N-PE
 Discharge current I_n (8/20 μ s) wire-PE / N-PE
 Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{scCR}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (L/N-PE)
 VPR (N-PE)
 SCCR
 I_n
 Category

230 V
 300 V / 305 V
 20 kA / 40 kA
 50 kA / 65 kA
 T2
 50 kA
 1 μ A
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 337 V
 ≤ 1.5 kV
 ≤ 25 ns, ≤ 100 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 4TE, Insta IP 20
 black, orange, blue
 -40 °C... 85 °C
 -40 °C... 85 °C

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V
 900 V
 1000 V
 150 kA
 20 kA
 SPD TYPE 1CA

230 V
 300 V /
 20 kA /
 50 kA /
 T2
 50 kA
 0.7 mA
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 337 V
 ≤ 1.5 kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 4TE, Insta IP 20
 orange, black
 -40 °C... 85 °C
 -40 °C... 85 °C

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V
 900 V
 150 kA
 20 kA
 SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 72 / 68	95 / 72 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 72 / 68	95 / 72 / 68
No	250 V 1A 1CO

Ordering data

without remote signalling contact
 with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 3+1 300/50	1	2591080000
VPU AC II 3+1 R 300/50	1	2591090000

Type	Qty.	Order No.
VPU AC II 4 300/50	1	2591140000
VPU AC II 4 R 300/50	1	2591150000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 300/50 2591010000,
 N-PE VPU AC I 1 N-PE 305/50 2591570000

Pluggable spare arrester L-N VPU AC II 0 300/50 2591010000




VPU AC II series surge protection

VPU AC II N-PE series surge protection

- Tested in accordance with IEC/EN 61643-11
- Pluggable, coded N-PE arrester
- High energy absorption with short response time
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II 1 N-PE 305 V / 65 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (N-PE)
Discharge current I_n (8/20 μ s) N-PE
Discharge current I_{max} (8/20 μ s) N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid / Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
 I_n
Category

230 V
305 V
40 kA
65 kA
T2
0.1 kA
1 μ A
1200 V
 ≤ 1.5 kV
 ≤ 100 ns
green = OK; red = arrester is defective - replace
Installation housing; 1TE, Insta IP 20
black, blue
-40 °C...85 °C
-40 °C...85 °C

4...16 mm² / 4...35 mm²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V
1000 V
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

no remote sig. contact

16 / 4 / 35
90 / 18 / 68
No

Ordering data

without remote signalling contact

Type	Qty.	Order No.
VPU AC II 1 N-PE 305/65	1	2591180000

Note

Accessories

Note


Pluggable spare arrester N-PE VPU AC II 0 N-PE 305 40/65 2591190000

VPU AC II Y-series surge protection


Suitable for 230 / 400 V mains systems

- Pluggable, coded arrester
- High energy absorption with short response time
- Installation in the distribution board
- ASI, advanced status indicator
- Co-ordination with VPU AC Type I

VPU AC II 1 R 300 V / 50 kA Y



VPU AC II 1+1 R 300 V / 50 kA Y



Technical data

Rated voltage (AC)
 Max. continuous voltage, U_c (AC) / N-PE
 Discharge current I_n (8/20 μ s) wire-PE / N-PE
 Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{SCCR}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (L/N-PE)
 VPR (N-PE)
 SCCR
 I_n
 Category

230 V
 300 V /
 20 kA /
 50 kA /
 T2
 50 kA
 0.3 mA
 160 A gG
 337 V
 ≤ 1.4 kV
 ≤ 25 ns
 green = ok, yellow = warning, red = arrester is defective - replace.
 Installation housing; 1TE, Insta IP 20
 orange, black
 $-40^\circ\text{C} \dots 85^\circ\text{C}$
 $-40^\circ\text{C} \dots 85^\circ\text{C}$

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V
 900 V

150 kA
 20 kA
 SPD TYPE 1CA

230 V
 300 V / 305 V
 20 kA / 40 kA
 50 kA / 65 kA
 T2
 50 kA
 1 μ A
 160 A gG
 337 V
 ≤ 1.4 kV
 ≤ 25 ns, ≤ 100 ns
 green = ok, yellow = warning, red = arrester is defective - replace.
 Installation housing; 2TE, Insta IP 20
 black, orange, blue
 $-40^\circ\text{C} \dots 85^\circ\text{C}$
 $-40^\circ\text{C} \dots 85^\circ\text{C}$

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V
 900 V
 1000 V
 150 kA
 20 kA
 SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

with remote signalling (R)

16 / 4 / 35
 105 / 18 / 70
 250 V 1A 1CO

with remote signalling (R)

16 / 4 / 35
 105 / 36 / 70
 250 V 1A 1CO

Ordering data

with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 1 R 300/50 Y	1	2639350000

Type	Qty.	Order No.
VPU AC II 1+1 R 300/50 Y	1	2639340000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 300/50 Y

Pluggable spare arrester L-N VPU AC II 0 300/50 Y,
 N-PE VPU AC II 0 N-PE 305/65 Y 2659950000




VPU AC II series surge protection

VPU AC II Y-series surge protection


Suitable for 230 / 400 V mains systems

- Pluggable, coded arrester
- High energy absorption with short response time
- Installation in the distribution board
- ASI, advanced status indicator
- Co-ordination with VPU AC Type I

VPU AC II 2 R 300 V / 50 kA Y



VPU AC II 3 R 300 V / 50 kA Y



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC) / N-PE
Discharge current I_n (8/20 μ s) wire-PE / N-PE
Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{SCCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

230 V
300 V /
20 kA /
50 kA /
T2
50 kA
0.5 mA
160 A gG
337 V
≤ 1.4 kV
≤ 25 ns
green = ok, yellow = warning, red = arrester is defective - replace.
Installation housing; 2TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

240 V
900 V

150 kA
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

with remote signalling contact (R)

Note

Accessories

Note

with remote signalling (R)

16 / 4 / 35
105 / 36 / 70
250 V 1A 1CO

with remote signalling (R)

16 / 4 / 35
105 / 54 / 70
250 V 1A 1CO

Type	Qty.	Order No.
VPU AC II 2 R 300/50 Y	1	2639360000

Type	Qty.	Order No.
VPU AC II 3 R 300/50 Y	1	2639330000

Pluggable spare arrester L-N VPU AC II 0 300/50 Y


Pluggable spare arrester L-N VPU AC II 0 300/50 Y

VPU AC II Y-series surge protection


Suitable for 230 / 400 V mains systems

- Pluggable, coded arrester
- High energy absorption with short response time
- Installation in the distribution board
- ASI, advanced status indicator
- Co-ordination with VPU AC Type I

VPU AC II 3+1 R 300 V / 50 kA Y



VPU AC II 4 R 300 V / 50 kA Y



Technical data

Rated voltage (AC)
 Max. continuous voltage, U_c (AC) / N-PE
 Discharge current I_n (8/20 μ s) wire-PE / N-PE
 Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{SCCR}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (L/N-PE)
 VPR (N-PE)
 SCCR
 I_n
 Category

230 V
 300 V / 305 V
 20 kA / 40 kA
 50 kA / 65 kA
 T2
 50 kA
 1 μ A
 160 A gG
 337 V
 ≤ 1.4 kV
 ≤ 25 ns, ≤ 100 ns
 green = ok, yellow = warning, red = arrester is defective - replace.
 Insta IP 20, Installation housing; 6 TE
 black, orange, blue
 -40 °C... 85 °C
 -40 °C... 85 °C

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

240 V
 900 V
 1000 V
 150 kA
 20 kA
 SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

with remote signalling (R)

16 / 4 / 35
 105 / 72 / 70
 250 V 1A 1CO

Ordering data

with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 3+1 R 300/50 Y	1	2639320000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 300/50 Y,
 N-PE VPU AC II 0 N-PE 305/65 Y 2659950000

Type	Qty.	Order No.
VPU AC II 4 R 300/50 Y	1	2639370000

Pluggable spare arrester L-N VPU AC II 0 300/50 Y




VPU AC II series surge protection


VPU AC II series surge protection

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 1 350 V / 50 kA



VPU AC II/R 2 350 V / 50 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC) / N-PE
Discharge current I_n (8/20 μ s) wire-PE / N-PE
Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
 I_n
Category

230 V
350 V /
20 kA /
50 kA /
T2
50 kA
0.3 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
403 V
 ≤ 1.75 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 1TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm²
4...35 mm²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

277 V
2000 V

200 kA
20 kA
SPD TYPE 1CA

230 V
350 V /
20 kA /
50 kA /
T2
50 kA
0.4 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
403 V
 ≤ 1.75 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm²
4...35 mm²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

277 V
2000 V

200 kA
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 18 / 68	95 / 18 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 36 / 68	95 / 36 / 68
No	250 V 1A 1CO

Ordering data

without remote signalling contact
with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 1 350/50	1	2591350000
VPU AC II 1 R 350/50	1	2591360000

Type	Qty.	Order No.
VPU AC II 2 350/50	1	2637010000
VPU AC II 2 R 350/50	1	2637020000

Note

Accessories

Note


Pluggable spare arrester L-N VPU AC II 0 250/50 25913400000

Pluggable spare arrester L-N VPU AC II 0 250/50 25913400000


VPU AC II series surge protection

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 3 350 V / 50 kA



VPU AC II/R 4 350 V / 50 kA



Technical data

Rated voltage (AC)
 Max. continuous voltage, U_c (AC) / N-PE
 Discharge current I_n (8/20 μ s) wire-PE / N-PE
 Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{scCR}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (L/N-PE)
 VPR (N-PE)
 SCCR
 I_n
 Category

230 V
 350 V /
 20 kA /
 50 kA /
 T2
 50 kA
 0.5 mA
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 403 V
 ≤ 1.75 kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 3TE, Insta IP 20
 orange, black
 $-40^\circ\text{C} \dots 85^\circ\text{C}$
 $-40^\circ\text{C} \dots 85^\circ\text{C}$

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

277 V
 2000 V

200 kA
 20 kA
 SPD TYPE 1CA

230 V
 350 V /
 20 kA /
 50 kA /
 T2
 50 kA
 0.7 mA
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 403 V
 ≤ 1.75 kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 4TE, Insta IP 20
 orange, black
 $-40^\circ\text{C} \dots 85^\circ\text{C}$
 $-40^\circ\text{C} \dots 85^\circ\text{C}$

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

277 V
 2000 V

200 kA
 20 kA
 SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 54 / 68	95 / 54 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 72 / 68	95 / 72 / 68
No	250 V 1A 1CO

Ordering data

without remote signalling contact
 with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 3 350/50	1	2591100000
VPU AC II 3 R 350/50	1	2591110000

Type	Qty.	Order No.
VPU AC II 4 350/50	1	2591120000
VPU AC II 4 R 350/50	1	2591130000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 250/50 25913400000

Pluggable spare arrester L-N VPU AC II 0 250/50 25913400000




VPU AC II series surge protection


VPU AC II series surge protection

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II 1+1 R 350 V / 50 kA



VPU AC II 3+1 R 350 V / 50 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC) / N-PE
Discharge current I_n (8/20 μ s) wire-PE / N-PE
Discharge current I_{max} (8/20 μ s) wire-PE / N-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
 I_n
Category

230 V
350 V /
20 kA /
50 kA /
T2
50 kA
0.3 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
403 V
 ≤ 1.75 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
orange, black, blue
-40 °C...85 °C
-40 °C...85 °C

4...16 mm²
4...35 mm²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

277 V
2000 V
1000 V
200 kA
20 kA
SPD TYPE 1CA

230 V
350 V /
20 kA /
50 kA /
T2
50 kA
0.3 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
403 V
 ≤ 1.75 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
orange, black, blue
-40 °C...85 °C
-40 °C...85 °C

4...16 mm²
4...35 mm²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

277 V
2000 V
1000 V
200 kA
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 36 / 68	95 / 36 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 72 / 68	95 / 72 / 68
No	250 V 1A 1CO

Ordering data

without remote signalling contact
with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 1+1 350/50	1	2637030000
VPU AC II 1+1 R 350/50	1	2637040000

Type	Qty.	Order No.
VPU AC II 3+1 350/50	1	2637050000
VPU AC II 3+1 R 350/50	1	2637060000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 250/50 25913400000,
N-PE VPU AC I 1 N-PE 305/50 2591570000


Pluggable spare arrester L-N VPU AC II 0 250/50 25913400000,
N-PE VPU AC I 1 N-PE 305/50 2591570000

VPU AC II series surge protection


Suitable for 400 / 690 V mains systems

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 1 480 V / 50 kA



VPU AC II/R 2 480 V / 50 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

400 V
480 V
20 kA
50 kA
T2
50 kA
0.32 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
581 V
≤ 2.3 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 1TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

400 V
2500 V

200 kA
20 kA

SPD TYPE 1CA

400 V
480 V
20 kA
50 kA
T2
50 kA
0.5 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
581 V
≤ 2.3 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 2TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

400 V
2000 V

200 kA
20 kA

SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Ordering data

without remote signalling contact	
with remote signalling contact (R)	

Note

Accessories

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 18 / 68	95 / 18 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 36 / 68	95 / 36 / 68
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU AC II 1 480/50	1	2591210000
VPU AC II 1 R 480/50	1	2591220000

Type	Qty.	Order No.
VPU AC II 2 480/50	1	2591230000
VPU AC II 2 R 480/50	1	2591240000

Pluggable spare arrester L-N VPU AC II 0 480/50 2591200000

Pluggable spare arrester L-N VPU AC II 0 480/50 2591200000




VPU AC II series surge protection

VPU AC II series surge protection


Suitable for 400 / 690 V mains systems

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II/R 3 480 V / 50 kA



VPU AC II/R 4 480 V / 50 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
I_n
Category

400 V
480 V
20 kA
50 kA
T2
50 kA
0.7 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
581 V
≤ 2.3 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 3TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

400 V
2500 V

200 kA
20 kA
SPD TYPE 1CA

400 V
480 V
20 kA
50 kA
T2
50 kA
0.9 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
581 V
≤ 2.3 kV
≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 4TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm ²
4...35 mm ²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

400 V
2500 V

200 kA
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 54 / 68	95 / 54 / 68
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 4 / 35	16 / 4 / 35
90 / 72 / 68	95 / 72 / 68
No	250 V 1A 1CO

Ordering data

without remote signalling contact	
with remote signalling contact (R)	

Type	Qty.	Order No.
VPU AC II 3 480/50	1	2591250000
VPU AC II 3 R 480/50	1	2591260000

Type	Qty.	Order No.
VPU AC II 4 480/50	1	2591270000
VPU AC II 4 R 480/50	1	2591280000

Note

Accessories

Note


Pluggable spare arrester L-N VPU AC II 0 480/50 2591200000

Pluggable spare arrester L-N VPU AC II 0 480/50 2591200000


VPU AC II series surge protection

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II R 1 750 V / 35 kA



VPU AC II R 2 750 V / 35 kA



Technical data

Rated voltage (AC)
 Max. continuous voltage, U_c (AC)
 Discharge current I_n (8/20 μ s) wire-PE
 Discharge current I_{max} (8/20 μ s) wire-PE
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{scCR}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (L/N-PE)
 VPR (N-PE)
 SCCR
 I_n
 Category

690 V
 750 V
 20 kA
 35 kA
 T2
 50 kA
 0.3 mA
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 871 V
 $\leq 3,4$ kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 1TE, Insta IP 20
 orange, black
 -40 °C... 85 °C
 -40 °C... 85 °C

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

600 V
 2500 V

200 kA
 20 kA
 SPD TYPE 1CA

690 V
 750 V
 20 kA
 35 kA
 T2
 50 kA
 0.5 mA
 250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
 871 V
 $\leq 3,4$ kV
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing; 2TE, Insta IP 20
 orange, black
 -40 °C... 85 °C
 -40 °C... 85 °C

4...16 mm²
 4...35 mm²
 15 mm
 2...4.5 Nm

CE; cURus; VDE
 IEC61643-11, EN61643-11

600 V
 2500 V

200 kA
 20 kA
 SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

with remote signalling (R)

16 / 4 / 35
 95 / 18 / 68
 250 V 1A 1CO

with remote signalling (R)

16 / 4 / 35
 95 / 36 / 68
 250 V 1A 1CO

Ordering data

with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II R 1 750/35	1	2591300000

Type	Qty.	Order No.
VPU AC II R 2 750/35	1	2591310000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 750/35 25912900000

Pluggable spare arrester L-N VPU AC II 0 750/35 25912900000




VPU AC II series surge protection

VPU AC II series surge protection

- Back-up fuse not necessary up to 315 A
- Pluggable, coded arrester
- High energy absorption with short response time
- No follow current
- Installation in the distribution board
- Co-ordination with VPU AC Type I

VPU AC II R 3 750 V / 35 kA



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

UL values

Rated Voltage U_n
VPR (L/N-PE)
VPR (N-PE)
SCCR
 I_n
Category

690 V
750 V
20 kA
35 kA
T2
50 kA
0.7 mA
250 gG @50 kA I_{scCR} , 315 gG @25 kA I_{scCR}
871 V
 $\leq 3,4$ kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 3TE, Insta IP 20
orange, black
-40 °C...85 °C
-40 °C...85 °C

4...16 mm²
4...35 mm²
15 mm
2...4.5 Nm

CE; cURus; VDE
IEC61643-11, EN61643-11

600 V
2500 V

200 kA
20 kA
SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

with remote signalling (R)

16 / 4 / 35
95 / 54 / 68
250 V 1A 1CO

Ordering data

with remote signalling contact (R)

Type	Qty.	Order No.
VPU AC II 3 R 750/35	1	2591320000

Note

Accessories

Note

Pluggable spare arrester L-N VPU AC II 0 750/35 25912900000




Type II surge protection U_c : 1000 V

Suitable for 1000 V mains systems

- Pluggable arrester
- Coded voltage level
- High energy absorption with short time to sparkover
- Insert can be rotated through 180°
- No follow-on current
- Installation in distribution board
- Thermal protection function

VPU II 1 / 1000 V / 40 kA AC

Single-phase



Technical data

Rated voltage (AC)
Max. continuous voltage, U_c (AC)
Discharge current I_n (8/20 μ s) wire-PE
Discharge current I_{max} (8/20 μ s) wire-PE
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scor}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p at I_n (L/N-PE)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

830 V
1000 V
20 kA
40 kA
T2
25 kA
0.7 mA
125 A gL > (if back up fuse > 125 A)
1205 V
 ≤ 3.8 kV
 ≤ 25 ns
green = OK; red = arrester is defective - replace
Installation housing; 1TE, Insta IP 20
black, orange
-40 °C...70 °C
-40 °C...80 °C

1.5...16 mm²
1.5...50 mm²
15 mm
2...3 Nm

CE
IEC61643-11, EN61643-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

16 / 1.5 / 35
94 / 17.8 / 69
No

Ordering data

without remote signalling contact

Type	Qty.	Order No.
VPU II 1 1000V/40KA AC	1	1473440000

Note

Accessories

Note

Spare arrester VPU II 0 1000 V/40 kA -1549700000

VPU PV lightning and surge protection

Lean design and latest technology guarantee best plant protection

Modern photovoltaic energy generation is streamlined to efficiency. Reliable surge protection with future-proof performance is a must to maximise system uptime and profitability. The VARITECTOR PU PV series is designed for use in PV string combiner boxes for generator voltages up to 1,500 V and complies with latest UL and EN standards for global application.

Type I and II protection

Type I and II protection is supported for 1,000V and 1,500V systems fully compliant to latest EN / IEC standards.

1,000 V
1,500 V

Maximum short-circuit capability

PV plants, which combine many panels in a string, are efficiently protected up to 11 kA of the prospective short-circuit current. Additional fuses for the SPD are not required.

I_{scpv}
11 kA



Slim and pluggable arresters

The surge protection devices are easily pluggable and enable a tool-free, fast and cost-effective replacement.

Pluggable inserts



Safe operation up to 4,000 m

PV plants, also such located in high altitude regions, are reliably protected. An additional risk analysis of deratings is not required for extraordinary locations.

up to
4,000 m



B



Customise your protection with VARITECTOR PU devices

A full scale portfolio for tailored DC and AC protection solutions




Several aspects need to be covered that are related to the type of system (e.g. rooftop systems or utility-scale open space systems). When selecting overvoltage protection measures, a set of regulations have to be observed.

PV-System with lightning rod system

In case the separation distance (typical >0,7m up to 1m) is met a Type II SPD can be used. Does the separation distance not meet the required value a Type I SPD should be in place for the DC-wiring.

PV-System without lightning rod system

This is a common set up in which a Type II SPD has to be in place for the DC-wiring.



The figure on the left shows a general PV system architecture. The selection guide table below gives the requirements out of the valid standards for surge protection in photovoltaic systems.

Because PV systems are always set up in exposed areas (exposed to direct lightning), it is advisable to always install Type I+II SPDs. This, in addition enhances the life time of installed protection components.

Surge protection selection guide

							
External lightning protection	Separation distance observed	Conductor length L1 < 10m	Conductor length L2 < 10m	①	②	③	④
no	-	no	no	Type II AC	Type II AC	Type II DC	Type II DC
no	-	no	yes	Type II AC	Type II AC	Type II DC	Type II DC
no	-	yes	no	Type II AC	-	Type II DC	Type II DC
no	-	yes	yes	Type II AC	-	Type II DC	-
yes	yes	no	no	Type I AC	Type II AC	Type II DC	Type II DC
yes	yes	no	yes	Type I AC	Type II AC	Type II DC	-
yes	yes	yes	no	Type I AC	-	Type II DC	Type II DC
yes	yes	yes	yes	Type I AC	-	Type II DC	-
yes	no	no	no	Type I AC	Type I AC	Type I DC	Type I DC
yes	no	no	yes	Type I AC	Type I AC	Type I DC	Type I DC
yes	no	-	no	Type I AC	Type I AC*	Type I DC	Type I DC
yes	no	-	yes	Type I AC	Type I AC*	Type I DC	Type I DC


* No SPD is required at installation point (2) if the AC converter and the main distribution are connected to the same earth bar with an earthing cable with a maximum length of 0.5m.

* No SPD is required at installation point (2) if the AC converter and the main distribution are connected to the same earth bar with an earthing cable with a maximum length of 0.5m.


Type I and II lightning arrester for use in photovoltaic applications

- Suitable for protection level III and IV (LPL III/IV)
- Can also be used as Type II surge protection
- Tested in accordance with EN 50539-11
- Suitable for use in accordance with IEC 60364-7-712/ EN 50539-12
- Use if the separation distance cannot be observed

VPU PV I+II/R 3 1000 V



VPU PV I+II/R 3 1500 V



Technical data

PV system voltage, max. U_{PV}
 Lightning test current I_{imp} (10/350 μ s)
 Discharge current, max. (8/20 μ s)
 Discharge current I_n (8/20 μ s)
 Rated voltage (DC)
 Leakage current at U_n
 Response time
 Operating height in the grounded PV system
 Operating height in ungrounded PV system
 Short-circuit current I_{SCP}
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Technical data - photovoltaic

Protection level U_p mode (+/-, -/PE, +/-PE)
 Short-circuit current I_{SCP}

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (DC/G)
 SCCR
 I_n
 Category

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

Ordering data

without remote signalling contact
 with remote signalling contact (R)

Note

Accessories

Note

1100 V
 6.25 kA
 40 kA
 20 kA
 1000 V
 30 μ A
 ≤ 25 ns
 ≤ 2000 m
 $< 4,000$ m, see operating instructions
 11000 A
 green = OK; red = arrester is defective - replace
 Installation housing: 3TE, Insta IP 20
 black, orange
 -40 °C... 70 °C
 -40 °C... 85 °C

1.5...16 mm²
 1.5...35 mm²
 15 mm
 2...4 Nm

≤ 3.8 kV
 11000 A
 CE; cURus
 EN 50539-11:2013+A1:2014, UL 1449 Ed.4

1100 V
 2500 V
 50 kA
 20 kA
 SPD TYPE 1CA

no remote sig. contact	with remote signalling (R)
16 / 1.5 / 35	16 / 1.5 / 35
96 / 54 / 86	102 / 54 / 86
No	250 V 1A 1CO

1500 V
 5 kA
 30 kA
 20 kA
 1500 V
 30 μ A
 ≤ 25 ns
 ≤ 2000 m
 $< 4,000$ m, see operating instructions
 11000 A
 green = OK; red = arrester is defective - replace
 Installation housing: 3TE, Insta IP 20
 black, orange
 -40 °C... 70 °C
 -40 °C... 85 °C

1.5...16 mm²
 1.5...35 mm²
 15 mm
 2...4 Nm

≤ 5.0 kV
 11000 A
 CE; cURus
 EN 50539-11:2013+A1:2014, UL 1449 Ed.4

1500 V
 4000 V
 65 kA
 20 kA
 SPD TYPE 1CA

no remote sig. contact	with remote signalling (R)
16 / 1.5 / 35	16 / 1.5 / 35
96 / 54 / 86	102 / 54 / 86
No	250 V 1A 1CO

Type	Qty.	Order No.
VPU PV I+II 3 1000	1	2530610000
VPU PV I+II 3 R 1000	1	2530620000

Pluggable replacement conductor VPU PV I+II 0 1000-2530600000 and VPU PV I+II 0M 1000-2534300000

Type	Qty.	Order No.
VPU PV I+II 3 1500	1	2530580000
VPU PV I+II 3 R 1500	1	2530590000


Pluggable replacement conductor VPU PV I+II 0 1500-2530570000 and VPU PV I+II 0M 1500-2534330000




Type II surge arrester for use in photovoltaic applications

- Pluggable arrester
- Suitable for protecting DC systems as Type II arrester
- Encapsulated, non-blow-out arrester
- Tested in accordance with EN 50539-11
- Pluggable arresters
- Suitable for use in accordance with IEC 60364-7-712 / EN 50539-12

VPU PV II 3/R 1000 V



VPU PV II 3/R 1500 V



Technical data

PV system voltage, max. U_{PV}
 Discharge current, max. (8/20 μ s)
 Discharge current I_n (8/20 μ s)
 Rated voltage (DC)
 Leakage current at U_n
 Response time
 Operating height in the grounded PV system
 Operating height in ungrounded PV system
 Short-circuit current I_{SCP}
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Technical data - photovoltaic

Protection level U_p mode (+/-, -/PE, +/-PE)
 Short-circuit current I_{SCP}

Approvals

Approvals
 Standards

UL values

Rated Voltage U_n
 VPR (DC/G)
 SCCR
 I_n
 Category

1100 V
 40 kA
 20 kA
 1000 V
 30 μ A
 ≤ 25 ns
 ≤ 2000 m
 $< 4,000$ m, see operating instructions
 11000 A
 green = OK; red = arrester is defective - replace
 Installation housing; 3TE, Insta IP 20
 black, orange
 -40 °C... 70 °C
 -40 °C... 85 °C

1.5...16 mm²
 1.5...35 mm²
 15 mm
 2...4 Nm

≤ 3.8 kV
 11000 A
 CE; cURus
 EN 50539-11:2013+A1:2014, UL 1449 Ed.4

1100 V
 1500 V
 50 kA
 20 kA
 SPD TYPE 1CA

1500 V
 30 kA
 20 kA
 1500 V
 30 μ A
 ≤ 25 ns
 ≤ 2000 m
 $< 4,000$ m, see operating instructions
 11000 A
 green = OK; red = arrester is defective - replace
 Installation housing; 3TE, Insta IP 20
 black, orange
 -40 °C... 70 °C
 -40 °C... 85 °C

1.5...16 mm²
 1.5...35 mm²
 15 mm
 2...4 Nm

$\leq 5,0$ kV
 11000 A
 CE; cURus
 EN 50539-11:2013+A1:2014, UL 1449 Ed.4

1500 V
 1800 V
 65 kA
 20 kA
 SPD TYPE 1CA

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

no remote sig. contact	with remote signalling (R)
16 / 1.5 / 35	16 / 1.5 / 35
96 / 54 / 70	102 / 54 / 70
No	250 V 1A 1CO

no remote sig. contact	with remote signalling (R)
16 / 1.5 / 35	16 / 1.5 / 35
96 / 54 / 70	102 / 54 / 70
No	250 V 1A 1CO

Ordering data

without remote signalling contact
 with remote signalling contact (R)

Note

Type	Qty.	Order No.
VPU PV II 3 1000	1	2530550000
VPU PV II 3 R 1000	1	2530180000

Type	Qty.	Order No.
VPU PV II 3 1500	1	2530640000
VPU PV II 3 R 1500	1	2530650000

Accessories

Note

Pluggable spare arrester VPU PV II 0 1000-2530660000


Pluggable spare arrester VPU PV II 0 1500-2530630000

Type II surge arrester for use in photovoltaic applications

- Pluggable arrester
- Suitable for protecting DC systems as Type II arrester
- Encapsulated, non-blow-out arrester
- Tested in accordance with EN 50539-11
- Pluggable arresters
- Suitable for use in accordance with IEC 60364-7-712 / EN 50539-12

VPU II 2 PV/R 600 V DC

Photovoltaics



Technical data

Max. continuous voltage, U_c (DC)
 Discharge current I_{max} (8/20 μ s) wire-PE
 Discharge current I_n (8/20 μ s) wire-PE
 PV voltage, acc. to IEC 60364-7-712
 Leakage current at U_n
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

Technical data - photovoltaic

Maximum continuous operating voltage UCPV mode +/-, -/PE, +/-PE
 Protection level U_p mode (+/-)
 Protection level U_p mode (+/PE)
 Protection level U_p mode (-/PE)
 Conditions and requirements
 Short-circuit current I_{SCP}
 PV system voltage, max. U_{SPV}

Approvals

Approvals
 Standards

600 V
 40 kA
 20 kA
 < 600 V
 30 μ A
 ≤ 25 ns
 green = OK; red = arrester is defective - replace
 Installation housing: 2TE, Insta IP 20
 black, orange
 -40 °C...70 °C
 -40 °C...80 °C

1.5...16 mm²
 1.5...50 mm²
 15 mm
 2...3 Nm

600 V DC
 ≤ 4.4 kV
 ≤ 2.2 kV
 ≤ 2.2 kV
 EN 50539-11
 200 A
 600 V

CE; EAC
 EN 50539-11

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

Note

no remote sig. contact with remote signalling (R)

16 / 1.5 / 35 16 / 1.5 / 35
 94 / 35.6 / 69 106 / 35.6 / 69
 No 250 V 1A 1CO

Ordering data

without remote signalling contact
 with remote signalling contact (R)

Type	Qty.	Order No.
VPU II 2 PV 600V DC	1	1351340000
VPU II 2 R PV 600V DC	1	1351370000

Note

Accessories

Note


Pluggable spare arrester VPU II 0 PV 600 V-1351320000



VPU III surge protection for terminal devices

Maximum type III protection from surges

This product line provides an integrated protective strategy for surge protection for end devices. Rail-based mounting installations are especially important for industrial applications. For this reason, the housing design has been adapted to the standardised installation dimensions. The VPU III has a wide array of available functions. A status signal and a connection for the floating contact make the unit easy to service. A defective device can easily be swapped out because of the plug-in connectors. The VPU III covers all standard nominal voltages in the power range: 12 V, 24 V, 48 V, 120 V and 230 V.





Faster to assemble

The optimised mounting rail clip enables easy and quick installation, without the need for tools.



**Best overview**

LEDs provide clearly visible information on the status of the protective function.

**Rapid status messaging**

The remote signalling contact provides reliable information regarding the status of the protective function.



Type III surge protection for end devices

Low-voltage consumer installations, small distribution units and electronics

Surge protection module type III

Our surge protection modules VPU III protects low voltage consumer installations and electronic devices from voltage surges that occur through atmospheric discharge (lightning) or switching activities (transients).

The VPU III can be built into small distribution boards or into multi-floor distribution boards.

The VPU III satisfies the requirements of IEC 61643-11.

Functional check and maintenance

Varistors can exhibit high temperatures as a result of ageing. In low-voltage systems, this can result in fire. The integrated temperature monitoring device automatically disconnects the varistor from the power supply. This disconnection is indicated by the warning lamp being extinguished.

With the VPU III, a switch contact is also fitted for signalling. With the VPU III SO LD, an LED is used to indicate status and with the VPU III SO LD+A a buzzer highlights any error messages.

The back-up fuse you install depends on the conductor cross-section and type of routing. For VPU III arresters, the maximum power rating is 16 A. The connection is rated to IEC 947-7-1 for the following cross-sections:

solid conductor: 0.5...2.5 mm²

flexible conductor: 0.5...2.5 mm²






Electrical connection

The VPU III surge protection device is installed after the VPU II arrester and before the device / consumer to be protected. It can protect electrical circuits of up to 16 A. An installation can be done in a consumer unit for an electrical circuit that protects monitors, for example..

Dimensioned drawing VPU III

Overall width 18 mm



The standard implementation for operating the VPU III products is a series connection to the end device. Under this operational state, the protective device can bear a long-term load of 16 A. For higher demands, parallel circuitry is used




Type III surge protection for terminal devices

Type III with varistors / gas discharge tube

- Type III surge protection
- Suitable for protecting terminals
- Installed in the vicinity of the equipment to be protected
- For mounting on rail TS 35
- Arrester with remote signalling contact
- Tested in accordance with IEC 61643-11


VPU III R 230 V / 6 kV

For use as device protector



VPU III R 120 V / 6 kV

For use as device protector



Technical data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (DC)
Combined pulse U_{oc}
Discharge current, max. (8/20 μ s)
Rated current I_n
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

230 V
300 V
6 kV
3 kA
16 A
T3
1.5 kA
30 μ A
16 A
438 V
≤ 1200 V
≤ 100 ns
Green LED = OK, Red LED = arrester is defective, replace
Installation housing: 1TE, Insta IP 20
orange
-5 °C...40 °C
-40 °C...70 °C

0.5...2.5 mm ²
0.5...2.5 mm ²
7 mm
0.4...0.5 Nm

CE; EAC; OEVE

120 V
150 V
150 V
212 V
6 kV
3 kA
16 A
T3
1.5 kA
30 μ A
16 A
229 V
< 700 V
≤ 100 ns
Green LED = OK, Red LED = arrester is defective, replace
Installation housing: 1TE, Insta IP 20
orange
-5 °C...40 °C
-40 °C...70 °C

0.5...2.5 mm ²
0.5...2.5 mm ²
7 mm
0.4...0.5 Nm

CE; EAC; OEVE

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Screw connection

2.5 / 0.5 / 2.5
102 / 18 / 71.5
250 V 10 A 1 NC

Screw connection

2.5 / 0.5 / 2.5
102 / 18 / 71.5
250 V 10 A 1 NC

Ordering data

Type	Qty.	Order No.
VPU III R 230V/6KV AC	1	1351650000

Note

Type	Qty.	Order No.
VPU III R 120V/6KV AC/DC	1	1351630000

Accessories

Note




Type III with varistors / gas discharge tube

- Type III surge protection
- Suitable for protecting terminals
- Installed in the vicinity of the equipment to be protected
- For mounting on rail TS 35
- Arrester with remote signalling contact
- Tested in accordance with IEC 61643-11


VPU III R 48 V / 4 kV

For use as device protector



VPU III R 24 V / 4 kV

For use as device protector



Technical data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (DC)
Combined pulse U_{oc}
Discharge current, max. (8/20 μ s)
Rated current I_n
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

48 V
68 V
50 V
72 V
4 kV
2 kA
16 A
T3
1.5 kA
30 μ A
16 A
92 V
 ≤ 220 V
 ≤ 100 ns
Green LED = OK, Red LED = arrester is defective, replace
Installation housing: 1TE, Insta IP 20
orange
-5 $^{\circ}$ C...40 $^{\circ}$ C
-40 $^{\circ}$ C...70 $^{\circ}$ C

0.5...2.5 mm²
0.5...2.5 mm²
7 mm
0.4...0.5 Nm

CE; EAC; OEVE

24 V
32 V
32 V
42 V
4 kV
2 kA
16 A
T3
1.5 kA
30 μ A
16 A
46 V
 ≤ 220 V
 ≤ 100 ns
Green LED = OK, Red LED = arrester is defective, replace
Installation housing: 1TE, Insta IP 20
orange
-5 $^{\circ}$ C...40 $^{\circ}$ C
-40 $^{\circ}$ C...70 $^{\circ}$ C

0.5...2.5 mm²
0.5...2.5 mm²
7 mm
0.4...0.5 Nm

CE; EAC; OEVE

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm
Signalling contact

Note

Screw connection

2.5 / 0.5 / 2.5
102 / 18 / 71.5
250 V 10 A 1 NC

Screw connection

2.5 / 0.5 / 2.5
102 / 18 / 71.5
250 V 10 A 1 NC

Ordering data

Screw connection
with acoustic signal (A)
without acoustic signal

Note

Type	Qty.	Order No.
VPU III R 48V/4kV AC/DC	1	1351600000

Type	Qty.	Order No.
VPU III R 24V/4kV AC/DC	1	1351580000

Accessories

Note


Type III surge protection for terminal devices

Type III with varistors / gas discharge tube

- Type III surge protection
- Suitable for protecting terminals
- Installed in the vicinity of the equipment to be protected
- For mounting on rail TS 35
- Arrester with remote signalling contact
- Tested in accordance with IEC 61643-11


VPU III R 12 V / 4 kV

For use as device protector



VPU III SO LD / +A

For use as device protector



Technical data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U_c (AC)
Max. continuous voltage, U_c (DC)
Combined pulse U_{oc}
Discharge current, max. (8/20 μ s)
Rated current I_n
Requirements class, acc. to EN 61643-11
Short-circuit current rating I_{scCR}
Leakage current at U_n
Fuse
Temporary surge voltage (over-voltage) - TOV
Protection level U_p (typ.)
Response time
Optical function display
Design
Colour
Ambient temperature (operational)
Storage temperature

Connection according to IEC 947-7-1

Solid
Stranded
Stripping length
Tightening torque

Approvals

Approvals
Standards

12 V
16 V
20 V
28 V
4 kV
2 kA
16 A
T3
1.5 kA
30 μ A
16 A
23 V
180 V
≤ 100 ns
Green LED = OK, Red LED = arrester is defective, replace
Installation housing: 1TE, Insta IP 20
orange
-5 °C...40 °C
-40 °C...70 °C

0.5...2.5 mm ²
0.5...2.5 mm ²
7 mm
0.4...0.5 Nm

CE; EAC; OEVE

230 V
275 V
3 kV
T3
1.5 kA
30 μ A
16 A
440 V
≤ 0.9 kV
$< 100\mu$ s
Green LED = OK, Red LED = arrester is defective, replace
Flush mounting
black
-25 °C...55 °C
-40 °C...80 °C

...
...
...
...
CE; EAC

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.)	mm ²
Height x width x depth	mm
Signalling contact	

Note

Screw connection

2.5 / 0.5 / 2.5
102 / 18 / 71.5
250 V 10 A 1 NC

Without audible signal with acoustic signal (A)

35 / 12 / 25	35 / 12 / 25
No	No

Cable length approx. 118 mm

Ordering data

Type	Qty.	Order No.
VPU III R 12V/4kV AC/DC	1	1351550000

Note

Type	Qty.	Order No.
VPU III SO LD+A	1	1351700000
VPU III SO LD	1	1351680000

Accessories


Note

Type III with varistors

- Type III surge protection
- Suitable for protecting 3-phase terminals
- Installed in the vicinity of the equipment to be protected
- For mounting on rail
- Arrester with remote signalling contact
- Tested in accordance with IEC 61643-11

VPU III 3 / 280 V

For use as device protector



Technical data

Rated voltage (AC)
 Rated voltage (DC)
 Max. continuous voltage, U_c (AC)
 Max. continuous voltage, U_c (DC)
 Combined pulse U_{dc}
 Discharge current I_{max} (8/20 μ s) wire-PE
 Rated current I_n
 Requirements class, acc. to EN 61643-11
 Short-circuit current rating I_{scCR}
 Leakage current at U_n
 Fuse
 Temporary surge voltage (over-voltage) - TOV
 Protection level U_p (typ.)
 Response time
 Optical function display
 Design
 Colour
 Ambient temperature (operational)
 Storage temperature

230 V
 275 V
 6 kV
 3 kA
 16 A
 T3
 1.5 kA
 30 μ A
 16 A
 440 V
 < 1000 V
 ≤ 100 ns
 Green LED = OK, Red LED = arrester is defective, replace
 Installation housing: 1TE, Insta IP 20
 grey
 -5 °C...40 °C
 -40 °C...70 °C

Connection according to IEC 947-7-1

Solid
 Stranded
 Stripping length
 Tightening torque

0.5...2.5 mm²
 0.5...2.5 mm²
 7 mm
 0.4...0.5 Nm

Approvals

Approvals
 Standards

CE; EAC

Dimensions / Signalling contact info

Clamping range (nominal / min. / max.) mm²
 Height x width x depth mm
 Signalling contact

2.5 / 0.5 / 2.5
 90 / 70 / 57
 250 V 10 A 1 NC

Note

Ordering data

Type	Qty.	Order No.
VPU III 3/280V	1	1393050000

Note

Accessories

Note



V-TEST II


Testing the protective function for all VARITECTOR PU AC and PV products

The surge protection function, when enabled, guarantees reliable protection of devices and systems. The IEC 62305/VDE 0185-305 requires regular testing of overvoltage surge protection devices. That applies to all applications – especially to building infrastructures.

The function of VARITECTOR surge protection devices can be tested with the V-TEST II. The handy, battery-powered device detects the type of surge protection and automatically checks whether the module is at the end of its life. Therefore, your system remains in operation, and you avoid service costs. V-TEST II is easy to use. It comes with a robust enclosure and a charging device. It has a high-quality TFT colour display and can be operated intuitively via a touchscreen.


High flexibility

V-TEST II is powered by rechargeable batteries and is therefore independent of the mains supply. Its flexible use is particularly relevant, as surge protection components are usually distributed at different points in the system.



Consistent testing

V-TEST II tests all components used in surge protection devices. These include gas discharge tubes (GDT), metal oxide varistors (MOV) and transient voltage arresters/Transient Voltage Suppressor (TVS) diodes.

**Automatic recognition**

The overvoltage protection variant is automatically detected by the V-TEST II. This leads to a reduction in operating errors.



VPU accessories

V-TEST II

- Portable, battery-operated testing instrument
- Supplied with flexible plug-in adapter
- Compact design with touchscreen operation



Technical data

Rated voltage	100...240 V AC
Degree of protection	IP 20
Measuring range	U < 1500 V / I = 0.1; 0.5; 1 mA
Standards	IEC 61326-1, IEC 61010-1

Note

Ordering data

Dimensions	
Height x Width x Depth	mm
Ordering data	
Type	
Order No.	
Qty.	
Note	

V-TEST II


205 x 220 x 82	
V-TEST II	
2661040000	
1	

Lightning and surge protection for data interfaces

Lightning and surge protection for data interfaces	Surge protection fundamentals for data signals	C.2
	Surge protection for data interfaces	C.4
	Installation instructions for data interfaces	C.20



Surge protection for data interfaces



“Data transmission” is the name given to the sending of characters, numbers, statuses and measurements between different, decentralised units. Decentralised units are, for example, controls, computers, measuring sensors, actuators, etc. One unit transmits the data, the second unit receives it. This corresponds to the simplest method of data transmission. It is often necessary for one unit to receive data and then send an “answer” back to the other unit. Two data lines in a back-to-back arrangement are required for this, or data lines are combined by providing each end of the data line with a transmitter and receiver.

Structures and properties of networks

There are various options for networking data terminals. We distinguish between star, ring, point-to-point and bus networks.

Star networks

The main unit is located in the centre. The individual data lines then radiate out from this centre to the individual terminals. In this system all data terminals are connected to the central terminal via their own cable.

Ring networks

The computers or data terminals are all connected to each other like a chain by means of, for example, coaxial cable. In this case the data is passed on from one data terminal to the next. Therefore, the entire ring is always under load. The advantage of the ring network is that it can cover a larger area than a star network because the length of the transmission path is only ever the distance between two adjacent data terminals.

Point-to-point networks

These are basically networks between two data terminals that are connected directly with each other, e.g. an RS 232 or RS 422 link.

Bus networks

These are networks based on the parallel connection of modules. All components operate on one and the same line. Therefore, only two/four wires are required for the data bus. If bus cabling includes branches, then we call that a tree structure. Every bus system includes a bus controller that issues “transmission licences” to the individual data terminals.

Transmission media

In order to be able to send any data at all, data lines are necessary:

Two- and three-wire systems

Data transmissions requiring relatively low transmission rates can make use of two-wire systems. For example, an ISDN system acting as an exchange line to a building requires only two wires.

However, there are bus systems which also require only two or three wires.

Four-wire systems

This is the current standard for the majority of corporate data networks. Two wires are used for transmitting data and two for receiving. These cables are well shielded and can transmit data with frequencies of up to 500 MHz over distances of up to 100 m.

Coaxial cable


Sending data via coaxial cables is a rather old technique. This method is too slow and inflexible and only a few businesses are still using such systems. Speeds of up to 12 Mbps are no longer adequate these days. Over longer distances, modern fibre-optic cables have been replacing this technology; these can transmit several hundred Mbps.

Serial interfaces

A serial interface operates with 8 data bits (1 byte). A start bit (low bit) is always sent before the output of a byte, and one or two stop bits (high bits) are appended to the end of the byte. This encryption is critical for the data receiver as it can then detect where each data byte begins and ends. Serial interfaces frequently operate with +5 V (logical 1) and 0 V (logical 0). Advantage: less cabling (only 3 wires). Disadvantage: slow data transmission.

**RS 232**


Serial interface for point-to-point connections up to 20 kbit/s
Voltage signal to earth:
logic 1 (mark) -15 V to -3 V
logic 0 (space) +3 V to +15 V
max. signal level ± 15 V
Lines up to 20 m long depending on transmission rate.



Protection module in terminal housing
VSSC 6 / RS232

Page C.14**RS 422**


Serial uni-directional high-speed interface for up to 10 parallel receivers
Differential voltage signal:
logic 1 (mark) $A-B < -0.3$ V
logic 0 (space) $A-B > +0.3$ V
max. signal level ± 12 V
Lines up to 1200 m long
max. data rate 10 Mbit/s



Protection module in plug-in housing
VSPC / RS485

Page C.8**RS485**


Serial bi-directional high-speed interface for up to 32 subscribers
2- or 4-wire system
Differential voltage signal:
logic 1 (mark) $A-B < -0.3$ V
logic 0 (space) $A-B > +0.3$ V
max. signal level -7 V to +12 V
Lines up to 1200 m long
max. data rate 10 Mbit/s



Protection module in plug-in housing
VSPC / RS485
VSPC / RS485 R

Page C.8
Page C.10

Protection module in terminal housing
VSSC 6 / RS485
VSSC 6 / RS485 DP

Page C.14**COAX**

Protective module for BNC- and N-cables

Page C.18

Protective module for F- and UHF-cables


Page C.19



Surge protection for data interfaces


VSPC 2CL HF - protection for two analogue high-frequency signals

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data


Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I ₁ (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Complete module, direct earthing



Complete module, indirect earthing



Dimensions of complete module (arrester + base element)	no remote sig. contact
Height x width x depth	mm 90 / 17.8 / 69
Note	
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.	

Base elements / base to arresters



Socket, ordering data

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 2CL FG	1	8924270000
Base element, direct earthing	VSPC BASE 2CL	1	8924710000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section.
-------------	---

VSPC 2CL HF - arrester / plug-in components



Ordering data	VSPC 2CL HF 5 V DC	VSPC 2CL HF 12 V DC	VSPC 2CL HF 24 V DC
Rated voltage (AC)			
Rated voltage (DC)	5 V	12 V	24 V
Max. continuous voltage, U _c (AC)			
Max. continuous voltage, U _c (DC)	6.4 V	15 V	28 V
Rated current I _n	450 mA	450 mA	450 mA
Input attenuation	103 MHz	104 MHz	109 MHz
Pulse-reset capacity	≤ 20 ms	≤ 80 ms	≤ 40 ms
Residual voltage, U _p typical	< 800 V	< 800 V	< 800 V
Protection level			
Protection level wire-wire 1kV/μs, type	12 V	25 V	45 V
Protection level wire-wire 8/20 μs, type	12 V	25 V	45 V
Protection level wire-PE 1kV/μs, type	450 V	450 V	450 V
Protection level wire-PE 8/20 μs, type	< 800 V	< 800 V	< 800 V

Ordering data				
without function indicator	Type	VSPC 2CL HF 5VDC	VSPC 2CL HF 12VDC	VSPC 2CL HF 24VDC
	Order No.	8924430000	8924460000	8924510000
	Qty.	1	1	1
Note				






Surge protection for data interfaces


VSPC 2CL HF - protection for two analogue
high-frequency signals with remote alert

- Optional monitoring function with status indicator and alert function
- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional version with floating earth PE connection to avoid voltage potential differences
- Usable in accordance with installations standard IEC 62305
- Tested in accordance with IEC/EN 61643-21: D1,C1,C2,C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data


Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _{imp} (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	45
MTTF	2537
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21, HART-compatible



Complete module, direct earthing, with remote alert



Complete module, indirect earthing, with remote alert



Dimensions of complete module (arrester + base element)	with remote signalling (R)
Height x width x depth	mm 98 / 17.8 / 69

Note	The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.
------	---

Base elements / base to arresters



Socket, ordering data

Description	Type	Qty.	Order No.
Base element, direct earthing with remote contact	VSPC BASE 2CL R	1	8951710000
Base element, indirect earthing with remote contact	VSPC BASE 2CL FG R	1	8951720000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section. Order with VSPC CONTROL UNIT.
------	--

VSPC 2CL HF - arrester / plug-in components
with remote alert



Ordering data		VSPC 2CL HF 5 V DC R	VSPC 2CL HF 12 V DC R	VSPC 2CL HF 24 V DC R
Rated voltage (AC)				
Rated voltage (DC)		5 V	12 V	24 V
Max. continuous voltage, U _c (AC)				
Max. continuous voltage, U _c (DC)		6.4 V	15 V	28 V
Rated current I _N		450 mA	450 mA	450 mA
Signalling contact		U _N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U _N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit	U _N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display		green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace	green = OK; red = arrester is defective - replace
Input attenuation		103 MHz	104 MHz	109 MHz
Pulse-reset capacity		≤ 20 ms	≤ 80 ms	≤ 40 ms
Residual voltage, U _p typical		< 800 V	< 800 V	< 800 V
Protection level				
Protection level wire-wire 1kV/μs, type		12 V	25 V	45 V
Protection level wire-wire 8/20 μs, type		12 V	25 V	45 V
Protection level wire-PE 1kV/μs, type		450 V	450 V	450 V
Protection level wire-PE 8/20 μs, type		< 800 V	< 800 V	< 800 V

Ordering data		VSPC 2CL HF 5VDC R	VSPC 2CL HF 12VDC R	VSPC 2CL HF 24VDC R
with function indicator				
Type		VSPC 2CL HF 5VDC R	VSPC 2CL HF 12VDC R	VSPC 2CL HF 24VDC R
Order No.		8951680000	8951690000	8951700000
Qty.		1	1	1
Note				






Surge protection for data interfaces


VSPC RS 485

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with V-TEST testing device
- Optional monitoring function with status indicator and alert functions
- Low residual voltage
- Version with floating-earth PE connection for avoiding voltage potential differences
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 μ s) and 2.5 kA (10/350 μ s) to PE




Technical data


Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 μ s
Surge current-carrying capacity C2	5 kA 8/20 μ s
Surge current-carrying capacity C3	100 A 10/1000 μ s
Surge current-carrying capacity D1	2.5 kA 10/350 μ s
Discharge current I_{imp} (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	0.2 kA / 2 x 0.2 kA / 0.2 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	57
MTTF	2003
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Complete module, direct earthing



Complete module, indirect earthing



Dimensions of complete module (arrester + base element)		no remote sig. contact
Height x width x depth	mm	90 / 17.8 / 69
Note		
The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.		

Base elements / base to arresters



Socket, ordering data

Description	Type	Qty.	Order No.
Base element, indirect earthing / floating earth FG	VSPC BASE 2CL FG	1	8924270000
Base element, direct earthing	VSPC BASE 2CL	1	8924710000

Note	Technical data can be found at the beginning of the VARITECTOR SPC section.
-------------	---

VSPC RS485 - arrester / plug-in components



Ordering data

Rated voltage (AC)
Rated voltage (DC)
Max. continuous voltage, U _c (AC)
Max. continuous voltage, U _c (DC)
Rated current I _n
Input attenuation
Pulse-reset capacity
Residual voltage, U _p typical
Protection level
Protection level wire-wire 1kV/μs, type
Protection level wire-wire 8/20 μs, type
Protection level wire-PE 1kV/μs, type
Protection level wire-PE 8/20 μs, type

VSPC RS485 2CH	
	5 V
	5 V
	5 V
	6.4 V
	450 mA
	113.6 MHz
	≤ 20 ms
	250 V
	10 V
	15 V
	10 V
	250 V

Ordering data	
without function indicator	Type
	Order No.
	Qty.
Note	


VSPC RS485 2CH
8924670000
1



Surge protection for data interfaces


VSPC RS485 with remote alert

- Pluggable arrester (impedance-neutral plugging/unplugging without interruption)
- Can be tested with the V-TEST testing device
- Optional monitoring function with status indicator and alert functions
- Lower residual voltage
- Version with floating-earth PE connection for avoiding voltage potential differences
- Tested in accordance with IEC 61643-21
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE




Technical data


Volume resistance	2.20 Ω
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C1, C2, C3, D1
Surge current-carrying capacity C1	< 1 kA 8/20 µs
Surge current-carrying capacity C2	5 kA 8/20 µs
Surge current-carrying capacity C3	100 A 10/1000 µs
Surge current-carrying capacity D1	2.5 kA 10/350 µs
Discharge current I _n (8/20 µs) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA / 2.5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	10 kA / 2 x 10 kA / 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	0.2 kA / 2 x 0.2 kA / 0.2 kA
Type of connection	Pluggable in VSPC BASE
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
Failure probability	
Ages	90
MTTF	1266
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Complete module, direct earthing, with remote alert



Complete module, indirect earthing, with remote alert



Dimensions of complete module (arrester + base element) with remote signalling (R)

Height x width x depth mm 98 / 17.8 / 69

Note The associated VSPC base element should be ordered with this. The dimension information provided refers to the complete module.

Base elements / base to arresters



Socket, ordering data

Description	Type	Qty.	Order No.
Base element, direct earthing with remote contact	VSPC BASE 2/4CH R	1	8951790000
Base element, indirect earthing with remote contact	VSPC BASE 2/4CH FG R	1	8951800000

Note Technical data can be found at the beginning of the VARITECTOR SPC section.
Order with VSPC CONTROL UNIT.

VSPC RS485 - arrester / plug-in components
with remote alert



Ordering data

VSPC RS485 2CH R	
Rated voltage (AC)	5 V
Rated voltage (DC)	5 V
Max. continuous voltage, U _c (AC)	5 V
Max. continuous voltage, U _c (DC)	6.4 V
Rated current I _N	450 mA
Signalling contact	U _N 250 V AC 0.1 A 1CO at VSPC R with VSPC control unit
Optical function display	green = OK; red = arrester is defective - replace
Input attenuation	113.6 MHz
Pulse-reset capacity	≤ 20 ms
Residual voltage, U _p typical	250 V
Protection level	
Protection level wire-wire 1kV/μs, type	10 V
Protection level wire-wire 8/20 μs, type	15 V
Protection level wire-PE 1kV/μs, type	10 V
Protection level wire-PE 8/20 μs, type	250 V

Ordering data

with function indicator	Type	VSPC RS485 2CH R
	Order No.	8951670000
	Qty.	1
Note		




Surge protection for data interfaces

V DATA Cat.6 surge protection for four wire pairs with RJ45 socket

- RJ45 connection
- All 4 wire pairs are protected
- Sturdy and compact metal housing
- Suitable for Cat. 5 (up to 100 MHz) and Cat. 6 (up to 250 MHz, Class E)
- Suitable for PoE+ (according to IEEE 802.3at)



C



Technical data

Requirements category acc. to IEC 61643-21	C2, D1
Surge current-carrying capacity C2	10 kA
Surge current-carrying capacity D1	1 kA 10/350 µs
Discharge current I _s (8/20 µs) wire-wire/wire-PE/GND-PE	/ 5 kA
Discharge I _{max} (8/20 µs) wire-wire/wire-PE/GND-PE	/ 10 kA
Lightning test I _{imp} (10/350 µs) wire-wire/wire-PE/GND-PE	/ 1 kA
Humidity	0...95 % (no condensation)
Type of connection	RJ45-Port
Storage temperature	-40 °C...85 °C
Ambient temperature (operational)	-40 °C...80 °C
Net weight	139 g
Protection degree	IP20
Approvals	
Standards	According to IEC61643-21, UL 497B Ed.4

Dimensions of complete module (arrester + base element)

Height x width x depth mm 75 / 19 / 46

Note

Can also be used for Cat. applications 5

V DATA Cat.6 surge protection for four wire pairs
with RJ45 socket


Ordering data	V DATA CAT6
Max. continuous voltage, Uc (AC)	48 V
Rated current I _N	1 A
Insertion loss	≤ 1 dB @ 250 MHz
Protection level U _p (typ.)	≤ 550 V
Frequency range, max.	250
Response time	< 1 ns
Volume resistance	< 0.1 Ω
Wire-wire capacitance @ 1 MHz, 1 Vrms	30 pF
Wire-PE capacitance @ 1 MHz, 1 Vrms	20 pF
Certificate No. (UL)	E311081RAY
Voltage Breakdown (VDC) L-L	53 V - 73 V
Voltage Breakdown (VDC) L-G	72 V - 120 V
Approvals	CE; EAC; UL

Ordering data	
Type	VDATA CAT6
Order No.	1348590000
Qty.	1
Note	





VSSC 6AN RS485, RS485 DP and RS232 –
for interface signals

- Two-stage surge protection with screw connection for RS422/RS485 data interfaces
- Surge protection in terminal block design
- Modular width of only 6.2 mm
- Space-saving design: 1 signal
- Torx® slotted screw connection
- Can be used in compliance with installation standard IEC 62305
- Tested in accordance with IEC 61643-21: D1, C2, C3
- Integrated PE foot, safely discharges up to 20 kA (8/20 µs) and 2.5 kA (10/350 µs) to PE



Technical data

Rated current I_N	500 mA
Volume resistance	1.8 Ω 10 %
Overload - failure mode	Modus 2
Requirements category acc. to IEC 61643-21	C2, C3, D1
Standards	IEC 61643-21
Surge current-carrying capacity C1	
Surge current-carrying capacity C2	2.5 kA 8/20 μ s 5 kV 1.2/50 μ s
Surge current-carrying capacity C3	10 A 10/1000 μ s
Surge current-carrying capacity D1	0.5 kA 10/350 μ s
Discharge current I_t (8/20 μ s) wire-wire/wire-PE/GND-PE	2.5 kA / 2.5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA / 10 kA
Lightning test I_{imp} (10/350 μ s) wire-wire/wire-PE/GND-PE	/ 0.5 kA
Storage temperature	-40 °C...80 °C
Ambient temperature (operational)	-40 °C...70 °C
Protection degree	IP20
UL 94 flammability rating	V-0
Connection data	
Type of connection	Screw connection
Tightening torque	0.5 Nm
Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, stranded, max.	4 mm ²
Wire cross-section, stranded, min.	0.5 mm ²
Stripping length	10 mm
Rail	TS 35
Failure probability	
λ_{ges}	60
MTTF	1903
SIL in compliance with IEC 61508	3
Approvals	
Approvals	CE; CSAEX; EAC; FUSAFETY; OEVE; UL
Standards	IEC 61643-21



Dimensions		Dimensions
Height x width x depth	mm	88.5 / 6.2 / 81
Note		

VSSC 6AN RS485, RS485 DP and RS232

Ordering data	RS485	RS485 DP	RS232
Rated voltage (DC)	12 V	12 V	12 V
Max. continuous voltage, U _c (DC)	15 V	15 V	15 V
Rated current I _N	500 mA	500 mA	500 mA
Input attenuation	113.6 MHz	113.6 MHz	1.4 MHz
Pulse-reset capacity	≤ 15 ms	≤ 15 ms	≤ 15 ms
Residual voltage, U _p typical	≤ 100 V	≤ 100 V	≤ 100 V
Protection level			
Protection level wire-PE 8/20 μs, type	≤ 100 V	≤ 100 V	≤ 100 V

Ordering data			
Type	VSSC6 RS485	VSSC6 RS485 DP	VSSC6 RS232
Order No.	1064980000	1065010000	1064990000
Qty.	10	10	10
Note	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000	End plate AP VSSC6 1063110000



The Concept

The IP20 Solution

Until now, all signal conditioning tasks were carried out by modules designed to IP20. For their own protection, these need to be installed in central switchgear cabinets.

However, decentralised solutions that do not require large switchgear cabinets are increasingly being sought for use in modern-day industrial automation technology.

It is true that shielded signals can be fed to the machinery via powerful fieldbus systems; but in each case, however, there remains an interconnecting cable between the subdistribution boards and the sensors/actuators that is susceptible to interference from surrounding operations. As has always been the case, signals are still influenced by overvoltages and earth loops; interference pulses are superimposed on sensor signals and malfunctions can be initiated.

The result is that signal conditioning modules sealed to IP20 require terminal boxes, such as switchgear cabinets, or even cost-intensive special solutions (for example, sensor-actuator distributors with integrated signal-conditioning functions providing as many functionalities as possible, even when these are surplus to requirements).




Single-stage surge protection

Surge protection protects equipment against surge voltages that can occur as a result of atmospheric discharges or storms. This type of protection, in the form of an adapter plug, is available in IP20 and IP67 versions and complies with the requirements of C 2 of IEC 61643-21.

JPOVP Cat.6 IP20

Ethernet Cat.6



Technical data

Technical data	
Rated voltage	34 V / 48 V
Operating voltage	48 V
Discharge current I_t (8/20 μ s) wire-wire	5 kA
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA
DC Response/dropout Volt	230 V
Response time	≤ 5 ns
Rated current I_n	0.2 A
Protection level	
Protection level wire-wire 1kV/ μ s, type	80 V
Protection level wire-wire 8/20 μ s, type	300 V
Protection level wire-PE 1kV/ μ s, type	130 V
Protection level wire-PE 8/20 μ s, type	600 V
General data	
Ambient temperature (operational)	-25 °C...60 °C
Overvoltage category	III
Pollution degree	2
Type of connection	IP20, RJ45 plug-in connector
Approvals	
Approvals	CE

Rated voltage	34 V / 48 V	
Operating voltage	48 V	
Discharge current I_t (8/20 μ s) wire-wire	5 kA	
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE	10 kA	
DC Response/dropout Volt	230 V	
Response time	≤ 5 ns	
Rated current I_n	0.2 A	
Protection level wire-wire 1kV/ μ s, type	80 V	
Protection level wire-wire 8/20 μ s, type	300 V	
Protection level wire-PE 1kV/ μ s, type	130 V	
Protection level wire-PE 8/20 μ s, type	600 V	
Ambient temperature (operational)	-25 °C...60 °C	
Overvoltage category	III	
Pollution degree	2	
Type of connection	IP20, RJ45 plug-in connector	
Approvals	CE	

Dimensions	
Height x width x depth	mm

53 / 36 / 14.4

Note

Each with 1.5 m cable

Ordering data

Type	Qty.	Order No.
JPOVP RJ45 Cat6 IP20	1	8805550000

Type	Qty.	Order No.
JPOVP RJ45 Cat6 IP20	1	8805550000

Note

--

Accessories

Note

Retaining clip JP CLIP M 8778490000
--

Surge protection for data interfaces

Coax surge protection

Surge protection for COAX data networks

- Metal housings
- Surge protection using gas discharge tube
- Easy handling using socket-adaptor function, with minimal attenuation

BNC Connector / M-F

Protection for video monitoring systems



N Connector / M-F

Protection for transmitters, GSM



C

Technical data

Transmission capacity, max.
 Max. continuous voltage, U_c (DC)
 Characteristic impedance
 Frequency range
 Operating current, I_{max}
 Insertion loss
 Return loss (attenuation)
 Standing wave ratio, VSWR
 Requirements category acc. to IEC 61643-21
 Lightning test current I_{imp} (10/350 μ s)
 Discharge current, max. (8/20 μ s)
 Response time
 Protection level U_p (typ.)
 Earthing
 Type of connection
 Version
 Ambient temperature (operational)

Approvals

Approvals

25 W
 90 V $\pm$ 20 %
 50 Ω
 0...3.5 GHz
 10 A
 < 0.2 dB
 > 20 dB
 < 1.2
 D1, C3, C2, C1
 5 kA
 20 kA
 $\leq$ 100 ns
 < 700 V
 Required with M6 screw
 Plug / socket
 Adapter plug
 -40 °C...80 °C

CE

25 W
 90 V $\pm$ 20 %
 50 Ω
 0...3.5 GHz
 10 A
 < 0.15 dB
 > 20 dB
 < 1.2
 D1, C3, C2, C1
 5 kA
 20 kA
 $\leq$ 100 ns
 < 700 V
 Required with M6 screw
 Plug / socket
 Adapter plug
 -40 °C...80 °C

CE

Dimensions

Height x width

Plug / socket

/ 26

Plug / socket

/ 26

Note

Ordering data

Type	Qty.	Order No.
BNC Connector / M-F	1	8947820000

Type	Qty.	Order No.
N Connector / M-F	1	8947830000


Note

Accessories

Note

Coax surge protection

- Surge protection for COAX data networks
- Metal housings
 - Surge protection using gas discharge tube
 - Easy handling using socket-adaptor function, with minimal attenuation



Technical data


Transmission capacity, max.
Max. continuous voltage, U_c (DC)
Characteristic impedance
Frequency range
Operating current, I_{max}
Insertion loss
Return loss (attenuation)
Standing wave ratio, VSWR
Requirements category acc. to IEC 61643-21
Lightning test current I_{imp} (10/350 μ s)
Discharge current, max. (8/20 μ s)
Response time
Protection level U_p (typ.)
Earthing
Type of connection
Version
Ambient temperature (operational)

Approvals

Approvals

F Connector / M-F

Protection for satellite systems





25 W
 $90\text{ V} \pm 20\%$
75 Ω
0...2 GHz
10 A
< 0.5 dB
> 20 dB
< 1.3
D1, C3, C2, C1
5 kA
20 kA
 $\leq 100\text{ ns}$
< 700 V
Required with M6 screw
Plug / socket
Adapter plug
-40 °C...80 °C

CE

UHF Connector / M-F

Protection for terrestrial TV



0.5 W
75 Ω
0...1 GHz
4 A
< 0.5 dB
> 20 dB
C3, C2, D1
20 kA
< 1 ns
< 600 V
Required with 1.5mm² connection cable
Plug / socket
Adapter plug
-40 °C...80 °C

CE

Dimensions

Height x width

Note

Plug / socket

/ 26

Plug / socket

73.4 / 43

Ordering data

Type	Qty.	Order No.
F Connector / M-F	1	8947840000

Type	Qty.	Order No.
UHF Connector / M-F	1	8947850000

Note

Accessories

Note

Installation instructions for data interfaces

The supply and earth lines of the protective modules should be kept short in order to achieve optimum protection for the data terminals.

Likewise, the transmission paths should also be kept as short as possible because the longer the line, the greater is the chance of interference having an effect.

Inserting surge protection increases the attenuation of the line and so changes the signal-to-noise ratio.

Installation position

Protective modules are frequently installed at both ends of the line.


It is important to ensure that protected and unprotected lines are routed separately. Further, there should be some clearance between power lines and data lines. A common cable duct must be subdivided with metal partitions.

Shielded lines for data interfaces

Systems involving several buildings should be designed with cable shielding capable of carrying current. These data lines often have two shields: one for carrying transient currents, the other as protection against coupled interference.

Circuit concepts

High transmission frequencies place greater demands on surge protection in protective circuits for data interfaces. Gas discharge tubes are frequently the sole means of protection in these cases. However, the disadvantage of this is that the protection level is very high. Lower protection levels can be attained at high transmission frequencies by using special low-capacity suppressor diodes.



Mains filter

Mains filter	WAVEFILTER	D.2
--------------	------------	-----



WAVEFILTER

WAVEFILTERS for simple radio interference suppression in the control cabinet

The WAVEFILTER series eliminates the time consuming work of screwing in mains filters. These filters are simply clipped on to the TS35 rail and connected to the device requiring suppression. The two-stage WAVEFILTER with overall width 22.5 mm in 3 A, 6 A and 10 A versions offers high attenuation.

The WAVEFILTER, with current-compensating choke, is ideal for applications in drive technology and control/automation systems, e.g. for suppressing continuous interference types such as "noise" or "ripple" caused by interfering radiation from other systems, or interference from frequency converters and switch-mode power supplies. A short, low ohm mass connection is required for the WAVEFILTER to function perfectly. We recommend earthing all devices directly with the largest possible cross-section to a central earthing point in the control cabinet.

Interference signals


We distinguish between two types of induced transient and continuous interference signals: symmetrical (differential mode) and asymmetrical (common mode). The symmetrical interference signals generate a voltage between the signal leads of the system. The asymmetrical interference voltages occur between the signal leads and earth.

The WAVEFILTER is suitable for attenuating both kinds of interference signal. In addition, WAVEFILTER 10 A also has an earthing conductor choke. This earthing conductor choke supports both attenuation on the earthing conductor for the filter and additional attenuation of asymmetrical interference voltages.


The WAVEFILTER has cULus approval.

Insertion loss


WAVEFILTER 3 A



WAVEFILTER 6 A



WAVEFILTER 10 A




Installation height 112.4 mm




Installation height 92.4 mm



Dimensions



Dimensions






Mains filter


WAVEFILTER

- Clips to TS 35
- High symmetrical and asymmetrical attenuation
- Suitable for voltages from 5 V to 250 V

WAVEFILTER 3 A 250 V



WAVEFILTER 6 A 250 V



Technical data

Rated voltage
Rated current I_N
Capacitance
Inductance L and L1
Leakage current at U_n
Test voltage P/N-PE
Test voltage P-N
Ambient temperature (operational)

Approvals

Approvals

250 V
3 A
 $C_L / C_{\text{gnd}}: 33\text{nF}$
2 mH
190 μA
2000 V AC
1700 V DC
-20 °C...40 °C

cURus; EAC

250 V
6 A
 $C_L: 33\text{ nF} / C_{\text{gnd}}: 22\text{ nF}$
0.8 mH
190 μA
2000 V AC
1700 V DC
-20 °C...40 °C

cURus; EAC

Dimensions

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm

Note

2.5 / 0.5 / 2.5
73.4 / 22.5 / 73.4

See attenuation curve in the introductory text in Chapter E

2.5 / 0.5 / 2.5
73.4 / 22.5 / 73.4

See attenuation curve in the introductory text in Chapter E

Ordering data

Type	Qty.	Order No.
WAVEFILTER 3A	1	8614780000

Type	Qty.	Order No.
WAVEFILTER 6A	1	8614800000

Note


Accessories

Note

WAVEFILTER

- Clips to TS 35
- High symmetrical and asymmetrical attenuation
- Suitable for voltages from 5 V to 250 V

WAVEFILTER 10 A 250 V



Technical data

Rated voltage
Rated current I_N
Capacitance
Inductance L and L1
Leakage current at U_n
Test voltage P/N-PE
Test voltage P-N
Ambient temperature (operational)

Approvals

Approvals

250 V
10 A
 C_L : 470 nF / C_{end} : 4.7 nF
0.8 mH
190 μ A
2000 V AC
1700 V DC
-20 °C...40 °C

cURus; EAC

Dimensions

Clamping range (nominal / min. / max.) mm²
Height x width x depth mm

Note

2.5 / 0.5 / 2.5
73.4 / 22.5 / 73.4

See attenuation curve in the introductory text in Chapter E

Ordering data

Type	Qty.	Order No.
WAVEFILTER 10A	1	8614770000

Note

Accessories

Note



Surge protection IP67 for intrinsically safe circuits

Surge protection IP67
for intrinsically safe circuits

VARITECTOR Cable Gland (VCG)


E.2

VARITECTOR Cable Gland (VCG)


VARITECTOR Cable Gland (VCG) protect intrinsically safe circuits in IP67 applications

- Tested in accordance with IEC/EN 61643-21
- Suitable for use in EX areas
- High protection class with IP67
- Screw-in housing with different threads

VCG 24 V EX 2



VCG 24 V EX 4



Technical data

Input voltage, max. U_i
Rated voltage (DC)
Rated voltage (DC), max.
Operating current, I_{max}
Frequency range
Insertion loss
Requirements category acc. to IEC 61643-21
Lightning test current, I_{imp} (10/350 μ s) wire-wire
Lightning test current, I_{imp} (10/350 μ s) Wire-PE
Discharge I_{max} (8/20 μ s) wire-wire/wire-PE/GND-PE
Discharge current I_n (8/20 μ s) wire-wire
Discharge current I_{max} (8/20 μ s) wire-PE
Discharge current I_n (8/20 μ s) wire-PE
Response time
Protection level U_p (typ.)
Protection level, U_p wire - wire
Protection level, U_p wire - PE
Dielectric strength at FG against PE
ATEX - gas labelling
ATEX - dust labelling
Input power, max. P_i
Input voltage, max. U_i
Internal inductance, max. L_i
Internal capacity, max. C_i
Protection degree
Version
Design
Ambient temperature (operational)

Approvals

Approvals
Standards

50 V
24 V
33 V
0.8 A
0...30 MHz
30 MHz
D1, C2
1 kA
1 kA
10 kA
5 kA
10 kA
5 kA
< 1 ns
< 1300 V
44 V
864 V
≥ 500 V
18ATEX0141X, II 1GD, Ex ia II T6 Ga, (-30 °C $\leq$ Ta $\leq$ 50 °C)
IEC Ex BAS 18.0085X, Ex ia IIIC T85 °C Da, (-30 °C $\leq$ Ta $\leq$ 50 °C)
2 W
50 V
60 μ H
0 nF
IP67
Stainless steel screw mounting housing
straight, 1/2" NPT; straight, M20 x 1.5; straight, G 1/2 (BSP 1/2)
-30 °C...60 °C

BASATEX; CE; IECExBAS

IEC 61643-21, IEC 60079-0, IEC 60079-11

50 V
24 V
33 V
0.8 A
0...30 MHz
30 MHz
D1, C2
2 kA
2 kA
20 kA
10 kA
10 kA
10 kA
< 1 ns
< 1300 V
44 V
864 V
≥ 500 V
18ATEX0141X, II 1GD, Ex ia II T6 Ga, (-30 °C $\leq$ Ta $\leq$ 50 °C)
IEC Ex BAS 18.0085X, Ex ia IIIC T85 °C Da, (-30 °C $\leq$ Ta $\leq$ 50 °C)
2 W
50 V
60 μ H
0 nF
IP67
Stainless steel screw mounting housing
straight, 1/2" NPT; straight, M20 x 1.5; straight, G 1/2 (BSP 1/2)
-30 °C...60 °C

BASATEX; CE; IECExBAS

IEC 61643-21, IEC 60079-0, IEC 60079-11

Dimensions

Wire connection method / Cross-section
Length

Note

Cable length: 250 mm (min.) / 1 mm ²
78 / 24 mm

Cable length: 250 mm (min.) / 1 mm ²
120 / 24 mm

Ordering data

Type	Qty.	Order No.
VCG 24V EX 2 NPT1/2	1	2593120000
VCG 24V EX 2 M20X1.5	1	2593140000
VCG 24V EX 2 G 1/2	1	2593160000

Note

Type	Qty.	Order No.
VCG 24V EX 4 NPT1/2	1	2593130000
VCG 24V EX 4 M20X1.5	1	2593150000
VCG 24V EX 4 G 1/2	1	2593170000

Accessories

Note

Service and support

Service and support	Our expertise for your requirements	V.2
	Benefit from optimum support when using our products	V.4

Our expertise for your requirements

Service connects - worldwide

Automation technology functions are becoming more complex in a globally-oriented world facing ambitious targets in terms of energy efficiency and smart production. We are your equal partners for the best connections in Industrial Connectivity. Our worldwide network of industrial managers for machine construction, process automation, energy and traffic engineering and for device manufacturers know the challenges you face and can support you in your specific applications.

Training course on technologies, applications and the detailed functionality of our products is available to you locally or at our headquarter in Germany. Our personal support can answer any questions reliably and expertly. Our online services are available 365 day a year around the clock to provide answers to your questions on our products - from user documentation through software to planning tools.

In short: Weidmüller's global service combines our expertise with your requirements.





Professional advice on planning

Our global network of industrial managers has extensive experience in automation technology and electrical connectivity. This expertise allows us to assist you with advice and planning support in order to work with you on resolving the everyday challenges of your applications.



Technology and application training

Industrial automation is moving towards smart production. It faces the challenges of new technologies and applications. Our varied range of training courses develops this knowledge further or provides more in-depth information on the handling of our products and solutions. Our seminars are modular and can be customised. We can train you and your employees in our academy, on your premises if you wish or online in our webinars at any time.



Customised installation

The challenges for the future are reducing costs and increasing efficiency. This requires intelligent, individual solutions which are tailored to your requirements. We can offer a highly qualified customer-specific production service in our application centre. Whether you need modified products, pre-assembled terminal rails or complete small cabinets: we produce the solutions developed for your application quickly and flexibly.

Online support and downloads

Exactly the right help and information on our solutions and products

If our products are used in your automation technology applications, you need the best possible individual support, from planning through installation to operation.

For every stage of your application, we can offer the right tools and information for our products and solutions. Up-to-date, uncomplicated, comprehensive and around the clock via our service portal at www.weidmueller.com/service.

Fast access to our support and services is available via Weidmüller webcodes. Simply select the service you want on the right hand side, then enter the webcode made up of five digits with a preceding hashtag into the search field in the top right corner of www.weidmueller.com and it will bring up the details you need.



Online and personal support

From planning through installation to operation, we can provide exactly the right help and information for each step of your application based on our solutions and products: up-to-date, uncomplicated and comprehensive, around the clock, online or in person.



Visit our website
for more information

www.weidmueller.com/service

Let's connect.

Engineering Support

As a developer, you need simple processes and system-wide tools. We support you in your development environment with comprehensive data, software tools and interfaces, product selection guides and development samples.



Engineering data

Webcode #01219



Product software

Webcode #01212



Whitepaper for device connectivity

Webcode #11359



Engineering software

Webcode #11377



Product configurators, product selection guides and samples

Webcode #01214

Technical data and downloads

Download all the documents and software relating to our products by simply entering the item number. You can also view our Online Catalogue and research the technical properties of our products.



Find downloads

Webcode #11379




Products in the Online Catalogue

Webcode #01217



Security Advisory Board

Webcode #11424



Product Change Notification

Webcode #11425

Commercial support

Integrate our product data into your commercial system using standardised interfaces or familiarise yourself with the wide range of products in our technical catalogues.



Electronic catalogue in BMECat format and other formats

Webcode #11378



Access our Webshop

Webcode #11382



Technical catalogue in PDF Format

Webcode #01218

More offers in online support and downloads

Not found what you are looking for? We have even more to offer you in online support and downloads.



Approvals, certificates and declaration of conformity

Webcode #11374

Here you will find information on the CE declaration of conformity, on RoHS and REACH and other company related certificates and approvals.

The basics of lightning and surge protection

The basics of lightning and surge protection	The importance of lightning and surge protection	W.2
	What are overvoltages?	W.4
	How do overvoltages occur?	W.5
	How do we achieve surge protection?	W.8
	Surge protection concept	W.9
	Classification and protective zones	W.11
	Lightning protection levels	W.12
	Guidelines SEV 4022	W.13
	Network forms	W.14
	3+1 circuit: universal solution	W.16
	General installation advice	W.18
	Surge protection installation instructions	W.21
	Planning aids	W.27
	Office building with lightning protection	W.28
	Industrial building with lightning protection	W.29
	Components for Surge protection	W.30
	Test criteria	W.33
	Electromagnetic compatibility	W.34
	Questions and answers concerning surge protection	W.36
	Glossary	W.40
	Country-specific standards and directives	W.46
	Summary of standards and regulations	W.48

The importance of lightning and surge protection



Causes of surge voltage	Protection measures described in			Installation of protective devices described in
	DIN V ENV 61024-1	DIN VDE 0185-103	E DIN VDE 0100 Part 443	DIN V VDE V 0100-534: 1999-04
Direct lightning strike	X	X		X
Remote lightning strike		X	X	X
Lightning fields		X		X
Switching operations			X	X

Cost-effective strategies demand an investment in surge protection. Such an investment would only be a fraction of the amount of possible damage. The shut down of a manufacturing plant because of the failure of a controller or the collapse of industrial data transmission can be very costly. But the significant overhead in repairing the problem is not the only factor. You must also take into account the system down times. The lifespan of your components (mean time between failure) will also be shortened. Surge voltages present a significant danger and this can be demonstrated in many other ways than the examples given in damage statistics from property insurers.

All electrical equipment is potentially threatened by surge voltages: this includes free-standing high-voltage switching facilities and also electronic micro-components. For low voltages, this risk is predominant in the fields of power supply, measure and control technology, telecommunications, and data transmission. We therefore work with protective strategies and systems when designing lightning and surge protection. Only an entire system can provide effective protection for all areas of power, signals and data and we offer an ideal form of surge protection for all these applications fields.

Surge protection has become an area of increasing significance. On the one hand, electrical and electronic components continue to get smaller. On the other hand, the levels of automation in the industrial and consumer electronics sectors are continuing to rise.

The safety clearances for insulation decrease as do the tolerance limits. Electronic circuits function at low voltage levels of only several hundred volts. Thus surge voltages can present a significant danger.

The German "Law on electromagnetic compatibility in devices" establishes the proper EMC-compliant design and layout for electrical and electronic devices.

Surge protection is an element of these EMC measures and implementation of this protection is described in a variety of IEC/VDE standards. Such measures can also help in obtaining the CE mark of approval.

To guarantee the safety of consumers, different product standards offer a method for ensuring a global product standard.

For energy protection, there is IEC 61643-11. For protection of measurement and control systems, IEC 61643-21 is relevant. These standards provide the rules which are globally valid for all manufacturers of surge protection components.

The standards also provide helpful support for users. IEC 61643-12 is valid for the installation of energy-protection components and IEC 61643-22 is valid when protecting measurement and control systems. IEC 62305 is the overall guideline for all applications when dealing with lightning and surge protection. This standard covers all the parameters: risk analysis, external and internal lightning protection.

The subject of surge protection is rather complicated and requires special knowledge. Therefore, this catalogue provides you with some helpful information. And if you want to know more, simply contact us. We are happy to help and advise you.

What are overvoltages?

Surges are extremely high voltages that damage or even completely destroy insulation and hence impair or completely disrupt the function of electrical and electronic components of all kinds.

Every electrical component is provided with insulation to isolate the electrical voltage from earth or other voltage-carrying parts. The insulation strength is dependent on the rated voltage and the type of electrical component, as stipulated by the IEC/VDE regulations. It is tested by applying the prescribed voltages for a defined period of time.


If the test voltage is exceeded in operation, the safety effect of the insulation is no longer guaranteed. The component can be damaged or completely ruined. Surges are voltage pulses that are higher than the test voltage, and these could detrimentally affect an electrical component or system. This means that components with a high rated voltage may be capable of withstanding a surge voltage. But components with a lower rated voltage would be very much at risk from the same surge. An overvoltage allowable in an electric motor can spell disaster for an electronic circuit!

Permanently higher voltages also occur with the 50/60 Hz mains frequency. These voltage can be coupled and can also occur as a result of faulty switching operations. The resulting continuous interference voltages are another reason for installing overvoltage protection.

Individual surge pulses, which have a high frequency because of their physical formation, have a current rise that is about ten thousand times steeper compared with 50 Hz voltage. If the current rise time in the 50/60 Hz range is 5 ms, then for an overvoltage it is around 1 μ s.

These surges are designated as “transient” voltages.

This means that they are short-lived, temporary oscillations. Their shape and frequency depends on the impedance of the circuit.



Edge behaviour between a 50 Hz sine wave and surge pulse

How do overvoltages occur?

Surges are primarily caused by:

- Transient switching operations
- Lightning due to atmospheric discharges
- Electrostatic discharges
- Faulty switching operations

Lightning


Bolts of lightning comprise extremely high currents. They can cause a large voltage drop and a large rise in potential, even in well-earthed buildings or systems, despite low earthing resistances.

This can then result in a galvanic, inductive or capacitive coupling of surge voltages within the circuits of electrical or electronic facilities. Any insulation will also be penetrated. So, in reality, there are no electrical isolation methods which provide reliable protection against surge voltages. Analogue converters, relays or opto modules are important for separating potentials, but they are definitely not surge protection components.

A natural lightning strike consists of a main discharge and a time-shifted post discharge. The strength of this second discharge is usually far below the energy level of the main discharge. Both discharges, however, have enough power to cause significant damage.

Our table below shows results from a natural lightning strike and a lightning current generator which simulates a lightning pulse.

The various forms of coupling must be considered in order to understand the effects of lightning.




The discharge curve of natural lightning (red) and a simulated lightning strike from lightning current generator (green)

Conductive coupling




Surges are transferred directly into circuits via common earthing impedances. The magnitude of the overvoltage depends on the amperage of the lightning and the earthing conditions. The frequency and the wave behaviour are mainly determined by the inductance and the speed of the current rise. Even distant lightning strikes can lead to overvoltages in the form of travelling waves, which affect different parts of electrical systems by way of conductive coupling

Inductive coupling



A high-amperage lightning strike generates a strong magnetic field. Starting from here, overvoltages reach nearby circuits by means of an induction effect (e.g. directly earthed conductor, power supply lines, data lines, etc.). According to the transformer principle, the coupling of induced voltages is considerable owing to the high-frequency current di/dt – even when primary and secondary windings consist of only a single winding each, i.e. the inductance is low.


Capacitive coupling



A capacitive coupling of overvoltages is also possible. The high voltage of the lightning generates an electric field with a high field strength. The transport of electrons can cause a capacitive decay to circuits with lower potentials and raise the potential concerned to an overvoltage level.

How do overvoltages occur?

Radiation coupling



Electromagnetic wave fields (E/H field), that also ensue during lightning (distant field condition, E/H field vectors perpendicular to each other), affect conductor structures in such a way that coupled overvoltages must be expected even without direct lightning strikes. Permanent wave fields from strong transmitters are also able to cause coupled interference voltages in lines and circuits.

Switching operations – transients

More often, it is switching operations that cause interference rather than lightning. High-amperage shutdowns in the mains in particular can generate considerable overvoltages (e. g. welding equipment). Switching operations generate overvoltages because, due to their construction, switching contacts that switch the current on or off do not operate in synchronisation with the current zero of an alternating current. This means that in the majority of cases there is a very rapid change of current, from a high value to zero (di/dt). Owing to the impedances in the circuit concerned, this leads to transient overvoltages with high-frequency oscillations and high voltage peaks. These can reach electrical components by conductive, inductive or capacitive means and endanger or damage them. The situation is similar in the case of short-circuits in the mains because these also represent a rapid switching operation.

Electrostatic discharges – ESD


Electrostatic discharges (ESD) caused by frictional charges are well known. You can experience them when getting out of a car or walking across a carpet. These discharges can be over 10,000 volts in strength. We speak of ESD when these discharge to a lower potential. If such a charge strikes, for example, electronic components, then these can be completely ruined. Special care is taken, for example, with ESD issues when manufacturing electronic circuit boards.

Faulty switching operations


Again and again, we experience faulty switching operations in the 50/60 Hz mains. These can be caused by a failed power supply unit controller or incorrect wiring in a panel. The relatively high voltages that can occur as a result also represent dangerous overvoltages. Protection against these is vital.

Description of interference voltages

Surge voltages that occur between live conductors, or between a live conductor and the neutral conductor, are called transverse voltage or symmetric interference [UQ].



Surge voltages that occur between a live conductor and the PE conductor are called longitudinal voltage or asymmetric interference [UL].



The forms of interference voltage

Coupled transient surge voltages are basically either symmetric (differential-mode interference) or asymmetric (common-mode) interferences, which are measured as longitudinal or transverse voltages.

Normal-mode interference (symmetrical interference)

A voltage between supply and return conductor, differential mode voltage/current. Occurs mainly at low interference frequencies in the existing lines. The interference current causes an interference voltage U_Q directly at the interference sink (between the input terminals). With galvanic or inductive coupling, both the effective sources and the interference sources are connected serially. The load and interference sources are connected in series as an inductive (magnetic field) or conductive coupling (common impedance). In symmetrical circuits (non-earthed or virtual potential earthed), the normal-mode interference occurs as symmetrical voltages.

In unsymmetrical circuits (earthed one side), the normal-mode interference occurs as unsymmetrical voltages.

Transverse voltage U_Q (normal-mode voltage)

This is a transient coupled interference between two active conductors. For asymmetric circuits with ground potential, the transverse voltage is equal to the longitudinal voltage [$U_Q = U_L$].

A remedy or limitation may be achieved by twisting the corresponding wires together and shielding or multiple shielding with cable sheath. This reduces the induction of transverse voltages.

Common-mode interference

(unsymmetrical interference)

Voltage between conductor and reference potential (earth), common-mode voltage/current. Mainly caused by a capacitive coupling (electrical field).


Therefore, significant common-mode interference currents only flow at higher interference frequencies. The interference voltage at the potentially susceptible device is caused by different voltage drops at the supply and return conductors (in each case between input terminal and reference earth).

The source of interference can be between a signal wire and reference conductor increase in reference potential between separate earths.

In symmetrical circuits, common-mode interference occurs as asymmetrical voltages between the d.c. offset of the circuit and the reference earth. The forward and return conductors have the same interference voltages compared to the reference ground. In unsymmetrical circuits, common-mode interference occurs as unsymmetrical voltages between the individual conductors and the reference earth.

Longitudinal voltage U_L (common-mode voltage)


A coupled transient interference voltage between an active conductor and the earth potential. As a rule, the longitudinal voltage is higher than the transverse voltage (transverse voltage is lower owing to cable shielding and twisting). Longitudinal voltages caused by lightning currents on cable shielding can assume quite high values, especially in the case of long lines entering a building from the outside.



Consequences

The impedances and stray capacitances are equal in ideal circuits. This means that the currents in the supply and return conductors generated by coupled overvoltages are also equal and so do not generate any interference voltage. However, in practice the impedances and stray capacitances in the supply and return conductors are different. This results in unequal currents which cause different voltages to earth in the supply and return conductors.

This means that the unequal impedances lead to the common-mode voltage becoming, for the most part, a normal-mode voltage because of the dissimilarity in the voltages to earth of the supply and return conductors.



How do we achieve surge protection?

We have to consider surge protection from two points of view:

- General protective measures during the planning and construction of buildings and electrical installations.
- Special protective measures realised by the installation of additional surge protection components.

Planning buildings and electrical installations

Some primary measures to prevent or limit surge voltage damages can be incorporated into buildings and electrical/electronic facilities right from the start. Although such measures can achieve only basic protection, they can save some of the costs involved when it comes to planning an effective, complete protection concept. Beginning with the first phase of construction, it is very important to set up an earthing or equipotential bonding facility of sufficient size. Only this will ensure full equipotential bonding in the event of a malfunction.

Thus when speaking of lightning protection, we only refer to lightning protection equipotential bonding. All cables are connected to the lightning protection equipotential bonding: including the power supply, measurement and control signals, telephone lines, and even the water and gas lines. When planning the electrical installation, care must be taken to ensure that electrical systems with dissimilar rated voltages are kept separate. Corresponding protection zones can then be set up and this leads to cost-savings in the surge protection.


Furthermore, the physical separation or shielding of lines that can influence each other is a good way to achieve maximum electrical isolation. Another good option is to split up the individual phases of three-phase systems corresponding to their functions, e.g. one phase only for the supply to instrumentation and control systems.

Of course, all these primary measures do not achieve complete protection. To do this, you must install additional protective components.

Surge protection components

Surge voltages are kept away from at-risk electrical components by first reducing them to a harmless dimension before they reach the components.

The quick reaction times of surge arresters are used to provide this protection. They must respond during the high-frequency rising phase of the overvoltage, i.e. before a dangerous value has been reached, and quench the overvoltage. The response time lies in the nanoseconds range.



Naturally the surge protection components must be able to withstand very high currents, since a surge can, under certain circumstances, deliver several thousand amperes. At the same time, no excessive (i.e., dangerous) residual voltages should remain, even if the operating current is very high. So surge protection components must exhibit a very low resistance discharge behaviour.

In addition, it is absolutely essential that the surge protection component is very quickly available again in electrical terms after the surge has been quenched by earthing it. This is necessary to ensure that the function of the circuit is guaranteed.

Good surge protection is characterised by:

- Fast response behaviour
- High current-carrying capacity
- Low residual voltage
- Good reactivation time


Weidmüller can supply protective components that fulfil these criteria. Depending on the application, these usually consist of a combination of individual components, as described in the chapter on surge components.

Which combination of protective components is available for the respective application is described in the chapters A, B and C.

It will become clearer, from the set-up of the protective elements, how and where a product is used.


The first protection mechanism is always installed at the building entrance, so that the initial coupling interference can be directly "intercepted" before the sensitive end devices.

Surge protection concept



Fundamental concept of protection

One important aspect of surge protection is the area of power supply and distribution. The procedure is linked to the systematic subdivision prescribed by the protective zones concept and the corresponding coordination of surge arresters. Protection of power supply lines forms the basis for protecting all electrical and electronic equipment right down to the smallest and most sensitive components.




A fundamental requirement for effective surge protection is the presence of properly functioning equipotential bonding to DIN VDE 0100 part 540 in a series, or better still, star or grid arrangement.

DIN VDE 0110 (insulation coordination) divides overvoltage protection for power supplies and power distribution into the following three areas:

1. Power supply

The surge voltage strength of the insulation is 6 kV from the incoming supply to the building – by means of underground cables or overhead lines – right up to the main distribution board (backup fuse and meter cupboard). Owing to the lightning protection zoning concept and the physical circumstances, high-energy overvoltages have to be discharged here.



Surge currents exceeding 200 kA can be generated by cloud-to-ground but also cloud-to-cloud lightning discharges.

As a rule, 50 % of the current is discharged via the lightning protection system and the remaining 50 % is coupled into the conductors and conductive parts in the building and distributed uniformly. The closer a conductor is to the lightning protection system, the greater is the launched voltage (which can exceed 100 kV). The pulse duration can be up to 0.5 ms. These powerful interference pulses are discharged to earth directly at the incoming supply or main distribution board by Type I lightning arresters and limited to voltages below 6 kV. Power follow currents and backup fuse values are just some of the aspects that need to be taken into account here.

Depending on the local circumstances and the discharge currents to be expected, sparkover gaps or varistor surge arresters are used, taking into account the type of network.

If a lightning protection system has been installed, or the power supply is via overhead lines, or buildings or plants are spread over a wide area and individual buildings are sited on elevated ground or open areas, high-capacity Type I arresters should always be employed.

2. Subdistribution

The surge voltage strength of the insulation is 4 kV from the main distribution board up to and including subdistribution boards. Owing to the co-ordinated use of arresters, Type II surge arresters are used here and, if necessary, decoupled from Type I arresters by means of coils. The use of decoupling coils is only necessary when the Type I arresters consist of one sparkover gap and the length of the line between the Type I and Type II arresters is less than 10 m. It is not necessary to decouple Weidmüller Type I and Type II arresters. The pulse currents that occur here are no longer that high because most of the energy has already been absorbed by the Type I arresters. Nevertheless, the line impedances give rise to high interference voltages which must be limited to less than 4 kV by the Type II arresters.


Type II arresters based on varistors are normally installed in the subdistribution board before the residual-current circuit-breakers.

3. Terminals, consumers, sockets

The surge voltage strength of the insulation is 2.5 kV from the subdistribution board to the electrical consumer. Surge arresters in Type III are used for this purpose. Depending on the application, they can be used as protective components or in composite switching together with gas discharge tubes, varistors, suppressor diodes and decoupling elements. These arresters are best installed directly before the device to be protected. This can be in a socket or trailing socket (on extension lead) but also in the terminal or junction box of the device itself.

To protect against permanent interference such as "ripples" or "noise" caused by other systems, additional filter circuits are available for the voltage supplies to devices. The insulation of the electrical consumer itself has a surge voltage strength of 1.5 kV.

Principle for selecting arresters according to IEC 60664-1 (DIN VDE 0110-1)



Classification and protective zones

The requirements placed on surge protection and the necessary tests for surge protection components are stipulated by national and international standards. A product can only be considered safe after the product has been fully tested.

For rated voltages up to 1000 V AC, the standards are valid for the manufacturers of surge protection devices and the installers of the surge protection within the facility or system. This catalogue contains a list of valid standards for your reference.


The insulation coordination for electrical equipment in low-voltage systems to IEC 60664-1 (IEC 60664-1) is critical for the design of a surge protection solution. This specifies different dielectric strengths within electrical systems. Based on this, individual lightning protection zones can be set up according to IEC/EN 62305-3.

Lightning protection zones

A protective zone is characterised by a fully earthed envelope. In other words, it has an enclosing shield which enables full equipotential bonding. This shielding can be formed by building materials such as metal facades or metal reinforcements. Lines that pass through this shield must be protected with arresters in such a way that a prescribed protection level is achieved. Further protective zones can be set up inside such a protective zone. Additional protective zones that only have to be fused below the higher-level protection zone's insulation strength can be set up inside such a protective zone.

This leads to a co-ordinated protection level for the objects to be protected. Not every individual section has to be protected with the maximum protection level (e.g. against lightning). Instead, the individual protective zones guarantee that a certain overvoltage level is not exceeded and hence cannot infiltrate that zone.

This leads to economic protection concepts with respect to the capital outlay for protective components.



Classification

Originally, the arrestors were classified according to coarse, medium and fine protection. These arrestors were designated classes B, C and D in DIN VDE 0675 Part 6 / A1. There was also a class A for external arresters (e.g. for low-voltage overhead lines); however, this class has now been abolished. IEC 61643-11 classifies the protective zones as Types I, II and III.




Comparison of surge protection classifications. Many national standards, e.g. in Austria, are derived from the aforementioned VDE or IEC standards.

Formerly DIN VDE 0675 Part 6 / A1	New IEC 61 643-11
Arresters of requirements class B, lightning protection equipotential bonding to DIN VDE 0185 part 1 ("B arresters")	"Type I" arresters
Arresters of requirements class C, surge protection in permanent installations, surge withstand voltage category (surge cat.) III ("C arresters")	"Type II" arresters
Arresters of requirements class D, surge protection in mobile/permanent installations, surge withstand voltage category (surge cat.) II ("D arresters")	"Type III" arresters

At Weidmüller, we make sure that all our surge protection products are tested by an independent testing lab for compliance with the relevant product standards. This is documented by test reports and corresponding test certificates.

Lightning protection levels

Lightning protection levels (LPL)



The lightning protection level applies only to the pulse current 10/350 or to Type I.

Lightning protection level I

Lightning protection level I covers a pulse of 200 kA. This is the worst-case scenario of a direct strike. This pertains to external lightning protection facilities.

Half of this pulse is conducted to the earth and the other half is conducted to the section of the facility that is conductive. If only a four-wire system is available, then a current of 25 kA is distributed to each wire. For a five-wire system, that would correspond to 20 kA.

This lightning protection class covers multiple areas, including: petrochemical facilities (Ex-zones) and explosive material depots.

Lightning protection level II

Lightning protection level II covers a pulse of 150 kA. This pertains to external lightning protection facilities. Half of this pulse is conducted to the earth and the other half is conducted to that section of the facility that is conductive.

If only a four-wire system is available, then a current of 19 kA is distributed to each wire. For a five-wire system, that would correspond to 15 kA.

This lightning protection class covers multiple areas, including: parts of hospitals, shipping warehouses with fire alarm systems and telecommunication towers.

Lightning protection level III/IV

Lightning protection level III covers a pulse of 100 kA.

This pertains to external lightning protection facilities.

Half of this pulse is conducted to the earth and the other half is conducted to that section of the facility that is conductive.

If only a four-wire system is available, then a current of 12.5 kA is distributed to each wire. For a five-wire system, that calculates to 10 kA. The 12.5 kA value is also used here. About 80% of all applications are covered by lightning protection class III. This includes houses, homes, administrative buildings, industrial facilities and so on.

Table 2.2.1**Buildings requiring lightning protection, lightning protection levels, control intervals**

Building, facility, zone, areas	Lightning protection level	Control intervals (years)
a Buildings that have rooms with a large number of occupants (e.g. theatres, concert halls, dance halls, cinemas, multi-purpose sporting/exhibition arenas, retail stores, restaurants, churches, schools, transportation facilities such as railway stations and similar sites of public assembly, including the associated buildings, which can be adversely affected by a lightning strike); Note Especially multi-purpose sports/exhibition arenas, theatres, cinemas, restaurants and similar sites with rooms where there could be 100 or more persons; sales sites with a total sales area of less than 1,200 m ² , if the calculated number exceeds 100 persons, sales sites with a total sales area of more than 1,200 m ² .	II	10
b Accommodation facilities (e.g. hotels, nursing homes, institutions, hospitals, prisons, military barracks); Note Especially hospitals, nursing homes where there are permanently or temporarily 10 or more persons who depend on outside help; especially hotels, inns and boarding houses where there are permanently or temporarily 15 or more persons that do not depend on outside help.	II	10
c Particularly tall buildings, including the adjoining buildings of normal height; high-rise buildings used as residential and commercial buildings, high chimneys and towers (church steeples). Note Buildings which are considered tall according to building legislation or where the top floor is more than 22 metres above the surrounding terrain serviced by firemen or where the eaves have a height of more than 25 metres.	III II	10 10
d Buildings made from combustible materials with a total volume of more than 3,000 m ³ ;	III	10
e Large agricultural and operational buildings (more than 3,000 m ³) including the adjoining silos and adjacent residential buildings which could be adversely affected by a lightning strike; fermenting facilities or biogas plants;	III	10
f Industrial and commercial buildings in high-risk areas (such as plants and equipment where flammable or explosive materials are handled or stored), wood processing factories, mills, chemical plants, textile and plastics factories, explosives and ammunition depots, pipelines, gas stations; – Areas at risk of fire – Explosion-risk zones under a roof	II – I II I	10 - 3 10 3
g Containers for flammable or explosive substances (such as flammable liquids or gases), warehouses for solid or liquid fuels and associated buildings and facilities (e.g. machine buildings, gas stations, storage buildings with filling equipment);		
h Buildings and facilities which house content with special value items (e.g. archives, museums, collections);	II	10
i Buildings and facilities which house sensitive technical equipment (e.g. IT and telecommunications facilities); Data centres;	II	10
j Buildings and installations in exposed topographic positions (e.g. free-standing building [alpine huts] in the mountains	III – I	10 – 3

Extract from the guidelines of the SEV 4022 Lightning Protection Systems 2008; please follow the installation regulations and standards in the individual countries.

W



Network forms to DIN VDE 0100-100 (IEC 60364-1)

The letters in this table describe the earthing conditions:


1st letter Earthing at current source	2nd letter Earthing of exposed conductive parts of electrical installation	3rd letter Routing of N and PE conductor (only applies to TN systems)
T- Direct earthing of current source (of transformer)	T- Exposed conductive parts of electrical installation are earthed directly	C- "Combined" N conductor and PE conductor are routed together as PEN conductor from current source into electrical installation
I- Insulated structure of current source	N- Exposed conductive parts of electrical installation are connected to earth of current source	S- "Separate" N conductor and PE conductor are routed separately from current source to exposed conductive parts of electrical installation

Four-conductor systems:

Still valid according to VDE but unfavourable for information technology systems from the point of view of EMC (VDE 0100-444 / -540).


TN-C systems ("classic earthing")

Neutral conductor and protective earth conductor functions are combined throughout the network in a single conductor, the PEN conductor.



TN-C-S systems ("modern earthing")

Neutral conductor, PEN conductor and equipotential bonding system are connected once at the main distribution board or after the incoming supply to the building. Therefore, a TN-C system becomes a TN-S system (TN-C-S system) from this point onwards.




Five-conductor systems:


The neutral point of the supply source is earthed (N and PE). Both conductors must be laid separately and insulated from the incoming supply onwards. In these systems the PE (protective earth conductor) does not carry any operating current but instead only discharge currents.

TN-S systems

Neutral conductor and protective earth conductor are separated throughout the network.

**TT systems**


One point is earthed directly (operational earth). The exposed conductive parts of the electrical installation are connected to earth lines separate from the operational earth.

**Special system:**

Used, for example, in medical applications

IT systems

There is no direct connection between active conductors and earthed parts. The exposed conductive parts of the electrical installation are earthed.



Surge protection with 3+1 circuitry in consumer loads with TT power systems

3+1 does not always equal 4! At least not in the case of protective circuits with arresters in a TT system.

In a TT system the supply is via the three phase conductors L1, L2 and L3 and the neutral conductor N, i.e. without an additional integral PE conductor. The equipotential bonding is then made separately within the consumer installation through the earthing. The outcome of this is that the neutral conductor can accommodate a higher voltage compared to the earth potential. Therefore, to protect against overvoltages between neutral conductor and earth potential, an arrester must be incorporated here as well.


The "four-arrester circuit" does not satisfy all safety aspects. Up to now, four arresters, i.e. one each between earth potential and L1, L2, L3 and N, were installed in consumer installations with TT systems. However, this "four-arrester circuit" is no longer regarded as the optimum solution because the physical characteristics of the varistors used may lead to unacceptably high touch voltages at the PE conductor in the consumer installation. Depending on the age of the system, leakage currents can flow through varistors and cause overvoltages via the earthing resistance.

The downstream RCD-(Fi) circuit breaker found in TT systems cannot detect such leakage currents. Therefore it cannot trigger. Furthermore, a failed, i.e. low-resistance, varistor would create a connection between N and PE. One remedy is to install an arrester disconnecter in sequence with the varistors. But an arrester disconnecter that monitors the varistors takes up space and costs extra.

If instead of varistors, sparkover gaps were to be arranged between the conductors and the equipotential bonding, then that, too, would not be an ideal solution. The longer time to sparkover and the characteristics of the sparkover gaps result in higher residual voltages.

The 3+1 circuit includes varistors with the three L conductors and the N conductor, and a sparkover gap between the base of the three varistors at the N conductor and the equipotential bonding rail (PE). The size of the sparkover gap must be such that it can accommodate the total current of the three phase conductors and the neutral conductor. The sparkover voltage of the sparkover gap in 230 V systems should be 1.5...2 kV.

TN-S system




The sparkover gap isolates the three varistors electrically from the PE so that leakage currents through the varistors cannot cause voltage increases at the PE. The residual-current circuit-breaker behind the 3+1 circuit then provides reliable protection against hazardous touch voltages in all situations.

In terms of its relevance for safety aspects, the 3+1 circuit described in VDE 0100 part 534 (section 534.2.2) (HD 60364-5-534) can therefore be regarded as a solution for surge protection in TT systems.

Note: Although the “four-arrester circuit”, i.e. with one varistor each between earth potential and L1, L2, L3 and N, is prescribed in VDE 0100 part 534 (section 524.2.1) for consumer installations in TN-S systems, the 3+1 circuit would also be possible here without increasing the risk. In ÖVE/ÖNORM E 8001-1/A2:2003-11-01, the 3+1 circuit is already expressly listed for use in TN-S and TT systems.

TT system



General installation advice

Many details have to be taken into account during the installation of surge protection and the electrical system in order to achieve optimum protection.

Arrangement and subdivision of electrical panel

Steel cabinets possess good magnetic shielding properties. The following points should be taken into consideration during the installation:

- Avoid unnecessarily long lines (particularly lines with a high volume of data traffic).
- Route sensitive signalling lines separately from lines with a high interference potential.
- Route shielded lines directly to the equipment and connect the shielding there (do not connect via additional terminal in switching cabinet).
- Classify equipment in groups with different sensitivities and place these together.

Place of installation

The surge protection devices should be mounted where the lines and cables enter the cabinet. This is the lowest mounting rail directly above the cable entries. This prevents interference being coupled within the cabinet; interference is discharged right at the entry to the cabinet. When using shielded lines, these can be connected at this point by using Weidmüller clamp straps.


Routing the lines

Signalling lines should be laid within the system/cabinet over the shortest route to the surge protection and then continue to the connected equipment. Protected and unprotected lines should be routed separately. The earth line should be regarded as an unprotected line. Metal partitions can be used along cable routes or in cable ducts to achieve this separation. If signalling lines are laid parallel to power lines, a clearance of min. 500 mm must be maintained. The best shielding offers metallic cable conduits along with a metal cover.

Earthing of products and connected products


All surge protection devices have an earth-connection terminal point. The earthing wire for the associated equipotential bonding rail must be connected to this point. The earthing wire should have as large a cross-section as possible and also be as short as possible. Every centimetre of extra cable length increases the residual voltage of the surge protection device (1 metre / 39 inch of cable = 1 kV voltage drop). In addition to the earthing terminal, the surge protection products for measurement control systems also offer the option of earthing via a DIN rail contact on a TS 35. In order to achieve the best earth contact, the rail should be mounted to an earthed metal back wall. In order to obtain a lower protection level, the earthing terminal on the surge protection products (for measurement and control systems) should be connected to the equipotential bonding every 60 cm / 24 inch. According to IEC 62305, the PE connection and the SPD spur may only be 0.5 m / 20 inch to the lightning protection equipotential bonding. It is possible to make the path as short as possible by using a so-called V-connection or by connecting to the accompanying PE.

Cable lengths




It is valid:

$a + c \leq 0.5 \text{ m} / 20 \text{ inch}$
 $a + c \leq 0.5 \text{ m} / 20 \text{ inch}$,
 then b is not relevant



$a + b \leq 0.5 \text{ m} / 20 \text{ inch}$




$b \leq 0.5 \text{ m} / 20 \text{ inch}$


Fuse protection

Surge protection devices for instrumentation and control systems frequently operate with a decoupling between the components. This decoupling is carried out using inductors or resistors. The decoupling dictates the cable type, cable routing and also a fusing for the maximum nominal current of the surge protection devices. The fusing for the VPU series on the power supply side must be installed in accordance with DIN VDE 0298 part 4 (cross section, quantity, type of conductor and the type of installation). This information is documented in the package insert and on the products for the corresponding VPU modules. In the event of overloads caused by partial lightning currents or transformer short circuits, the lightning arrester and surge arrester (SPD) must be protected by a back-up fuse if F1 is greater than the value specified by the manufacturer. In compliance with the ratio 1:1.6, the maximum nominal value should be configured for the SPD. Depending on the installation of the connecting cables, F1 can be increased during the lifespan of the facility. If a circuit breaker or a main circuit breaker is used instead of the safety fuse required in the installation instructions, then the triggering characteristics must be followed. An equivalent main circuit breaker (MCB) can be used instead of the fuse. In normative terms, however, a test is only carried out in combination with the SPD and the fuse.

Lightning current strength of NH fuses for surge currents 10/350 μ s





Lightning current strength of NH fuses for surge currents 8/20 μ s



Behaviour of NH fuses for lightning surge current (10/350 μ s)

It is important to understand that the question is not how small the SPD fusing should be; rather the maximum back-up fuse that should be used, as the capacity of the small fuses to carry lightning current is very limited. Unrestricted SPD protection is only available when the installation accommodates the maximum value.

Nominal current and design



Installation site of the lightning and surge protection products

VARITECTOR PU meets the new regulations of the installation and surge protection standard DIN VDE 0100-443 and -534

The new regulations of the installation and surge protection standard have applied since 1 October 2016. These new standards must be taken into consideration in ongoing plans for buildings to be completed after January 2019 and in new electrical planning.

Regulated:

- DIN VDE 0100-443 describes when surge protection must be installed.
- DIN VDE 0100-534 describes the protective measures that must be implemented.

New regulations in DIN VDE 0100-443

Surge protection is obligatory in all newly planned buildings

With the new regulation, the installation of surge protection devices is now also required for transient surge voltages, which have an effect on:

- New: Large crowds of people - e.g. in large (residential) buildings, churches, schools and offices.
- New: individuals, e.g. in residential buildings and small offices if these buildings contain equipment in category I or II (e.g. household appliances, portable tools and sensitive electrical devices)

As a result of this revised standard, surge protection must now be installed in all newly planned buildings, i.e. private residential buildings, housing communities, functional buildings, etc.



Consideration of self-generated switching surge voltages

Even intrinsic switching surge voltages have been included in the standard for the first time. Intrinsic switching surge voltages can be generated by the following devices:

- Switching of highly inductive, capacitive loads like air-conditioning systems, converters, lifts, etc.
- Switching of high load currents like flow heaters, corridor lighting, crane systems, charging stations for electric vehicles, etc.
- Switching a generator feed, CHP unit, etc.

The surge protection previously required was only installed if faults occurred on the mains side.

Overhead power supply

As soon as an overhead line network is routed to or near the building, the new regulation now requires the installation of surge protection.


New regulations in DIN VDE 0100-534

Installation location of the surge protection device

For effective protection, the surge protection must be fitted by the installer as close as possible to the feed point for the electrical system. For a residential building, for example, this is directly at the mains infeed in the bottom connection area of the meter cabinet. Potential intrinsic sources of interference within the building must also be taken into consideration. In this case, too, the surge protection must be installed as close as possible to the cause.

Protective range of surge protection devices


For the first time, the maximum distance is now defined between a surge protection arrester and the devices to be protected (effective protection range). The cable length should be ≤ 10 m. If this distance cannot be maintained, an additional surge protection arrester must be fitted as close as possible to the device to be protected. In addition, the installation conditions have been tightened, so that the maximum cable length for surge protection must now be ≤ 0.5 m.




The rule:

$$a + c \leq 0.5 \text{ m}$$

$A + c \leq 0.5 \text{ m}$, then b is not relevant



$$a + b \leq 0.5 \text{ m} / 20 \text{ inch}$$



$$b \leq 0.5 \text{ m} / 20 \text{ inch}$$

Installation instructions for Weidmüller's VPU AC I, VPU AC II and VPU III lightning/surge protection in power grids

Surge protection should only be installed by trained personnel. Please follow all local regulations concerning connection methods during the installation.



All arresters must be installed by a qualified electrician. In addition, the VPU I LCF leakage current free arresters can be installed in the pre-metering area. VDE 0100 part 534, „Selection and installation of equipment“ describes the construction of facilities with surge protection equipment.

This is related to the following standards:

a. IEC 60364-4-43:

“Protection for surge voltages from atmospheric origins and from switching operations”

b. IEC 60364-5-53:

“Selection and installation of electrical equipment”

c. IEC 61024-1:

“Protection of buildings against lightning strikes”

d. IEC 61312-1:

“Protection against lightning electromagnetic pulses”

1 Application


Type I VPU I lightning protection and the Type II VPU II surge protection are used to protect low-voltage consumer installations and electronic devices against surge voltages that may arise as a result of atmospheric discharges (thunderstorms) or switching operations.

The VPU I and VPU AC II are Type I/II lightning arresters according to IEC 61643-11, ENV 61024-1 and IEC 1312-1. In the event of a lightning strike, the required equipotential bonding (lightning protection equipotential bonding according to IEC 62305 part 1) between the building lightning protection and the earthing system for the power supply is provided by built-in varistors.

The VPU II complies with Type II of IEC 61643-11. Metal-oxide varistors are used as voltage-limiting components. The VPU III and VPO-DS Type III surge protection for end devices protect low-voltage consumer installations and electronic devices against surges and switching operations. The VPU III or VPO DS is installed in addition to the VPU II in the small distributor, floor distributor, cable conduit, or directly behind the outlet. They meet the requirements of IEC 61643-11 and EN 61643-11.

2 Installation location

The type II arrester must be installed in the meter cabinet or in a distributor in such a way that the terminal compartment is not accessible to unauthorised persons. The type I arrester is installed near the power feed so that there is the required lightning current equipotential bonding between the lightning protection facility and the power distribution system.



3 Electrical connection

The shortest possible cables should be used to connect the class I lightning arrester and the VPU II surge protector with the phase conductors (L1, L2, L3) or the neutral wire (N) and the earth (PE) on the consumer installation. Unprotected cables should never run in parallel with protected cables (You will find sample connections on the removable supplement).

3.1 Connection to the phase conductor and the neutral wire

When connecting cables to the VPU I/VPU II arresters, normally the same wire cross-section is used both for the phase conductors (L1, L2, L3) and the neutral wire (N). If you need to reduce the cross-sections, then a protective device (e.g. a main port fuse) should be used to protect the connecting cables from short circuits. The terminals of the arrester must not be used as branch terminals.

The back-up fuse for the VPU AC II and for the VPU AC I can be selected up to 315 A.

Notes:

In the TN-CS power grid, 3-pole type II are used (on the TN-C side). If the PEN conductor uses a separate PE and N, then a 4-pole arrester should be used (on the TN-S side). According to DIN VDE 0100-534/A1, a VPU AC II 3+1 300 V protector can be installed in a TT mains system type. For an IT grid with a 400-V phase-wire voltage, the VPU AC II 4 480 V is installed.


3.2 Connection to the earth

The earthing wire of the arrester is connected via the shortest path to the earthing system of the consumer installation. Longer connecting cables reduce the effectiveness of the surge protection. They should not be routed in parallel to other cables. An equipotential bonding rail is available as a connection point in electrical consumer systems with equipotential bonding. You must be certain that the earthing for the arrester is connected to the earthing system of the consumer installation.

In TN power grids, the PEN conductor and the earthing line of the arrester should be connected to each other. The PEN conductor from the electrical utility may not be used as the earth.

If the PE or PEN rail on a distributor is used as the earthing terminal, then the rail must be connected via a separate earth wire to the earthing system of the consumer installation.

Two ground terminals are provided in the type I arrester. Both terminal points must be connected. One leads to the equipotential bonding connection on the building and the other leads to the PE conductor on the installation. For Type I lightning arresters, a conductor for carrying lightning current must be used that is at least 16 mm². A minimum cross-section of 6 mm² is required with Type II surge protection.



4 Installation of surge protection for end devices (Type III arresters)

The VPU III or VPO-DS arrester is installed together with and after the VPU II. The VPU III or VPO DS is built into the cable that is to be protected. It can then protect a circuit up to 16 A. The VPU III can be installed in small distribution boards for one circuit (e.g. for protecting monitors). The VPO DS can be installed in devices or in cable conduits on-site.



5 Functional check

It is important to visually inspect VPU lightning arresters and surge protectors, especially during stormy weather. If the colour of the viewing window changes or if the LED is red, then the SPD must be replaced. As the varistors get older, the temperature of the varistors may increase. In low-voltage networks this can lead to fire. Therefore all SPDs have a built-in temperature monitoring mechanism that isolates the varistor automatically from the power supply in the event of danger. A signal or LED indicates that it has been switched off. An additional switching contact (remote signalling contact) reports this separation (this is labelled with R in all product designations). The functionality of all VPU modules can be tested using testing equipment (such as the V-TEST), which is available separately.

5.1 Replacements

When an arrester has a red window (as described by point 5) or a red LED, then the arrester should be replaced by a qualified electrician. The individual Type I-II arresters are pluggable and coded for voltage.

For the insulation resistance test, the SPD must be disconnected from the facility during the duration of the measurement (e.g. by pulling out the upper sections) or the arresters are disconnected from the power network. Weidmüller provides special notice stickers for the electrical cabinet (order number 1287670000) for this purpose. A proper arrester that matches the nominal voltage must be re-installed.

6 Connecting the remote signalling (R)

The signal contact is designed as a change-over (CO) contact. It is connected to terminals 11 and 14. Terminals 11/12 are in normal operation (window is green) closed and terminals 11/14 are open. In the event of an error (red box), the connecting terminals 11/14 are closed and 11/12 are open.

For the VPU III, the response of the isolating mechanism is signalled when a non-reversible thermal fuse opens. The alert circuit is connected using cables with a maximum cross-section of 1.5 mm². The connecting cables must not be run parallel to the earthing cable. A protective circuit using fine surge protection (Type III) according to the voltage level can reduce interference on and in the evaluation device.

7 Back-up fuse

The lightning and surge protection devices of Class I and Class II behave passively during normal operation. No current is drawn. This provides the necessary protection against short circuits and overloads by using a fuse that is designed for the installation method and the cross-section of the connected cable. The VPU product series is also tested with a maximum back-up fuse. This back-up fuse is listed in the technical specifications or the side label on the product. If the fuse used in the system has a smaller or equal value, then it can be used for cable protection on the power feed. If the power-feed fuse has a value greater than the fuse specified in the technical specifications, additional fuses must be integrated depending on the connecting cable in the wiring harness of the VPU module. Remember that the fuse for the wiring harness is also capable of carrying a lightning current. This fuse should not be too small which would make the SPD ineffective during an actual power surge.

8 Application

VPU I LCF, VPU I and VPU AC I establish the required lightning protection equipotential bonding for existing lightning protection systems and power feeds.

The encapsulated VPU I LCF, VPU I and VPU AC I are preferably used in the distributors in building installations. The VPU I LCF products can be used before the meter, as they do not cause leakage current during operation. VPU I LCF, VPU I and VPU AC I are tested both as lightning protection and surge protection, i.e. permissible for type I and type II, whereby VPU II and VPU AC II surge protection is approved for type II and III, i.e. surge voltage protection and terminal device surge protection.

VPU III is type III terminal device surge protection

9 Approvals

All products bear the CE mark.

10 A brief overview of the installation standard for lightning and surge protection

Based on VDE 0100-534, derived from the IEC 60364-5-53 standard. This standard specifies the surge protection (Type I or II) that should be installed.

The IEC 60364-5-534 standard may not be the same as the adopted standards from each country. The country-specific standards and application-based standards or rules must be observed during the installation. The installation must be carried out by locally licensed professionals.

The VDE 0100-534 distinguishes between the connection diagrams **A**, **B** and **C**.

The following is derived in actual practice:

A = 3+0 circuitry

B = 4+0 circuitry

C = 3+1 circuitry

Surge protection installation instructions

VDE 0100-534 now states that there should be a gap of ≤ 0.5 m between the SPD in the vicinity of the installation location and the direct connection to N or PE.


IEC 60364-5-534 specifies that the earth must be established from the SPD to the equipotential bonding rail or to PE – whichever is the shortest connection.

Both cables are specified in the VDE.

During the insulation test, the SPD must be isolated from the facility for the duration of the measurement.


Establishing SPDs after an RCD is only permitted under special preconditions.

Protection against surge currents




The F2 fuse ensures protection against SPD short circuits. These fuses should be chosen based on the rated currents listed in the installation instructions from the SPD manufacturer. The F2 fuse does not need to be used when the characteristics of the F1 fuse (which is part of the electrical facility) correspond to a combination of the rated currents specified by the SPD manufacturer.

Planning aids



VPU product selection assistant

Simply and quickly find the suitable VPU products for your application using our product selection assistant. You will find the product selection assistant at galaxy.weidmueller.com.




Tender specification sheets for surge protection

You will find current tender specification sheets at catalog.weidmueller.com. You are shown current specifications and data for your planning activities in the product view of the "Tender specification sheets" menu item.

Tender specification sheets	
Long specification	Multi-pole lightning arrester according to the requirements of Class III acc. to IEC 61643-11, EN61643-11:2013. Consisting of V0 material, the arrester provides overvoltage protection in applications acc. to IEC 61643-12. The use of a high-performance varistor meets the inspection requirements for Class II surge protection systems on the basis of the standards. The arrester is installed in the vicinity of the power supply for the equipment that needs protection, in a standard installation/electrical distribution enclosure.
Short specification	Class II arrester with InImax: 20/40 kA suitable for three-phase 230 V TN-S, TT mains systems. Protection level < 1.55 kV. With remote alert Type: Weidmüller VPU II 3+1 R 280 V/40 kA Order no. 1352670000 or equivalent

Applications, installation positions: Application Office building



Power (low-voltage supply)

- 1 Type I** Arresters with sparkover gaps with/without high-power varistors, VPU I LCF
- 2 Type I** Arresters with high-power varistors, VPU I series
- 3 Type II** Arresters with high-power varistors, VPU II series
- 4 Type III** Arresters for installing in subdistribution boards, VPU III series
- 5 Type III** Arresters in the form of plug-in surge protectors, VPU III SO

Data


- 8** Surge protection for data lines, e.g. Ethernet CAT.5

Power and data

- 6 Type III** Arrester VSPC
- 7 Type III** Arrester VSPC


Instrumentation and control equipment

- 9** Surge protection for measurement and control circuits, e.g. VSPC or VSSC



Applications, installation positions:

Application Industrial building



Standards

IEC 61643-11, SPDs connected to low-voltage power distribution systems.
Type I, Type II and Type III products are tested in accordance with this standard.

IEC/EN 62305-1 until 4, Protection against lightning.

This lightning protection standard defines everything to do with internal and external lightning protection. It includes four sections:

- "Protection against Lightning – Part 1: General principles"
- "Protection against Lightning – Part 2: Risk management: assessing the damage risk for buildings and structures"
- "Protection against Lightning – Part 3: Physical damage to structures and life hazard"
- "Protection against Lightning – Part 4: Electrical and electronic systems within structures"

Regulations for installation

IEC 60364-5-53, Electrical installations of buildings – Part 5-53.

(Content in VDE 0100-534). Standard for the installation of low-voltage facilities.

VDE 0800, **VDE 0843-T5**, **VDE 0845** describe the selection and installation for communication electronics.

Guidelines for the SEV lightning protection system SN 4022:2004 and the SEV 4113 foundation earth

	Current
	Telecom
	Gas
	Water

LPZ_{OA}

Unprotected area outside of the building. Direct lightning strike; no shielding against electro-magnetic interference.

LPZ_{OB}

Area protected by lightning protection system. No shielding against LEMP.

W



Components for Surge protection

Surge protection devices (SPDs)

There is no ideal component that can fulfil all the technical requirements of surge protection equally effectively. Instead, we use a variety of components with different physical methods of operation that complement each other; these possess distinct protective effects. Super-fast reaction time, high current-carrying capacity, low residual voltage and long service life cannot be found in one single component.

In practice we use three principal components:

1. **spark gaps**
2. **varistors**
3. **suppression diodes**


Therefore, to optimise the surge protection solution, carefully matched groups of these components are often combined in one protective module.

1. Spark gaps / GDT




Possible types:
Blow-out spark gap
Encapsulated spark gap
Gas-filled spark gap

Pulse form shape without GDT



Pulse form shape with GDT





The name says it all. High voltages are discharged to earth via a spark gap (e.g. gas discharge tube) that has been fired. The discharge capacity of sparkover gaps is very high – up to 100 kA depending on type.

Gas sparkover gaps are incorporated in insulating glass or ceramic (aluminium oxide) housings. The electrodes of the sparkover gap are made from a special alloy and placed in housings which are vacuum sealed and filled with a noble gas such as argon or neon. They are aligned with respect to shape and clearance distance, so that the applied voltage produces a distribution of field strengths. This results in a fairly precise voltage value for the complete ignition of the spark gap. The housings are vacuum-tight and filled with an inert gas such as argon or neon. The spark gap has a bipolar function. The ignition voltage value, however, is dependent on the steepness of the applied surge voltage.

The ignition characteristic curve for gas-filled spark gaps reveals that the ignition voltages increase for those surge voltages which climb more steeply. The consequence is that, for very steep surge voltages, the ignition voltage (that is, the protection level) is relatively high and can be well in excess of the rated voltage for the spark gap (approx. 600–800 V). The problematic quenching behaviour of the fired sparkover gap can be a disadvantage. The arc has a very low voltage and is only extinguished when the value drops below this. Therefore, when designing the geometry of a sparkover gap, care is taken to ensure that – through long distances and also through cooling – the voltage of the arc remains as high as possible and so is quenched relatively quickly. Nevertheless, a longer follow current can ensue. This can draw its energy, in addition, from the incoming supply of the circuit to be protected. One effective solution is to wire a sparkover gap and a fast-acting fusible link in series.

2. Varistors / MOV





The varistors used with surge protection (MOV-Metal Oxide Varistors) have resistance which depends on the voltage. This is implemented with metal-oxide (zinc-oxide) discs. There is a low-ohm resistance in the range above the rated voltage. The surge voltage is limited since a current flows through the varistor. The varistor works bi-directionally. Depending on the type, varistors have either a middle or high discharging capacity. It is in the range from 40 kA to 80 kA. The response time is less than 25 ns. However there are also disadvantages when using varistors. Two factors that must be taken into account are the relatively high capacitance and the aging characteristics.

Leakage currents occur over time, depending on the frequency of the triggering, because individual resistance elements break down. This can cause temperature rise or even destroy them completely.

This is one reason for thermal fuses being built into Weidmüller products. The high capacity of the varistors is problematic for circuits with high frequencies. Some signal attenuation should be expected at frequencies above 100 kHz. We therefore recommend that they are not used in data transmission systems.

3. Suppression diodes / TAZ








Suppressor diodes function in a similar fashion as Zener diodes. There are uni-directional and bi-directional versions. Uni-directional suppressor diodes are often used in DC circuits. Compared to standard Zener diodes, suppressor diodes have a higher current-carrying capacity and are significantly quicker. At a certain breakdown voltage level, they become conductive very quickly. They therefore discharge the surge voltage. However their current-carrying capacity is not very high. It is only a few hundred amps. Instead, they feature a very quick reaction time which lies in the picosecond range.

Unfortunately, suppression diodes possess a significant inherent capacitance. Therefore, like with varistors, their possible attenuation effect on high frequencies must be taken into account.

4. Combination circuits

Combining the components described above results in surge protection products that can match individual requirements. If a voltage pulse reaches the input of such a combination circuit, then the gas discharge tube is fired and discharges high current. The residual pulse is attenuated by a downstream inductance and subsequently received and limited by the varistor and/or suppression diode. If the gas discharge tube is not triggered, i.e. in the case of a slower voltage rise, then the pulse is discharged by the varistor or the suppression diode alone.

The sequence of the individual components results in an increasing response sensitivity towards the output. An interference voltage with a rise of $1 \text{ kV}/\mu\text{s}$ and a peak value of 10 kV at the input is limited by a gas-filled surge arrester to approx. $600\text{--}700 \text{ V}$. The second stage, decoupled from the first by means of an inductance, suppresses this value to approx. 100 V . This voltage pulse is then reduced to approx. 35 V (in a 24 V protective combination) by the suppression diode. Therefore, the downstream electronics need only be able to cope with a voltage pulse of approx. $1.5 \times U_B$.




Test criteria

The classification is based on the experience that type I arresters could be overloaded under extremely high loads, and also on more recent investigations of lightning discharges. This resulted in the standardised form of the current curve 10/350 μ s for type I arresters under test. The test parameters are between 12.5 and 25 kA I_{peak} or I_{imp} . The specification „10/350 μ s“ means that the surge current has reached 90% of the maximum after 10 μ s and then drops to half its value after 350 μ s. The area under this curve corresponds to the current energy used for testing. Type II arresters (formerly „C“ arresters) are still tested with the current curve 8/20. The rated discharge current for our arresters is up to 75 kA for a 2-pole supply and up to 100 kA for a 4-pole supply. „Type III“ arresters (previously „D“ arresters) are used for device protection. The test applies for them with a 2-Ohm hybrid surge current generator having a maximum loading voltage of 0.1 kV to max. 20 kV, which, in

Classification formerly	VDE IEC 0675	37A	Test values	Application
Coarse protection	B-arrester	Type I	$I_{imp} = 25$ kA 10/350 μ s curve	Protection against direct lightning strike (incoming supply, main distribution board, etc.)
Medium protection	C-arrester	Type II	single pole $I_n = 20$ kA 8/20 μ s curve 3 or 4-pole $I_n = 100$ kA 8/20 μ s curve	Protection for permanent installations (electricity distribution etc.)
Fine protection	D-arrester	Type III	$U_{oc} = 20$ kV max. $I_s = 10$ kA max. hybrid generator	Protection for devices (sockets etc.)




the case of a short circuit delivers 0.05 kA to 10 kA for 8/20 μ s.

Relationship between 10/350 μ s and 8/20 μ s



	1	2
Wave form [μs]	10/350	8/20
I_{max} [kA]	100	5
Q [As]	50	0.1
W/R [J/Ω]	$2.5 - 10^6$	$0.4 - 10^3$
Norm	DIN V VDE V 0185-1	DIN V VDE 0432 T.2


 Simulated surge pulse 8/20 μ s
 Simulated lightning impulse 10/350 μ s



Electromagnetic compatibility

EMC – electromagnetic compatibility – means the trouble-free interaction between electrical and electronic systems and devices without mutual interference. In this respect, any electrical item can act both as transmitter (source of interference) and receiver (potentially susceptible device) simultaneously.

Normally it is not sufficient to construct an EMC-compliant electrical or electronic system using EMC-compliant components and to then expect that everything will operate smoothly. Only when you use the proper surge protection devices in the proper places in the facility, can you operate without outages using coupled surge voltages. The method for using surge protection devices is also linked to the influence of interference sinks and interference sources. It integrates with the lightning protection zone strategy and insulation coordination to form a complete protection system.



EMC laws and directives

There are a multitude of standards and statutory requirements aimed at controlling mutual interference-free operation. With the establishment of the unified European market in 1989, the EEC Directive (EN 50-370 part 1+2) on electromagnetic compatibility was adopted and then implemented into national law. In Germany, the law on the electromagnetic compatibility (EMVG) was endorsed in 1992. The current version of this law was passed in 2008 as was the international standard IEC 61000. Electromagnetic influences can be caused by natural processes, e.g. a lightning strike, and also technical processes, e.g. high-speed changes in the status of currents and voltages. We distinguish between periodic interference (system hum, RF irradiation), transient interference (brief, often high-energy pulses) and noise (broad distribution of interference energy across the frequency range).

The model used in EMC observations designates the transmitter as the **source of interference** emission and the receiver as the **interference drain**. The transmission of the interference takes place via line-bound and/or field-bound (H-field/E-field) coupling mechanisms.

When considered as a source of interference, a device or a system may not exceed emissions thresholds specified in the EMC standards.

When considered as a potentially susceptible device, the same system must exhibit the immunity to interference specified in the standards.


However, the arrangement of various electrical systems within a complex plant or in a room and the many lines for power supplies, inputs and outputs to controls and bus systems give rise to diverse potential influences. Surges can be introduced by lightning, switching operations, etc. via the various coupling paths. This can lead to the following effects:

- Reduced functionality
- Malfunctions
- Failure of functions
- Damage

These last two functional interferences result in stoppages for entire production facilities and cause high breakdown costs.

The following points must be taken into account in order to achieve a system or plant that operates according to EMC guidelines:

- Lightning protection
- Earthing
- Routing of cables
- Cable shielding
- Panel construction
- Sensors and actuators
- Transmitters and receivers
- Frequency converters
- Bus and field devices
- ESD



FAQ list

When do I need a Type I arrester, when a Type II arrester?

In a lightning protection system set up on a building, the Type I arrester achieves the lightning protection equipotential bonding for the supply voltage. The Type I arrester is used when higher pulses are expected and is installed in the vicinity of the incoming supply.

The Type I arrester is intended for use in lightning protection equipotential bonding, in compliance with DIN VDE 0185 part 1 and IEC 62305. The Type I arrester meets the requirements of Type I (B) DIN VDE 0675 and IEC 61643-1 Type I.

The Type II arrester is used to protect low-voltage consumer installations and electronic equipment against surge voltages arising from atmospheric discharges (thunderstorms) or switching operations. The Type II arresters comply with VDE 0675 part 6, Type II (C), Draft and DIN VDE 0675 part 6, A2 and the IEC 61643-11 Type II.

See also „New regulation of VDE 0100“ from page W.22.

When is a decoupling inductance needed?

When using Weidmüller arresters of Type I and II based on varistors, no decoupling inductance is needed.

Why are there 3- and 4-pole versions?

Various arresters are used depending on the network structure. A widely used network structure is the TN system. In the TN-C system, the electricity supply company routes the potential of the operational earth of the low-voltage source (transformer) to the consumer installation via the integral PEN conductor. The PE conductor has the same potential as the N conductor in this case. A 3-pole arrester is used here. Every rule has an exception: in the TN-S system, PE and N are separate. This means there can be a potential shift between PE and N. A 4-pole PU is used in this case. In addition, a combination of 3- or 4-pole modules reduces the amount of wiring.

What other network structures are available?

TT-System

In the TT system, surge protection Type I/II arresters are not used between the active conductor and the earth potential like in TN systems. Instead they are used between phases L1, L2 and L3 and the neutral conductor.

In a “classic” arrangement of surge protection devices between the phases and the earth potential, the devices may not be capable of extinguishing mains follow currents at the end of their lifespan. They could even create a short circuit. Depending on the earth resistance that exists for the consumer installation, a fault current could flow back to the supply source. Usually, because of the relatively high loop resistances in TT systems, the fuses which conduct the operating current do not detect this fault current as a fault and thus do not isolate promptly. This can lead to increases in potential in the building’s entire equipotential bonding system. Dangerous parasitic voltages can be transferred if more

distant buildings are being supplied from these consumer systems or if consumer loads are being operated via portable cables beyond the range of the building’s equipotential bonding system. The 3+1 circuitry can be used in such instances.

IT-System

An IT system is set up in some consumer installations for reasons of availability. A single-phase earth fault practically creates a TN system. The power supply is not interrupted but instead maintained. IT systems are used in medical applications, for example. A device for monitoring insulation provides information on the quality of the insulation of active conductors and connected consumers in relation to the earth potential. Surge protection devices are incorporated between the active conductors and the main equipotential bonding. The fuses, conductor cross-section and conductor routes are handled as for T systems. Likewise, all active conductors are protected against local earth potential in sub-circuit distribution boards. VPU surge protection devices in Type III surge protection for end devices are used (such as VPU III or VPU III SO) to protect sensitive consumer loads. The arrester must be sized for the voltage of the phase conductor.

What does this have to do with the 3+1 circuitry?

If Type II arresters are now being led to a neutral conductor instead of a local earth in a TT system, then, for an arrester that has become low ohm, only the wire resistance of the neutral wire limits the incipient follow-on current. Immediately after the fault, this is isolated from the spur line fuses or from the main fuses that are carrying the operating current. A pure short-circuit current has emerged out of a fault current that was subject to an earthing facility and resistor. The connection between the neutral conductor and the main equipotential bonding is established using a spark gap. This conducts the total surge currents occurring at the installation site without overloading. This 3+1 circuitry is also implemented for the circuit distributors. The phase conductors L1, L2 and L3 are connected via the neutral conductor. From there, a spark gap link is established with the PE rail. The same information on the TN system applies when working with local equipotential bonding systems, when there is a separate discharge to the equipotential bonding, and when the surge protection components are being arranged ahead of the fault-current protective circuits.

How does monitoring work with VPU arresters?

Each individual element of the PU arrester is equipped with a thermal monitoring mechanism. This state-of-the-art design isolates the aged arrester from the power supply network. This helps to prevent fires. This thermal monitoring mechanism functions using a special solder which separates itself within 30 seconds when a current of about 0.2 A flows through the varistor. The functionality is indicated when the viewing window is green, or for the

VPU series with arresters marked R, using a remote alert output with a CO contact.

Does a lightning/surge protection system continue to operate after a surge voltage?

Yes, if the leakage current on, for example, the class II remains below the nominal leakage current for each individual disk. However the varistor does age during each discharge. The ageing accumulates over its lifetime and then leads to the failure of the arrester after several years. This can be monitored using remote signalling. Another method, which is required by IEC 62305-3, is a periodic check of the lightning protection system. The V-TEST 2 can help by allowing you to test the function of each individual module.

How are the VPU modules tested?

The VPU AC I, VPU AC II and VPU III are tested in accordance with IEC 61643-11. The arresters from the VPU I series correspond with Type I and Type II. The VPU II series corresponds with Type II. The VPU III and VPU III SO series are designed and tested in accordance with the requirements of IEC 61643-11. They are in Type III.

Where are the VPU modules installed?

The dimensions of the VPU modules for installation distributors, comply with DIN 43 880 A1 draft 6/81. The Type I arresters are installed in the vicinity of the power feed and main equipotential bonding. The Type II arresters are installed in the distributor and the VPU III are installed in the sub-distributions, closer to the object being protected. The insulation co-ordination in DIN VDE 0110 requires that facility components have certain insulation strengths. This can be achieved through the gradual application of arresters in Type I, II and III.

What must be considered when installing the VPU modules?

IEC 60364-5-53 describes the selection and installation of surge protection in buildings worldwide. The German draft standard VDE V 0100-534 describes the selection and set-up of surge protection systems. VDE 0100-443 describes when surge protection must be installed.

What is the difference between a spark gap and a varistor?

A varistor is a voltage-dependent resistor which switches off the surge voltage "softly". A spark gap is a mechanical component or an encapsulated, gas-filled ceramic unit whereby the spark gap switches through immediately, and after the spark, only the ignition voltage is present (80 – 120 V). Depending on the type of spark gap, the capability to suppress the 50-Hz mains follow-on current must also be considered. The varistors, however, do not draw any mains follow-on current.

What are triggered spark gaps?


These spark gaps have additional electronics. They "see" the interference pulse and ignite the spark gap. This means that the protection level is kept low and the time to spark is reduced. This saves on decoupling coils.

When should I use CL or SL circuits with surge protection components for measurement and control systems?


The difference between the switching in the CL (current loop) and SL (symmetrical loop) is the integration of the suppressor diodes. The CL circuit has a diode between the lines. This system is used for current loops and offers direct protection at the input or output of the analogue sensor.

The SL circuit operates symmetrically to earth, i.e. two Transzorb diodes are connected to earth. If this is used in a current loop instead of the CL circuit, the residual voltage is twice as high because there are two diodes instead of just the one of the CL circuit.

2 CL protective circuit



2 SL protective circuit





Glossary

3 + 1 circuit	Surge protection for TT-/TNS power networks with 3 varistors and an N-PE spark gap. There are no parasitic voltages in the event of defective varistors.
Ageing	Change in the original power data caused by interference pulse due to operations or unfavourable environmental conditions.
Arrester	Protective device that discharges the energy either symmetrically between the conductors or asymmetrically between the cables and the earth.
Asymmetric interference voltage	Voltage between the "electrical centre", and common ground (earth). Voltage between conductor and signal ground (earth).
Back-up fuse	Dependent on the connection cross-section and/or maximum longitudinal decoupling of the proposed fuse.
Binary signals	Switching signals with on and off states.
Burst	For a surge pulse that reoccurs during a specific time interval.
Cable lengths	With a spur line connecting the lightning arrester, the length of the phase-side and earth-side cables should be kept as short as possible and should never be longer than 0.5 metres / 20 inch. The earth-side connection should be as short as possible. Installation site: At the feed point of the facility, for Type I and II. In the immediate vicinity of the end device being protected for Type III.
Capacitive coupling	Coupling of the interference circuit and the useful circuit because of a potential difference with coupling capacitances.
Combination circuit	Protective circuit (e.g. from gas discharge tube, varistor and/or suppressor diode)
Combined pulse	The hybrid generator, when idle, creates a 1.2/50 μ s pulse and, when in short circuit, a 8/20 μ s pulse. The ratio of peak open-circuit voltage (U_{Oc}) to peak short-circuit current (I_{sc}) is 2 ohms.
Common-mode interference	The interference source is between a signal wire and a reference conductor (e.g. capacitive coupling, or increase in potential of spatially dispersed earths).
Continuous operating current I_c	Current per protective path for continuous voltage U_c .
Cut-off mechanism	Device which disconnects the arrester in case of a system malfunction and displays this.
Degree of protection for housing (IP code)	Degree of protection ensured by the housing against touch access to live parts and against the ingress of solid foreign objects or water. Testing in accordance with IEC 529 section 7.4.
Differential-mode interference	Interference source and useful source are in series (e.g. magnetic or galvanic coupling).
EMC	Electromagnetic compatibility.
External lightning protection	The external lightning protection consists primarily of an air-termination device, arresters and an earthing system. It is responsible for protecting the facility buildings from lightning strikes which could cause fire or mechanical destruction.
Follow-on current I_f	Current that flows through the surge protection device immediately following a discharge and is delivered from the power grid.
Follow-on current extinguishing capability I_{fi}	The VPU I, II and III series do not generate any power follow current between L-PEN (follow current) and thus simplify the installation. Therefore, the strength of the short circuit current, or power follow current, from the generator or transformer, does not have to be taken into account.

Fuse, back-up fuse	A back-up fuse is required if the upstream fuse F1 is greater than the maximum value specified by the manufacturer. Remember to select the largest nominal value in keeping with the ratio F1 to F2 (back-up fuse before SPD) = 1 : 1.6. Be sure to take the triggering characteristics into account if a circuit breaker is being used in the surge protection equipment instead of the fuse specified in the installation instructions.
Galvanic coupling	The interference circuit and the useful circuit have a common impedance.
Gas discharge tube	Voltage-dependent, encapsulated switch with high current-carrying capacity.
HAK	House junction box.
I&C	Measurement and control systems.
IMAX	Maximum current that can be switched by an arrester.
Inductive coupling	Coupling from two or more current-carrying conductor loops.
Insertion loss (attenuation)	Attenuation in decibels that is added by inserting a four-pole.
INSTA	Installation housing in accordance with DIN 43880, suitable for installation in distribution boards.
Insulation co-ordination or rated impulse withstand voltage	Standing surge current strength of the insulation in parts of the facility, according to DIN VDE 0110 T.1.
Internal lightning protection	Internal lightning protection refers to protecting electrical equipment from power surges.
Intrinsically safe circuit	Intrinsically safe circuits are especially vulnerable because even a small amount of energy is sufficient to nullify their intrinsic safety. During the installation of intrinsically safe circuits (including cables and wires), be sure that you do not exceed the maximum allowable inductance, capacitance, or the L/R ratio and the surface temperature.
I_L	Maximum nominal current via the internal cross-connection of an arrester with two connections for one phase.
$I_{peak} = I_{imp}$	Current peak value of a test pulse.
I_{sn}	Peak value of the nominal discharge current.
IT power network	Power system with three phase conductors, constructed with insulation to the earth potential. The building's PE is not connected to the power grid.
Leakage current	Current that flows to PE at nominal voltage.
LEMP	Lightning electromagnetic pulse = electromagnetic interference pulse.
Lightning protection equipotential bonding	Equipotential bonding of separated metal parts with the LPS using a direct connection or connection via surge protection devices in order to reduce the lightning current caused by the potential difference.
Lightning pulse current I_{imp}	Defined by the peak value I_{peak} and the charge Q, when tested in accordance with Type I with 10/350 μ s pulse.
Limiting frequency	Specifies the max. frequency at which a transfer will function. At higher frequencies, the protective circuit cushions so strongly that no transfer is possible.
Longitudinal voltage	Interference voltage between the active conductor and the earth.

LPL	Lightning protection level LPL I = 200 kA LPL II = 150 kA LPL III = 100 kA Maximum lightning current that can enter as a direct strike in the external lightning protection. Various applications and buildings are categorised according to these lightning protection levels. 10/350 µs: test current for lightning arrester (Type I products), for simulating or reproducing a lightning bolt. 8/20 µs: test current for lightning arrester (Type II products), for simulating or reproducing a surge voltage.
LPS	Lightning protection system – a complete system that is used to reduce the physical damage to a building or facility that could be caused by direct lightning strikes.
LPZ	Lightning protection zone = lightning protection zone The lightning protection zones are divided into: external lightning protection LPZ 0 / OA / OB and internal lightning protection LPZ 1, 2, 3.
Max. continuous voltage U_c	The highest RMS value of the AC voltage or the highest value of the DC voltage that is allowed continually on the protective path of the surge protection device. Continual voltage = rated voltage.
Maximum discharge surge current I_{max}	Peak value of the current 8/20 µs during duty test for Type II (type 50 kA).
Measured limiting voltage	Max. voltage level while loading with pulses of a specific form and amplitude during the test.
Mode 1	State where the voltage-limiting part of the SPD was disconnected. The voltage-limiting function is no longer available, but the cable is still functional.
Mode 2	State where the voltage-limiting part of the SPD was short-circuited due to a very low impedance within the SPD. The line is inoperable, but the measuring equipment is still protected by means of a short-circuit.
MOV	See varistor.
Nominal discharge surge current	At peak value of the surge current 8/20 µs, during test for Type II (type 20 kA)
PAS main earth rail	Metal rail which is connected with the foundation, and which can be used to connect metal installations, external conductive parts, power supply cables, telecommunications cables, water pipes and gas pipes to the LPS.
PE	Protective system and earth system to which energy is discharged.
Protection level, U_p	Specifies the residual voltage that can still be measured at the terminals during a surge voltage pulse (preferred value is greater than the largest measured limiting voltage). Important parameter that characterises the performance of the SPD.
Protective path	Component circuitry in a SPD: conductor to conductor, conductor to earth, conductor to neutral, neutral to earth are designated as protective paths.
Pulse current 10/350 µs	Pulse voltage with a front time of 10 µs and a half-value time of 350 µs.
Pulse current 8/20 µs	Pulse voltage with a front time of 8 µs and a half-value time of 20 µs.
Pulse voltage 1.2/50 µs	Pulse voltage with a front time of 1.2 µs and a half-value time of 50 µs.
Radiation coupling	Electromagnetic field coupled to one or more conductive loops.
Rated voltage UC	The maximum RMS value of the AC voltage which may continuously be applied to an arrester.

RCD circuit breaker	If a fault current exceeds a certain threshold, then the RCD switches off within 0.2 seconds.
Recommended fuse	The nominal value of the fuse recommended by the manufacturer and specified by the technical data sheet.
Remote signalling contact (FM)	A volt-free contact for the power products for signalling triggered/defective arresters. For the measurement/control SPD/VSPC products, this connection with the VSPC CONTROL UNIT is required to produce a signal. The Weidmüller diagrams show this with the letter R which stands for "remote signal contact".
Requirement class B / T 1 / Type I	For the purpose of lightning protection equipotential bonding according to DIN VDE 0185-1, also see Type I.
Requirement class C / T 2 / Type II	For the purpose of surge protection in the fixed facility, preferably for use in impulse withstand voltage category III, also see Type II.
Requirement class D / T 3 / Type III	For the purpose of surge protection in the fixed facility, preferably for use in impulse withstand voltage category II, also see Type III.
Short-circuit withstand rating	Maximum prospective short-circuit current that the surge protection device can withstand.
Sparkover time	Response times can vary between a few μ s to ps, depending on the type and construction of the protective components.
SPD	Surge protective device (lightning and surge protection device).
Suppressor diode	Voltage-dependent, fast-switching semiconductor diode.
Surge protection (OVP/SPD)	Switching circuitry/wiring of a circuit used to limit the output voltage; and the sum of all lightning protection measures used to protect the technical equipment against lightning currents and surge voltages.
Surge protection device (SPD)	Device with at least one non-linear component, used to limit the surge voltages and to discharge the surge currents.
Surge protection equipment (SPE)	Surge protection devices and surge protection equipment for a facility, including the cables associated with the surge protection.
Surge voltage	Unwanted continuous or short-term differences in potential between the conductors or between conductor and earth which create interference or destruction.
Surge voltage protection classes	Classification of electrical equipment in accordance with their dielectric strength relative to the nominal voltage, EN 50178.
Symmetric interference voltage	Voltage between the outward and return conductors (differential-mode voltage).
TAZ	See suppressor diode.
TN power grid	Power grid as a 4- or 5-wire system; 3 phases and the PEN come into the building. PE from the building and PE from power system are connected to each other.

TOV error mode	TOV = arresters must be able to withstand persistent voltage increases with mains frequency, so-called "temporary overvoltages" or "TOVs". Various error states inside and outside the low voltage consumer facility of a building can occur to cause TOVs. An example of one of the causes of TOVs described in VDE 0100, part 442, is an earth fault on the high voltage side of the local grid transformer. Failure mode Mode1: Surge protection has switched itself off, no protection is being provided. Mode2: Surge protection has short circuited with an internal connection, the terminal equipment is protected by the short. The supply or the signal is no longer operational.
Transverse voltage	Interference voltage between two conductors in circuit.
Triggered sparkover gap	A gas-filled sparkover gap which is ignited by a capacitive voltage divider with a pre-set voltage value.
TT power grid	Power system with 4 wires; 3-phase conductors and the neutral conductor come into the building. The building's PE is not connected to the power grid.
Type I	For the purpose of lightning protection equipotential bonding according to IEC 37A/44/CDV; also refer to requirement class B.
Type II	For the purpose of surge protection in the fixed facility, preferably for use in impulse withstand voltage category III, also see requirements class B.
Type III	For the purpose of surge protection in the fixed facility, preferably for use in impulse withstand voltage category II, also see requirements class B.
Varistor	Voltage-dependent metal oxide resistor; the resistance decreases with increasing voltage.





Surge protection forum

Construction standards/directives/legal basis

The continued availability of electrical and electronic equipment and systems is critical. It is therefore important to prevent loss and faults that are frequently caused by overvoltage events. It is for this reason that there are standards and directives for lightning and surge protection that cover buildings, parts of buildings, structural and technical installations (objects).

The technical committee IEC TC 81 deals with lightning protection issues worldwide. The new IEC 62305 standard was introduced following a decision in October 2001. Since January 2006, IEC 62305 has been divided into four parts:

- IEC 62305-1: General principles
- IEC 62305-2: Risk management
- IEC 62305-3: Physical damage to structures and life hazard
- IEC 62305-4: Electrical and electronic systems within structures

The German committee responsible for German implementation decided to maintain the VDE classification of the new standard series DIN EN 62305 as VDE 0185-305 parts 1-4.

Country-specific standards and directives

- DIN EN 62305-1 (VDE 0185-305-1)
- DIN EN 62305-2 (VDE 0185-305-2)
- DIN EN 62305-3 (VDE 0185-305-3)
- DIN EN 62305-4 (VDE 0185-305-4)

It is known that lightning protection equipotential bonding is not sufficient in itself to protect electrical equipment from voltage surges.

On account of that, standards such as:

- DIN VDE 0100 part 410
- DIN VDE 0100 part 540
- DIN VDE 0100 part 443
- DIN VDE 0100 part 534
- DIN VDE 0800 part 1
- DIN VDE 0800 part 2
- DIN VDE 0800 part 10
- DIN VDE 0845 part 1
- DIN VDE 0845 part 2

explicitly require measures for protection against voltage surges. In DIN VDE 0100, the surge protection measures for low-voltage installations and, in the DIN VDE 0800 standard, the surge protection measures for communication engineering as a whole are described. Appendix A of DIN VDE 0100-534 shows the selectively graded use of surge arresters of Type I (B arresters) in the main power supply, Type II (C arresters) in the sub-circuit


distribution board and Type III (D arresters) in the area of the final circuit. Appendix A of DIN VDE 0100 part 534.

IEC 61643-5-53 has been available since 2002. It is implemented in VDE 0100-534 and describes the selection and installation of surge protection for electrical facilities. This is intended as a replacement for DIN VDE 0100-534. The international equivalent is IEC 60364-5-53:2002-06. The chapter 534: "Devices for protection against overvoltages" contains the devices for protection against overvoltages, the selection of these and their use in the building installation. The rules that apply on the low voltage side are adapted to communication electronics as a whole and are described by the national series of standards 0800 parts 1, 2 and 10 and 0845 parts 1 and 2. DIN VDE 0800 describes general issues such as earthing, equipotential bonding, etc. and DIN VDE 0845 the measures for protecting against overvoltage events of all kinds.

Guidelines of the loss insurers

The guidelines apply to decisions on whether lightning and surge protection is to be provided for buildings, parts of buildings, structural and technical installations. The guidelines become, on agreement, a binding part of the insurance contract between insurer and policyholder.

However, their application does not exempt the insured party from observance of legislation, statutory instruments, official requirements and generally accepted codes of practice such as that described in the DIN VDE standards. The building regulations of different countries and the relevant statutory and official regulations and codes of practice, call for lightning protection systems to be installed in certain buildings for reasons of public safety, e.g. in shops, hospitals, schools



and children's homes, etc. The generally acknowledged code of practice, in this case DIN EN 62305 (VDE 0185-305):2006-11 or DIN VDE 0185, must be adhered to when installing technical systems. Issues relating to installation arise not only in connection with official requirements but also when the insurers call for lightning protection, e.g. for high-racking warehouses or plants with a high risk of explosion. Similar relationships apply to surge protection. For example, DIN VDE 0100 part 443 specifies risk factors which determine the installation of surge protection measures.

The Association of German Property Insurers (VdS) publishes a number of documents covering particular applications, e.g. electrical installations, IT systems, agricultural businesses and residential buildings:

- VdS 2192: Leaflet on surge protection for loss prevention
- VdS 2014: Determining causes of damage due to lightning and surge
- VdS 2258: Protection against surge
- VdS 2006: Lightning protection by means of lightning arresters
- VdS 2017: Lightning and surge protection for agricultural businesses
- VdS 2031: Lightning and surge protection in electrical installations
- VdS 2028: Foundation earth electrodes for equipotential bonding and lightning protection earth termination
- VdS 2019: surge protection in residential buildings
- VdS 2569: surge protection for electronic IT systems
- VdS 2010: Risk-based lightning and surge protection
- VdS 2007: IT installations
- VdS 3428: surge protection devices

Furthermore, in Germany lightning protection is also covered in the construction law requirements of the individual federal states and also in national regulations. In light of this situation, the Association of German Property Insurers has produced a table to simplify the assignment of lightning protection classes and surge protection requirements to buildings and installations (VdS guideline 2010). This takes into account the experience and findings of loss prevention experts as well as legislation, official regulations and standards.

Legal basis

Basically, lightning and surge protection is not a mandatory provision in the form of legislation, even though lightning and surge protection is covered in Germany's EMC Act. However, it is important to know that there is indeed a legal basis. This comes into play when a loss event has occurred and, as a result, legal proceedings become relevant.

In Germany, the following legal aspects must be taken into account:

Civil law:

- **BGB (German Civil Code)**
 - cl. 633 Contractor's duty of warranty; removal of defects
 - cl. 276 Responsibility for one's own conduct
 - cl. 278 Responsibility for persons employed in performing an obligation
 - cl. 459 Liability for defect of quality
 - cl. 823b Unlawful actions

- **Produkthaftungsgesetz (Product Liability Act)**

- cl. 3 Identification of a defect/Competence

- **Gerätesicherheit (Safety of Equipment)**

- cl. 3 Code of practice

- **AVBEltV (General Conditions for Electricity Supplies to Standard-rate Customers)**

- Duty to observe the standards

Statutory instruments:

- **Gewerbeordnung (Trade and Industry Act)**

- cl. 24 Installations requiring monitoring
- cl. 120a Mortal danger and other health risks

- **VOB (Contract Procedures for Building Works)**

- cl. 3 Suspected defects
- cl. 4/2 Responsibility/Code of practice
- cl. 4/3 Written notification of concerns

Basically, a person undertaking work is always liable for ensuring that his work is free from defects. The decisive starting point from which to establish whether work is free from defects is adherence to the generally accepted codes of practice.

Surge protection standards and regulations

In the case of national and international standards and specifications on the same subject, the document with the widest scope takes precedence (e.g. international "IEC", European "CENELEC" or "CNC", national (Germany) "DIN VDE" or Austria "ÖVE" (Similar to TÜV Germany, also valid in Austria.)).

IEC	EN	VDE	others	
	EN 60728-11			Cable distribution systems for television and sound signals – Part 11: Safety requirements
	HD 60364-5-53	VDE 0100-534		Electrical installations of buildings – Part 5-53: Selection and erection of electrical equipment – Isolation, switching and control – Part: 534: Surge protection device
	HD 60364-5-54	VDE 0100-540		Electrical installations of buildings – Part 5-54: Selection and erection of electrical equipment – Earthing arrangements, protective conductors and protective bonding conductors
IEC 60664-1	EN 60664-1	VDE 0110-1		Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests
IEC 60079-11	EN 60079-14	VDE 0165 Part 1		Electrical apparatus for use in the presence of combustible dust – Part 14: Selection and installation
IEC 60079-11	EN 60079-11	VDE 0170 Part 7		Explosive atmospheres – Part 11: Equipment protection by intrinsic safety "I"
IEC 62305-1	EN 62305-1	VDE 0185-305-1		Protection against lightning – Part 1: General principles
IEC 62305-2	EN 62305-2	VDE 0185-305-2		Protection against lightning – Part 2: Risk management
IEC 62305-3	EN 62305-3	VDE 0185-305-3		Protection against lightning – Part 3: Physical damage to structures and life hazard
IEC 62305-4	EN 62305-4	VDE 0185-305-4		Protection against lightning – Part 4: Electrical and electronic systems within structures
IEC 60529	EN 60 529	VDE 0470-1		Degrees of protection provided by enclosures (IP code)
IEC 60099-4	EN 60099-4	VDE 0675, Part 4		Surge arresters – Part 4: Metal-oxide surge arresters without gaps for A.C. systems
IEC 60099-5	EN 60099-5	VDE 0675, Part 5		Surge arresters – Part 5: Selection and application recommendations
IEC 61643-11	EN 61643-11	VDE 0675-6-11		Low-voltage surge protective devices – Part 11: Surge protective devices connected to low-voltage power systems – Requirements and tests
IEC 61643-12	EN 61643-12	VDE 0675-6-12		Surge protection devices for low voltage – Part 12: Selection and reasons for use
IEC 61643-21	EN 61643-21	VDE 845-3-1		Surge protection devices for low voltages – part 21: Surge protective devices for use in telecommunications and signal conditioning networks - Performance requirements and testing methods
IEC 61643-22	TS 61643-22	VDE V 845-3-2		Surge protection devices for low voltages – part 22: Surge protective devices for use in telecommunications and signal conditioning networks - Selection and application strategies
IEC 60038	EN 60038	VDE 0175-1		IEC standard voltages
			KTA 2206, 2009-11	Lightning protection standard for nuclear power plants
			VDE publication 44	Lightning protection systems, explanations to DIN 57185/VDF 01 85, published by VDE
			DIN-VDE publication	Publication No. 519; Lightning protection systems 1, external lightning protection, published by VDE
			DKE publication No. 520	Publication No. 520; Lightning protection systems 2, internal lightning protection, published by VDE
			ÖVE 8001 §18	Protection of electrical systems from transient overvoltages
The above list is not exhaustive.				

IEC	EN	VDE	others	
IEC 61400-24	EN 61400-24	VDE 0127-24	IEC 61400-24	Wind power facilities - part 24: Lightning protection for wind turbines
			VdS 2010	Risk-oriented lightning and surge protection
The above list is not exhaustive.				

Risk-based lightning and surge protection, guidelines for damage prevention; VdS damage prevention in the German General Association of Property Insurers Association (GDV)				
			VdS 2019	Surge protection in residential buildings
			VdS 2258	Protection against surge voltages
			VdS 2031	Lightning and surge protection in electrical facilities
			VdS 3428: 2005-04	Directives for electrical equipment – surge protection devices (arresters)
			UTE C 61-740-51	French standard for testing SPDs in photovoltaic applications
			DIN CLC/TS 50539-12 VDE V 0675-39-12	Surge protection for low voltage – Surge protection devices for special applications including DC – part 12: Selection and application strategies – Surge protection devices for use in photovoltaic installations
IEC 61643-31	EN 61643-31	VDE 0675-6-31		Standard for testing SPDs in photovoltaic applications
IEC 61643-32	EN 61643-32	VDE 0675-6-32		SPO for use in PV installations
The above list is not exhaustive.				

UL Approvals

UL497B	UL Standard for measurement and control protection
UL94	UL Standard for plastic material
UL1449 Ed.4	UL standard for power protection



Index

Index	Index Type	X.2
	Index Order No.	X.4

Type	Order No.	Page
------	-----------	------

VSPC 1CL 24VDC	8924480000	A.2
VSPC 1CL 24VDC	8924480000	A.3
VSPC 1CL 24VDC	8924480000	A.17
VSPC 1CL 24VDC EX	8953600000	A.139
VSPC 1CL 24VDC R	8951550000	A.19
VSPC 1CL 48VAC	8924520000	A.3
VSPC 1CL 48VAC	8924520000	A.17
VSPC 1CL 5VDC	8924420000	A.3
VSPC 1CL 5VDC	8924420000	A.17
VSPC 1CL 5VDC EX	8953660000	A.139
VSPC 1CL 5VDC R	8951530000	A.19
VSPC 1CL 60VAC	8924530000	A.17
VSPC 1CL PW 24V	8951510000	A.29
VSPC 1CL PW 24V EX	8953610000	A.143
VSPC 2CL 12VDC	8924440000	A.3
VSPC 2CL 12VDC	8924440000	A.21
VSPC 2CL 12VDC R	8951470000	A.23
VSPC 2CL 24VAC	8924490000	A.21
VSPC 2CL 24VAC R	1093400000	A.23
VSPC 2CL 24VDC	8924470000	A.2
VSPC 2CL 24VDC	8924470000	A.4
VSPC 2CL 24VDC	8924470000	A.21
VSPC 2CL 24VDC EX	8953720000	A.141
VSPC 2CL 24VDC R	8951480000	A.23
VSPC 2CL 48VAC	8951490000	A.21
VSPC 2CL 5VDC	8924400000	A.21
VSPC 2CL 5VDC R	8951460000	A.23
VSPC 2CL HF 12VDC	8924460000	A.2
VSPC 2CL HF 12VDC	8924460000	A.4
VSPC 2CL HF 12VDC	8924460000	A.25
VSPC 2CL HF 12VDC	8924460000	C.5
VSPC 2CL HF 12VDC R	8951690000	A.27
VSPC 2CL HF 12VDC R	8951690000	C.7
VSPC 2CL HF 24VDC	8924510000	A.4
VSPC 2CL HF 24VDC	8924510000	A.25
VSPC 2CL HF 24VDC	8924510000	C.5
VSPC 2CL HF 24VDC R	8951700000	A.27
VSPC 2CL HF 24VDC R	8951700000	C.7
VSPC 2CL HF 5VDC	8924430000	A.3
VSPC 2CL HF 5VDC	8924430000	A.4
VSPC 2CL HF 5VDC	8924430000	A.25
VSPC 2CL HF 5VDC	8924430000	C.5
VSPC 2CL HF 5VDC R	8951680000	A.27
VSPC 2CL HF 5VDC R	8951680000	C.7
VSPC 2SL 12VAC EX	8953630000	A.145
VSPC 2SL 12VDC	8924230000	A.31
VSPC 2SL 12VDC EX	8953620000	A.145
VSPC 2SL 12VDC R	8951620000	A.33
VSPC 2SL 24VAC	8924350000	A.31
VSPC 2SL 24VAC R	8951640000	A.33
VSPC 2SL 24VDC	8924330000	A.31
VSPC 2SL 24VDC EX	8953670000	A.145
VSPC 2SL 24VDC R	8951630000	A.33
VSPC 2SL 48VAC	8924370000	A.31
VSPC 2SL 48VAC EX	8953640000	A.145
VSPC 2SL 5VDC	8924210000	A.3
VSPC 2SL 5VDC	8924210000	A.31
VSPC 2SL 5VDC R	8951610000	A.33
VSPC 3/4WIRE 24VDC	8924550000	A.2
VSPC 3/4WIRE 24VDC	8924550000	A.39
VSPC 3/4WIRE 5VDC	8924540000	A.39
VSPC 3/4WIRE 5VDC EX	8953650000	A.149
VSPC 4SL 12VAC EX	1161150000	A.147
VSPC 4SL 12VDC	8924220000	A.35
VSPC 4SL 12VDC EX	1161170000	A.147
VSPC 4SL 12VDC R	8951580000	A.37
VSPC 4SL 24VAC	8924340000	A.35
VSPC 4SL 24VAC EX	1161180000	A.147
VSPC 4SL 24VAC R	8951600000	A.37
VSPC 4SL 24VDC	8924320000	A.35
VSPC 4SL 24VDC EX	1161190000	A.147
VSPC 4SL 24VDC R	8951590000	A.37
VSPC 4SL 48VAC	8924360000	A.35
VSPC 4SL 5VDC	8924200000	A.35
VSPC 4SL 5VDC R	8951570000	A.37
VSPC 4SL 60VAC	8924380000	A.35
VSPC BASE 1CL	8924730000	A.2
VSPC BASE 1CL	8924730000	A.3
VSPC BASE 1CL	8924730000	A.16
VSPC BASE 1CL	8924730000	A.52
VSPC BASE 1CL FG	8924290000	A.2
VSPC BASE 1CL FG	8924290000	A.3
VSPC BASE 1CL FG	8924290000	A.16
VSPC BASE 1CL FG	8924290000	A.53
VSPC BASE 1CL FG EX	8951810000	A.138
VSPC BASE 1CL FG EX	8951810000	A.150
VSPC BASE 1CL FG R	8951740000	A.18
VSPC BASE 1CL FG R	8951740000	A.58
VSPC BASE 1CL PW	1070230000	A.25
VSPC BASE 1CL PW	1070230000	A.52
VSPC BASE 1CL PW FG	1105700000	A.28
VSPC BASE 1CL PW FG	1105700000	A.53
VSPC BASE 1CL PW FG EX	1070470000	A.142
VSPC BASE 1CL PW FG EX	1070470000	A.150
VSPC BASE 1CL R	8951730000	A.18
VSPC BASE 1CL R	8951730000	A.54
VSPC BASE 2/4CH	8924740000	A.2
VSPC BASE 2/4CH	8924740000	A.3

Type	Order No.	Page
------	-----------	------

VSPC BASE 2/4CH	8924740000	A.38
VSPC BASE 2/4CH	8924740000	A.40
VSPC BASE 2/4CH	8924740000	A.42
VSPC BASE 2/4CH	8924740000	A.44
VSPC BASE 2/4CH	8924740000	A.52
VSPC BASE 2/4CH FG	8924300000	A.2
VSPC BASE 2/4CH FG	8924300000	A.3
VSPC BASE 2/4CH FG	8924300000	A.38
VSPC BASE 2/4CH FG	8924300000	A.40
VSPC BASE 2/4CH FG	8924300000	A.42
VSPC BASE 2/4CH FG	8924300000	A.44
VSPC BASE 2/4CH FG	8924300000	A.53
VSPC BASE 2/4CH FG R	8951800000	A.42
VSPC BASE 2/4CH FG R	8951800000	A.55
VSPC BASE 2/4CH FG R	8951800000	C.10
VSPC BASE 2/4CH R	8951790000	A.42
VSPC BASE 2/4CH R	8951790000	A.54
VSPC BASE 2/4CH R	8951790000	C.10
VSPC BASE 2CL	8924710000	A.2
VSPC BASE 2CL	8924710000	A.3
VSPC BASE 2CL	8924710000	A.4
VSPC BASE 2CL	8924710000	A.20
VSPC BASE 2CL	8924710000	A.24
VSPC BASE 2CL	8924710000	A.46
VSPC BASE 2CL	8924710000	A.48
VSPC BASE 2CL	8924710000	A.52
VSPC BASE 2CL	8924710000	C.4
VSPC BASE 2CL	8924710000	C.8
VSPC BASE 2CL FG	8924270000	A.2
VSPC BASE 2CL FG	8924270000	A.3
VSPC BASE 2CL FG	8924270000	A.4
VSPC BASE 2CL FG	8924270000	A.20
VSPC BASE 2CL FG	8924270000	A.24
VSPC BASE 2CL FG	8924270000	A.46
VSPC BASE 2CL FG	8924270000	A.48
VSPC BASE 2CL FG	8924270000	A.53
VSPC BASE 2CL FG	8924270000	C.4
VSPC BASE 2CL FG	8924270000	C.8
VSPC BASE 2CL FG R	8951720000	A.22
VSPC BASE 2CL FG R	8951720000	A.26
VSPC BASE 2CL FG R	8951720000	A.50
VSPC BASE 2CL FG R	8951720000	A.55
VSPC BASE 2CL FG R	8951720000	C.6
VSPC BASE 2CL FG EX	8951820000	A.140
VSPC BASE 2CL FG EX	8951820000	A.150
VSPC BASE 2CL R	8951710000	A.22
VSPC BASE 2CL R	8951710000	A.26
VSPC BASE 2CL R	8951710000	A.50
VSPC BASE 2CL R	8951710000	A.54
VSPC BASE 2CL R	8951710000	C.6
VSPC BASE 2SL	8924720000	A.3
VSPC BASE 2SL	8924720000	A.30
VSPC BASE 2SL	8924720000	A.52
VSPC BASE 2SL FG	8924280000	A.3
VSPC BASE 2SL FG	8924280000	A.30
VSPC BASE 2SL FG	8924280000	A.53
VSPC BASE 2SL FG EX	8951830000	A.144
VSPC BASE 2SL FG EX	8951830000	A.150
VSPC BASE 2SL FG R	8951780000	A.32
VSPC BASE 2SL FG R	8951780000	A.55
VSPC BASE 2SL R	8951770000	A.32
VSPC BASE 2SL R	8951770000	A.54
VSPC BASE 4SL	8924700000	A.34
VSPC BASE 4SL	8924700000	A.52
VSPC BASE 4SL FG	8924260000	A.34
VSPC BASE 4SL FG	8924260000	A.53
VSPC BASE 4SL FG EX	8951840000	A.146
VSPC BASE 4SL FG EX	8951840000	A.148
VSPC BASE 4SL FG EX	8951840000	A.150
VSPC BASE 4SL FG R	8951760000	A.36
VSPC BASE 4SL FG R	8951760000	A.55
VSPC BASE 4SL R	8951750000	A.36
VSPC BASE 4SL R	8951750000	A.54
VSPC CONTROL UNIT 24VDC	8972270000	A.58
VSPC GDT 2CH 150Vac/230Vdc	8924590000	A.41
VSPC GDT 2CH 90V	8924570000	A.2
VSPC GDT 2CH 90V	8924570000	A.3
VSPC GDT 2CH 90V	8924570000	A.41
VSPC GROUND	8924680000	A.56
VSPC LOCKING CLIP	1317340000	A.57
VSPC MOV 2CH 230V	8924610000	A.43
VSPC MOV 2CH 230V R	8951660000	A.43
VSPC MOV 2CH 24V	8924600000	A.43
VSPC MOV 2CH 24V R	8951650000	A.43
VSPC RS485 2CH	8924670000	A.2
VSPC RS485 2CH	8924670000	A.3
VSPC RS485 2CH	8924670000	A.49
VSPC RS485 2CH	8924670000	C.9
VSPC RS485 2CH R	8951670000	A.51
VSPC RS485 2CH R	8951670000	C.11
VSPC TAZ 4CH 24V	8924650000	A.45
VSPC TELE UK0 2WIRE	8924660000	A.3
VSPC TELE UK0 2WIRE	8924660000	A.4
VSPC TELE UK0 2WIRE	8924660000	A.47
VSSC4 CL 12VDC 0.5A	1063720000	A.97
VSSC4 CL 24VAC/DC 0.5A	1063730000	A.70
VSSC4 CL 24VAC/DC 0.5A	1063730000	A.97
VSSC4 CL FG 12VDC 0.5A	1063760000	A.97

Type	Order No.	Page
------	-----------	------

VSSC4 CL FG 24VAC/DC Ex	1063810000	A.157
VSSC4 CL FG 48VAC/DC Ex	1063820000	A.157
VSSC4 CL FG24VAC/DC0.5A	1063770000	A.70
VSSC4 CL FG24VAC/DC0.5A	1063770000	A.97
VSSC4 CL FG48VAC/DC0.5A	1063780000	A.97
VSSC4 GDT 110VAC/DC20kA	1064050000	A.103
VSSC4 GDT 240VAC/DC20kA	1064060000	A.103
VSSC4 GDT55VUC 20kA EX	1064040000	A.161
VSSC4 MOV 120VAC/DC	1063990000	A.101
VSSC4 MOV 12VDC	1063950000	A.101
VSSC4 MOV 150VAC/DC	1064010000	A.101
VSSC4 MOV 240VAC/DC	1064020000	A.101
VSSC4 MOV 24VAC/DC	1063960000	A.101
VSSC4 MOV 48VAC/DC	1063970000	A.101
VSSC4 MOV 60VAC/DC	1063980000	A.101
VSSC4 RC 240VAC/DC	1064130000	A.107
VSSC4 RC 24VAC/DC	1064120000	A.107
VSSC4 SL 12VDC 0.5A	1063830000	A.99
VSSC4 SL 24VAC/DC 0.5A	1063840000	A.99
VSSC4 SL 48VAC/DC 0.5A	1063860000	A.99
VSSC4 SL 60VAC/DC 0.5A	1063870000	A.99
VSSC4 SL FG 12VDC 0.5A	1063880000	A.99
VSSC4 SL FG 24VAC/DC Ex	1063930000	A.159
VSSC4 SL FG 48VAC/DC Ex	1063940000	A.159
VSSC4 SL FG24VAC/DC0.5A	1063890000	A.99
VSSC4 TAZ 12VDC	1064070000	A.105
VSSC4 TAZ 24VAC/DC	1064080000	A.105
VSSC4 TAZ 48VAC/DC	1064090000	A.105
VSSC6 CL FG 12VDC 0.5A	1064260000	A.73
VSSC6 MOV 120VAC/DC	1064610000	A.81
VSSC6 MOV 12VDC	1064530000	A.81
VSSC6 MOV 240VAC/DC	1064630000	A.81
VSSC6 MOV 24VAC/DC	1064540000	A.81
VSSC6 MOV 48VAC/DC	1064570000	A.81
VSSC6 MOV 60VAC/DC	1064600000	A.81
VSSC6 RS232	1064990000	A.70
VSSC6 RS232	1064990000	A.91
VSSC6 RS232	1064990000	C.15
VSSC6 RS485	1064980000	A.70
VSSC6 RS485	1064980000	A.91
VSSC6 RS485	1064980000	C.15
VSSC6 RS485 DP	1065010000	A.3
VSSC6 RS485 DP	1065010000	A.70
VSSC6 RS485 DP	1065010000	A.91
VSSC6 RS485 DP	1065010000	C.15
VSSC6 RS485 PA EX	1065020000	A.165
VSSC6 TAZ 12VDC	1064730000	A.89
VSSC6 TAZ 24VAC/DC	1064740000	A.89
VSSC6 CL 12VDC 0.5A	1064150000	A.70
VSSC6 CL 12VDC 0.5A	1064150000	A.73
VSSC6 CL 24VAC/DC 0.5A	1064170000	A.70
VSSC6 CL 24VAC/DC 0.5A	1064170000	A.73
VSSC6 CL 48VAC/DC 0.5A	1064190000	A.70
VSSC6 CL 48VAC/DC 0.5A	1064190000	A.73
VSSC6 CL 60VAC/DC 0.5A	1064210000	A.73
VSSC6 CLFG24VAC/DC0.5A	1064270000	A.70
VSSC6 CLFG24VAC/DC0.5A	1064270000	A.73
VSSC6 CLFG48VAC/DC0.5A	1064280000	A.73
VSSC6 CLFG60VAC/DC0.5A	1064290000	A.73
VSSC6 GDT 110VAC/DC10kA	1064690000	A.70
VSSC6 GDT 110VAC/DC10kA	1064690000	A.85
VSSC6 GDT 110VAC/DC20kA	1064700000	A.70
VSSC6 GDT 110VAC/DC20kA	1064700000	A.85
VSSC6 GDT 240VAC/DC10kA	1064710000	A.85
VSSC6 GDT 240VAC/DC20kA	1064720000	A.70
VSSC6 GDT 240VAC/DC20kA	1064720000	A.85
VSSC6 GDT 24VAC/DC 10kA	1064640000	A.85
VSSC6 RTD	1139710000	A.70
VSSC6 RTD	1139710000	A.93
VSSC6 RTD EX	1130670000	A.167
VSSC6 TR CL 12VDC 0.5A	1064220000	A.75
VSSC6 TRCL24VAC/DC0.5A	1064230000	A.75
VSSC6 TRCL48VAC/DC0.5A	1064240000	A.75
VSSC6 TRCL60VAC/DC0.5A	1064250000	A.75
VSSC6 TRLDMOV 12VDC	1064800000	A.83
VSSC6 TRLDMOV 24VAC/DC	1064810000	A.83
VSSC6 TRLDMOV 48VAC/DC	1064820000	A.83
VSSC6 TRLDMOV120VAC/DC	1064840000	A.83
VSSC6 TRLDMOV240VAC/DC	1064860000	A.83
VSSC6 TRLDTAZ 24VAC/DC	1064950000	A.89
VSSC6SL FG LD12VDC0.5A	1064420000	A.77
VSSC6SL LD 12VDC 0.5A	1064340000	A.70
VSSC6SL LD 12VDC 0.5A	1064340000	A.77
VSSC6SL LD24VAC/DC0.5A	1064350000	A.77
VSSC6SLFGLD24VAC/DC0.5A	1064430000	A.77
VSSC6SLFGLD48VAC/DC0.5A	1064440000	A.77
VSSC6SLTRFG24VAC/DC EX	1214440000	A.163
VSSC6TRCLFG12VDC0.5A	1064300000	A.70
VSSC6TRCLFG12VDC0.5A	1064300000	A.75
VSSC6TRCLFG24VAC/DC EX	1066490000	A.163
VSSC6TRCLFG24VAC/DC0.5A	1064310000	A.70
VSSC6TRCLFG24VAC/DC0.5A	1064310000	A.75
VSSC6TRCLFG48VAC/DC0.5A	1064320000	A.75
VSSC6TRCLFG60VAC/DC0.5A	1064330000	A.75
VSSC6TRGDT110VAC/DC10kA	1064890000	A.87
VSSC6TRGDT240VAC/DC10kA	1064920000	A.87
VSSC6TRGDT24VAC/DC10kA	1064870000	A.87
VSSC6TRSL24VAC/DC0.5A	1354790000	A.79
VSSC6TRSLFG24VAC/DC0.5A	1354800000	A.79

Order No.	Type	Page
-----------	------	------

1060000000

1063720000	VSSC4 CL 12VDC 0.5A	A.97
1063730000	VSSC4 CL 24VAC/DC 0.5A	A.70
1063730000	VSSC4 CL 24VAC/DC 0.5A	A.97
1063740000	VSSC4 CL 48VAC/DC 0.5A	A.97
1063760000	VSSC4 CL FG 12VDC 0.5A	A.97
1063770000	VSSC4 CL FG24VAC/DC0.5A	A.70
1063770000	VSSC4 CL FG24VAC/DC0.5A	A.97
1063780000	VSSC4 CL FG48VAC/DC0.5A	A.97
1063810000	VSSC4 CL FG 24VAC/DC Ex	A.157
1063820000	VSSC4 CL FG 48VAC/DC Ex	A.157
1063830000	VSSC4 SL 12VDC 0.5A	A.99
1063840000	VSSC4 SL 24VAC/DC 0.5A	A.99
1063860000	VSSC4 SL 48VAC/DC 0.5A	A.99
1063870000	VSSC4 SL 60VAC/DC 0.5A	A.99
1063880000	VSSC4 SL FG 12VDC 0.5A	A.99
1063890000	VSSC4 SL FG24VAC/DC0.5A	A.99
1063930000	VSSC4 SL FG 24VAC/DC Ex	A.159
1063940000	VSSC4 SL FG 48VAC/DC Ex	A.159
1063950000	VSSC4 MOV 12VDC	A.101
1063960000	VSSC4 MOV 24VAC/DC	A.101
1063970000	VSSC4 MOV 48VAC/DC	A.101
1063980000	VSSC4 MOV 60VAC/DC	A.101
1063990000	VSSC4 MOV 120VAC/DC	A.101
1064010000	VSSC4 MOV 150VAC/DC	A.101
1064020000	VSSC4 MOV 240VAC/DC	A.101
1064040000	VSSC4 GDT55VUC 20KA EX	A.161
1064050000	VSSC4 GDT 110VAC/DC20KA	A.103
1064060000	VSSC4 GDT 240VAC/DC20KA	A.103
1064070000	VSSC4 TAZ 12VDC	A.105
1064080000	VSSC4 TAZ 24VAC/DC	A.105
1064090000	VSSC4 TAZ 48VAC/DC	A.105
1064120000	VSSC4 RC 24VAC/DC	A.107
1064130000	VSSC4 RC 240VAC/DC	A.107
1064150000	VSSC6 CL 12VDC 0.5A	A.70
1064150000	VSSC6 CL 12VDC 0.5A	A.73
1064170000	VSSC6 CL 24VAC/DC 0.5A	A.70
1064170000	VSSC6 CL 24VAC/DC 0.5A	A.73
1064190000	VSSC6 CL 48VAC/DC 0.5A	A.70
1064190000	VSSC6 CL 48VAC/DC 0.5A	A.73
1064210000	VSSC6 CL 60VAC/DC 0.5A	A.73
1064220000	VSSC6 TR CL 12VDC 0.5A	A.75
1064230000	VSSC6 TRCL24VAC/DC0.5A	A.75
1064240000	VSSC6 TRCL48VAC/DC0.5A	A.75
1064250000	VSSC6 TRCL60VAC/DC0.5A	A.75
1064260000	VSSC6 CL FG 12VDC 0.5A	A.73
1064270000	VSSC6 CLFG24VAC/DC0.5A	A.70
1064270000	VSSC6 CLFG24VAC/DC0.5A	A.73
1064280000	VSSC6 CLFG48VAC/DC0.5A	A.73
1064290000	VSSC6 CLFG60VAC/DC0.5A	A.73
1064300000	VSSC6TRCLFG12VDC0.5A	A.70
1064300000	VSSC6TRCLFG12VDC0.5A	A.75
1064310000	VSSC6TRCLFG24VAC/DC0.5A	A.70
1064310000	VSSC6TRCLFG24VAC/DC0.5A	A.75
1064320000	VSSC6TRCLFG48VAC/DC0.5A	A.75
1064330000	VSSC6TRCLFG60VAC/DC0.5A	A.75
1064340000	VSSC6SL LD 12VDC 0.5A	A.70
1064340000	VSSC6SL LD 12VDC 0.5A	A.77
1064350000	VSSC6SL LD24VAC/DC0.5A	A.77
1064380000	VSSC6TRSLD12VDC0.5A	A.79
1064390000	VSSC6TRSLD24VAC/DC0.5A	A.79
1064400000	VSSC6TRSLD48VAC/DC0.5A	A.79
1064420000	VSSC6SL FG LD12VDC0.5A	A.77
1064430000	VSSC6SLFGLD24VAC/DC0.5A	A.77
1064440000	VSSC6SLFGLD48VAC/DC0.5A	A.77
1064490000	VSSC6TRSLFGLD12VDC0.5A	A.79
1064500000	VSSC6TRSLFGLD24VUC 0.5A	A.79
1064530000	VSSC6 MOV 12VDC	A.81
1064540000	VSSC6 MOV 24VAC/DC	A.81
1064570000	VSSC6 MOV 48VAC/DC	A.81
1064600000	VSSC6 MOV 60VAC/DC	A.81
1064610000	VSSC6 MOV 120VAC/DC	A.81
1064630000	VSSC6 MOV 240VAC/DC	A.81
1064640000	VSSC6 GDT 24VAC/DC 10kA	A.85
1064690000	VSSC6 GDT 110VAC/DC10kA	A.70
1064690000	VSSC6 GDT 110VAC/DC10kA	A.85
1064700000	VSSC6 GDT 110VAC/DC20kA	A.70
1064700000	VSSC6 GDT 110VAC/DC20kA	A.85
1064710000	VSSC6 GDT 240VAC/DC10kA	A.85
1064720000	VSSC6 GDT 240VAC/DC20kA	A.70
1064720000	VSSC6 GDT 240VAC/DC20kA	A.85
1064730000	VSSC6 TAZ 12VDC	A.89
1064740000	VSSC6 TAZ 24VAC/DC	A.89
1064800000	VSSC6 TRLDMOV 12VDC	A.83
1064810000	VSSC6 TRLDMOV 24VAC/DC	A.83
1064820000	VSSC6 TRLDMOV 48VAC/DC	A.83
1064840000	VSSC6 TRLDMOV120VAC/DC	A.83
1064860000	VSSC6 TRLDMOV240VAC/DC	A.83
1064870000	VSSC6TRGDT24VAC/DC10kA	A.87
1064880000	VSSC6TRGDT110VAC/DC10kA	A.87
1064920000	VSSC6TRGDT240VAC/DC10kA	A.87
1064950000	VSSC6 TRLDITAZ 24VAC/DC	A.89
1064980000	VSSC6 RS485	A.70
1064980000	VSSC6 RS485	A.91
1064980000	VSSC6 RS485	C.15
1064990000	VSSC6 RS232	A.70
1064990000	VSSC6 RS232	A.91
1064990000	VSSC6 RS232	C.15

Order No.	Type	Page
-----------	------	------

1065010000	VSSC6 RS485 DP	A.3
1065010000	VSSC6 RS485 DP	A.70
1065010000	VSSC6 RS485 DP	A.91
1065010000	VSSC6 RS485 DP	C.15
1065020000	VSSC6 RS485 PA EX	A.165
1066490000	VSSC6TRCLFG24VAC/DC EX	A.163

1070000000

1070230000	VSPC BASE 1CL PW	A.28
1070230000	VSPC BASE 1CL PW	A.52
1070470000	VSPC BASE 1CL PW FG EX	A.142
1070470000	VSPC BASE 1CL PW FG EX	A.150

1090000000

1093400000	VSPC 2CL 24VAC R	A.23
------------	------------------	------

1100000000

1105700000	VSPC BASE 1CL PW FG	A.28
1105700000	VSPC BASE 1CL PW FG	A.53

1130000000

1130670000	VSSC6 RTD EX	A.167
1139710000	VSSC6 RTD	A.70
1139710000	VSSC6 RTD	A.93

1160000000

1161150000	VSPC 4SL 12VAC EX	A.147
1161170000	VSPC 4SL 12VDC EX	A.147
1161180000	VSPC 4SL 24VAC EX	A.147
1161190000	VSPC 4SL 24VDC EX	A.147

1300000000

1309470000	QB 17,8/2	A.57
------------	-----------	------

1310000000

1317340000	VSPC LOCKING CLIP	A.57
------------	-------------------	------

1340000000

1348590000	VDATA CAT6	A.3
1348590000	VDATA CAT6	C.13

1350000000

1351330000	VPU I 1 R LCF 280V/35KA	B.2
1351330000	VPU I 1 R LCF 280V/35KA	B.12
1351340000	VPU II 2 PV 600V DC	B.7
1351340000	VPU II 2 PV 600V DC	B.67
1351350000	VPU I 1 LCF 280V/35KA	B.2
1351350000	VPU I 1 LCF 280V/35KA	B.12
1351370000	VPU II 2 R PV 600V DC	B.7
1351370000	VPU II 2 R PV 600V DC	B.67
1351380000	VPU I 1 R LCF 400V/35KA	B.2
1351380000	VPU I 1 R LCF 400V/35KA	B.12
1351400000	VPU I 1 LCF 400V/35KA	B.2
1351400000	VPU I 1 LCF 400V/35KA	B.12
1351550000	VPU III R 12V/4KV AC/DC	B.6
1351550000	VPU III R 12V/4KV AC/DC	B.74
1351570000	VPU I 1 R LCF 280V/25KA	B.2
1351570000	VPU I 1 R LCF 280V/25KA	B.15
1351580000	VPU III R 24V/4KV AC/DC	B.6
1351580000	VPU III R 24V/4KV AC/DC	B.73
1351590000	VPU I 1 LCF 280V/25KA	B.2
1351590000	VPU I 1 LCF 280V/25KA	B.15
1351600000	VPU III R 48V/4KV AC/DC	B.6
1351600000	VPU III R 48V/4KV AC/DC	B.73
1351620000	VPU I 2 R LCF 280V/25KA	B.2
1351620000	VPU I 2 R LCF 280V/25KA	B.15
1351630000	VPU III R 120V/6KV AC/DC	B.6
1351630000	VPU III R 120V/6KV AC/DC	B.72
1351640000	VPU I 2 LCF 280V/25KA	B.2
1351640000	VPU I 2 LCF 280V/25KA	B.15
1351650000	VPU III R 230V/6KV AC	B.6
1351650000	VPU III R 230V/6KV AC	B.72
1351670000	VPU I 3 R LCF 280V/25KA	B.2
1351670000	VPU I 3 R LCF 280V/25KA	B.13
1351680000	VPU III SO LD	B.6
1351680000	VPU III SO LD	B.74
1351690000	VPU I 3 LCF 280V/25KA	B.2
1351690000	VPU I 3 LCF 280V/25KA	B.13
1351700000	VPU III SO LD+A	B.6
1351700000	VPU III SO LD+A	B.74
1351720000	VPU I 4 R LCF 280V/25KA	B.2
1351720000	VPU I 4 R LCF 280V/25KA	B.13
1351730000	VPU I 4 LCF 280V/25KA	B.2
1351730000	VPU I 4 LCF 280V/25KA	B.13
1351740000	VPU I 1+1 R LCF 280V/25KA	B.2
1351740000	VPU I 1+1 R LCF 280V/25KA	B.14
1351750000	VPU I 1+1 LCF 280V/25KA	B.2
1351750000	VPU I 1+1 LCF 280V/25KA	B.14
1351770000	VPU I 3+1 R LCF 280V/25KA	B.2
1351770000	VPU I 3+1 R LCF 280V/25KA	B.14

Order No.	Type	Page
-----------	------	------

1351780000	VPU I 3+1 LCF 280V/25KA	B.2
1351780000	VPU I 3+1 LCF 280V/25KA	B.14
1351800000	VPU I 1 R 400V/25KA	B.2
1351800000	VPU I 1 R 400V/25KA	B.18
1351820000	VPU I 1 400V/25KA	B.2
1351820000	VPU I 1 400V/25KA	B.18
1351830000	VPU I 1+1 R 400V/25KA	B.2
1351830000	VPU I 1+1 R 400V/25KA	B.20
1351840000	VPU I 1+1 400V/25KA	B.2
1351840000	VPU I 1+1 400V/25KA	B.20
1351850000	VPU I 3 R 400V/25KA	B.2
1351850000	VPU I 3 R 400V/25KA	B.18
1351870000	VPU I 3 400V/25KA	B.18
1351870000	VPU I 3 400V/25KA	B.2
1351880000	VPU I 3+1 R 400V/25KA	B.2
1351880000	VPU I 3+1 R 400V/25KA	B.20
1351890000	VPU I 3+1 400V/25KA	B.2
1351890000	VPU I 3+1 400V/25KA	B.20
1351900000	VPU I 1 N-PE 260V/50KA	B.3
1351900000	VPU I 1 N-PE 260V/50KA	B.21
1351920000	VPU I 1 N-PE 260V/100KA	B.3
1351920000	VPU I 1 N-PE 260V/100KA	B.21
1351950000	VPU I 1 N-PE 440V/50KA	B.3
1351950000	VPU I 1 N-PE 440V/50KA	B.23
1351970000	VPU I 1 N-PE 440V/100KA	B.3
1351970000	VPU I 1 N-PE 440V/100KA	B.23
1354790000	VSSC6TRSL24VAC/DC0.5A	A.79
1354800000	VSSC6TRSLFG24VAC/DC0.5A	A.79

1390000000

1393050000	VPU III 3/280V	B.6
1393050000	VPU III 3/280V	B.75

1400000000

1402570000	PLUG VPU	B.43
------------	----------	------

1420000000

1421440000	VSSC6SLTRFG24VAC/DC EX	A.163
------------	------------------------	-------

1430000000

1438010000	VPU I 4 400V/25KA	B.2
1438010000	VPU I 4 400V/25KA	B.19
1438020000	VPU I 4 R 400V/25KA	B.2
1438020000	VPU I 4 R 400V/25KA	B.19

1470000000

1473440000	VPU II 1 1000V/40KA AC	B.5
1473440000	VPU II 1 1000V/40KA AC	B.61

2060000000

2062910000	VPU I 3 R 280V/25KA	B.2
2062910000	VPU I 3 R 280V/25KA	B.16
2062940000	VPU I 3 280V/25KA	B.2
2062940000	VPU I 3 280V/25KA	B.16
2062950000	VPU I 4 R 280V/25KA	B.2
2062950000	VPU I 4 R 280V/25KA	B.16
2062960000	VPU I 4 280V/25KA	B.2
2062960000	VPU I 4 280V/25KA	B.16
2063040000	VPU I 1+1 R 280V/25KA	B.2
2063040000	VPU I 1+1 R 280V/25KA	B.17
2063060000	VPU I 1+1 280V/25KA	B.2
2063060000	VPU I 1+1 280V/25KA	B.17
2063070000	VPU I 3+1 R 280V/25KA	B.2
2063070000	VPU I 3+1 R 280V/25KA	B.17
2063080000	VPU I 3+1 280V/25KA	B.2
2063080000	VPU I 3+1 280V/25KA	B.17

2530000000

2530180000	VPU PV II 3 R 1000	B.7
2530180000	VPU PV II 3 R 1000	B.66
2530550000	VPU PV II 3 1000	B.7
2530550000	VPU PV II 3 1000	B.66
2530580000	VPU PV I+II 3 1500	B.7
2530580000	VPU PV I+II 3 1500	B.65
2530590000	VPU PV I+II 3 R 1500	B.7
2530590000	VPU PV I+II 3 R 1500	B.65
2530610000	VPU PV I+II 3 1000	B.7
2530610000	VPU PV I+II 3 1000	B.65
2530620000	VPU PV I+II 3 R 1000	B.7
2530620000	VPU PV I+II 3 R 1000	B.65
2530640000	VPU PV II 3 1500	B.7
2530640000	VPU PV II 3 1500	B.66
2530650000	VPU PV II 3 R 1500	B.7
2530650000	VPU PV II 3 R 1500	B.

Order No.	Type	Page
-----------	------	------

2591650000	VPU AC II 1 150/50	B.4
2591650000	VPU AC II 1 150/50	B.45
2591660000	VPU AC II 1 R 150/50	B.4
2591660000	VPU AC II 1 R 150/50	B.45
2591670000	VPU AC II 2 150/50	B.4
2591670000	VPU AC II 2 150/50	B.45
2591680000	VPU AC II 2 R 150/50	B.4
2591680000	VPU AC II 2 R 150/50	B.45
2591690000	VPU AC II 3 150/50	B.4
2591690000	VPU AC II 3 150/50	B.46
2591700000	VPU AC II 3 R 150/50	B.4
2591700000	VPU AC II 3 R 150/50	B.46
2591710000	VPU AC II 4 150/50	B.4
2591710000	VPU AC II 4 150/50	B.46
2593120000	VC6 24V EX 2 NPT1/2	E.2
2593130000	VC6 24V EX 4 NPT1/2	E.2
2593140000	VC6 24V EX 2 M20X1,5	E.2
2593150000	VC6 24V EX 4 M20X1,5	E.2
2593160000	VC6 24V EX 2 G 1/2	E.2
2593170000	VC6 24V EX 4 G 1/2	E.2

2610000000

2619100000	VPU AC I 1 440/25 LCF	B.2
2619100000	VPU AC I 1 440/25 LCF	B.34
2619120000	VPU AC I 1 R 440/25 LCF	B.2
2619120000	VPU AC I 1 R 440/25 LCF	B.34
2619130000	VPU AC I 2 440/25 LCF	B.2
2619130000	VPU AC I 2 440/25 LCF	B.33
2619140000	VPU AC I 2 R 440/25 LCF	B.2
2619140000	VPU AC I 2 R 440/25 LCF	B.33
2619160000	VPU AC I 3 440/25 LCF	B.2
2619160000	VPU AC I 3 440/25 LCF	B.33
2619170000	VPU AC I 3 R 440/25 LCF	B.2
2619170000	VPU AC I 3 R 440/25 LCF	B.33
2619190000	VPU AC I 4 440/25 LCF	B.2
2619190000	VPU AC I 4 440/25 LCF	B.32
2619200000	VPU AC I 4 R 440/25 LCF	B.2
2619200000	VPU AC I 4 R 440/25 LCF	B.32
2619210000	VPU AC I 1+1 440/25 LCF	B.2
2619210000	VPU AC I 1+1 440/25 LCF	B.34
2619220000	VPU AC I 1+1 R 440/25 LCF	B.2
2619220000	VPU AC I 1+1 R 440/25 LCF	B.34
2619240000	VPU AC I 3+1 440/25 LCF	B.2
2619240000	VPU AC I 3+1 440/25 LCF	B.32
2619260000	VPU AC I 3+1 R 440/25 LCF	B.2
2619260000	VPU AC I 3+1 R 440/25 LCF	B.32

2630000000

2636910000	VPU AC I 3+1 300/12,5 LCF	B.2
2636910000	VPU AC I 3+1 300/12,5 LCF	B.25
2636920000	VPU AC I 3+1 R 300/12,5 LCF	B.2
2636920000	VPU AC I 3+1 R 300/12,5 LCF	B.25
2636930000	VPU AC I 1+1 300/12,5 LCF	B.2
2636930000	VPU AC I 1+1 300/12,5 LCF	B.24
2636940000	VPU AC I 1+1 R 300/12,5 LCF	B.2
2636940000	VPU AC I 1+1 R 300/12,5 LCF	B.24
2636950000	VPU AC I 1 300/12,5 LCF	B.2
2636950000	VPU AC I 1 300/12,5 LCF	B.24
2636960000	VPU AC I 1 R 300/12,5 LCF	B.2
2636960000	VPU AC I 1 R 300/12,5 LCF	B.24
2636970000	VPU AC I 3 300/12,5 LCF	B.2
2636970000	VPU AC I 3 300/12,5 LCF	B.25
2636980000	VPU AC I 3 R 300/12,5 LCF	B.2
2636980000	VPU AC I 3 R 300/12,5 LCF	B.25
2636990000	VPU AC II 1 75/50	B.4
2637000000	VPU AC II 2 75/50	B.4
2637010000	VPU AC II 2 350/50	B.4
2637010000	VPU AC II 2 350/50	B.54
2637020000	VPU AC II 2 R 350/50	B.4
2637020000	VPU AC II 2 R 350/50	B.54
2637030000	VPU AC II 1+1 350/50	B.4
2637030000	VPU AC II 1+1 350/50	B.56
2637040000	VPU AC II 1+1 R 350/50	B.4
2637040000	VPU AC II 1+1 R 350/50	B.56
2637050000	VPU AC II 3+1 350/50	B.4
2637050000	VPU AC II 3+1 350/50	B.56
2637060000	VPU AC II 3+1 R 350/50	B.4
2637060000	VPU AC II 3+1 R 350/50	B.56
2638440000	VPU ZP I 3+1 300/12,5	B.3
2638440000	VPU ZP I 3+1 300/12,5	B.39
2638450000	VPU ZP I 3 300/12,5	B.3
2638450000	VPU ZP I 3 300/12,5	B.38
2639320000	VPU AC II 3+1 R 300/50 Y	B.4
2639320000	VPU AC II 3+1 R 300/50 Y	B.53
2639330000	VPU AC II 3 R 300/50 Y	B.4
2639330000	VPU AC II 3 R 300/50 Y	B.52
2639340000	VPU AC II 1+1 R 300/50 Y	B.4
2639340000	VPU AC II 1+1 R 300/50 Y	B.51
2639350000	VPU AC II 1 R 300/50 Y	B.4
2639350000	VPU AC II 1 R 300/50 Y	B.51
2639360000	VPU AC II 2 R 300/50 Y	B.4
2639360000	VPU AC II 2 R 300/50 Y	B.52
2639370000	VPU AC II 4 R 300/50 Y	B.4
2639370000	VPU AC II 4 R 300/50 Y	B.53

Order No.	Type	Page
-----------	------	------

2650000000

2659900000	VPU ZP I 3 300/7,5	B.3
2659900000	VPU ZP I 3 300/7,5	B.38
2659910000	VPU ZP I 3+1 300/7,5	B.3
2659910000	VPU ZP I 3+1 300/7,5	B.39

2660000000

2661040000	V-TEST II	B.78
------------	-----------	------

2670000000

2674310000	VPU ZPA I 3 R 300/12,5	B.3
2674350000	VPU ZPA I 3 300/12,5	B.3
2674360000	VPU ZPA I 3 A 300/12,5	B.3
2674370000	VPU ZPA I 3 RA 300/12,5	B.3
2674380000	VPU ZPA I 3+1 300/12,5	B.3
2674390000	VPU ZPA I 3+1 R 300/12,5	B.3
2674400000	VPU ZPA I 3+1 A 300/12,5	B.3
2674410000	VPU ZPA I 3+1 RA 300/12,5	B.3
2674420000	VPU ZPA I 3 300/7,5	B.3
2674430000	VPU ZPA I 3 R 300/7,5	B.3
2674440000	VPU ZPA I 3 A 300/7,5	B.3
2674450000	VPU ZPA I 3 RA 300/7,5	B.3
2674460000	VPU ZPA I 3+1 300/7,5	B.3
2674470000	VPU ZPA I 3+1 R 300/7,5	B.3
2674500000	VPU ZPA I 3+1 A 300/7,5	B.3
2674510000	VPU ZPA I 3+1 RA 300/7,5	B.3

8440000000

8448920000	MCZ OVP CL 24VDC 0,5A	A.2
8448920000	MCZ OVP CL 24VDC 0,5A	A.3
8448920000	MCZ OVP CL 24VDC 0,5A	A.114
8448940000	MCZ OVP SL 24VDC 0,5A	A.2
8448940000	MCZ OVP SL 24VDC 0,5A	A.115
8448960000	MCZ OVP CL 24VUC 1,25A	A.116
8448970000	MCZ OVP SL 24VUC 1,25A	A.2
8448970000	MCZ OVP SL 24VUC 1,25A	A.116
8449000000	MCZ OVP CL 48VUC 0,5A	A.116
8449030000	MCZ OVP SL 48VUC 0,5A	A.117
8449040000	MCZ OVP CL 48VUC 1,25A	A.3
8449040000	MCZ OVP CL 48VUC 1,25A	A.117
8449050000	MCZ OVP SL 48VUC 1,25A	A.118

8470000000

8472880000	MCZ OVP CL 24VAC 0,5A	A.114
------------	-----------------------	-------

8610000000

8614770000	WAVEFILTER 10A	D.5
8614780000	WAVEFILTER 3A	D.4
8614800000	WAVEFILTER 6A	D.4

8700000000

8704240000	MCZ OVP CL FG 24VUC 0,5A	A.119
------------	--------------------------	-------

8800000000

8805550000	JPOVP RJ45 Cat6 IP20	A.3
8805550000	JPOVP RJ45 Cat6 IP20	C.17

8820000000

8823280000	MCZ OVP SL FG 24VUC 0,5A	A.118
------------	--------------------------	-------

8920000000

8924200000	VSPC 4SL 5VDC	A.35
8924210000	VSPC 2SL 5VDC	A.3
8924210000	VSPC 2SL 5VDC	A.31
8924220000	VSPC 4SL 12VDC	A.35
8924230000	VSPC 2SL 12VDC	A.31
8924260000	VSPC BASE 4SL FG	A.34
8924260000	VSPC BASE 4SL FG	A.53
8924270000	VSPC BASE 2CL FG	A.2
8924270000	VSPC BASE 2CL FG	A.3
8924270000	VSPC BASE 2CL FG	A.4
8924270000	VSPC BASE 2CL FG	A.20
8924270000	VSPC BASE 2CL FG	A.24
8924270000	VSPC BASE 2CL FG	A.46
8924270000	VSPC BASE 2CL FG	A.48
8924270000	VSPC BASE 2CL FG	A.53
8924270000	VSPC BASE 2CL FG	C.4
8924270000	VSPC BASE 2CL FG	C.8
8924280000	VSPC BASE 2SL FG	A.3
8924280000	VSPC BASE 2SL FG	A.30
8924280000	VSPC BASE 2SL FG	A.53
8924290000	VSPC BASE 1CL FG	A.2
8924290000	VSPC BASE 1CL FG	A.3
8924290000	VSPC BASE 1CL FG	A.16
8924290000	VSPC BASE 1CL FG	A.53
8924300000	VSPC BASE 2/4CH FG	A.2
8924300000	VSPC BASE 2/4CH FG	A.3
8924300000	VSPC BASE 2/4CH FG	A.38
8924300000	VSPC BASE 2/4CH FG	A.40

Order No.	Type	Page
-----------	------	------

8924300000	VSPC BASE 2/4CH FG	A.42
8924300000	VSPC BASE 2/4CH FG	A.44
8924300000	VSPC BASE 2/4CH FG	A.53
8924320000	VSPC 4SL 24VDC	A.35
8924330000	VSPC 2SL 24VDC	A.31
8924340000	VSPC 4SL 24VAC	A.35
8924350000	VSPC 2SL 24VAC	A.31
8924360000	VSPC 4SL 48VAC	A.35
8924370000	VSPC 2SL 48VAC	A.31
8924380000	VSPC 4SL 60VAC	A.35
8924400000	VSPC 2CL 5VDC	A.21
8924420000	VSPC 1CL 5VDC	A.3
8924420000	VSPC 1CL 5VDC	A.17
8924430000	VSPC 2CL HF 5VDC	A.3
8924430000	VSPC 2CL HF 5VDC	A.4
8924430000	VSPC 2CL HF 5VDC	A.25
8924430000	VSPC 2CL HF 5VDC	C.5
8924440000	VSPC 2CL 12VDC	A.3
8924440000	VSPC 2CL 12VDC	A.21
8924450000	VSPC 1CL 12VDC	A.2
8924450000	VSPC 1CL 12VDC	A.3
8924450000	VSPC 1CL 12VDC	A.17
8924460000	VSPC 2CL HF 12VDC	A.2
8924460000	VSPC 2CL HF 12VDC	A.3
8924460000	VSPC 2CL HF 12VDC	A.4
8924460000	VSPC 2CL HF 12VDC	A.25
8924460000	VSPC 2CL HF 12VDC	C.5
8924470000	VSPC 2CL 24VDC	A.2
8924470000	VSPC 2CL 24VDC	A.4
8924470000	VSPC 2CL 24VDC	A.21
8924480000	VSPC 1CL 24VDC	A.2
8924480000	VSPC 1CL 24VDC	A.3
8924480000	VSPC 1CL 24VDC	A.17
8924490000	VSPC 2CL 24VAC	A.21
8924500000	VSPC 1CL 24VAC	A.17
8924510000	VSPC 2CL HF 24VDC	A.3
8924510000	VSPC 2CL HF 24VDC	A.25
8924520000	VSPC 1CL 48VAC	A.3
8924520000	VSPC 1CL 48VAC	A.17
8924530000	VSPC 1CL 60VAC	A.17
8924540000	VSPC 3/4WIRE 5VDC	A.39
8924550000	VSPC 3/4WIRE 24VDC	A.2
8924550000	VSPC 3/4WIRE 24VDC	A.39
8924570000	VSPC GDT 2CH 90V	A.2
8924570000	VSPC GDT 2CH 90V	A.41
8924570000	VSPC GDT 2CH 90V	A.43
8924590000	VSPC GDT 2CH 150Vac/230Vdc	A.41
8924600000	VSPC MOV 2CH 24V	A.43
8924610000	VSPC MOV 2CH 230V	A.43
8924650000	VSPC TAZ 4CH 24V	A.45
8924660000	VSPC TELE UKO 2WIRE	A.3
8924660000	VSPC TELE UKO 2WIRE	A.4
8924660000	VSPC TELE UKO 2WIRE	A.47
8924670000	VSPC RS485 2CH	A.2
8924670000	VSPC RS485 2CH	A.3
8924670000	VSPC RS485 2CH	A.49
8924670000	VSPC RS485 2CH	C.9
8924680000	VSPC GROUND	A.56
8924700000	VSPC BASE 4SL	A.34
8924700000	VSPC BASE 4SL	A.52
8924710000	VSPC BASE 2CL	A.2
8924710000	VSPC BASE 2CL	A.3
8924710000	VSPC BASE 2CL	A.4
8924710000	VSPC BASE 2CL	A.48
8924710000	VSPC BASE 2CL	A.52
8924710000	VSPC BASE 2CL	C.4
8924710000	VSPC BASE 2CL	C.8
8924720000	VSPC BASE 2SL	A.3
8924720000	VSPC BASE 2SL	A.30
8924720000	VSPC BASE 2SL	A.52
8924730000	VSPC BASE 1CL	A.2
8924730000	VSPC BASE 1CL	A.3
8924730000	VSPC BASE 1CL	A.16
8924730000	VSPC BASE 1CL	A.52
8924740000	VSPC BASE 2/4CH	A.2
8924740000	VSPC BASE 2/4CH	A.3
8924740000	VSPC BASE 2/4CH	A.38
8924740000	VSPC BASE 2/4CH	A.40
8924740000	VSPC BASE 2/4CH	A.42
8924740000	VSPC BASE 2/4CH	A.44
8924740000	VSPC BASE 2/4CH	A.52

8940000000

8947820000	BNC Connector / M-F	C.18
8947830000	N Connector / M-F	C.18
8947840000	F Connector / M-F	C.19
8947850000	UHF Connector / M-F	C.19
8948600000	MCZ OVP HF 24V 0,3A	A.2
8948600000	MCZ OVP HF 24V 0,3A	A.3
8948600000	MCZ OVP HF 24V 0,3A	A.113
8948610000	MCZ OVP HF 12V 0,3A	A.2
8948610000	MCZ OVP HF 12V 0,3A	A.3
8948610000	MCZ OVP HF 12V 0,3A	A.112
8948620000	MCZ OVP HF 5V 0,3A	A.2

Order No.	Type	Page
-----------	------	------

8948620000	MCZ OVP HF 5V 0,3A	A.3
8948620000	MCZ OVP HF 5V 0,3A	A.112

We cannot guarantee that there are no mistakes in the publications or software provided by us to the customer for the purpose of making orders. We try our best to quickly correct errors in our printed media.


X

All orders are based on our general terms of delivery, which can be reviewed on the websites of our group companies where you place your order. On demand we can also send the general terms of delivery to you.

TN-C systems

Neutral conductor and protective earth conductor functions are combined throughout the network in a single conductor, the PEN conductor (4-conductor-system).


Position	LPL	Type	Order No.	Page
1	I/II	VPU I 3 LCF 280 V/25 kA	1351690000	B.13
	III/IV	VPU AC I 3 300/12.5 LCF	2636970000	B.25
2		VPU AC II 3 300/50	2591160000	B.48
3		VPU III 3 280 V	1393050000	B.75



TN-C-S systems

Neutral conductor, PEN conductor and equipotential bonding system are connected once at the main distribution board or after the incoming supply to the building. Therefore, a TN-C system becomes a TN-S system (TN-C-S system) from this point onwards.


Position	LPL	Type	Order No.	Page
1	I/II	VPU I 3 LCF 280 V/25 kA	1351690000	B.13
	III/IV	VPU AC I 3 300/12.5 LCF	2636970000	B.25
2		VPU AC II 3+1 300/50	2591080000	B.49
		VPU AC II 4 300/50	2591140000	B.49
3		VPU III R 230 V/6 KV AC	1351650000	B.72



TN-S systems

Neutral conductor and protective earth conductor are separated throughout the network.


Position	LPL	Type	Order No.	Page
1	I/II	VPU I 3+1 LCF 280 V/25 kA	1351780000	B.14
	III/IV	VPU AC I 3+1 300/12.5 LCF	2636910000	B.25
2		VPU AC II 3+1 300/50	2591080000	B.49
3		VPU III R 230 V/6 KV AC	1351650000	B.72



TT systems

One point is earthed directly (operational earth). The exposed conductive parts of the electrical installation are connected to earth lines separate from the operational earth.


Position	LPL	Type	Order No.	Page
1	I/II	VPU I 3+1 LCF 280 V/25 kA	1351780000	B.14
	III/IV	VPU AC I 3+1 300/12.5 LCF	2636910000	B.25
2		VPU AC II 3+1 300/50	2591080000	B.49
3		VPU AC II 3+1 300/50	2591080000	B.49



IT systems

There is no direct connection between active conductors and earthed parts. The exposed conductive parts of the electrical installation are earthed.

Position	LPL	Type	Order No.	Page
1	I/II	VPU AC I 3 440/25 LCF	2619160000	B.33
	III/IV	VPU AC I 3 480/10	2591530000	B.30
2		VPU AC II 3 480/50	2591250000	B.58
3		VPU AC II 3 480/50	2591250000	B.58



Terms

SPD = Surge Protection Device

Classification of surge arresters

1. Power lines

Class I, Type 1, Type 1
(lightning arrester)
Class II, Type 2, Type 2
(surge protection)
Class III, Type 3, Type 3
(surge protection for end devices)

2. Measurement/control cables and data cables

Class D1 (lightning arrester)
Class C2 (surge protection)
Class C1 (surge protection for end devices)

Surge voltage category (EN 60664-1)

Rated impulse voltage

IV = 6 kV (before the meter)
III = 4 kV (after the meter, HV + UV, fixed installation)
II = 2.5 kV (outlet/end device)
I = 1.5 kV (in end device)

LPZ = Lightning Protection Zone

External lightning protection
LPZ 0 / 0A / 0B
Internal lightning protection LPZ 1, 2, 3

LPL = Lightning Protection Level

I = 200 kA
II = 150 kA
III + IV = 100 kA

LPS = Lightning Protection System


Lightning protection system

SPM = Surge Protection Measures


International standards

Application standard:
IEC 62305 – Application of lightning and surge protection with 4 chapters:
General overview, Risk analysis, Internal and external lightning protection
IEC 61643-12 – Usage for energy protection
IEC 61643-22 – Usage for measurement and control signals
IEC 61643-32 – Photovoltaic application

Testing pulse for surge arrester



EMC lightning protection - zone concept in accordance with IEC 62305-4



LPZ 0_A

Direct impact is possible and full electromagnetic field

LPZ 0_B

No direct impact is possible but full electromagnetic field

LPZ 1

Pulse currents are further limited by current distribution; the lightning field is attenuated by room shielding

LPZ 2...n

Pulse currents further limited; reduction of the field by room shielding

Weidmüller – Your Partner in Industrial Connectivity

As experienced experts we support our customers and partners around the world with products, solutions and services in the industrial environment of power, signal and data. We are at home in their industries and markets and know the technological challenges of tomorrow. We are therefore continuously developing innovative, sustainable and useful solutions for their individual needs. Together we set standards in Industrial Connectivity.

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
32758 Detmold, Germany
T +49 5231 14-0
F +49 5231 14-292083
www.weidmueller.de

Personal support can
be found on our website:
www.weidmueller.com/contact

Made in Germany



Order number: 2617750000/06/2019/SMR